



FlexNet Manager Suite Schema Reference

Legal Information

Document Name: FlexNet Manager Suite 2016 R1 SP1 Schema Reference (for on-premises and cloud implementations)

Part Number: FMS-12.1.0-DR01

Product Release Date: December 19, 2016

Copyright Notice

Copyright © 2016 Flexera Software LLC. All Rights Reserved.

This publication contains proprietary and confidential technology, information and creative works owned by Flexera Software LLC and its licensors, if any. Any use, copying, publication, distribution, display, modification, or transmission of such publication in whole or in part in any form or by any means without the prior express written permission of Flexera Software LLC is strictly prohibited. Except where expressly provided by Flexera Software LLC in writing, possession of this publication shall not be construed to confer any license or rights under any Flexera Software LLC intellectual property rights, whether by estoppel, implication, or otherwise.

All copies of the technology and related information, if allowed by Flexera Software LLC, must display this notice of copyright and ownership in full.

FlexNet Manager Suite incorporates software developed by others and redistributed according to license agreements. Copyright notices and licenses for this externally-developed software are provided in the link below.

Intellectual Property

For a list of trademarks and patents that are owned by Flexera Software, see <http://www.flexerasoftware.com/intellectual-property>. All other brand and product names mentioned in Flexera Software products, product documentation, and marketing materials are the trademarks and registered trademarks of their respective owners.

Restricted Rights Legend

The Software is commercial computer software. If the user or licensee of the Software is an agency, department, or other entity of the United States Government, the use, duplication, reproduction, release, modification, disclosure, or transfer of the Software, or any related documentation of any kind, including technical data and manuals, is restricted by a license agreement or by the terms of this Agreement in accordance with Federal Acquisition Regulation 12.212 for civilian purposes and Defense Federal Acquisition Regulation Supplement 227.7202 for military purposes. The Software was developed fully at private expense. All other use is prohibited.

Overview

The data underlying FlexNet Manager Suite is arranged in a number of distinct databases. Most frequently these databases live within a single database server, although in very large scale implementations, it is possible to implement them across multiple servers.

The most fundamental distinction is between:

- Data imported from various instances of the FlexNet inventory agent as software and hardware inventory from individual computers within the enterprise (see [Inventory Database Schema](#))
- Data used to calculate license positions, combining the software applications recognized from the imported inventory, the license entitlements collated from purchase records and other sources, structural information about the enterprise itself, and so on (see [Compliance Database Schema](#)).

A small set of tables is common to both these databases. These shared tables are documented within each of the above chapters.

In support of this basic structure, there are also the following major aspects:

- Staging tables used to rationalize data being imported into the main compliance database by `ComplianceReader.exe` (see [Compliance Reader Database Schema](#))
- A separate schema for presenting summarized license information on a once-separate web portal (see [License Portal Database Schema](#)).

Each of the chapters covering these schemata has a common structure:

- The chapter header includes a list of different *aspects* of the data described in the chapter. (These aspects are also the lowest level included in the summary table of contents for the entire volume.)
- The chapter header is followed by a reminder of the information structure in each of the database table descriptions.
- Each aspect then has a section header page listing all the individual database tables contained within that aspect.
- Finally, the detailed topics, one for each database table, listing all the properties (columns) in the table and various attributes of each one.

This structure makes it easy to drill down from a high-level understanding of the data structure to an individual table. Conversely, if you know a table name, use the PDF search mechanism in your reader software to locate its description. Similarly, you can also search for individual properties within tables, even when you don't know their provenance.

One final chapter takes a slightly different approach. Rather than documenting an internal schema, it covers the schema used for spreadsheets importing inventory information, and the mapping of those columns to the relevant database tables and column.

This document is not an exhaustive description of the entire database structure. For example, the system makes widespread use of views extracted from these underlying tables for (amongst other reasons) performance

improvements. These views are not documented here. Nor are the mechanisms used in a multi-tenant implementation for partitioning each tenant's data made explicit in this document. However, this is a complete description of all the basic data tables from which all else is derived.

Furthermore, the descriptions of each database table are compiled automatically using the same mechanism that generates the database schemata themselves. This process guarantees complete coverage of all tables at each release.

Contents

1. Compliance Database Schema.....	1
Information Structure	2
BatchProcessing.Common Tables	3
BatchProcessing Tables.....	15
Compliance.Logic.Administration Tables	18
Compliance.Logic.Assets Tables.....	42
Compliance.Logic.Beacon Tables	64
Compliance.Logic.Core Tables.....	129
Compliance.Logic.Discovery Tables.....	351
Compliance.Logic.Licensing Tables	369
Compliance.Logic.Structure Tables	663
Compliance.Logic.Users Tables	671
Compliance.SAP Tables.....	682
ManageSoft Tables.....	774
ReferenceData Tables.....	776
Rights Tables	780
Targeting Tables	784
Tenants Tables	789
2. Compliance Reader Database Schema	792
Information Structure	793
Compliance.InventoryReader.Logic Tables.....	794
Compliance.InventoryWriter.Matching Tables	901
3. Inventory Database Schema	909
Information Structure	910
AD Tables.....	911
Allocation Tables	916
ClientAccess Tables.....	925
DirectoryObjects Tables	931
Directory Tables.....	935
Distribution Tables	943
IM_Right Tables	952

Installation Tables.....	954
Inventory Tables	960
Licensing Tables.....	1004
ManageSoft Tables.....	1012
Networking Tables	1014
Packaging Tables	1017
ReferenceData Tables.....	1035
Rights Tables	1039
ScriptResult Tables	1043
Status Tables	1045
Targeting Tables	1048
Tenants Tables	1053
Usage Tables.....	1056
WakeOnLAN Tables	1061
WorkFlow Tables	1065
4. License Portal Database Schema	1073
Information Structure	1074
Compliance.ECM.Logic Tables.....	1075
5. Inventory Spreadsheet Templates	1086
Information Structure for Spreadsheet Inventory Imports	1087
Compliance.InventoryReader.Logic Tables.....	1090

1

Compliance Database Schema

This chapter describes the schema for the main database underlying FlexNet Manager Suite.

Separately documented is the schema for the inventory tables for inventory gathered by the FlexNet inventory agent, either when installed on 'adopted' devices, or when executing a remote, zero-touch inventory (see [Inventory Database Schema](#)).

Some tables from that inventory database are (correctly) duplicated in this compliance database, and these shared tables are also listed toward the end of this chapter.

Information Structure

The following information is provided about database tables. Items appear only when relevant to the database column, and are suppressed where they do not apply. Two of these items (shown bold) are columns in the following pages, and the remainder are displayed within the **Details**.

Item	Comment
Database Column	The name of the column in the SQL table.
<i>Type</i>	The data type of the contents of the database column.
Size	For types that have a maximum capacity, the upper limit is provided in parentheses.
Key	The word "Key" appears when a column is a unique key field within the table. It is possible for several database columns to be part of the key, so that this indicator may appear for several columns in a table.
Generated ID	This indicates that a numeric ID is assigned by the database.
Nullable	If this indicator is present, the database column permits nulls.
Computed	This indicator appears for columns that are automatically computed by the database.
Default	If a column has a default value declared in the schema, this is specified at the end of the first set of details for the column.
Details	Describes the data stored in the database column, including many of the indicators described above.

BatchProcessing.Common Tables

The complete set of database tables documented here includes:

- BatchProcessExecution table (see [BatchProcessExecution Table](#))
- BatchProcessExecutionData table (see [BatchProcessExecutionData Table](#))
- BatchProcessExecutionDataName table (see [BatchProcessExecutionDataName Table](#))
- BatchProcessSchedule table (see [BatchProcessSchedule Table](#))
- BatchProcessStatus table (see [BatchProcessStatus Table](#))
- BatchProcessType table (see [BatchProcessType Table](#))
- BatchProcessTypeLimit table (see [BatchProcessTypeLimit Table](#))

BatchProcessExecution Table

BatchProcessExecution is a table storing the details of batch processes requested and executed.

Table 1: Database columns for BatchProcessExecution table

Database Column	Details
BatchProcessExecutionID	<i>Type:</i> integer. Key. Generated ID A unique identifier for a batch processor.
GUID	<i>Type:</i> unique identifier. Key The GUID identifying a batch process execution.
BatchProcessTypeID	<i>Type:</i> integer. Key The type of this batch process execution. Foreign key to the BatchProcessType table.
Submitted	<i>Type:</i> datetime The date and time at which this batch process execution was submitted.
OperatorLogin	<i>Type:</i> text (max 512 characters). Nullable The login name of the operator requesting the batch process, NULL indicates a system request.
BeaconID	<i>Type:</i> integer. Key. Nullable The ID of the beacon which requested a batch process execution. Foreign key to the Beacon table.
BatchProcessorHostname	<i>Type:</i> text (max 128 characters). Key. Nullable The batch processor responsible for the execution of this batch process. A processor by this name may be in the BatchProcessor table, but this is not required.
BatchProcessStatusID	<i>Type:</i> integer Status of the batch process execution. Foreign key to the BatchProcessStatus table.
StartTime	<i>Type:</i> datetime. Nullable The date and time the batch process execution was started.
FinishTime	<i>Type:</i> datetime. Key. Nullable The date and time the batch process execution finished.
Progress	<i>Type:</i> integer Percentage indicator of how far through the batch process execution is.

Database Column	Details
ReturnCode	<i>Type:</i> integer. Nullable The return code of the batch process execution.
Output	<i>Type:</i> text. Nullable Contains any output reported by a batch process execution.
GroupName	<i>Type:</i> text (max 50 characters). Nullable The group name used to partition this batch process. Only relevant for types that require separation by group.
TenantUID	<i>Type:</i> text (max 40 characters). Nullable The tenant UID for this batch process. Only relevant for types that require separation by tenant.
RawMessage	<i>Type:</i> text. Nullable The raw, serialized message. Used for pending messages to reconstruct the queue when the batch processor restarts.

BatchProcessExecutionData Table

This table stores any extra data needed for a BatchProcessExecution record.

Table 2: Database columns for BatchProcessExecutionData table

Database Column	Details
BatchProcessExecution DataID	<i>Type:</i> integer. Key. Generated ID A unique identifier for this table.
BatchProcessExecutionID	<i>Type:</i> integer. Key The ID of the BatchProcessExecution record this data is asociated with. Foreign key to the BatchProcessExecution table.
BatchProcessExecution DataNameID	<i>Type:</i> integer. Key An identifier for the data being stored in this row
DataValue	<i>Type:</i> text The value being stored in this row

BatchProcessExecutionDataName Table

This table holds a list of the different types of data that can be stored in BatchProcessExecutionData.

Table 3: Database columns for BatchProcessExecutionDataName table

Database Column	Details
BatchProcessExecution DataNameID	<i>Type:</i> integer. Key. Generated ID A unique identifier for this table.
Name	<i>Type:</i> text (max 128 characters). Key Name of the setting.

BatchProcessSchedule Table

BatchProcessSchedule stores the schedule of a batch process.

Table 4: Database columns for BatchProcessSchedule table

Database Column	Details
BatchProcessScheduleID	<i>Type:</i> integer. Key. Generated ID A unique identifier for this table.
BatchProcessTypeID	<i>Type:</i> integer. Key The process type ID this schedule belongs to. Foreign key to the BatchProcessType table.
TenantUID	<i>Type:</i> text (max 40 characters). Key. Nullable The tenant UID for this batch schedule.
BatchProcessScheduleData	<i>Type:</i> text The Quartz scheduler data
UpdatedBy	<i>Type:</i> text (max 200 characters). Nullable The last operator to update the event.
UpdatedDate	<i>Type:</i> datetime. Nullable The date the event was last updated.
GUID	<i>Type:</i> unique identifier. Key Unique identifier for schedule.
LastRun	<i>Type:</i> datetime. Nullable The datetime this schedule was last executed.
Enabled	<i>Type:</i> boolean The datetime this schedule was last executed.

BatchProcessStatus Table

BatchProcessStatus is a static table listing status values for batch process execution.

Table 5: Database columns for BatchProcessStatus table

Database Column	Details
BatchProcessStatusID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each BatchProcessStatus. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = Submitted• 2 = Queued• 3 = Processing• 4 = Success• 5 = Error• 6 = Duplicate
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing an status of batch process execution. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the status resource string has no translation.</p>

BatchProcessType Table

BatchProcessType is a static table storing the types of batch processes

Table 6: Database columns for BatchProcessType table

Database Column	Details
BatchProcessTypeID	<p>Type: integer. Key. Generated ID</p> <p>A unique identifier for each BatchProcessType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = License reconcile • 2 = PO line import • 3 = Enterprise group import • 4 = User assignment import • 5 = Inventory import • 6 = Active directory import • 7 = Entitlement recommendations recalculation • 8 = SAP user recommendations export • 9 = Business adapter import • 10 = Generate business adapter config • 15 = ServiceNow export • 16 = FNMEA enterprise groups export • 17 = IBM Passport Advantage import • 18 = Data Warehouse access rights update • 19 = Update license consumption of IBM PVU licenses • 20 = Data Warehouse export • 21 = Import SAP inventories • 22 = Import SAP package license • 23 = Inventory import and license reconcile • 24 = Recognition data import • 25 = Inventory manager compliance import • 26 = Compliance import readers only • 27 = Compliance import writers only • 28 = Recognition data download • 29 = Recognition data cleanup • 30 = IM Data maintenance

Database Column	Details
	<ul style="list-style-type: none"> • 31 = SAP user and activity information import • 32 = Inventory import spreadsheet and license reconcile • 33 = FNMP Data maintenance • 34 = FNMP software usage history update • 35 = Delete activity log history • 36 = Baseline import processing • 37 = Sync FNMS tenants with Cognos
TypeName	<i>Type:</i> text (max 256 characters). Key The unique name of the batch process type.
ResourceName	<i>Type:</i> text (max 256 characters) The unique name of the localizable resource string representing a batch process type. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the type resource string has no translation.
StarvedAt	<i>Type:</i> integer. Nullable The age, in minutes, after which a task of this type will be given priority over other tasks to avoid starvation.
Timeout	<i>Type:</i> integer. Nullable The age, in minutes, after which a task of this type will be regarded as failed if its processor becomes unresponsive.
BatchProcessTypeLimitID	<i>Type:</i> integer. Nullable An optional reference to a limit that will restrict the number of items of this type that can execute at the same time.

BatchProcessTypeLimit Table

BatchProcessTypeLimit is a table storing the limits placed on the parallel execution of tasks within the Batch Processor. A limit is associated with one or more BatchProcessTypes. The limit value is the number of tasks of the associated types that may be executed at any one time.

Note that these limits are applied after the standard parallel execution restrictions are applied. This means that these limits will generally affect a single tenant system. They will take effect only if the limit is applied to types that are allowed to run in parallel for a tenant. For example, if a limit is applied to a types that run the ComplianceReader executable, the Business importer and the ARL import, it may be possible to reach the limit.

In a multi-tenant system, the limits allow the system administrator to define reasonable limits to try to ensure that the Batch scheduler does not overload the hardware it is allotted.

Table 7: Database columns for BatchProcessTypeLimit table

Database Column	Details
BatchProcessTypeLimitID	Type: integer. Key. Generated ID A unique identifier for a BatchProcessTypeLimit.
Name	Type: text (max 128 characters). Key The name of this BatchProcessTypeLimit. This name will be used internally to reference the limit, and will be shown in the tracing output.
MaxTasks	Type: integer The number of tasks associated with this limit that may be executed in parallel by the Batch scheduler. A zero or negative value in this column will cause the limit to be ignored.

BatchProcessing Tables

The complete set of database tables documented here includes:

- BatchProcessor table (see [BatchProcessor Table](#))
- BatchProcessorProcessType table (see [BatchProcessorProcessType Table](#))

BatchProcessor Table

BatchProcessor is a table storing the machines responsible for executing batch processes.

Table 8: Database columns for BatchProcessor table

Database Column	Details
BatchProcessorID	<i>Type:</i> integer. Key. Generated ID A unique identifier for a batch processor.
Hostname	<i>Type:</i> text (max 128 characters). Key The host name of this batch processor.
LastHeartbeat	<i>Type:</i> datetime. Nullable The UTC date and time this batch processor configured.
LastExecution	<i>Type:</i> datetime. Nullable The UTC date and time this batch processor last executed a batch process.

BatchProcessorProcessType Table

This table records the mapping of process types to batch processors.

Table 9: Database columns for BatchProcessorProcessType table

Database Column	Details
BatchProcessorID	<i>Type:</i> integer. Key The ID of the BatchProcessor record this data is asociated with. Foreign key to the BatchProcessor table.
BatchProcessTypeID	<i>Type:</i> integer. Key The ID of the BatchProcessType record this data is asociated with. Foreign key to the BatchProcessorType table.

Compliance.Logic.Administration Tables

The complete set of database tables documented here includes:

- APIServiceAccount table (see [APIServiceAccount Table](#))
- ComplianceConnection table (see [ComplianceConnection Table](#))
- ComplianceConnectionParameter table (see [ComplianceConnectionParameter Table](#))
- ComplianceCultureType table (see [ComplianceCultureType Table](#))
- ComplianceOperator table (see [ComplianceOperator Table](#))
- ComplianceOperatorTenant table (see [ComplianceOperatorTenant Table](#))
- ComplianceResourceString table (see [ComplianceResourceString Table](#))
- ComplianceSetting table (see [ComplianceSetting Table](#))
- ComplianceTenantSetting table (see [ComplianceTenantSetting Table](#))
- ConfigurationFile table (see [ConfigurationFile Table](#))
- ConfigurationFileType table (see [ConfigurationFileType Table](#))
- ConnectionType table (see [ConnectionType Table](#))
- Currency table (see [Currency Table](#))
- MasterConfigurationFile table (see [MasterConfigurationFile Table](#))
- OperatorTenantSetting table (see [OperatorTenantSetting Table](#))
- ResourceStringCultureType table (see [ResourceStringCultureType Table](#))
- RightDefinition table (see [RightDefinition Table](#))
- SettingName table (see [SettingName Table](#))
- TimezoneType table (see [TimezoneType Table](#))

APIServiceAccount Table

Stores a collection of external API service accounts.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 10: Database columns for APIServiceAccount table

Database Column	Details
APIServiceAccountID	Type: integer. Key. Generated ID Unique identifier for a API service account.
ComplianceOperatorID	Type: integer. Key. Nullable Reference to a compliance operator.
AccessThreshold	Type: integer. Nullable API access alert threshold
AccessCount	Type: integer API access count.
LastSync	Type: datetime. Nullable Indicates the last datetime this account is synced with FNOOD or validateToken API is called.
Description	Type: text (max 256 characters). Nullable Description for this service account.
CreationUser	Type: text (max 256 characters). Nullable Created by.
CreationDate	Type: datetime. Nullable Creation date.
UpdatedUser	Type: text (max 256 characters). Nullable Operator who made the latest change to the currency record.
UpdatedDate	Type: datetime. Nullable Updated date

ComplianceConnection Table

The ComplianceConnection table stores details about databases configured for use in compliance imports, such as Microsoft SMS.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 11: Database columns for ComplianceConnection table

Database Column	Details
ComplianceConnectionID	<i>Type:</i> integer. Key. Generated ID A unique identifier for a compliance connection.
ConnectionTypeID	<i>Type:</i> integer. Key The compliance connection type. Foreign key to the ConnectionType table.
ConnectionName	<i>Type:</i> text (max 128 characters). Key The internal, unique name of the connection.
ConnectionNameDisplayName	<i>Type:</i> text (max 64 characters) The name of the connection for display purposes.
UseFnmpDbServerAsSource	<i>Type:</i> boolean Use the FNMP database server as the source.
Server	<i>Type:</i> text (max 128 characters). Nullable The name of the SQL Server.
UseWindowsAuth	<i>Type:</i> boolean. Nullable If this field is set to True, the connection will use Windows authentication when connecting to the database. If False, SQL authentication will be used.
Username	<i>Type:</i> text (max 128 characters). Nullable The username to use when connecting with SQL authentication.
Password	<i>Type:</i> text. Nullable The password to use when connecting with SQL authentication.
DatabaseName	<i>Type:</i> text (max 128 characters). Nullable The name of the database to connect to.
ConnectionString	<i>Type:</i> text. Nullable The connection string used to connect to a datasource.

Database Column	Details
LastImportDate	<p><i>Type:</i> datetime. Nullable</p> <p>Date and time when data from this data source was successfully imported into the staging area (reader execution). The imported data may not have been applied to the core tables.</p>
LastImportStarted	<p><i>Type:</i> datetime. Nullable</p> <p>Date and time when the import from this data source started.</p>
LastImportEnded	<p><i>Type:</i> datetime. Nullable</p> <p>Date and time when the import from this data source ended.</p>
LastImportSuccessful	<p><i>Type:</i> boolean</p> <p>Whether or not the last import attempted for this datasource succeeded or failed.</p>
SourceType	<p><i>Type:</i> text (max 256 characters)</p> <p>The source database type (one of several predefined values, such as ManageSoft or SMS).</p>
SourceTypeDisplayName	<p><i>Type:</i> text (max 128 characters)</p> <p>A version of the SourceType field, that has been scoped to be specific to this connection.</p>
Signature	<p><i>Type:</i> text (max 128 characters)</p> <p>A connection signature optionally given by the source database. This allows the source database to identify its connection.</p>
PrimaryConnection	<p><i>Type:</i> boolean. Key</p> <p>Set this to True if this is the primary data source to import from. If computers or users exist in multiple connections, data from the primary connection is always given precedence.</p>
TestConnection	<p><i>Type:</i> boolean</p> <p>Indicate if this connection is a test connection. If this is set to True writer will not populate target FNMP tables with data in the imported tables from this connection. If this is set to False writer will populate data from this connection as is. Compliance Reader Editor UI sets connection as test so that test data would not accidentally be written to target FNMP tables.</p>
Enabled	<p><i>Type:</i> boolean</p> <p>Indicate if this connection is enabled. If this is set to False reader will not import data from this connection.</p>

Database Column	Details
GroupName	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>The GroupName represents subgroups of data from the source. For example, for a citrix connection, this stores a farm name. If this is Null, then there is no sub-grouping (import all).</p>
ExpiryPeriod	<p><i>Type:</i> integer. Nullable</p> <p>The number of days before considering records in ImportedComputer to be out of date and should be considered stale. NULL means use the Compliance Setting value StaleInventoryThreshold. 0 means always include device data regardless of age.</p>
PerformStaleInventory Check	<p><i>Type:</i> boolean</p> <p>Indicates if this connection needs to have the inventory checked to see if data is considered stale. It is reset to 1 after completing the reader's step of an import.</p>
IsRemote	<p><i>Type:</i> boolean</p> <p>Is this a remote connection, where the source side of the readers are running on a remote location (an Inventory Beacon)?</p>
ConnectionExID	<p><i>Type:</i> unique identifier. Key</p> <p>The externally unique identifier for this connection, that can be used by both an Inventory Beacon and the server to track a connection.</p>
BeaconUID	<p><i>Type:</i> unique identifier. Key. Nullable</p> <p>The unique ID of the beacon where this connection is running.</p>

ComplianceConnectionParameter Table


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 12: Database columns for ComplianceConnectionParameter table

Database Column	Details
ComplianceConnectionID	<i>Type:</i> integer. Key A unique identifier for a compliance connection.
Name	<i>Type:</i> text (max 256 characters). Key The name of the compliance connection parameter
Value	<i>Type:</i> text The value of the compliance connection parameter
Type	<i>Type:</i> text (max 64 characters) The type of compliance connection parameter

ComplianceCultureType Table

The ComplianceCultureType table holds all the different languages that FlexNet Manager Suite supports.

Table 13: Database columns for ComplianceCultureType table

Database Column	Details
CultureType	<i>Type:</i> text (max 12 characters). Key A unique identifier for a culture type.
DefaultCulture	<i>Type:</i> boolean Indicates whether this language is a default language on the system.
Installed	<i>Type:</i> boolean Indicates whether string for this language are installed.
DisplayName	<i>Type:</i> text (max 80 characters) The display name for this culture.

ComplianceOperator Table

ComplianceOperator stores the list of people (operators) authorized to use FlexNet Manager Suite. Operators need not be end-users of the enterprise.

Table 14: Database columns for ComplianceOperator table

Database Column	Details
ComplianceOperatorID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the operator.
OperatorLogin	<i>Type:</i> text (max 256 characters). Key The login (account name) of the operator. Usually of the form [domain\account].
OperatorName	<i>Type:</i> text (max 512 characters). Nullable The name of the operator.
IsEnabled	<i>Type:</i> boolean When False, this operator may not use FlexNet Manager Suite, even if he or she is assigned to roles granting them access.
Email	<i>Type:</i> text (max 200 characters). Nullable The operator's email address.
JobTitle	<i>Type:</i> text (max 128 characters). Nullable The job title of the end-user.
ComplianceUserID	<i>Type:</i> integer. Key. Nullable An optional link to an end-user in the system. Foreign key to the ComplianceUser table.
CreationUser	<i>Type:</i> text (max 128 characters). Nullable The operator who created the record.
CreationDate	<i>Type:</i> datetime The date the record was created.
UpdatedUser	<i>Type:</i> text (max 128 characters). Nullable The operator who last updated the record.
UpdatedDate	<i>Type:</i> datetime. Nullable The date the record was last updated.
BusinessReportingToken	<i>Type:</i> text (max 256 characters). Nullable A token that is issued to an operator to allow them to authenticate with the business reporting framework.

Database Column	Details
TenantID	<i>Type:</i> small integer. Nullable The default tenant that this operator works on. Note that there is no tenant-filtered view on this table.
GlobalOperator	<i>Type:</i> boolean Allows an operator to access all tenants.
Interactive	<i>Type:</i> boolean Non-interactive accounts are service accounts.
LastLogin	<i>Type:</i> datetime. Nullable Last login datetime.
LastLogout	<i>Type:</i> datetime. Nullable Last logout datetime.

ComplianceOperatorTenant Table

ComplianceOperatorTenant stores the list of people (operators) authorized to access a tenant.

Table 15: Database columns for ComplianceOperatorTenant table

Database Column	Details
ComplianceOperatorID	<i>Type:</i> integer. Key The operatorID that the permission will be granted for.
TenantId	<i>Type:</i> small integer. Key The tenantID that the operator will be granted access for.
CreationUser	<i>Type:</i> text (max 128 characters). Nullable The operator who created the record.
CreationDate	<i>Type:</i> datetime The date the record was created.
IsEnabled	<i>Type:</i> boolean When False, this operator may not use FlexNet Manager Suite, even if he or she is assigned to roles granting them access.

ComplianceResourceString Table

The ComplianceResourceString table holds all the strings that require translation.

Table 16: Database columns for ComplianceResourceString table

Database Column	Details
ResourceString	Type: text (max 256 characters). Key A unique identifier for a string.

ComplianceSetting Table

The ComplianceSetting table holds the settings for the configuration and business rules of the application. With the introduction of SettingName, ComplianceTenantSetting and OperatorTenantSetting tables, if new global setting is to be added to ComplianceSetting table, the ComplianceSettingID must not overlap with those defined in SettingName table.

Table 17: Database columns for ComplianceSetting table

Database Column	Details
ComplianceSettingID	<i>Type:</i> integer. Key. Generated ID A unique identifier for a setting.
SettingName	<i>Type:</i> text (max 128 characters). Key A primary key for the setting.
SettingValue	<i>Type:</i> text (max 512 characters) The setting that indicates specified behavior.

ComplianceTenantSetting Table

ComplianceTenantSetting is a multi-tenant table that stores configuration and business rules specific to each tenant.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 18: Database columns for ComplianceTenantSetting table

Database Column	Details
SettingNameID	Type: integer. Key ID of the setting name. Foreign key to the SettingName table.
SettingValue	Type: text (max 512 characters). Nullable Value of the setting.

ConfigurationFile Table

The ConfigurationFile table stores configuration files generated from the master configuration files used by FlexNet Manager Suite.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 19: Database columns for ConfigurationFile table

Database Column	Details
ConfigurationFileID	Type: integer. Key. Generated ID A unique identifier for a configuration file.
ConfigurationFileTypeID	Type: integer. Key The configuration file type. Foreign key to the ConfigurationFileType table.
Name	Type: text (max 100 characters) The name of the configuration file.
Revision	Type: integer The revision of the configuration file.
XMLFile	Type: text The content of the configuration file.

ConfigurationFileType Table

ConfigurationFileType is a static table storing the types of configuration files used by FlexNet Manager Suite.

Table 20: Database columns for ConfigurationFileType table

Database Column	Details
ConfigurationFileTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each ConfigurationFileType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = SQL Server• 2 = Other (the inventory source is another type of data store, like an Excel sheet or MS Access database).
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a configuration file type. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the type resource string has no translation.</p>

ConnectionType Table

ConnectionType is a static table storing the types of connection that can be used to import data into FlexNet Manager Suite.

Table 21: Database columns for ConnectionType table

Database Column	Details
ConnectionTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each ConnectionType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = SQL Server • 2 = Other (the inventory source is another type of data store, like an Excel sheet or MS Access database). • 5 = PowerShell
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a connection type. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the type resource string has no translation.</p>

Currency Table

Currency stores a collection of currencies that can be used for money values.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 22: Database columns for Currency table

Database Column	Details
CurrencyID	Type: integer. Key. Generated ID Unique identifier for a currency.
CurrencyName	Type: text (max 256 characters) Name of currency.
CurrencyResourceID	Type: text (max 64 characters). Nullable The resource string containing the name of this currency to display on the user interface.
CurrencyCode	Type: text (max 32 characters). Key Code assigned to currency.
LongPrefix	Type: text (max 32 characters) Long prefix to display in front of the money value.
LongSuffix	Type: text (max 32 characters) Long suffix to display after the money value.
LongFormat	Type: text (max 80 characters). Nullable Long format of the currency. This is a calculated field.
ShortPrefix	Type: text (max 32 characters) Short prefix to display in front of the money value.
ShortSuffix	Type: text (max 32 characters) Short suffix to display after the money value.
ShortFormat	Type: text (max 80 characters). Nullable Short format of the currency. This is a calculated field.
IsActive	Type: boolean. Key Indicates whether this currency is enabled.

Database Column	Details
Comments	<i>Type:</i> text. Nullable Operator comments about this currency.
Countries	<i>Type:</i> text (max 2048 characters). Nullable A semicolon-separated list of the country codes for countries to which this currency is applicable.
ActivationDate	<i>Type:</i> datetime. Nullable Date currency was enabled.
RetirementDate	<i>Type:</i> datetime. Nullable Date that currency was retired.
UpdatedUser	<i>Type:</i> text (max 256 characters). Nullable Operator who made the latest change to the currency record.
UpdatedDate	<i>Type:</i> datetime. Nullable Date that the currency record was changed.

MasterConfigurationFile Table

The MasterConfigurationFile table stores master configuration files used by FlexNet Manager Suite.

Table 23: Database columns for MasterConfigurationFile table

Database Column	Details
MasterConfigurationFileID	<i>Type:</i> integer. Key. Generated ID A unique identifier for a configuration file.
ConfigurationFileTypeID	<i>Type:</i> integer. Key The configuration file type. Foreign key to the ConfigurationFileType table.
Name	<i>Type:</i> text (max 100 characters) The name of the configuration file.
Revision	<i>Type:</i> integer The revision of the configuration file.
XMLFile	<i>Type:</i> text The content of the configuration file.

OperatorTenantSetting Table

OperatorTenantSetting is a multi-tenant table that stores configuration and preferences for each operator per tenant


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 24: Database columns for OperatorTenantSetting table

Database Column	Details
OperatorTenantSettingID	<i>Type:</i> integer. Key. Generated ID Unique identifier of an operator tenant setting, this is a primary key.
ComplianceOperatorID	<i>Type:</i> integer. Key The operator of the setting. Foreign key to the ComplianceOperator table.
SettingNameID	<i>Type:</i> integer. Key ID of the setting name. Foreign key to the SettingName table.
SettingValue	<i>Type:</i> text (max 512 characters). Nullable Value of the setting.

ResourceStringCultureType Table

The ResourceStringCultureType table holds all translations of all the resource strings.

Table 25: Database columns for ResourceStringCultureType table

Database Column	Details
ResourceString	<i>Type:</i> text (max 256 characters). Key A unique identifier for a resource string. Foreign key to the ComplianceResourceString table.
CultureType	<i>Type:</i> text (max 12 characters). Key A unique identifier for a culture type. Foreign key to the ComplianceCultureType table.
ResourceValue	<i>Type:</i> text (max 1000 characters) A translated resource string.

RightDefinition Table

RightDefinition defines additional access rights that supplement the built-in rights.

Table 26: Database columns for RightDefinition table

Database Column	Details
RightDefinitionID	<i>Type:</i> integer. Key. Generated ID A unique identifier for a right definition.
ResourceName	<i>Type:</i> text (max 16 characters). Key Resource (such as inventory, usage tracking, and so on) that access right relates to. Foreign key to the Resource table.
ActionClassName	<i>Type:</i> text (max 16 characters). Key Action class (such as modify, read, and so on) of access right. Foreign key to the ActionClass table.
ParentFeature	<i>Type:</i> text (max 50 characters) The product feature to which this access right applies.
Title	<i>Type:</i> text (max 1000 characters) Default value for access right title.
TitleResourceString	<i>Type:</i> text (max 256 characters). Key. Nullable The unique name of the localizable resource string representing an access right. Foreign key to the ComplianceResourceString table.
MinAccessType	<i>Type:</i> text (max 50 characters). Nullable Minimum access type that allows this right. Possible values include NoAccess, ReadOnlyAccess, NormalAccess, AdministratorAccess and CustomAccess.
DisplayIndex	<i>Type:</i> integer. Nullable Order in which rights are displayed (smaller numbers are displayed first). FlexNet Manager Suite built-in rights have the value 100.

SettingName Table

SettingName is a static table containing ids of setting names that are referenced by ComplianceTenantSetting and OperatorTenantSetting tables. As settings in ComplianceSetting table is migrated to either ComplianceTenantSetting and OperatorTenantSetting, ComplianceSetting table will be changed to refer to this table as well for global settings.

Table 27: Database columns for SettingName table

Database Column	Details
SettingNameID	Type: integer. Key. Generated ID A unique identifier for a setting name.
Name	Type: text (max 128 characters). Key Name of the setting.

TimezoneType Table

This table stores a collection of timezonetypes.

Table 28: Database columns for TimezoneType table

Database Column	Details
TimezoneTypeID	<i>Type:</i> integer. Key. Generated ID Unique identifier for a TimezoneType.
TimezoneID	<i>Type:</i> text (max 128 characters) The .NET representation of the time zone id.
ResourceName	<i>Type:</i> text (max 256 characters). Nullable The unique name of the localizable resource string representing a timezone type. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 256 characters) The default display timezone name

Compliance.Logic.Assets Tables

The complete set of database tables documented here includes:

- AcquisitionMode table (see [AcquisitionMode Table](#))
- Asset table (see [Asset Table](#))
- AssetComplianceColumn table (see [AssetComplianceColumn Table](#))
- AssetComplianceStatus table (see [AssetComplianceStatus Table](#))
- AssetContract table (see [AssetContract Table](#))
- AssetPropertyValue table (see [AssetPropertyValue Table](#))
- AssetPurchaseOrder table (see [AssetPurchaseOrder Table](#))
- AssetStatus table (see [AssetStatus Table](#))
- AssetType table (see [AssetType Table](#))
- AssetTypeProperty table (see [AssetTypeProperty Table](#))
- AssetWarrantyType table (see [AssetWarrantyType Table](#))
- DepreciationMethod table (see [DepreciationMethod Table](#))
- EndOfLifeReason table (see [EndOfLifeReason Table](#))
- LeaseEndReason table (see [LeaseEndReason Table](#))

AcquisitionMode Table

AcquisitionMode is a static table listing all the methods by which a company may obtain an asset.

Table 29: Database columns for AcquisitionMode table

Database Column	Details
AcquisitionModeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each AcquisitionMode. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = Purchased • 2 = Leased • 3 = Rented • 4 = Loaned.
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing an acquisition mode. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the mode resource string has no translation.</p>

Asset Table

The Asset table contains details of all the assets being managed within FlexNet Manager Suite.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 30: Database columns for Asset table

Database Column	Details
AssetID	<i>Type:</i> integer. Key. Generated ID A unique identifier for an asset.
ParentAssetID	<i>Type:</i> integer. Key. Nullable The parent asset. Foreign key to another asset in this same Asset table.
ShortDescription	<i>Type:</i> text (max 256 characters) A brief description of the asset.
SerialNumber	<i>Type:</i> text (max 150 characters). Key. Nullable The serial number of the asset.
AssetTypeID	<i>Type:</i> integer. Key The asset type. Foreign key to the AssetType table.
AssetTag	<i>Type:</i> text (max 256 characters). Nullable A user-defined asset tag for a particular asset. This may be a barcode number.
AssetStatusID	<i>Type:</i> integer. Key The status of the asset. Defaults to Purchased. Foreign key to the AssetStatus table.
PurchasePrice	<i>Type:</i> currency. Nullable The purchase price of the asset.
PurchasePriceRateID	<i>Type:</i> integer. Nullable The currency rate to apply to the purchase price of the asset. Foreign key to the CurrencyRate table.
AcquisitionModeID	<i>Type:</i> integer. Nullable The method of acquisition used for the asset. Defaults to Purchased. Foreign key to the AcquisitionMode table.

Database Column	Details
PrimaryPurchaseOrderNo	<i>Type:</i> text (max 50 characters). Nullable The purchase order number which was used to purchase the asset.
PrimaryPurchaseOrderDate	<i>Type:</i> datetime. Nullable The date the primary purchase order was made.
VendorID	<i>Type:</i> integer. Key. Nullable The vendor from whom the asset was purchased. Foreign key to the Vendor table.
Manufacturer	<i>Type:</i> text (max 200 characters). Nullable The manufacturer of the asset.
ManufacturerPartNo	<i>Type:</i> text (max 100 characters). Nullable The manufacturer's part number for this asset.
ModelNo	<i>Type:</i> text (max 200 characters). Nullable The model number of the asset.
DeliveryDate	<i>Type:</i> datetime. Nullable The date the asset was received.
AssetWarrantyTypeID	<i>Type:</i> integer The type of warranty for the asset. Defaults to None. Foreign key to the AssetWarrantyType table.
WarrantyExpirationDate	<i>Type:</i> datetime. Nullable The date the warranty expires.
InstallationDate	<i>Type:</i> datetime. Nullable The date the asset was installed.
RetirementDate	<i>Type:</i> datetime. Nullable The date the asset was retired.
DisposalDate	<i>Type:</i> datetime. Nullable The date the asset was disposed of.
DeletionDate	<i>Type:</i> datetime. Nullable The date the asset was deleted.
InventoryDate	<i>Type:</i> datetime. Nullable The date the asset last had inventory reported.
InventoryAgent	<i>Type:</i> text (max 64 characters). Nullable The name of the person or tool that performed the last inventory.

Database Column	Details
InventoryDateManual	<i>Type:</i> datetime. Nullable The date the asset last had inventory updated (entered) manually.
InventoryAgentManual	<i>Type:</i> text (max 64 characters). Nullable The name of the person or tool that performed the last manual inventory.
RequestNo	<i>Type:</i> text (max 60 characters). Nullable The request number for the asset.
PartNo	<i>Type:</i> text (max 100 characters). Nullable The vendor's part number for this asset.
IsLeased	<i>Type:</i> boolean Flag to indicate if this asset is leased. This field is no longer in use in FlexNet Manager Suite.
LeaseNo	<i>Type:</i> text (max 60 characters). Nullable The contract number of the lease agreement for this asset.
LeaseName	<i>Type:</i> text (max 100 characters). Nullable A contract name of the lease agreement for this asset.
LeaseStartDate	<i>Type:</i> datetime. Nullable The start date of the lease for this asset.
LeaseEndDate	<i>Type:</i> datetime. Nullable The end date of the lease for this asset.
LeaseTerminationDate	<i>Type:</i> datetime. Nullable The date that the lease for this asset is terminated.
LeaseEndReasonID	<i>Type:</i> integer The reason for the end of lease for this asset.
LeasePrice	<i>Type:</i> currency. Nullable The purchase price of the lease for this individual asset.
LeasePriceRateID	<i>Type:</i> integer. Nullable The purchase price of the lease currency rate for this individual asset.
LeasePeriodicPayment	<i>Type:</i> currency. Nullable The price of periodic payments associated with this contract.
LeasePeriodicPayment RateID	<i>Type:</i> integer. Nullable The price of periodic payments currency rate associated with this contract.

Database Column	Details
LeasePeriodTypeID	<i>Type:</i> integer The frequency with which the lease payments are applicable.
LeaseBuyoutCost	<i>Type:</i> currency. Nullable The buyout cost of the lease for this asset.
LeaseBuyoutCostRateID	<i>Type:</i> integer. Nullable The buyout cost of the lease currency rate associated for this asset.
LeaseComments	<i>Type:</i> text. Nullable Comments recorded about the lease for this asset. This field is no longer in use in FlexNet Manager Suite.
AssignToUserID	<i>Type:</i> integer. Key. Nullable The end-user the asset has been assigned to. Foreign key to the ComplianceUser table.
Comments	<i>Type:</i> text. Nullable Comments entered about the asset.
ChargeBackPrice	<i>Type:</i> currency. Nullable Amount to be charged back for the use of this asset. No calculations based on this charge and the frequency will be provided.
ChargeBackPriceRateID	<i>Type:</i> integer. Nullable The currency rate to be applied to the charge back value of the asset. Foreign key to the CurrencyRate table.
ChargeBackPeriodTypeID	<i>Type:</i> integer The frequency with which the charge back price is charged. Defaults to None. Foreign key to the PeriodType table.
EndOfLifeRecipient	<i>Type:</i> text (max 128 characters). Nullable The person or organization who received the asset when it was disposed of.
EndOfLifeReasonID	<i>Type:</i> integer The reason the asset was disposed of. Foreign key to the EndOfLifeReason table.
ResalePrice	<i>Type:</i> currency. Nullable The amount the asset was sold for.
ResalePriceRateID	<i>Type:</i> integer. Nullable The currency rate to be applied to the resale price of the asset. Foreign key to the CurrencyRate table.

Database Column	Details
CreationUser	<i>Type:</i> text (max 128 characters). Nullable The operator who created the record.
CreationDate	<i>Type:</i> datetime The date the record was created.
UpdatedUser	<i>Type:</i> text (max 128 characters). Nullable The operator who last updated the record.
UpdatedDate	<i>Type:</i> datetime. Nullable The date the record was last updated.
LocationID	<i>Type:</i> text (max 128 characters). Key. Nullable Any enterprise location associated with this asset. Foreign key to the GroupEx table.
BusinessUnitID	<i>Type:</i> text (max 128 characters). Key. Nullable Any corporate unit in the enterprise associated with this asset. Foreign key to the GroupEx table.
CostCenterID	<i>Type:</i> text (max 128 characters). Key. Nullable Any cost center in the enterprise associated with this asset. Foreign key to the GroupEx table.
CategoryID	<i>Type:</i> text (max 128 characters). Key. Nullable Any enterprise category associated with this asset. Foreign key to the GroupEx table.
DepreciationCurrentValue	<i>Type:</i> currency. Nullable The current value of the asset, after depreciation has been applied.
DepreciationCurrent ValueRateID	<i>Type:</i> integer. Nullable The currency rate to be applied to the depreciation current value of the asset. Foreign key to the CurrencyRate table.
DepreciationResidualValue	<i>Type:</i> currency. Nullable The residual value of the asset (value when fully depreciated).
DepreciationResidual ValueRateID	<i>Type:</i> integer. Nullable The currency rate to be applied to the residual value of the asset. Foreign key to the CurrencyRate table.
DepreciationMethodID	<i>Type:</i> integer. Nullable The depreciation method (straight line or residual value). Foreign key to the DepreciationMethod table.

Database Column	Details
DepreciationPeriod	<p><i>Type:</i> integer</p> <p>The depreciation period (in years), for customers to use for straight line depreciation.</p>
DepreciationRate	<p><i>Type:</i> decimal. Nullable</p> <p>The annual depreciation rate (as a percentage - like 50% per year), for customers to use for residual value depreciation. Stored as a value between 0 (for 0%) and 1 (for 100%).</p>
WrittenOffValue	<p><i>Type:</i> currency. Nullable</p> <p>The written-off value is the value of the asset at the time of retirement/disposal.</p>
WrittenOffValueRateID	<p><i>Type:</i> integer. Nullable</p> <p>The currency rate to be applied to the written-off value of the asset. Foreign key to the CurrencyRate table.</p>

AssetComplianceColumn Table

The AssetComplianceColumn table lists the columns (or aspects of the asset record) for which compliance changes can be tracked.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 31: Database columns for AssetComplianceColumn table

Database Column	Details
AssetComplianceColumnID	<p>Type: integer. Key. Generated ID</p> <p>A unique identifier for each AssetComplianceColumn. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = Operating System• 2 = Service Pack• 3 = Number of Processors• 4 = Processor Type• 5 = Max Clock Speed• 6 = Total Memory• 7 = Chassis Type• 8 = Number of Hard Drives• 9 = Total Disk Size• 10 = Number of Network Cards• 11 = Number of Display Adapters• 12 = IP Address• 13 = MAC Address• 14 = Host• 15 = Number of Cores• 16 = Number of Threads.
ColumnNameResourceName	<p>Type: text (max 256 characters). Nullable</p> <p>The unique name of the localizable resource string representing a compliance-tracked column. Foreign key to the ComplianceResourceString table.</p>

Database Column	Details
ColumnName	<i>Type:</i> text (max 128 characters). Key The text to display if the column resource string has no translation.
IsColumnNumeric	<i>Type:</i> boolean Indicates whether the column is numeric (True) or a string (False).
ComplianceAction	<i>Type:</i> integer Bitwise value to indicate what type of action to track change on.
TrackComplianceBitwise Value	<i>Type:</i> integer Bitwise value indicating which asset types compliance tracking is turned on for.

AssetComplianceStatus Table

AssetComplianceStatus is a static table listing possible asset compliance states, such as compliant, new, changed, or ignored.

Table 32: Database columns for AssetComplianceStatus table

Database Column	Details
AssetComplianceStatusID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each AssetComplianceStatus. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = New• 2 = Compliant• 3 = Changed• 4 = Ignore.
StatusResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing an asset compliance status. Foreign key to the ComplianceResourceString table.</p>
StatusDefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the status resource string has no translation.</p>

AssetContract Table

The AssetContract table links assets to related contracts.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 33: Database columns for AssetContract table

Database Column	Details
AssetContractID	<i>Type:</i> integer. Key. Generated ID A unique identifier for this record.
ContractID	<i>Type:</i> integer. Key The contract linked to the asset. Foreign key to the Contract table.
AssetID	<i>Type:</i> integer. Key The asset linked to the contract. Foreign key to the Asset table.

AssetPropertyValue Table

For each asset, AssetPropertyValue stores the values for the custom properties defined in AssetTypeProperty.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 34: Database columns for AssetPropertyValue table

Database Column	Details
AssetPropertyValueID	Type: integer. Key. Generated ID A unique identifier for this record.
AssetTypePropertyID	Type: integer. Key The property whose value is being stored. The type of the asset should match the type that the property is associated with. Foreign key to the AssetTypeProperty table.
AssetID	Type: integer. Key The asset associated with the property value. Foreign key to the Asset table.
PropertyValue	Type: text (max 4000 characters) The value of the property for the specified Asset.
CreationUser	Type: text (max 128 characters). Nullable The operator who created the record.
CreationDate	Type: datetime The date the record was created.
UpdatedUser	Type: text (max 128 characters). Nullable The operator who last updated the record.
UpdatedDate	Type: datetime. Nullable The date the record was last updated.

AssetPurchaseOrder Table

The AssetPurchaseOrder table links assets to related purchase order lines.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 35: Database columns for AssetPurchaseOrder table

Database Column	Details
AssetID	Type: integer. Key The asset linked to a purchase order. Foreign key to the Asset table.
PurchaseOrderDetailID	Type: integer. Key The purchase order line linked to an asset. Foreign key to the PurchaseOrderDetail table.

AssetStatus Table

AssetStatus is a static table storing a list of possible asset states, such as purchased, in storage, installed, retired, disposed and other.

Table 36: Database columns for AssetStatus table

Database Column	Details
AssetStatusID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each AssetStatus. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = Purchased• 2 = In Storage• 3 = Installed• 4 = Retired• 5 = Disposed• 6 = Other.
StatusResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing an asset status. Foreign key to the ComplianceResourceString table.</p>
StatusDefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the status resource string has no translation.</p>

AssetType Table

AssetType stores the collection of the types of assets that can be created in FlexNet Manager Suite.

Table 37: Database columns for AssetType table

Database Column	Details
AssetTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each AssetType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = Workstation • 2 = Server • 3 = Monitor • 4 = Desk • 5 = Chair • 6 = Printer • 7 = Router • 8 = Switch • 9 = Telephone • 10 = Cell phone • 11 = Laptop. • 12 = Mobile Device.
AssetTypeResourceName	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>The unique name of the localizable resource string representing a document type. Foreign key to the ComplianceResourceString table.</p>
AssetTypeName	<p><i>Type:</i> text (max 64 characters). Key</p> <p>The text to display if the type resource string has no translation.</p>
XMLFile	<p><i>Type:</i> text. Nullable</p> <p>The layout of the property dialog for this type of asset, stored in XML format.</p>
ParentAssetTypeID	<p><i>Type:</i> integer. Nullable</p> <p>An asset type which is a parent of this asset type. Foreign key to the same AssetType table.</p>

Database Column	Details
ManagedType	<i>Type:</i> boolean. Key Set this field to True if this type of asset is directly managed by FlexNet Manager Suite (for example, laptops, servers and workstations).
BitwiseValue	<i>Type:</i> integer The bitwise value of the asset type. This value is used when tracking compliance changes for assets linked to computers.

AssetTypeProperty Table

AssetTypeProperty defines extra custom properties for all assets.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 38: Database columns for AssetTypeProperty table

Database Column	Details
AssetTypePropertyID	Type: integer. Key. Generated ID A unique identifier for a property of an asset type.
PropertyName	Type: text (max 256 characters). Key The name of the property.
AssetTypeID	Type: integer. Key. Nullable Asset type with which this property is associated. Foreign key to the AssetType table.
HardwareClassName	Type: text (max 256 characters). Nullable The WMI class name associated with this property. This field applies for hardware properties that are mapped to hardware inventory tables.
HardwarePropertyName	Type: text (max 256 characters) The WMI property name associated with this property. This field applies for hardware properties that are mapped to hardware inventory tables.
CustomPropertyDisplayXMLID	Type: integer. Nullable Foreign key to a record in the CustomPropertyDisplayXML table, describing how to show the property on a property dialog.

AssetWarrantyType Table

AssetWarrantyType is a static table listing all the types of warranties.

Table 39: Database columns for AssetWarrantyType table

Database Column	Details
AssetWarrantyTypeID	<i>Type:</i> integer. Key. Generated ID A unique identifier for each AssetWarrantyType. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• 1 = None• 2 = One year on site• 3 = Three years on site.
WarrantyTypeResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing an asset warranty type. Foreign key to the ComplianceResourceString table.
WarrantyTypeDefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the type resource string has no translation.

DepreciationMethod Table

DepreciationMethod is a static table storing the collection of available depreciation methods.

Table 40: Database columns for DepreciationMethod table

Database Column	Details
DepreciationMethodID	<i>Type:</i> integer. Key. Generated ID A unique identifier for each DepreciationMethod. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• 1 = Straight line• 2 = Residual value.
ResourceName	<i>Type:</i> text (max 50 characters). Key The unique name of the localizable resource string representing a depreciation method. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the method resource string has no translation.

EndOfLifeReason Table

EndOfLifeReason is a static table storing the collection of all reasons for disposing of an asset.

Table 41: Database columns for EndOfLifeReason table

Database Column	Details
EndOfLifeReasonID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each EndOfLifeReason. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = [empty string] • 2 = Lost • 3 = Stolen • 4 = Disposed • 5 = Sold • 6 = Donated • 7 = Broken.
ResourceName	<p><i>Type:</i> text (max 50 characters). Key</p> <p>The unique name of the localizable resource string representing an end-of-life reason. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the reason resource string has no translation.</p>

LeaseEndReason Table

LeaseEndReason is a static table listing all the reasons that a company terminates a lease.

Table 42: Database columns for LeaseEndReason table

Database Column	Details
LeaseEndReasonID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each LeaseEndReason. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = [empty string]• 2 = Lease Ended - Asset Returned• 3 = Early Termination - Asset Returned• 4 = Buyout• 5 = Early Buyout• 6 = Trade.
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a lease-end reason. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the reason resource string has no translation.</p>

Compliance.Logic.Beacon Tables

The complete set of database tables documented here includes:

- ActiveDirectoryComputer table (see [ActiveDirectoryComputer Table](#))
- ActiveDirectoryDomain table (see [ActiveDirectoryDomain Table](#))
- ActiveDirectoryGroup table (see [ActiveDirectoryGroup Table](#))
- ActiveDirectoryMember table (see [ActiveDirectoryMember Table](#))
- ActiveDirectoryUser table (see [ActiveDirectoryUser Table](#))
- AdministrationAccount table (see [AdministrationAccount Table](#))
- AppVPackageMapping table (see [AppVPackageMapping Table](#))
- AvailablePackage table (see [AvailablePackage Table](#))
- AvailablePackageType table (see [AvailablePackageType Table](#))
- BaselineImport table (see [BaselineImport Table](#))
- Beacon table (see [Beacon Table](#))
- BeaconActivityStatus table (see [BeaconActivityStatus Table](#))
- BeaconAdministrationAccount table (see [BeaconAdministrationAccount Table](#))
- BeaconAgentEvent table (see [BeaconAgentEvent Table](#))
- BeaconDiscoveryStatus table (see [BeaconDiscoveryStatus Table](#))
- BeaconDiscoveryTaskSummaryStatus table (see [BeaconDiscoveryTaskSummaryStatus Table](#))
- BeaconDownloadedPolicy table (see [BeaconDownloadedPolicy Table](#))
- BeaconExecutionStatusType table (see [BeaconExecutionStatusType Table](#))
- BeaconFilter table (see [BeaconFilter Table](#))
- BeaconIssueStatus table (see [BeaconIssueStatus Table](#))
- BeaconIssueStatusType table (see [BeaconIssueStatusType Table](#))
- BeaconPolicy table (see [BeaconPolicy Table](#))
- BeaconPolicyPropertyValue table (see [BeaconPolicyPropertyValue Table](#))
- BeaconPropertyValue table (see [BeaconPropertyValue Table](#))
- BeaconRule table (see [BeaconRule Table](#))
- BeaconRuleAction table (see [BeaconRuleAction Table](#))
- BeaconRuleActionPropertyValue table (see [BeaconRuleActionPropertyValue Table](#))

- BeaconRuleBeaconTargetMapping table (see [BeaconRuleBeaconTargetMapping Table](#))
- BeaconSiteSubnetMapping table (see [BeaconSiteSubnetMapping Table](#))
- BeaconTarget table (see [BeaconTarget Table](#))
- BeaconTargetAgentEvent table (see [BeaconTargetAgentEvent Table](#))
- BeaconTargetDiscoveredDeviceMapping table (see [BeaconTargetDiscoveredDeviceMapping Table](#))
- BeaconTargetPropertyValue table (see [BeaconTargetPropertyValue Table](#))
- BeaconTargetSiteMapping table (see [BeaconTargetSiteMapping Table](#))
- BeaconTargetSiteSubnetMapping table (see [BeaconTargetSiteSubnetMapping Table](#))
- BeaconUpgradeMode table (see [BeaconUpgradeMode Table](#))
- BeaconUpgradeStatus table (see [BeaconUpgradeStatus Table](#))
- BeaconWebServerStatus table (see [BeaconWebServerStatus Table](#))
- DiscoveredDeviceDiscoveredBy table (see [DiscoveredDeviceDiscoveredBy Table](#))
- DiscoveredDeviceDiscoveryStatus table (see [DiscoveredDeviceDiscoveryStatus Table](#))
- DiscoveredDeviceInventoryStatus table (see [DiscoveredDeviceInventoryStatus Table](#))
- DiscoveredDeviceTaskDetailedError table (see [DiscoveredDeviceTaskDetailedError Table](#))
- DiscoveredDeviceTaskStatus table (see [DiscoveredDeviceTaskStatus Table](#))
- DiscoveredDeviceTaskStatusHistory table (see [DiscoveredDeviceTaskStatusHistory Table](#))
- DiscoveredDeviceTaskType table (see [DiscoveredDeviceTaskType Table](#))
- ErrorCategory table (see [ErrorCategory Table](#))
- FNMEAAGent table (see [FNMEAAGent Table](#))
- IncomingBaseline table (see [IncomingBaseline Table](#))
- ReconcileSoftwareLicenseReconcileExemptionReason table (see [ReconcileSoftwareLicenseReconcileExemptionReason Table](#))
- RuleDiscoveryActionSummary table (see [RuleDiscoveryActionSummary Table](#))
- RuleInventoryActionSummary table (see [RuleInventoryActionSummary Table](#))
- SoftwareLicenseReconcileExemptionReasonData table (see [SoftwareLicenseReconcileExemptionReasonData Table](#))
- StatusCodeCategory table (see [StatusCodeCategory Table](#))
- UIAlignmentType table (see [UIAlignmentType Table](#))
- UIFieldType table (see [UIFieldType Table](#))
- UIInsertType table (see [UIInsertType Table](#))

- UIItem table (see [UIItem Table](#))
- UIItemTargetSubType table (see [UIItemTargetSubType Table](#))

ActiveDirectoryComputer Table

The ActiveDirectoryComputer table stores the active directory data for computers.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 43: Database columns for ActiveDirectoryComputer table

Database Column	Details
ActiveDirectoryComputerID	<i>Type:</i> integer. Key. Generated ID Auto-generated Active Directory computer ID
GUID	<i>Type:</i> unique identifier. Key The GUID of the computer.
ComputerName	<i>Type:</i> text (max 64 characters) The computer name.
ActiveDirectoryDomainID	<i>Type:</i> integer. Key Foreign key to the ActiveDirectoryDomain table
SID	<i>Type:</i> text (max 256 characters). Key. Nullable The SID of the computer.

ActiveDirectoryDomain Table

The ActiveDirectoryDomain table stores the active directory domains.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 44: Database columns for ActiveDirectoryDomain table

Database Column	Details
ActiveDirectoryDomainID	Type: integer. Key. Generated ID Auto-generated Active Directory Domain ID
QualifiedName	Type: text (max 100 characters). Key The fully qualified domain name
FlatName	Type: text (max 32 characters) The domain flat name

ActiveDirectoryGroup Table

The ActiveDirectoryGroup table stores the active directory data.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 45: Database columns for ActiveDirectoryGroup table

Database Column	Details
ActiveDirectoryGroupID	Type: integer. Key. Generated ID Auto-generated Active Directory Group ID
GUID	Type: unique identifier. Key The GUID of the AD group.
SID	Type: text (max 256 characters). Key. Nullable The SID of the AD group.
Name	Type: text (max 128 characters). Nullable The AD group name
ActiveDirectoryDomainID	Type: integer. Key Foreign key to the ActiveDirectoryDomain table

ActiveDirectoryMember Table

The ActiveDirectoryMember table stores the active directory data for AD member objects.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 46: Database columns for ActiveDirectoryMember table

Database Column	Details
GUID	Type: unique identifier. Key The GUID of the member object.
ParentGroupGUID	Type: unique identifier. Key The parent AD group GUID.

ActiveDirectoryUser Table

The ActiveDirectoryUser table stores the active directory data for users.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 47: Database columns for ActiveDirectoryUser table

Database Column	Details
ActiveDirectoryUserID	Type: integer. Key. Generated ID Auto-generated Active Directory user ID
GUID	Type: unique identifier. Key The GUID of the user.
SAMAccountName	Type: text (max 20 characters). Key The user name.
ActiveDirectoryDomainID	Type: integer. Key Foreign key to the ActiveDirectoryDomain table
Sid	Type: text (max 256 characters). Key. Nullable The SID of the user.

AdministrationAccount Table

Records the complete set of administration accounts configured on inventory beacons.

Table 48: Database columns for AdministrationAccount table

Database Column	Details
AccountID	Type: integer. Key. Generated ID Unique id for the account.
AccountName	Type: text (max 256 characters). Key The logical name of the account.

AppVPackageMapping Table

The AppVPackageMapping table is a table that maps App-V 4.6 packages to installer evidence.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 49: Database columns for AppVPackageMapping table

Database Column	Details
AppVPackageMappingID	Type: integer. Key. Generated ID Auto-generated App-V 4.6 package mapping ID.
PackageName	Type: text (max 256 characters). Key The App-V 4.6 package name.
PackageVersion	Type: text (max 128 characters). Key The App-V 4.6 package version.
DisplayName	Type: text (max 256 characters) The display name of the software as reported by the installer evidence.
Version	Type: text (max 72 characters) The version of the software as reported by the installer evidence.
Publisher	Type: text (max 200 characters) The publisher of the software as reported by the installer evidence.

AvailablePackage Table

Packages which are available to beacons.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 50: Database columns for AvailablePackage table

Database Column	Details
AvailablePackageID	Type: integer. Key. Generated ID The ID of the available package.
FullName	Type: text (max 256 characters). Key The full path of the package within the repository.
Version	Type: text (max 32 characters). Key The version of the package.
AvailablePackageTypeID	Type: integer. Key The type of the package. Foreign key to the AvailablePackageType table.
RelativeURLToOSD	Type: text (max 256 characters) The relative URL to the OSD of the package for use in inventory agent policy.
UseInAgentPolicy	Type: boolean Whether the package should be added to policy for inventory agents.
Build	Type: text (max 8 characters). Key The build number of the package, necessary for choosing between patched versions of the same release.
WebUIRelativeURL	Type: text (max 256 characters). Nullable The relative URL to download the package from WebUI

AvailablePackageType Table

Table 51: Database columns for AvailablePackageType table

Database Column	Details
AvailablePackageTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each AvailablePackageType. Possible values are:</p> <ul style="list-style-type: none"> • 1 = Adoption • 2 = Upgrade • 3 = Inventory agent plugin • 4 = Software • 5 = Other • 6 = Inventory beacon upgrade
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a purchase order line item type. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the type resource string has no translation.</p>

BaselineImport Table


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 52: Database columns for BaselineImport table

Database Column	Details
BaselineImportID	<i>Type:</i> integer. Key. Generated ID The baseline import ID
Type	<i>Type:</i> text (max 16 characters) The baseline type
Date	<i>Type:</i> datetime The date of the baseline import
PurchaseOrderID	<i>Type:</i> integer. Key. Nullable The purchase order for the baseline import
ComplianceOperatorID	<i>Type:</i> integer. Key The compliance operator who performed the baseline import

Beacon Table

The Beacon table contains beacon definition.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 53: Database columns for Beacon table

Database Column	Details
BeaconID	Type: integer. Key. Generated ID Unique ID assigned to each beacon.
BeaconUID	Type: unique identifier. Key Unique string ID of the beacon.
BeaconName	Type: text (max 64 characters) Name of the beacon.
BeaconDescription	Type: text (max 256 characters). Nullable Description of the beacon.
BeaconStatus	Type: boolean Boolean indicating to include or exclude Beacon.
LastKnownActivityTime	Type: datetime. Nullable Last known time that communication has been received from the beacon.
ActivityStatusID	Type: integer Last known activity status reported by the beacon.
PolicyDownloadedTime	Type: datetime. Nullable Policy downloaded time
CurrentPolicyRevisionNo	Type: integer. Nullable Last downloaded policy revision number
BeaconLocation	Type: text (max 256 characters). Nullable Location field for Beacon.
PrimaryParentUID	Type: unique identifier. Nullable The parent of the Beacon. For the core Beacon, the PrimaryParentUID is NULL.

Database Column	Details
BeaconPassword	<i>Type:</i> text (max 64 characters). Nullable The password used by the beacon to authenticate with.
HTTPAccessData	<i>Type:</i> text. Nullable The HTTPEndPointStatus object, used for storing a summary of how to access the sahres on this beacon.
UpgradeModeID	<i>Type:</i> integer The upgrade mode selected for this beacon.
UpgradeStatusID	<i>Type:</i> integer The latest information reported by a beacon about any upgrade activity or changes.
LastKnownPolicy	<i>Type:</i> datetime. Nullable The last known time that the beacon has communicated with the server.
Version	<i>Type:</i> text (max 50 characters). Nullable Version of installed beacon on the server
WebServerStatusID	<i>Type:</i> integer The last known time that the beacon has communicated with the server.
UpgradeStatusTime	<i>Type:</i> datetime. Nullable The time the last upgrade status was reported.
AvailablePackageID	<i>Type:</i> integer. Key. Nullable If the beacon upgrade mode is set to specific version, then this stored the specific package to upgrade to.
ParentServerURL	<i>Type:</i> text. Nullable The parent to which this beacon will communicate with.
DownloadURL	<i>Type:</i> text. Nullable The download URL of the parent.
UploadURL	<i>Type:</i> text. Nullable The upload URL of the parent.

BeaconActivityStatus Table

BeaconActivityStatus is a static table listing all of the states of a beacon.

Table 54: Database columns for BeaconActivityStatus table

Database Column	Details
BeaconActivityStatusID	<i>Type:</i> integer. Key. Generated ID
ResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing the BeaconActivityStatus record. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 256 characters) The text to display if the state resource string has no translation.

BeaconAdministrationAccount Table

Records an administration account discovered on an inventory beacon.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 55: Database columns for BeaconAdministrationAccount table

Database Column	Details
AccountID	Type: integer. Key Unique id for the account.
ServerUID	Type: unique identifier. Key Identifies the distribution server which discovered the account.

BeaconAgentEvent Table

The BeaconAgentEvent table contains a list of events that can be included in agent schedules.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 56: Database columns for BeaconAgentEvent table

Database Column	Details
BeaconAgentEventID	<i>Type:</i> integer. Key. Generated ID Unique ID assigned to each beacon agent event.
EventName	<i>Type:</i> text (max 256 characters). Key Event name.
EventUID	<i>Type:</i> unique identifier. Key Event uid.
Value	<i>Type:</i> text An XML representation of the agent event data.

BeaconDiscoveryStatus Table

Discovery and remote execution status of Beacon


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 57: Database columns for BeaconDiscoveryStatus table

Database Column	Details
BeaconDiscoveryStatusID	Type: integer. Key. Generated ID The ID of the beacon discovery status.
ServerUID	Type: unique identifier. Key The inventory beacon that has run the task.
State	Type: text (max 256 characters) State of the discovery/execution - Running/Finished.
StartDateTime	Type: datetime Execution start time.
Duration	Type: integer Duration in Seconds of the discovery execution.
DiscoveredCount	Type: integer Total number of devices discovered.
ExecutionSuccess	Type: integer Total number successful remote executions.
ExecutionFailure	Type: integer Total number failed remote executions.

BeaconDiscoveryTaskSummaryStatus Table

Task summary list for a particular beacon


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 58: Database columns for BeaconDiscoveryTaskSummaryStatus table

Database Column	Details
TaskSummaryStatusID	Type: integer. Key. Generated ID The ID of the device status.
BeaconDiscoveryStatusID	Type: integer. Key The beacon discovery status table which this refers to.
TaskTypeID	Type: integer The type of task which was run.
SuccessCount	Type: integer Success count in this particular execution.
FailureCount	Type: integer Failure count in this particular execution.

BeaconDownloadedPolicy Table

The BeaconDownloadedPolicy table contains policies downloaded by inventory beacons.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 59: Database columns for BeaconDownloadedPolicy table

Database Column	Details
BeaconDownloadedPolicyID	<i>Type:</i> integer. Key. Generated ID The ID of the downloaded beacon policy.
RevisionNumber	<i>Type:</i> integer. Key The revision number of this policy.
PolicyXML	<i>Type:</i> XML The beacon policy xml downloaded by inventory beacons.

BeaconExecutionStatusType Table

BeaconExecutionStatusType is a static table listing possible beacon status values.

Table 60: Database columns for BeaconExecutionStatusType table

Database Column	Details
BeaconExecutionStatus TypeID	<i>Type:</i> integer. Key. Generated ID A unique identifier for each BeaconExecutionStatusType. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• 1 = Unknown• 2 = Started• 3 = Not configured• 4 = Running• 5 = Finished• 6 = Stopped
ResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing a batch process type. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the type resource string has no translation.

BeaconFilter Table

The BeaconFilter table contains target filters.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 61: Database columns for BeaconFilter table

Database Column	Details
BeaconFilterID	Type: integer. Key. Generated ID Unique ID automatically assigned to each beacon target filters.
BeaconTargetID	Type: integer. Key Target this filter refers to.
Include	Type: boolean Boolean string indicating to include or exclude filter value.
IsLinked	Type: boolean Boolean indicating if the filter is linked to site/subnet/device or an independent filter.
Value	Type: text (max 256 characters) Filter value.
FilterType	Type: text (max 64 characters) Filter type set for this filter.

BeaconIssueStatus Table

Records beacon issue detail information.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 62: Database columns for BeaconIssueStatus table

Database Column	Details
BeaconIssueStatusID	Type: integer. Key. Generated ID Unique id for the BeaconIssueStatus.
BeaconID	Type: integer. Key Beacon that this issue status relates to
BeaconIssueStatusTypeID	Type: integer. Key Issue type
IsActive	Type: boolean Policy downloaded time
IssueDetail	Type: text. Nullable Detail information about the issue

BeaconIssueStatusType Table

BeaconIssueStatusType is a static table listing possible beacon alerts.

Table 63: Database columns for BeaconIssueStatusType table

Database Column	Details
BeaconIssueStatusTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each BeaconIssueStatusType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 0 = Unknown• 1 = Policy load• 2 = Policy download• 3 = Discovery execution• 4 = Action execution• 5 = Self hosted web server• 6 = Service exit• 7 = Package download• 8 = Active Directory import• 9 = SAP Inventory import• 10 = SAP recommendation set download• 11 = Beacon self upgrade• 12 = Beacon Parent Configuration
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a batch process type. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the type resource string has no translation.</p>

BeaconPolicy Table

The BeaconPolicy table contains the beacon policy.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 64: Database columns for BeaconPolicy table

Database Column	Details
BeaconPolicyID	Type: integer. Key. Generated ID The ID of the beacon policy.
RevisionNumber	Type: integer The revision number of this policy.
AgentScheduleData	Type: text. Nullable The Schedule object, used for storing the global schedule for managed devices.
CreationDate	Type: datetime Date and time when the policy was created.
LastChangedOn	Type: datetime. Nullable Date and time that the policy was last modified.
ApprovedBeaconPackageID	Type: integer. Key. Nullable The beacon upgrade package that has been approved by the customer. NULL indicates to stay always on the latest.
LastDiscoveryFullExportTime	Type: datetime. Nullable The last time a discovery export was generated.
LastDiscoveryFullExportVersion	Type: integer. Nullable The revision number of the last full discovery export.
LastTargetRefreshTime	Type: datetime. Nullable The last time special internal targets were recalculated and refreshed.

BeaconPolicyPropertyValue Table

The BeaconPolicyPropertyValue table contains beacon policy property value elements.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 65: Database columns for BeaconPolicyPropertyValue table

Database Column	Details
BeaconPolicyPropertyID	Type: integer. Key. Generated ID Unique ID assigned to each beacon policy property.
KeyName	Type: text (max 256 characters). Key Property Key.
Value	Type: text (max 256 characters) Property Value.

BeaconPropertyValue Table

The BeaconPropertyValue table contains beacon property value elements.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 66: Database columns for BeaconPropertyValue table

Database Column	Details
BeaconPropertyID	Type: integer. Key. Generated ID Unique ID assigned to each beacon property.
BeaconID	Type: integer. Key Beacon this property refers to.
KeyName	Type: text (max 256 characters). Key Property Key.
Value	Type: text (max 256 characters) Property Value.

BeaconRule Table

The BeaconRule table contains the details of beacon rules.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 67: Database columns for BeaconRule table

Database Column	Details
BeaconRuleID	Type: integer. Key. Generated ID The ID of the beacon rule.
BeaconRuleActionID	Type: integer. Key The reference of Action from the beacon rule.
RuleName	Type: text (max 128 characters) The name of the rule.
RulePriority	Type: small integer Beacon rules are prioritised according to the rule priority. Higher priority takes precedence over lower priorities.
MaximumAge	Type: integer. Nullable Maximum age of the rule before it is re-scheduled.
ExternalID	Type: unique identifier. Key The ID that exists externally.
BeaconScheduleData	Type: text The Schedule object.
Include	Type: boolean Boolean string indicating to include or exclude rule.
Internal	Type: boolean Is this rule used internally, or managed by the user.
NameResourceName	Type: text (max 256 characters). Nullable Resource for translation of Name column. Foreign key to ComplianceResourceString table.

BeaconRuleAction Table

The BeaconRuleAction table contains beacon rule action.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 68: Database columns for BeaconRuleAction table

Database Column	Details
BeaconRuleActionID	Type: integer. Key. Generated ID Unique ID automatically assigned to each beacon actions.
Name	Type: text (max 100 characters). Key Name of Action.
Description	Type: text (max 256 characters). Nullable Description of Action.
NameResourceName	Type: text (max 256 characters). Nullable Resource for translation of Name column. Foreign key to the ComplianceResourceString table.
DescriptionResourceName	Type: text (max 256 characters). Nullable Resource for translation of Description column. Foreign key to the ComplianceResourceString table.
Internal	Type: boolean Is this action used internally, or managed by the user.

BeaconRuleActionPropertyValue Table

The BeaconRuleActionPropertyValue table contains beacon action property value elements.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 69: Database columns for BeaconRuleActionPropertyValue table

Database Column	Details
BeaconRuleAction PropertyID	Type: integer. Key. Generated ID Unqie ID assigned to each beacon action property.
BeaconRuleActionID	Type: integer. Key Beacon action this property refers to.
KeyName	Type: text (max 256 characters). Key Property Key.
Value	Type: text Property Value.

BeaconRuleBeaconTargetMapping Table

Table that maps targets to rule.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 70: Database columns for BeaconRuleBeaconTargetMapping table

Database Column	Details
BeaconRuleID	Type: integer. Key Foreign key to the BeaconRule table.
BeaconTargetID	Type: integer. Key Foreign key to the BeaconTarget table.

BeaconSiteSubnetMapping Table

Table that maps site to Beacons.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 71: Database columns for BeaconSiteSubnetMapping table

Database Column	Details
BeaconID	Type: integer. Key Foreign key to the Beacon table.
SubnetID	Type: integer. Key Foreign key to the SiteSubnet table.

BeaconTarget Table

The BeaconTarget table contains beacon rule targets.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 72: Database columns for BeaconTarget table

Database Column	Details
BeaconTargetID	Type: integer. Key. Generated ID Unique ID automatically assigned to each beacon targets.
Name	Type: text (max 100 characters). Key Name identifying the target.
Description	Type: text (max 256 characters). Nullable Name identifying the target.
Internal	Type: boolean. Key Is this target used internally, or managed by the user.
Visible	Type: boolean Can this target be displayed to the user for selection etc. This does not apply to the actual Targets page.

BeaconTargetAgentEvent Table

Table that maps agent events to targets.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 73: Database columns for BeaconTargetAgentEvent table

Database Column	Details
BeaconTargetID	Type: integer. Key Foreign key to the BeaconTarge; table.
BeaconAgentEventUID	Type: unique identifier. Key Foreign key to the BeaconAgentEvent table.

BeaconTargetDiscoveredDeviceMapping Table

Table that maps site to targets.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 74: Database columns for BeaconTargetDiscoveredDeviceMapping table

Database Column	Details
BeaconTargetID	Type: integer. Key Foreign key to the BeaconTarget table.
DeviceID	Type: integer. Key Foreign key to the DiscoveredDevice table.
Include	Type: boolean Boolean string indicating to include or exclude Device.

BeaconTargetPropertyValue Table

The BeaconTargetPropertyValue table contains beacon target property value elements.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 75: Database columns for BeaconTargetPropertyValue table

Database Column	Details
BeaconTargetPropertyID	Type: integer. Key. Generated ID Unique ID assigned to each beacon target property.
BeaconTargetID	Type: integer. Key Beacon target this property refers to.
KeyName	Type: text (max 256 characters). Key Property Key.
Value	Type: text (max 256 characters) Property Value.

BeaconTargetSiteMapping Table

Table that maps site to targets.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 76: Database columns for BeaconTargetSiteMapping table

Database Column	Details
BeaconTargetID	Type: integer. Key Foreign key to the BeaconTarget table.
SiteID	Type: integer. Key Foreign key to the Site table.
Include	Type: boolean Boolean string indicating to include or exclude Device.

BeaconTargetSiteSubnetMapping Table

Table that maps site to targets.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 77: Database columns for BeaconTargetSiteSubnetMapping table

Database Column	Details
BeaconTargetID	Type: integer. Key Foreign key to the BeaconTarget table.
SubnetID	Type: integer. Key Foreign key to the SiteSubnet table.
Include	Type: boolean Boolean string indicating to include or exclude Device.

BeaconUpgradeMode Table

BeaconUpgradeMode is a static table listing all of the styles of upgrade that a beacon can follow.

Table 78: Database columns for BeaconUpgradeMode table

Database Column	Details
BeaconUpgradeModeID	<i>Type:</i> integer. Key. Generated ID
ResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing the BeaconUpgradeMode record. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 256 characters) The text to display if the state resource string has no translation.

BeaconUpgradeStatus Table

BeaconUpgradeStatus is a static table listing all of the upgrade states that a beacon can be in.

Table 79: Database columns for BeaconUpgradeStatus table

Database Column	Details
BeaconUpgradeStatusID	Type: integer. Key. Generated ID
ResourceName	Type: text (max 256 characters). Key The unique name of the localizable resource string representing the BeaconUpgradeStatus record. Foreign key to the ComplianceResourceString table.
DefaultValue	Type: text (max 256 characters) The text to display if the state resource string has no translation.

BeaconWebServerStatus Table

BeaconWebServerStatus is a static table listing all of the states of the beacons web server.

Table 80: Database columns for BeaconWebServerStatus table

Database Column	Details
BeaconWebServerStatusID	<i>Type:</i> integer. Key. Generated ID
ResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing the BeaconWebServerStatus record. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 256 characters) The text to display if the state resource string has no translation.

DiscoveredDeviceDiscoveredBy Table

By which inventory beacon was this device discovered? Sometimes useful when other identifying features are duplicated, and when the distribution server should do something to the device.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 81: Database columns for DiscoveredDeviceDiscoveredBy table

Database Column	Details
DeviceID	Type: integer. Key The id of the device discovered.
ServerUID	Type: unique identifier. Key The inventory beacon that discovered it.
RuleID	Type: integer. Key. Nullable The RuleID executed on the beacon that discovered the device.
CanAdminister	Type: boolean. Nullable Does the distribution server have administrative privileges for the device?
LastUpdate	Type: datetime The date and time that the distribution server last reported its discovery of this device.
AccountID	Type: integer. Key. Nullable Account that can administer the device.
AccountIDOverride	Type: integer. Key. Nullable Account that can administer the device, overridden by the user.

DiscoveredDeviceDiscoveryStatus Table


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 82: Database columns for DiscoveredDeviceDiscoveryStatus table

Database Column	Details
DeviceID	Type: integer. Key
TaskTypeID	Type: integer. Key
BeaconRuleID	Type: integer. Key Rule that executed this task.
BeaconPolicyRevision Number	Type: integer The beacon policy revision number where rule is found
SessionUID	Type: unique identifier. Nullable
DiscoveryDate	Type: datetime. Nullable
RuleDiscoveryAction SummaryID	Type: integer Rule discovery summary.
BeaconUID	Type: unique identifier. Key. Nullable The inventory beacon that ran the task.

DiscoveredDeviceInventoryStatus Table


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 83: Database columns for DiscoveredDeviceInventoryStatus table

Database Column	Details
DeviceID	Type: integer. Key
TaskTypeID	Type: integer. Key
BeaconRuleID	Type: integer. Key. Nullable Rule that executed this task.
BeaconPolicyRevision Number	Type: integer. Nullable The beacon policy revision number where rule is found
SessionUID	Type: unique identifier. Nullable
InventoryDate	Type: datetime. Nullable
RuleInventoryAction SummaryID	Type: integer Rule action summary.
BeaconUID	Type: unique identifier. Key. Nullable The inventory beacon that ran the task.

DiscoveredDeviceTaskDetailedError Table


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 84: Database columns for DiscoveredDeviceTaskDetailedError table

Database Column	Details
DiscoveredDeviceTask DetailedErrorID	<i>Type:</i> integer. Key. Generated ID The ID of the discovered device error.
DiscoveredDeviceTask StatusHistoryID	<i>Type:</i> integer. Key Discovered device task status.
Status	<i>Type:</i> text (max 256 characters). Key The status code of task.
DetailedStatus	<i>Type:</i> text. Nullable The detailed error status.

DiscoveredDeviceTaskStatus Table

Records any task status information for DiscoveredDevice.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 85: Database columns for DiscoveredDeviceTaskStatus table

Database Column	Details
DiscoveredDeviceTask StatusID	Type: integer. Key. Generated ID The ID of the discovered device task.
DeviceID	Type: integer. Key Device identity number.
TaskTypeID	Type: integer. Key The type of task which was run on the device.
BeaconUID	Type: unique identifier. Key. Nullable The inventory beacon that has run the task.
BeaconRuleID	Type: integer. Key. Nullable Rule that executed this task.
Success	Type: boolean. Key Status of the task. It can be Success OR Failed
Credential	Type: text (max 256 characters). Nullable The credential name for the task performed.
Status	Type: text (max 256 characters) The status code of task.
DetailedStatus	Type: text. Nullable The detailed error status.
StartDateTime	Type: datetime Date and time the task was started.
BeaconPolicyRevision Number	Type: integer. Nullable The beacon policy revision number where rule is found
SessionUID	Type: unique identifier. Nullable An identifier TaskExecutionStatus table

Database Column	Details
IsSkipTask	<i>Type:</i> boolean Determines whether the task status is a skip task
IsDiscoveryTask	<i>Type:</i> boolean Determines whether the task status is a discovery task

DiscoveredDeviceTaskStatusHistory Table

Records any task status information for DiscoveredDevice.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 86: Database columns for DiscoveredDeviceTaskStatusHistory table

Database Column	Details
DiscoveredDeviceTask StatusHistoryID	Type: integer. Key. Generated ID The ID of the discovered device task.
DeviceID	Type: integer. Key Device identity number.
TaskTypeID	Type: integer. Key The type of task which was run on the device.
SessionUID	Type: unique identifier. Key An identifier TaskExecutionStatus table
BeaconUID	Type: unique identifier. Key The inventory beacon that has run the task.
BeaconRuleID	Type: integer. Key. Nullable Rule that executed this task.
Success	Type: boolean. Key Status of the task. It can be Success OR Failed
Credential	Type: text (max 256 characters). Nullable The credential name for the task performed.
Status	Type: text (max 256 characters) The status code of task.
DetailedStatus	Type: text. Nullable The detailed error status.
StartDateTime	Type: datetime Date and time the task was started.
BeaconPolicyRevision Number	Type: integer. Nullable The beacon policy revision number where rule is found

Database Column	Details
IsSkipTask	<i>Type:</i> boolean. Key Determines whether the task status is a skip task
IsDiscoveryTask	<i>Type:</i> boolean. Key Determines whether the task status is a discovery task

DiscoveredDeviceTaskType Table

This table stores the information about different types of tasks executed on a discovered device and their associated IDs.

Table 87: Database columns for DiscoveredDeviceTaskType table

Database Column	Details
TaskTypeID	<i>Type:</i> integer. Key. Generated ID The id for the task.
TaskTypeName	<i>Type:</i> text (max 32 characters). Key The name of the task.

ErrorCategory Table

Reported error category

Table 88: Database columns for ErrorCategory table

Database Column	Details
ErrorCategoryID	<i>Type:</i> integer. Key. Generated ID The ID of the error category.
ResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing a error category name. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the type resource string has no translation.

FNMEAAgent Table

The FNMEAAgent table stores the FNM-EA connection defined in inventory beacons.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 89: Database columns for FNMEAAgent table

Database Column	Details
FNMEAAgentID	Type: integer. Key. Generated ID Auto-generated FNMEA agent connection ID
BeaconID	Type: integer. Key. Nullable Beacon where the FNM-EA agent connection is defined
AgentIdentifier	Type: unique identifier. Key The GUID of the FNM-EA agent defined on inventory beacon.
AgentName	Type: text (max 128 characters) The FNM-EA agent name defined on inventory beacon.
LastReportedLogRotation	Type: datetime. Nullable Date time of the last report log rotation.
LastReportedAgentStatus	Type: datetime. Nullable Date time of the last reported status.

IncomingBaseline Table


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 90: Database columns for IncomingBaseline table

Database Column	Details
Type	Type: text (max 16 characters). Key The baseline type
Date	Type: datetime. Key The date of the baseline data
ProductPool	Type: text (max 128 characters). Key The license product pool
ProductFamily	Type: text (max 256 characters). Key The license product family
ProductVersion	Type: text (max 50 characters). Key The license product version
EffectiveQuantity	Type: integer The effective quantity of the license
UpgradeQuantity	Type: integer The upgrade quantity of the license
UpgradeWithMaintenance Quantity	Type: integer The upgrade with maintenance quantity of the license
ActiveSAQuantity	Type: integer The active software assurance quantity of the license
ExpiringSA0To12Months	Type: integer The software assurance quantity expiring within 0-12 months
ExpiringSA12To24Months	Type: integer The software assurance quantity expiring within 12-24 months
ExpiringSA24PlusMonths	Type: integer The software assurance quantity expiring greater than 24 months

ReconcileSoftwareLicenseReconcileExemptionReason Table

The ReconcileSoftwareLicenseReconcileExemptionReason table stores the staging license reconcile generated exemption reasons.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 91: Database columns for ReconcileSoftwareLicenseReconcileExemptionReason table

Database Column	Details
SoftwareLicenseID	Type: integer. Key Foreign key to the SoftwareLicense table
ComplianceComputerID	Type: integer. Key. Nullable Foreign key to the ComplianceComputer table
ComplianceUserID	Type: integer. Key. Nullable Foreign key to the ComplianceUser table
SoftwareLicense ExemptionReasonID	Type: integer. Key Foreign key to the SoftwareLicenseExemptionReason table
AccessingUserID	Type: integer. Key. Nullable Foreign key to the AccessingUser table

RuleDiscoveryActionSummary Table

Summary of the discovery action.

Table 92: Database columns for RuleDiscoveryActionSummary table

Database Column	Details
RuleDiscoveryAction SummaryID	<i>Type:</i> integer. Key. Generated ID The ID of the discovery action summary.
ResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing a discovery action summary. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the type resource string has no translation.

RuleInventoryActionSummary Table

Summary of the inventory gathering action.

Table 93: Database columns for RuleInventoryActionSummary table

Database Column	Details
RuleInventoryActionSummaryID	<i>Type:</i> integer. Key. Generated ID The ID of the inventory gathering action summary.
ResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing a discovery action summary. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the type resource string has no translation.

SoftwareLicenseReconcileExemptionReasonData Table

The SoftwareLicenseReconcileExemptionReasonData table stores the exemption reasons generated by the license reconcile.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 94: Database columns for SoftwareLicenseReconcileExemptionReasonData table

Database Column	Details
SoftwareLicenseID	Type: integer. Key Foreign key to the SoftwareLicenseSnapshot table
ComplianceComputerID	Type: integer. Key. Nullable Foreign key to the ComplianceComputerSnapshot table
ComplianceUserID	Type: integer. Key. Nullable Foreign key to the ComplianceUserSnapshot table
SoftwareLicense ExemptionReasonID	Type: integer. Key Foreign key to the SoftwareLicenseExemptionReason table
AccessingUserID	Type: integer. Key. Nullable Foreign key to the AccessingUserSnapshot table
LicenseMeasurementID	Type: integer. Key The snapshot ID. Foreign key to the LicenseMeasurement table.

StatusCodeCategory Table

Reported error category

Table 95: Database columns for StatusCodeCategory table

Database Column	Details
StatusCodeCategoryID	<i>Type:</i> integer. Key. Generated ID The ID of the error category.
StatusCode	<i>Type:</i> text (max 256 characters). Key Status code.
ErrorCategoryID	<i>Type:</i> integer. Nullable An identifier ErrorCategory table

UIAlignmentType Table

Table 96: Database columns for UIAlignmentType table

Database Column	Details
UIAlignmentTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each UIAlignmentType. Possible values are:</p> <ul style="list-style-type: none"> • 1 = UseAvailableSpace • 2 = ForceLeft • 3 = ForceRight
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a insert type. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the type resource string has no translation.</p>

UIFieldType Table

Table 97: Database columns for UIFieldType table

Database Column	Details
UIFieldTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each UIFieldType. Possible values are:</p> <ul style="list-style-type: none">• 1 = Tab• 2 = Section• 3 = Integer• 4 = Text box• 5 = Text area• 6 = Date• 7 = Date and time• 8 = Combo box• 9 = Check box
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a connection type. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the type resource string has no translation.</p>

UIInsertType Table

Table 98: Database columns for UIInsertType table

Database Column	Details
UIInsertTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each UIInsertType. Possible values are:</p> <ul style="list-style-type: none"> • 1 = Before • 2 = After • 3 = Start of
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a insert type. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the type resource string has no translation.</p>

UIItem Table


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 99: Database columns for UIItem table

Database Column	Details
UIItemID	Type: integer. Key. Generated ID
TargetTypeID	Type: integer. Key Type of object. Foreign key to the TargetType table.
ItemResourceName	Type: text (max 256 characters). Key Name of the item
ItemName	Type: text (max 256 characters) Name of the item
UIFieldTypeID	Type: integer. Nullable UI field type if the element type is of type 'field'. Foreign key to the UIFieldType table.
UIInsertTypeID	Type: integer Insert type. Foreign key to UIInsertType table.
UIAlignmentTypeID	Type: integer. Nullable Alignment type. Foreign key to UIAlignmentType table.
TabName	Type: text (max 80 characters) Name of the object to place the UI item.
RelativePositionTo	Type: text (max 80 characters) Name of the object to place the UI item.
Position	Type: integer
Width	Type: integer
DataSource	Type: XML. Nullable Data source for item of element type 'field' and of field type combo box . .
SequenceNumber	Type: integer Sequence where items to be added into UI

Database Column	Details
FromTable	<i>Type:</i> text. Nullable The name of the database table where the field can be found.
SelectName	<i>Type:</i> text. Nullable The name of the field in the database.
WhereClause	<i>Type:</i> text. Nullable The SQL "WHERE" statement that limits the information returned.
Required	<i>Type:</i> boolean Is the field a mandatory field.
StringLength	<i>Type:</i> integer String length.
ReadOnly	<i>Type:</i> boolean Is the field a readonly field.

UIItemTargetSubType Table


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 100: Database columns for UIItemTargetSubType table

Database Column	Details
UIItemTargetSubTypeID	Type: integer. Key. Generated ID
UIItemID	Type: integer. Key Type of object. Foreign key to the UIItem table.
TargetSubTypeID	Type: integer. Key object subtype. Foreign key to the various object type tables.

Compliance.Logic.Core Tables

The complete set of database tables documented here includes:

- Activity table (see [Activity Table](#))
- ActivitySource table (see [ActivitySource Table](#))
- ActivityTraceLog table (see [ActivityTraceLog Table](#))
- ActivityType table (see [ActivityType Table](#))
- Alert table (see [Alert Table](#))
- AlertCategory table (see [AlertCategory Table](#))
- AlertTarget table (see [AlertTarget Table](#))
- AlertType table (see [AlertType Table](#))
- AssetContractPaymentSchedule table (see [AssetContractPaymentSchedule Table](#))
- Attribute table (see [Attribute Table](#))
- BusinessImportLogDetail table (see [BusinessImportLogDetail Table](#))
- BusinessImportLogObject table (see [BusinessImportLogObject Table](#))
- BusinessImportLogSummary table (see [BusinessImportLogSummary Table](#))
- BusinessImportResult table (see [BusinessImportResult Table](#))
- ComplianceComputer table (see [ComplianceComputer Table](#))
- ComplianceComputerConnection table (see [ComplianceComputerConnection Table](#))
- ComplianceComputerContract table (see [ComplianceComputerContract Table](#))
- ComplianceComputerInventorySourceType table (see [ComplianceComputerInventorySourceType Table](#))
- ComplianceComputerPropertyValue table (see [ComplianceComputerPropertyValue Table](#))
- ComplianceComputerRole table (see [ComplianceComputerRole Table](#))
- ComplianceComputerStatus table (see [ComplianceComputerStatus Table](#))
- ComplianceComputerType table (see [ComplianceComputerType Table](#))
- ComplianceComputerTypeProperty table (see [ComplianceComputerTypeProperty Table](#))
- ComplianceComputerUsage table (see [ComplianceComputerUsage Table](#))
- ComplianceEvent table (see [ComplianceEvent Table](#))
- ComplianceEventAction table (see [ComplianceEventAction Table](#))
- ComplianceEventHistory table (see [ComplianceEventHistory Table](#))

- ComplianceEventState table (see [ComplianceEventState Table](#))
- ComplianceEventType table (see [ComplianceEventType Table](#))
- ComplianceHistory table (see [ComplianceHistory Table](#))
- ComplianceHistoryColumn table (see [ComplianceHistoryColumn Table](#))
- ComplianceHistoryType table (see [ComplianceHistoryType Table](#))
- ComplianceImage table (see [ComplianceImage Table](#))
- ComplianceLicenseUser table (see [ComplianceLicenseUser Table](#))
- CompliancePredefinedSearch table (see [CompliancePredefinedSearch Table](#))
- ComplianceResponsibility table (see [ComplianceResponsibility Table](#))
- ComplianceSavedSearch table (see [ComplianceSavedSearch Table](#))
- ComplianceSchedule table (see [ComplianceSchedule Table](#))
- ComplianceSearchFolder table (see [ComplianceSearchFolder Table](#))
- ComplianceSearchType table (see [ComplianceSearchType Table](#))
- ComplianceSearchTypeColumn table (see [ComplianceSearchTypeColumn Table](#))
- ComplianceSearchTypeRelation table (see [ComplianceSearchTypeRelation Table](#))
- ComplianceTask table (see [ComplianceTask Table](#))
- ComplianceUserPropertyValue table (see [ComplianceUserPropertyValue Table](#))
- ComplianceUserTypeProperty table (see [ComplianceUserTypeProperty Table](#))
- ComputerChassisType table (see [ComputerChassisType Table](#))
- ConsolidatedLicenseUser table (see [ConsolidatedLicenseUser Table](#))
- ConsolidationType table (see [ConsolidationType Table](#))
- Contract table (see [Contract Table](#))
- ContractNote table (see [ContractNote Table](#))
- ContractNotification table (see [ContractNotification Table](#))
- ContractNotificationResponsibility table (see [ContractNotificationResponsibility Table](#))
- ContractProperty table (see [ContractProperty Table](#))
- ContractPropertyValue table (see [ContractPropertyValue Table](#))
- ContractScopingData table (see [ContractScopingData Table](#))
- ContractSecurityUser table (see [ContractSecurityUser Table](#))
- ContractState table (see [ContractState Table](#))

- ContractStatus table (see [ContractStatus Table](#))
- ContractType table (see [ContractType Table](#))
- ContractUseRight table (see [ContractUseRight Table](#))
- ContractUseRightIBM table (see [ContractUseRightIBM Table](#))
- ContractVendor table (see [ContractVendor Table](#))
- CurrencyRate table (see [CurrencyRate Table](#))
- CurrencyRateSnapshot table (see [CurrencyRateSnapshot Table](#))
- CustomPropertyDisplayXML table (see [CustomPropertyDisplayXML Table](#))
- DisplayXML table (see [DisplayXML Table](#))
- Document table (see [Document Table](#))
- DocumentHistory table (see [DocumentHistory Table](#))
- DocumentNote table (see [DocumentNote Table](#))
- DocumentType table (see [DocumentType Table](#))
- Event table (see [Event Table](#))
- EventLogCategory table (see [EventLogCategory Table](#))
- EventLogDetail table (see [EventLogDetail Table](#))
- EventLogLevel table (see [EventLogLevel Table](#))
- EventLogStatus table (see [EventLogStatus Table](#))
- EventLogSummary table (see [EventLogSummary Table](#))
- EventParameter table (see [EventParameter Table](#))
- EventParameterType table (see [EventParameterType Table](#))
- EventSeverity table (see [EventSeverity Table](#))
- EventTarget table (see [EventTarget Table](#))
- EventType table (see [EventType Table](#))
- EventTypeStatus table (see [EventTypeStatus Table](#))
- ILMTPVUCounts table (see [ILMTPVUCounts Table](#))
- ImportResolverErrorResult table (see [ImportResolverErrorResult Table](#))
- ImportResolverType table (see [ImportResolverType Table](#))
- InstalledSoftwareAttribute table (see [InstalledSoftwareAttribute Table](#))
- Instance table (see [Instance Table](#))

- InstanceAttribute table (see [InstanceAttribute Table](#))
- InstanceEnvironment table (see [InstanceEnvironment Table](#))
- InstancePropertyValue table (see [InstancePropertyValue Table](#))
- InstanceRole table (see [InstanceRole Table](#))
- InstanceType table (see [InstanceType Table](#))
- InstanceTypeProperty table (see [InstanceTypeProperty Table](#))
- InstanceUser table (see [InstanceUser Table](#))
- IntervalType table (see [IntervalType Table](#))
- LicenseUser table (see [LicenseUser Table](#))
- LicenseUserConnection table (see [LicenseUserConnection Table](#))
- LicenseUserExcluded table (see [LicenseUserExcluded Table](#))
- LicenseUserType table (see [LicenseUserType Table](#))
- LogFile table (see [LogFile Table](#))
- MSEARLSoftwareTitleEdition table (see [MSEARLSoftwareTitleEdition Table](#))
- MSSelectLevel table (see [MSSelectLevel Table](#))
- MSSelectPool table (see [MSSelectPool Table](#))
- MobileDevice table (see [MobileDevice Table](#))
- NotificationItem table (see [NotificationItem Table](#))
- NotificationTemplate table (see [NotificationTemplate Table](#))
- NotificationType table (see [NotificationType Table](#))
- OperatorManageState table (see [OperatorManageState Table](#))
- OperatorTaskTypeSetting table (see [OperatorTaskTypeSetting Table](#))
- OracleInstance table (see [OracleInstance Table](#))
- PaymentSchedule table (see [PaymentSchedule Table](#))
- PaymentScheduleCategory table (see [PaymentScheduleCategory Table](#))
- PaymentScheduleDetail table (see [PaymentScheduleDetail Table](#))
- PaymentScheduleDetailPaymentStatus table (see [PaymentScheduleDetailPaymentStatus Table](#))
- PaymentScheduleTerm table (see [PaymentScheduleTerm Table](#))
- PaymentScheduleType table (see [PaymentScheduleType Table](#))
- Project table (see [Project Table](#))

- PurchaseOrder table (see [PurchaseOrder Table](#))
- PurchaseOrderDetail table (see [PurchaseOrderDetail Table](#))
- PurchaseOrderDetailProperty table (see [PurchaseOrderDetailProperty Table](#))
- PurchaseOrderDetailPropertyValue table (see [PurchaseOrderDetailPropertyValue Table](#))
- PurchaseOrderDetailStatus table (see [PurchaseOrderDetailStatus Table](#))
- PurchaseOrderDetailType table (see [PurchaseOrderDetailType Table](#))
- PurchaseOrderProperty table (see [PurchaseOrderProperty Table](#))
- PurchaseOrderPropertyValue table (see [PurchaseOrderPropertyValue Table](#))
- PurchaseOrderStatus table (see [PurchaseOrderStatus Table](#))
- PurchaseOrderType table (see [PurchaseOrderType Table](#))
- PurchaseProgram table (see [PurchaseProgram Table](#))
- QuerySnapshot table (see [QuerySnapshot Table](#))
- RelationType table (see [RelationType Table](#))
- ResponsibilityType table (see [ResponsibilityType Table](#))
- RestrictedAccessType table (see [RestrictedAccessType Table](#))
- RulesEngineRuleDefinition table (see [RulesEngineRuleDefinition Table](#))
- RulesEngineRuleType table (see [RulesEngineRuleType Table](#))
- SecurityType table (see [SecurityType Table](#))
- SerialNumberBlackList table (see [SerialNumberBlackList Table](#))
- SessionUIDBeacon table (see [SessionUIDBeacon Table](#))
- ShippingMethod table (see [ShippingMethod Table](#))
- SoftwareLicenseContractPaymentSchedule table (see [SoftwareLicenseContractPaymentSchedule Table](#))
- SystemShutdown table (see [SystemShutdown Table](#))
- TaskExecutionStatus table (see [TaskExecutionStatus Table](#))
- TaskExecutionStatusStep table (see [TaskExecutionStatusStep Table](#))
- TaskStep table (see [TaskStep Table](#))
- TaskStepEventType table (see [TaskStepEventType Table](#))
- TermAndCondition table (see [TermAndCondition Table](#))
- TermAndConditionTask table (see [TermAndConditionTask Table](#))
- TermAndConditionType table (see [TermAndConditionType Table](#))

- UserNameBlacklist table (see [UserNameBlacklist Table](#))
- VMEnabledState table (see [VMEnabledState Table](#))
- VMHostManagedBySoftware table (see [VMHostManagedBySoftware Table](#))
- VMPool table (see [VMPool Table](#))
- VMPoolType table (see [VMPoolType Table](#))
- VMSourceType table (see [VMSourceType Table](#))
- VMState table (see [VMState Table](#))
- VMType table (see [VMType Table](#))
- Vendor table (see [Vendor Table](#))
- VendorContact table (see [VendorContact Table](#))
- VendorProperty table (see [VendorProperty Table](#))
- VendorPropertyValue table (see [VendorPropertyValue Table](#))
- VirtualMachine table (see [VirtualMachine Table](#))
- XMLInsertType table (see [XMLInsertType Table](#))

Activity Table

The Activity table stores errors and events processed by the beacon, devices, rules etc.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 101: Database columns for Activity table

Database Column	Details
ActivityID	<i>Type:</i> integer. Key. Generated ID Synthetic key for this table.
SourceTypeID	<i>Type:</i> integer The source type ID such as Beacon, External and so on
SourceTypeName	<i>Type:</i> text (max 256 characters) The source type name such as Beacon, External and so on
ActivityTypeID	<i>Type:</i> integer. Key Foreign key to the ActivityType table.
ActivityUID	<i>Type:</i> unique identifier. Key UID to uniquely identify the activity.
DateCreated	<i>Type:</i> datetime Time that the activity is created in the database.

ActivitySource Table

ActivitySource is a static table listing all of the Sources that can generate the activity logs.

Table 102: Database columns for ActivitySource table

Database Column	Details
ActivitySourceID	Type: integer. Key. Generated ID
ResourceName	Type: text (max 256 characters). Key The unique name of the localizable resource string representing the ActivitySource record. Foreign key to the ComplianceResourceString table.
DefaultValue	Type: text (max 256 characters) The text to display if the state resource string has no translation.

ActivityTraceLog Table

The ActivityTraceLog table stores the logs generated by the trace logger for the corresponding activity.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 103: Database columns for ActivityTraceLog table

Database Column	Details
TraceID	Type: integer. Key. Generated ID The unique row identifier.
ActivityUID	Type: unique identifier. Nullable The Guid of the activity that trace logger is logging the events for.
DateCreated	Type: datetime. Nullable The date and time when the event occurred.
LogMessage	Type: text. Nullable The actual message logged by the trace logger.
LogLevel	Type: integer. Nullable The log level that the trace logger is logging to.
EventID	Type: integer. Key. Nullable The unique row identifier in negative form.

ActivityType Table

The ActivityType table stores details about the different types of Activities.

Table 104: Database columns for ActivityType table

Database Column	Details
ActivityTypeID	<i>Type:</i> integer. Key. Generated ID Synthetic key for this table.
ActivityTypeName	<i>Type:</i> text (max 256 characters). Key A short piece of text representing the Activity Type. Internal use only- not to be displayed to the operator.
ActivityMessageResource	<i>Type:</i> text (max 256 characters) A resource name used to look up a description for this Activity
IsMonitored	<i>Type:</i> boolean Flag that determines whether to track this activity

Alert Table

The Alert table stores alerts and notifications that the system can attach to different objects to be displayed to the operator.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 105: Database columns for Alert table

Database Column	Details
AlertID	Type: integer. Key. Generated ID Synthetic key for this table.
AlertTypeID	Type: integer. Key Foreign key to the AlertType table.
Ignored	Type: boolean. Key This flag indicates whether this alert has been ignored by an operator. If so, then the IgnoredDate and IgnoredOperator values will be populated.
IgnoredDate	Type: datetime. Nullable If the alert has been ignored by an operator, then this field shows the date when this was done.
IgnoredOperator	Type: text (max 256 characters). Nullable If the alert has been ignored by an operator, then this field shows which operator ignored the alert.
CreationDate	Type: datetime Date and time (UTC) when alert was created.

AlertCategory Table

The AlertCategory table stores the different catogories of alerts.

Table 106: Database columns for AlertCategory table

Database Column	Details
AlertCategoryID	<i>Type:</i> integer. Key. Generated ID Synthetic key for this table.
DefaultName	<i>Type:</i> text (max 128 characters) The default name for this alert category
ResourceName	<i>Type:</i> text (max 128 characters). Key A resource name used to look up a description for this alert category

AlertTarget Table

The AlertTarget table stores the links between alerts and other tables in the database.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 107: Database columns for AlertTarget table

Database Column	Details
AlertID	Type: integer. Key Link to the Alert table
TargetTypeID	Type: integer. Key A link the the TargetType table. this value specifies which kind of object the alert is linked to.
TargetID	Type: integer. Key used to attach the Alert to its target. The target table depends on the TargetTypeID of the linked AlertType.
FieldName	Type: text. Nullable A semi-colon separated list of view-model names that represent the fields that the alert is attached to. A null value indicates that the alert applies to the overall object as a whole.

AlertType Table

The AlertType table stores details about the different types of alerts.

Table 108: Database columns for AlertType table

Database Column	Details
AlertTypeID	Type: integer. Key. Generated ID Synthetic key for this table.
AlertTypeName	Type: text (max 256 characters). Key A short piece of text representing the Alert Type. Internal use only- not to be displayed to the operator.
AlertMessageResource	Type: text (max 256 characters) A resource name used to look up a description for this alert
AlertCategoryID	Type: integer The category of this type of alert

AssetContractPaymentSchedule Table

AssetContractPaymentSchedule links a payment schedule to an asset, via a link from that asset to a contract.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 109: Database columns for AssetContractPaymentSchedule table

Database Column	Details
AssetContractPaymentScheduleID	<i>Type:</i> integer. Key. Generated ID Unique identifier to represent a link between a payment schedule and an asset. This allows an asset to link multiple times to a payment schedule, each time with its own start and end dates.
AssetContractID	<i>Type:</i> integer. Key Identifies a link between an asset and a contract. Foreign key to the AssetContract table.
PaymentScheduleID	<i>Type:</i> integer. Key Identifies a payment schedule. Foreign key to the PaymentSchedule table.
ActiveStartDate	<i>Type:</i> datetime Start date of the association between the payment schedule and asset.
ActiveEndDate	<i>Type:</i> datetime. Nullable End date of the association between the payment schedule and asset.

Attribute Table

Attribute holds the collection of possible attributes of database instances.

Table 110: Database columns for Attribute table

Database Column	Details
AttributeID	<i>Type:</i> integer. Key. Generated ID A unique identifier for an attribute.
AttributeName	<i>Type:</i> text (max 256 characters). Key The name of the attribute.

BusinessImportLogDetail Table

The BusinessImportLogDetail table stores per record import execution details for a business import execution.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 111: Database columns for BusinessImportLogDetail table

Database Column	Details
ImportDetailID	Type: integer. Key. Generated ID Surrogate ID that uniquely identifies an import execution detail.
ImportID	Type: integer. Key Business import ID this execution detail relates to, foreign key to BusinessImportLogSummary table.
RecordNumber	Type: integer. Nullable Row number of source data in staging table that this execution detail related to.
Action	Type: text (max 10 characters). Nullable The trace action of the import execution detail.
MGSRecordKey	Type: text (max 50 characters). Nullable ID of matching FNMS table record the Record Number is matched against.
ImportObjectID	Type: integer. Key. Nullable Import object that this execution detail is related to, foreign key to BusinessImportLogObject table.
RecordDescription	Type: text (max 255 characters). Nullable Value of the trace field specified in the import element of business adapter xml if any.
Message	Type: text (max 3000 characters). Nullable Messages related to this import execution detail.

BusinessImportLogObject Table

The BusinessImportLogObject table stores summary data for the execution of individual object imports within a business import execution.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 112: Database columns for BusinessImportLogObject table

Database Column	Details
ImportObjectID	Type: integer. Key. Generated ID Surrogate ID that uniquely identifies an object in a business import execution.
ImportID	Type: integer. Key Business import ID this object belongs, foreign key to BusinessImportLogSummary table.
ObjectName	Type: text (max 50 characters). Nullable Name of the business import object.
ObjectType	Type: text (max 50 characters). Nullable Type of the business import object.
StartDate	Type: datetime. Nullable Date and time when the object began to be imported on FNMS server.
EndDate	Type: datetime. Nullable Date and time when import of the object is completed on FNMS server.
Status	Type: integer. Nullable Status of object import: 0 - Not completed, 1 - Completed.
Processed	Type: integer. Nullable Number of rows from data source that are processed for the object import.
Matched	Type: integer. Nullable Number of rows in the staging table that match records in the corresponding FNMS table for the object.
Rejected	Type: integer. Nullable Number of rows in the staging table that are rejected for the object import.

Database Column	Details
Updated	<i>Type:</i> integer. Nullable Number of rows in the staging table that are updated for the object import.
Created	<i>Type:</i> integer. Nullable Number of rows in the staging table that are created for the object import.
Deleted	<i>Type:</i> integer. Nullable Number of rows in the staging table that are deleted for the object import.

BusinessImportLogSummary Table

The BusinessImportLogSummary table stores summary data for each business import execution.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 113: Database columns for BusinessImportLogSummary table

Database Column	Details
ImportID	Type: integer. Key. Generated ID Surrogate ID that uniquely identifies a business import.
ImportName	Type: text (max 255 characters). Nullable Import name of the business import.
ImportType	Type: text (max 50 characters). Nullable Import type of the business import.
Action	Type: text (max 20 characters). Nullable The mode the business import is operating in e.g. Import, Simulation.
StartDate	Type: datetime. Nullable Date and time when the business import is started on FNMS server.
EndDate	Type: datetime. Nullable Date and time when the business import is completed on FNMS server.
Status	Type: integer. Nullable Status of the business import: 0 - Not completed, 1 - Completed.
Processed	Type: integer. Nullable Number of rows from data source that are processed for import.
Rejected	Type: integer. Nullable Number of rows from data source that are rejected from importing.
SessionUID	Type: unique identifier. Key. Nullable Unique task run identifier of the business import, nullable for business import initiated on the server.

BusinessImportResult Table

The BusinessImportResult table contains the results of all business imports executed on the batch server.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 114: Database columns for BusinessImportResult table

Database Column	Details
BusinessImportResultID	Type: integer. Key. Generated ID A unique identifier for the business import result.
ImportName	Type: text (max 256 characters) The name of the business import.
BeaconID	Type: integer. Key A link to Beacon from which this import was uploaded.
ImportStarted	Type: datetime The time at which the import was executed.
ImportEnded	Type: datetime The time at which the import was completed.
Result	Type: boolean Whether the import succeeded.

ComplianceComputer Table

ComplianceComputer stores information about computers used in the enterprise, including hardware details, inventory source information and computer types.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 115: Database columns for ComplianceComputer table

Database Column	Details
ComplianceComputerID	<i>Type:</i> integer. Key. Generated ID A unique identifier for a ComplianceComputer.
ComplianceComputerTypeID	<i>Type:</i> integer. Key A unique identifier for the type of computer. Foreign key to the ComplianceComputerType table.
IsComplianceComputerTypeIDFromInventory	<i>Type:</i> boolean This is true for records sourced from inventory, where the inventory source has specified the value of the ComplianceComputerTypeID. A true value will exclude this record from some processes that infer the type of a record. This value is set by the import process.
ComputerName	<i>Type:</i> text (max 256 characters). Key. Nullable The name of the computer.
ComplianceDomainID	<i>Type:</i> integer. Key. Nullable The domain to which the computer belongs. Foreign key to the ComplianceDomain table.
ComplianceComputerStatusID	<i>Type:</i> integer. Key The last recorded status for this computer. Foreign key to the ComplianceComputerStatus table.
ComplianceComputerRoleID	<i>Type:</i> integer. Key The functional role of this computer. Foreign key to the ComplianceComputerRole table.
ComplianceComputerInventorySourceTypeID	<i>Type:</i> integer. Key Whether this computer has ever been reported in inventory, or has been manually created and maintained. Foreign key to the ComplianceComputerInventorySourceType table.

Database Column	Details
AssetID	<p><i>Type:</i> integer. Key. Nullable</p> <p>When the computer is being managed as an asset, this is a foreign key to the Asset table; and is otherwise null.</p>
OperatingSystem	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>The operating system of the computer.</p>
ServicePack	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>The latest service pack reported as installed on the operating system.</p>
NumberOfProcessors	<p><i>Type:</i> integer. Nullable</p> <p>The number of processors in the computer.</p>
NumberOfProcessorsDefault	<p><i>Type:</i> integer. Nullable</p> <p>The inventoried number of processors in the computer.</p>
ProcessorType	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>The type of processor in the computer.</p>
ProcessorTypeDefault	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>The inventoried type of processor in the computer.</p>
MaxClockSpeed	<p><i>Type:</i> integer. Nullable</p> <p>The maximum clock speed of the fastest processor in the computer in megahertz.</p>
MaxClockSpeedDefault	<p><i>Type:</i> integer. Nullable</p> <p>The inventoried maximum clock speed of the fastest processor in the computer in megahertz.</p>
TotalMemory	<p><i>Type:</i> big integer. Nullable</p> <p>The total RAM in the computer.</p>
ChassisTypeID	<p><i>Type:</i> integer. Key</p> <p>The type of case for the computer, as reported in hardware inventory, defaulting to Unknown if no chassis type is reported. Foreign key to the ComputerChassisType table.</p>
AssignedChassisTypeID	<p><i>Type:</i> integer. Nullable</p> <p>The type of case for the computer, as set by an operator. Foreign key to the ComputerChassisType table.</p>
NumberOfHardDrives	<p><i>Type:</i> integer. Nullable</p> <p>The number of hard drives in the computer.</p>
TotalDiskSpace	<p><i>Type:</i> big integer. Nullable</p> <p>The total size of all hard drives in the computer.</p>

Database Column	Details
NumberOfNetworkCards	<i>Type:</i> integer. Nullable The number of network cards in the computer.
NumberOfDisplayAdapters	<i>Type:</i> integer. Nullable The number of graphics cards in the computer.
IPAddress	<i>Type:</i> text (max 256 characters). Nullable The IP address of the computer.
MACAddress	<i>Type:</i> text (max 256 characters). Nullable The MAC Addresses of the computer.
Manufacturer	<i>Type:</i> text (max 128 characters). Key. Nullable The manufacturer of the computer.
ModelNo	<i>Type:</i> text (max 128 characters). Nullable The model number of the computer.
ModelNoDefault	<i>Type:</i> text (max 128 characters). Nullable The inventoried model number of the computer.
SerialNo	<i>Type:</i> text (max 100 characters). Key. Nullable The serial number of the computer.
ComplianceUserID	<i>Type:</i> integer. Key. Nullable The end-user who last logged onto the computer. Foreign key to the ComplianceUser table.
AssignedUserID	<i>Type:</i> integer. Key. Nullable The end-user assigned to this computer by an operator. Foreign key to the ComplianceUser table.
CalculatedUserID	<i>Type:</i> integer. Key. Nullable An end-user of this computer, calculated by looking at usage. Foreign key to the ComplianceUser table.
LocationID	<i>Type:</i> text (max 128 characters). Key. Nullable Any enterprise location associated with this computer. Foreign key to the GroupEx table.
BusinessUnitID	<i>Type:</i> text (max 128 characters). Key. Nullable Any corporate unit in the enterprise associated with this computer. Foreign key to the GroupEx table.

Database Column	Details
CostCenterID	<i>Type:</i> text (max 128 characters). Key. Nullable Any cost center in the enterprise associated with this computer. Foreign key to the GroupEx table.
CategoryID	<i>Type:</i> text (max 128 characters). Key. Nullable Any enterprise category associated with this computer. Foreign key to the GroupEx table.
InventoryDate	<i>Type:</i> datetime. Key. Nullable The date the computer last had inventory reported.
HardwareInventoryDate	<i>Type:</i> datetime. Nullable The date when the hardware was last reported.
ServicesInventoryDate	<i>Type:</i> datetime. Nullable The date when a service was last reported.
UpdatedUser	<i>Type:</i> text (max 128 characters). Nullable The name of the operator who last updated the computer details.
UpdatedDate	<i>Type:</i> datetime. Nullable The date the record was last updated.
CreationUser	<i>Type:</i> text (max 128 characters). Nullable The operator who created the record.
CreationDate	<i>Type:</i> datetime The date the computer was created.
InventoryAgent	<i>Type:</i> text (max 64 characters). Nullable The name of the person or tool that performed the last inventory.
NumberOfCores	<i>Type:</i> integer. Nullable The number of cores in the computer.
NumberOfCoresDefault	<i>Type:</i> integer. Nullable The inventoried number of cores in the computer.
NumberOfSockets	<i>Type:</i> integer. Nullable The number of sockets in the computer.
NumberOfSocketsDefault	<i>Type:</i> integer. Nullable The inventoried number of sockets in the computer.
AssetComplianceStatusID	<i>Type:</i> integer. Nullable For computers managed as assets, the latest compliance status of the computer. Foreign key to the AssetComplianceStatus table.

Database Column	Details
PartialNumberOfProcessors	<i>Type:</i> decimal. Nullable The fractional processor count available to this computer.
PartialNumberOfProcessorsDefault	<i>Type:</i> decimal. Nullable The inventoried fractional processor count available to this computer.
UntrustedSerialNo	<i>Type:</i> boolean Is this computer known to have a serial number from a data source that should not be trusted.
ILMTAgentID	<i>Type:</i> big integer. Key. Nullable Store the unique ID used by the ILMT agent on this device, if the inventory source is aware of this value.
UUID	<i>Type:</i> unique identifier. Nullable The computer's UUID, in the byte order reported in inventory.
HostIdentifyingNumber	<i>Type:</i> text (max 128 characters). Key. Nullable Virtual hosts may have an identifier that is unique only across that hardware model. It is less unique than the true hardware serial number, for example.
HostType	<i>Type:</i> text (max 128 characters). Key. Nullable The type (similar to model number) of the host, used for matching.
NumberOfLogicalProcessors	<i>Type:</i> integer. Nullable The number of logical processors in the computer.
NumberOfLogicalProcessorsDefault	<i>Type:</i> integer. Nullable The inventoried number of logical processors in the computer.
PrimaryComplianceUserID	<i>Type:</i> integer. Key. Nullable Primary user of the computer based off the assigned user and calculated user.
MDScheduleGeneratedDate	<i>Type:</i> datetime. Nullable The last time the managed device schedule was regenerated.
MDScheduleContainsPVUScan	<i>Type:</i> boolean. Nullable Does this managed device include an event in its current schedule for running extra IBM PVU hardware scans.
HostID	<i>Type:</i> text (max 100 characters). Key. Nullable Numeric identifier of the current host
FirmwareSerialNumber	<i>Type:</i> text (max 100 characters). Key. Nullable Serial number in the system firmware such as BIOS, EEPROM etc.

Database Column	Details
MachineID	<i>Type:</i> text (max 100 characters). Key. Nullable For AIX, it is the System ID. For HP-UX, it is the Machine/Software ID. It is unset for other platforms.

ComplianceComputerConnection Table

ComplianceComputerConnection stores a link between computers in ComplianceComputer which have been reported in inventory, and external IDs that can be used to identify them in their inventory sources. Computers reported in multiple inventory sources will appear multiple times in this table.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 116: Database columns for ComplianceComputerConnection table

Database Column	Details
ComplianceComputerID	Type: integer. Key A unique identifier for the computer. Foreign key to the ComplianceComputer table.
ComplianceConnectionID	Type: integer. Key The inventory source where the computer was reported. Foreign key to the ComplianceConnection table.
ExternalID	Type: big integer The (hopefully unique) identifier for the computer in the external inventory source.

ComplianceComputerContract Table

ComplianceComputerContract stores links between computers and contracts, some of which may influence license compliance.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 117: Database columns for ComplianceComputerContract table

Database Column	Details
ComplianceComputerContractID	<i>Type:</i> integer. Key. Generated ID A unique identifier for this record.
ContractID	<i>Type:</i> integer. Key A unique identifier for a contract linked to a computer. Foreign key to the Contract table.
ComplianceComputerID	<i>Type:</i> integer. Key A unique identifier for a computer linked to a contract. Foreign key to the ComplianceComputer table.

ComplianceComputerInventorySourceType Table

ComplianceComputerInventorySourceType is a static table used to define possible computer inventory source values (that is, whether the computer was created manually or reported by the compliance importer).

Table 118: Database columns for ComplianceComputerInventorySourceType table

Database Column	Details
ComplianceComputerInventorySourceTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each ComplianceComputerInventorySourceType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = Automatic (computer was recently updated during an inventory import)• 2 = VM Host (a dummy or “light” computer created using the host inventory of a virtual machine)• 3 = Manual (computer was created manually by an operator, using FlexNet Manager Suite, and has never been updated by the compliance importer).
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a computer inventory source. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the inventory resource string has no translation.</p>

ComplianceComputerPropertyValue Table

For each computer, ComplianceComputerPropertyValue stores the values for the custom properties defined in ComplianceComputerTypeProperty.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 119: Database columns for ComplianceComputerPropertyValue table

Database Column	Details
ComplianceComputer PropertyValueID	Type: integer. Key. Generated ID A unique identifier for a property value.
ComplianceComputerID	Type: integer. Key The computer associated with this property value. Foreign key to the ComplianceComputer table
ComplianceComputerType PropertyID	Type: integer. Key The property whose value is being stored. The type of the computer should match the type that the property is associated with. Foreign key to the ComplianceComputerTypeProperty table.
PropertyValue	Type: text (max 4000 characters) The value of the custom property.
CreationUser	Type: text (max 128 characters). Nullable The operator who created the record.
CreationDate	Type: datetime The date the record was created.
UpdatedUser	Type: text (max 128 characters). Nullable The operator who last updated the record.
UpdatedDate	Type: datetime. Nullable The date the record was last updated.

ComplianceComputerRole Table

ComplianceComputerRole is a static table listing all the different roles to which computers can be assigned, and which may impact licensing terms.

Table 120: Database columns for ComplianceComputerRole table

Database Column	Details
ComplianceComputerRoleID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each ComplianceComputerRole. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = Production• 2 = Warm Standby / Passive Failover• 3 = Hot Standby / Active Failover• 4 = Backup / Archive• 5 = Test• 6 = Training• 7 = Cold Standby / Disaster recovery• 8 = Development.
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a computer role. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the inventory resource string has no translation.</p>
ManageLicenses	<p><i>Type:</i> boolean</p> <p>Set this to True if computers in this role are to be included in compliance calculations, and to False if this role exempts a computer from the license management process. Of the computer roles listed above, only Active computers have their licenses managed.</p>

ComplianceComputerStatus Table

ComplianceComputerStatus is a static table used to define possible values for the status of computers reported in FlexNet Manager Suite.

Table 121: Database columns for ComplianceComputerStatus table

Database Column	Details
ComplianceComputer StatusID	<i>Type:</i> integer. Key. Generated ID A unique identifier for each ComplianceComputerStatus. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• 1 = New (this is the first appearance of this computer in inventory)• 2 = Ignored (an operator has marked this computer to be ignored)
ResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing a computer status. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the status resource string has no translation.

ComplianceComputerType Table

ComplianceComputerType is a static table listing all types of computers that can be created.

Table 122: Database columns for ComplianceComputerType table

Database Column	Details
ComplianceComputerTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each ComplianceComputerType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = Computer • 2 = VM Host • 3 = Virtual Machine • 4 = Remote Device. • 5 = Mobile Device. • 6 = VDI Template.
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a computer role. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the type resource string has no translation.</p>
XMLFile	<p><i>Type:</i> text. Nullable</p> <p>The layout of the property dialog for this type of computer, stored in XML format.</p>
CanCreate	<p><i>Type:</i> boolean. Key</p> <p>Whether the end-user can manually create computers of this type.</p>
CanEdit	<p><i>Type:</i> boolean. Key</p> <p>Whether the end-user can manually edit computers of this type.</p>

ComplianceComputerTypeProperty Table

ComplianceComputerTypeProperty defines extra custom properties for computers of the specified type.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 123: Database columns for ComplianceComputerTypeProperty table

Database Column	Details
ComplianceComputerType PropertyID	<i>Type:</i> integer. Key. Generated ID A unique identifier for a property.
PropertyName	<i>Type:</i> text (max 256 characters). Key The name of the property.
ComplianceComputerTypeID	<i>Type:</i> integer. Key Computer type with which this property is associated. Foreign key to the ComplianceComputerType table.
CustomPropertyDisplayXMLID	<i>Type:</i> integer. Nullable Foreign key to a record in the CustomPropertyDisplayXML table, describing how to show the property on a property dialog.

ComplianceComputerUsage Table

This table links user IDs with computer IDs, allowing ECM to determine who uses a computer most frequently; and this is one factor in determining the assigned user for a computer.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 124: Database columns for ComplianceComputerUsage table

Database Column	Details
ComplianceComputerUsageID	Type: integer. Key. Generated ID Unique identifier for a ComplianceComputerUsage record.
ComplianceComputerID	Type: integer. Key Foreign key to the ComplianceComputer table.
ComplianceUserID	Type: integer. Key Foreign key to the ComplianceUser table.
DateRecorded	Type: datetime. Key The date and time that the record was inserted.

ComplianceEvent Table

The ComplianceEvent table lists all the 'compliance events' that FlexNet Manager Suite has detected. These are any event, such as the arrival of a new application version or a change in primary application for a license, that should trigger recalculation of linked applications through upgrade and downgrade rights. Depending on license properties, some of these events trigger automatic recalculation, and others trigger a proposal to the operator for manual response. This table records the current state for each event, with a history of state changes available in the ComplianceEventHistory table. Where the compliance event results in changes to the applications linked to a license, further details are recorded in the SoftwareLicenseChangeEvent table.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 125: Database columns for ComplianceEvent table

Database Column	Details
ComplianceEventID	Type: integer. Key. Generated ID A unique identifier for an event.
EventTypeID	Type: integer The type of event. Foreign key to the ComplianceEventType table.
Priority	Type: integer. Nullable The priority of the event.
Severity	Type: integer. Nullable The severity of the event.
EventActionID	Type: integer The proposed action for the event. Foreign key to the ComplianceEventAction table.
EventStateID	Type: integer The current state of the event. Foreign key to the ComplianceEventState table.
UpdatedBy	Type: text (max 200 characters) The last operator to update the event.
UpdatedDate	Type: datetime The date the event was last updated.

ComplianceEventAction Table

The ComplianceEventAction table holds the list of possible actions in the handling of ‘compliance events’. These are any event, such as the arrival of a new application version or a change in primary application for a license, that should trigger recalculation of linked applications through upgrade and downgrade rights.

Table 126: Database columns for ComplianceEventAction table

Database Column	Details
EventActionID	<i>Type:</i> integer. Key. Generated ID A unique identifier for each ComplianceEventAction. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• 1 = Notification (the event is automatically managed, and the operator is to be advised of the result)• 2 = Request for Action (the license is not managed automatically, and the operator receives a suggested action).
EventActionResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing an event type. Foreign key to the ComplianceResourceString table.
EventActionDefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the type resource string has no translation.

ComplianceEventHistory Table

ComplianceEventHistory stores a history of state changes for each compliance event.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 127: Database columns for ComplianceEventHistory table

Database Column	Details
ComplianceEventHistoryID	Type: integer. Key. Generated ID Unique identifier for an event history record.
ComplianceEventID	Type: integer. Key The event whose history is being recorded. Foreign key to the ComplianceEvent table.
UserName	Type: text (max 60 characters) The operator who made the change.
HistoryDate	Type: datetime The date of the change.
FieldName	Type: text (max 256 characters). Nullable The field name that has been updated. Foreign key to the ComplianceResourceString table.
OldValue	Type: text (max 500 characters). Nullable The value before the change.
NewValue	Type: text (max 500 characters). Nullable The value after the change.

ComplianceEventState Table

ComplianceEventState is a static table holding all possible event states.

Table 128: Database columns for ComplianceEventState table

Database Column	Details
EventStateID	<i>Type:</i> integer. Key. Generated ID A unique identifier for each ComplianceEventState. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• 1 = New (action needs to be taken for this event)• 2 = Postponed (no action needs to be taken at this time)• 3 = Accepted (the proposed action has been taken for this event)• 4 = Rejected (the proposed action will not be taken).
EventStateResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing an event state. Foreign key to the ComplianceResourceString table.
EventStateDefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the state resource string has no translation.

ComplianceEventType Table

ComplianceEventType is a static table that holds all possible types of event.

Table 129: Database columns for ComplianceEventType table

Database Column	Details
EventTypeID	<i>Type:</i> integer. Key. Generated ID A unique identifier for each ComplianceEventType. Reserved for future expansion. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• 1 = Software License Change.
EventTypeResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing an event type. Foreign key to the ComplianceResourceString table.
EventTypeDefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the type resource string has no translation.

ComplianceHistory Table

The ComplianceHistory table records changes to many entities used in FlexNet Manager Suite. This table has a series of ID columns, any one (or sometimes more) of which may be set to associate the history with a particular item. These ID columns no longer have foreign keys to other tables. This allows us to retain history of deleted objects in order to maintain an audit trail (as yet, there is no UI around this information), and also to improve performance when deleting objects.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 130: Database columns for ComplianceHistory table

Database Column	Details
ComplianceHistoryID	Type: big integer. Key. Generated ID Unique identifier for a history record.
AssetID	Type: integer. Key. Nullable ID from the Asset table.
ComplianceComputerID	Type: integer. Key. Nullable ID from the ComplianceComputer table.
ContractID	Type: integer. Key. Nullable ID from the Contract table.
VendorID	Type: integer. Key. Nullable ID from the Vendor table.
VirtualMachineID	Type: integer. Nullable ID from the VirtualMachine table.
PurchaseOrderID	Type: integer. Nullable ID from the PurchaseOrder table.
PurchaseOrderDetailID	Type: integer. Key. Nullable ID from the PurchaseOrderDetail table.
SoftwareLicenseID	Type: integer. Key. Nullable ID from the SoftwareLicense table
SoftwareTitleID	Type: integer. Key. Nullable ID from the SoftwareTitle table

Database Column	Details
PaymentScheduleID	Type: integer. Key. Nullable ID from the PaymentSchedule table
InstanceID	Type: integer. Key. Nullable ID from the Instance table
ComplianceUserID	Type: integer. Key. Nullable ID from the ComplianceUser table
ComplianceOperatorID	Type: integer. Nullable ID from the ComplianceOperator table
DocumentID	Type: integer. Key. Nullable ID from the Document table
DocumentNoteID	Type: integer. Nullable ID from the DocumentNote table
ContractNoteID	Type: integer. Nullable ID from the ContractNote table
ProjectID	Type: integer. Key. Nullable ID from the Project table
FieldName	Type: text (max 256 characters). Nullable The field name that has been updated. Foreign key to the ComplianceResourceString table.
OldValue	Type: text (max 4000 characters). Nullable Typically the value before the change, although at times, when multiple pieces of information are required to identify the action taking place, this field may store other supporting information. For example, when an operator is granted rights to access a contract, this field stores the type of access (such as "Normal" or "Administrator") while the NewValue field stores the name of the contract.
NewValue	Type: text (max 4000 characters). Nullable Typically the value after the change, although refer to the above definition of the OldValue column for a description of extenuating circumstances.
NeedsApproval	Type: boolean Set this field to True if the change requires approval. Used usually to track changes to computer hardware.

Database Column	Details
ValuesAreResourceStrings	<i>Type:</i> boolean Set this field to True if the old and new values should be looked up as resource strings.
ComplianceHistoryTypeID	<i>Type:</i> integer Foreign key to the HistoryType table.
UserName	<i>Type:</i> text (max 60 characters) The operator who made the change.
HistoryDate	<i>Type:</i> datetime. Key The date of the change.
Comments	<i>Type:</i> text (max 2000 characters). Nullable Comments recorded about the change after it was made.

ComplianceHistoryColumn Table

The ComplianceHistoryColumn table lists the fields (columns) for which history details can be recorded.

Table 131: Database columns for ComplianceHistoryColumn table

Database Column	Details
ComplianceHistoryColumnID	<i>Type:</i> integer. Key. Generated ID A unique identifier for a history column.
TableName	<i>Type:</i> text (max 128 characters). Key The name of the database table to which the history-record settings apply. This may have a suffix of .1 or .2. These suffixes are used for grouping purposes. Do not edit this field.
ColumnName	<i>Type:</i> text (max 128 characters). Key A description of the column in the specified TableName for which the history record settings apply. If this row relates to an entire table, the ColumnName will contain the word "History", for example, "Asset History" or "Contract History".
BitwiseValue	<i>Type:</i> integer. Key The bitwise value uniquely identifies each row relating to a single TableName. Typically, a value of 1 indicates that this row relates to an entire table. A value greater than 1 indicates that this row relates to a single field in the table. Do not edit this field.
RecordHistory	<i>Type:</i> boolean Boolean field to indicate if history should be recorded. Set this value to 1 (True) to record history details. Set this value to 0 (False) if no history details should be recorded.

ComplianceHistoryType Table

ComplianceHistoryType is a static table listing all valid types of history records.

Table 132: Database columns for ComplianceHistoryType table

Database Column	Details
ComplianceHistoryTypeID	<i>Type:</i> integer. Key. Generated ID A unique identifier for a history type.

Database Column	Details
ComplianceHistoryType Description	<p>Type: text (max 100 characters)</p> <p>A unique identifier for each ComplianceHistoryType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = Insert • 2 = Delete • 3 = Update • 4 = Link • 5 = Unlink • 6 = Allocated • 7 = Unallocated • 8 = Assigned • 9 = Unassigned • 10 = Operator unlinked from user due to duplicate login (operator history) • 11 = Operator unlinked from user due to duplicate login (user history) • 12 = Rights to contract granted • 13 = Rights to contract updated • 14 = Rights to contract removed • 15 = Rights to document granted • 16 = Rights to document updated • 17 = Rights to document removed • 18 = Receives (referring to escalations or alerts) • 19 = No longer receives (referring to escalations or alerts) • 20 = Assigned responsibility • 21 = Unassigned responsibility • 22 = Final state of entity when deleted • 23 = Rights to contract removed because contract was deleted • 24 = Rights to document removed because document was deleted • 25 = No longer receives (referring to escalations or alerts) because entity deleted

Database Column	Details
	<ul style="list-style-type: none">• 26 = Unassigned responsibility because entity was deleted• 27 = Responsibility type changed.
ResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing a history type. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the type resource string has no translation.

ComplianceImage Table

The ComplianceImage table stores a collection of images to use on property display dialogs.

Table 133: Database columns for ComplianceImage table

Database Column	Details
ComplianceImageName	<i>Type:</i> text (max 50 characters). Key The name of the image.
ComplianceImageFile	<i>Type:</i> text The binary representation of the image.

ComplianceLicenseUser Table

If external end-users, reported by systems such as SAP and stored in the `LicenseUser` table, can be matched to existing end-users in the enterprise (stored in the `ComplianceUser` table), the link between them is recorded in the `ComplianceLicenseUser` table.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 134: Database columns for `ComplianceLicenseUser` table

Database Column	Details
<code>LicenseUserID</code>	<i>Type:</i> integer. Key A unique identifier for the external end-user. Foreign key to the <code>LicenseUser</code> table.
<code>ComplianceUserID</code>	<i>Type:</i> integer. Key A unique identifier for the end-user in the enterprise. Foreign key to the <code>ComplianceUser</code> table.

CompliancePredefinedSearch Table

The CompliancePredefinedSearch holds a list of the predefined asset and licenses searches available to the operator. Each predefined search has its own grid in the FlexNet Manager Suite UI, and is accessed from a node which is a child of either Licenses or Assets nodes.

Table 135: Database columns for CompliancePredefinedSearch table

Database Column	Details
CompliancePredefinedSearchID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each CompliancePredefinedSearch. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = New Inventory • 2 = Changed Assets • 3 = Lease Expiry • 4 = Warranty Expiry • 5 = Missing Computers • 6 = License Breach • 7 = License Expiry • 8 = License Contract Expiry • 9 = License Unused • 10 = UnLicensed Apps • 11 = UnLicensed Installs • 12 = License Group Breach • 13 = License Upgrade Downgrade.
SearchNameResource	<p><i>Type:</i> text (max 128 characters). Key</p> <p>Resource string identifying the predefined search.</p>
SearchNameDefault	<p><i>Type:</i> text (max 128 characters)</p> <p>The name of the predefined search.</p>
AmberThreshold	<p><i>Type:</i> integer</p> <p>Indicates when the amber state should be shown in the related traffic light summary.</p>

Database Column	Details
RedThreshold	<i>Type:</i> integer Indicates when the red state should be shown in the related traffic light summary.
DateSearch	<i>Type:</i> boolean. Key True indicates that the search is date based. False means count based.
ComplianceSearchType	<i>Type:</i> text (max 128 characters). Key. Nullable Type of search. Matches the name of a row in the ComplianceSearchType table.

ComplianceResponsibility Table

ComplianceResponsibility links end-users to a contract with various responsibility types.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 136: Database columns for ComplianceResponsibility table

Database Column	Details
ComplianceResponsibilityID	<i>Type:</i> integer. Key. Generated ID A unique identifier for a record.
ResponsibilityTypeID	<i>Type:</i> integer The particular type of responsibility. Foreign key to the ResponsibilityType table.
ContractID	<i>Type:</i> integer. Key The contract for which this end-user has some responsibility. Foreign key to the Contract table.
ComplianceUserID	<i>Type:</i> integer. Key The end-user who has this responsibility for (or relationship to) the contract. Foreign key to the ComplianceUser table.
Comment	<i>Type:</i> text (max 500 characters). Nullable Any operator comments related to the user responsibility.

ComplianceSavedSearch Table

The ComplianceSavedSearch table holds the name of a custom view and any descriptive information about it.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 137: Database columns for ComplianceSavedSearch table

Database Column	Details
ComplianceSavedSearchID	Type: integer. Key. Generated ID A unique identifier for a custom view.
SearchName	Type: text (max 64 characters). Nullable The name of the custom view.
Description	Type: text (max 1000 characters). Nullable A description of the custom view.
SearchGridLayout	Type: text. Nullable The grid layout used in the custom view.
SearchSQL	Type: text. Nullable SQL statement that generates the data set for the custom view.
SearchSQLConnection	Type: text (max 500 characters) SQL connection to use to execute search SQL: 'Live', 'DataWarehouse', 'QuerySnapshot', 'ExternalFNMEA', or connection string.
SearchMapping	Type: XML. Nullable Search query XML to SQL mapping.
SearchXML	Type: XML. Nullable Search query XML.
CreatedBy	Type: text (max 128 characters) The operator who created the custom view.
CreationDate	Type: datetime The date the custom view was created.
ModifiedBy	Type: text (max 128 characters). Nullable The operator who last modified the custom view.

Database Column	Details
ModificationDate	<i>Type:</i> datetime. Nullable The date the custom view was last modified.
ComplianceSearchTypeID	<i>Type:</i> integer. Key The type of the custom view. Foreign key to the ComplianceSearchType table.
ComplianceSearchFolderID	<i>Type:</i> integer. Key The folder in which this custom view is stored. Foreign key to the ComplianceSearchFolder table.
CreatedByOperatorID	<i>Type:</i> integer. Key. Nullable ID of the operator who created the view. Foreign key to the ComplianceOperator table.
RestrictedAccessTypeID	<i>Type:</i> integer. Key Defined access type to the view. Foreign key to the RestrictedAccessType table.
CanDelete	<i>Type:</i> boolean Set this to False for predefined custom views which an operator is not allowed to delete.
CanChangeMasterObject	<i>Type:</i> boolean Set this to False if the this view has a fixed master object.
ComplianceSavedSearchSystemID	<i>Type:</i> integer. Key. Nullable An identifier for a system custom view.
SearchNameResourceName	<i>Type:</i> text (max 256 characters). Nullable The unique name of the localizable resource string representing a column name. Foreign key to the ComplianceResourceString table.
DescriptionResourceName	<i>Type:</i> text (max 256 characters). Nullable The unique name of the localizable resource string representing a column name. Foreign key to the ComplianceResourceString table.
SavedSearchLink	<i>Type:</i> text. Nullable The saved built in report or view link.
SavedSearchFilter	<i>Type:</i> text. Nullable The saved filter for report or view

ComplianceSchedule Table

ComplianceSchedule defines schedules that take place repeatedly at a specified interval.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 138: Database columns for ComplianceSchedule table

Database Column	Details
ComplianceScheduleID	Type: integer. Key. Generated ID A unique identifier for the schedule.
TermAndConditionID	Type: integer. Key. Nullable The term/condition that the schedule is associated with. Foreign key to the TermAndCondition table.
StartDate	Type: datetime The date on which this schedule first applies.
EndDate	Type: datetime The date on which this schedule ends.
RepeatIntervalTypeID	Type: integer. Key. Nullable The type of repeat interval. Foreign key to the IntervalType table.
RepeatInterval	Type: integer. Nullable The interval between repeats of this schedule.

ComplianceSearchFolder Table

The ComplianceSearchFolder table identifies a folder for storing a custom search (or view), and tracks the parent-child relationships of folders to establish their hierarchy.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 139: Database columns for ComplianceSearchFolder table

Database Column	Details
ComplianceSearchFolderID	<i>Type:</i> integer. Key. Generated ID A unique identifier for a saved search folder.
Name	<i>Type:</i> text (max 128 characters). Key. Nullable The name of the folder.
ParentFolderID	<i>Type:</i> integer. Key. Nullable Identifies the parent that contains this folder. Foreign key to another folder in this ComplianceSearchFolder table.
ComplianceSearchTypeID	<i>Type:</i> integer. Key The kind of custom view stored in this folder. Foreign key to the ComplianceSearchType table.
Path	<i>Type:</i> text (max 128 characters). Key. Nullable The internal path to the folder.
PredefinedSearchesCreated	<i>Type:</i> boolean. Nullable Set this field to True to indicate that this folder holds generated searches.
CanDelete	<i>Type:</i> boolean. Nullable Set this field to False for predefined folders which operators are not allowed to deleted.
CreatedByOperatorID	<i>Type:</i> integer. Key. Nullable ID of the operator who created the view. Foreign key to the ComplianceOperator table.
RestrictedAccessTypeID	<i>Type:</i> integer. Key Defined access type to the view. Foreign key to the RestrictedAccessType table.
ComplianceSearchFolderSystemID	<i>Type:</i> integer. Key. Nullable An identifier for a system custom view folder.

Database Column	Details
NameResourceName	<i>Type:</i> text (max 256 characters). Key. Nullable The unique name of the localizable resource string representing a folder name. Foreign key to the ComplianceResourceString table.

ComplianceSearchType Table

ComplianceSearchType is a static table holding the name of the basic objects, such as an asset or license, for which custom views can be created.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 140: Database columns for ComplianceSearchType table

Database Column	Details
ComplianceSearchTypeID	<p>Type: integer. Key. Generated ID</p> <p>A unique identifier for a type of compliance search. Possible values, together with the associated names of the object being searched, are:</p> <ul style="list-style-type: none"> • -1 = Custom • 1 = Asset • 2 = License • 3 = Contract • 4 = Vendor • 5 = PurchaseOrder • 6 = SoftwareTitle • 7 = User • 8 = Computer • 13 = PurchaseOrderDetail • 14 = VirtualMachine • 15 = InstalledSoftware • 16 = SoftwareLicenseAllocation • 17 = PaymentSchedule • 18 = PaymentScheduleDetail • 19 = OracleInstance • 20 = OracleComponent • 21 = Suite • 22 = SuiteMember • 23 = TermAndCondition • 24 = ContractHistoryView • 25 = ContractDocumentView • 26 = DocumentNote • 27 = ComplianceResponsibility • 28 = ContractNote • 29 = Location

Database Column	Details
	<ul style="list-style-type: none"> • 30 = CostCenter • 31 = CorporateStructure • 32 = Category • 33 = VendorContact • 34 = Cluster.
TypeName	<i>Type:</i> text (max 64 characters). Key The name of the objects being searched.
TypeNameResourceName	<i>Type:</i> text (max 256 characters). Nullable The unique name of the localizable resource string representing a type name. Foreign key to the ComplianceResourceString table.
QuerySetup	<i>Type:</i> text. Nullable Query pre-calculation statement executed before custom view query.
QueryFilter	<i>Type:</i> text. Nullable Query filter template executed before custom view query.
QueryTemplate	<i>Type:</i> text. Nullable Query template for this search type.
IsCustom	<i>Type:</i> boolean False if the relation is out of the box, false otherwise.

ComplianceSearchTypeColumn Table

The ComplianceSearchTypeColumn table identifies all columns that may be used in custom views.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 141: Database columns for ComplianceSearchTypeColumn table

Database Column	Details
ComplianceSearchTypeColumnID	Type: integer. Key. Generated ID A unique identifier for a custom view column.
ColumnName	Type: text (max 128 characters). Key The default value of the display column name.
ColumnNameResourceName	Type: text (max 256 characters). Nullable The unique name of the localizable resource string representing a column name. Foreign key to the ComplianceResourceString table.
QuerySetup	Type: text. Nullable Query pre-calculation statement executed before the custom view query.
FromTable	Type: text. Nullable The name of the database table where the column can be found.
SelectName	Type: text. Nullable The name of the column in the database.
JoinClause	Type: text. Nullable The SQL join that links other tables to provide the relevant data for this column.
WhereClause	Type: text. Nullable The SQL "WHERE" statement that limits the information returned by the custom view.
SelectOptionsSQL	Type: text. Nullable The SQL that selects the predefined list that the user can display when filtering on this column.

Database Column	Details
FilterGroupType	<p><i>Type:</i> integer. Nullable</p> <p>An ID that indicates the kind of value expected in this column, which in turn determines what kinds of filter options (such as <i>Contains</i>, <i>Starts With</i>) will be offered for this column. Possible values (and their associated meanings) are:</p> <ul style="list-style-type: none"> • 1 = string • 2 = number • 3 = list • 4 = date • 5 = group • 6 = money • 7 = boolean.
DefaultFilterType	<p><i>Type:</i> integer. Nullable</p> <p>The type of field that should be used to search for information in this column. Possible values (and their associated meanings) are the same as for the previous field.</p>
ComplianceSearchTypeID	<p><i>Type:</i> integer. Key</p> <p>The type of that the column is related to. Foreign key to the <i>ComplianceSearchType</i> table.</p>
RequiresSearchTypeID	<p><i>Type:</i> integer. Nullable</p> <p>For special cases, a column may need data from another compliance object as well. Foreign key to the <i>ComplianceSearchType</i> table.</p>
Mandatory	<p><i>Type:</i> boolean</p> <p>Set this field to <i>True</i> if this column must always be returned in the SQL “SELECT” statement.</p>
PrimaryKey	<p><i>Type:</i> boolean</p> <p>Set this field to <i>True</i> if this column is the primary key of the SQL “SELECT” statement.</p>
SelectByDefault	<p><i>Type:</i> boolean</p> <p>Set this field to <i>True</i> if this column should be included (checked) by default when the operator is creating a custom view. If <i>False</i>, the operator may include it manually.</p>
IsCustom	<p><i>Type:</i> boolean</p> <p><i>False</i> if the relation is out of the box, <i>false</i> otherwise.</p>

Database Column	Details
LinkAction	<i>Type:</i> text (max 64 characters). Nullable The action to be used for the drill through link on this column.
LinkController	<i>Type:</i> text (max 64 characters). Nullable The controller to be used for the drill through link on this column.
LinkIndicateOrigin	<i>Type:</i> boolean Whether the drill through link on this column contains the report page URL as the origin URL.
LinkFragmentField	<i>Type:</i> text (max 64 characters). Nullable The fragment field name to be used for the drill through link on this column.
IsMultiEditEnabled	<i>Type:</i> boolean Whether the multiple object drill through is enabled on this object type.
MultiEditConditionField	<i>Type:</i> text (max 256 characters). Nullable Field on which the multiple object drill through will be evaluated against.

ComplianceSearchTypeRelation Table

The ComplianceSearchTypeRelation table tracks relationships between different objects for which operators can create custom views.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 142: Database columns for ComplianceSearchTypeRelation table

Database Column	Details
ComplianceSearchTypeRelationID	Type: integer. Key. Generated ID A unique identifier for a relationship.
RelationName	Type: text (max 256 characters). Key The unique internal name of this relation.
DescriptionResourceName	Type: text (max 256 characters). Nullable The unique name of the localizable resource string representing a relationship name. Foreign key to the ComplianceResourceString table.
DescriptionDefault	Type: text (max 256 characters) The default description of the relationship.
FromSearchTypeID	Type: integer. Key The ComplianceSearchType that represents the source of the relationship.
ToSearchTypeID	Type: integer. Key The ComplianceSearchType that represents the destination of the relationship.
ToMany	Type: boolean Set this field to True to allow more than one related row in the destination table for each row in the source table. If this field is False, rows have a one-to-one relationship.
JoinClause	Type: text The SQL join clause used to join the source object with a related object.
FilterClause	Type: text The SQL filter clause used to filter the source object with a related object.
IsCustom	Type: boolean False if the relation is out of the box, false otherwise.

ComplianceTask Table

ComplianceTask holds a collection of tasks, which are audit responsibilities generated by settings on a TermAndCondition.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 143: Database columns for ComplianceTask table

Database Column	Details
ComplianceTaskID	Type: integer. Key. Generated ID A unique identifier for the task.
ComplianceScheduleID	Type: integer. Key. Nullable The schedule the task is associated with. Foreign key to the ComplianceSchedule table.
TaskDate	Type: datetime. Nullable The date for the task.

ComplianceUserPropertyValue Table

For each end-user, ComplianceUserPropertyValue stores the values for the custom properties defined in ComplianceUserTypeProperty.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 144: Database columns for ComplianceUserPropertyValue table

Database Column	Details
ComplianceUserProperty ValueID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the property value.
ComplianceUserType PropertyID	<i>Type:</i> integer. Key The property whose value is being stored. Foreign key to the ComplianceUserTypeProperty table.
ComplianceUserID	<i>Type:</i> integer. Key The end-user associated with this property value. Foreign key to the ComplianceUser table.
PropertyValue	<i>Type:</i> text (max 4000 characters) The value of the property for the specified ComplianceUser.
CreationUser	<i>Type:</i> text (max 128 characters). Nullable The operator who created the record.
CreationDate	<i>Type:</i> datetime The date the record was created.
UpdatedUser	<i>Type:</i> text (max 128 characters). Nullable The operator who last updated the record.
UpdatedDate	<i>Type:</i> datetime. Nullable The date the record was last updated.

ComplianceUserTypeProperty Table

ComplianceUserTypeProperty defines extra custom properties for all end-users.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 145: Database columns for ComplianceUserTypeProperty table

Database Column	Details
ComplianceUserType PropertyID	Type: integer. Key. Generated ID A unique identifier for the property.
PropertyName	Type: text (max 256 characters). Key The name of the property.
CustomPropertyDisplayX MLID	Type: integer. Nullable Foreign key to a record in the CustomPropertyDisplayXML table, describing how to show the property on a property dialog.

ComputerChassisType Table

ComputerChassisType is a static table listing all possible computer chassis (case) types.

Table 146: Database columns for ComputerChassisType table

Database Column	Details
ChassisTypeID	<p>Type: integer. Key. Generated ID</p> <p>A unique identifier for each ComputerChassisType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = Other • 2 = Unknown • 3 = Desktop • 4 = Low Profile Desktop • 5 = Pizza Box • 6 = Mini Tower • 7 = Tower • 8 = Portable • 9 = Laptop • 10 = Notebook • 11 = Other Hand Held • 12 = Docking Station • 13 = All in One • 14 = Sub Notebook • 15 = Space-Saving • 16 = Lunch Box • 17 = Main System Chassis • 18 = Expansion Chassis • 19 = Sub-Chassis • 20 = Bus Expansion Chassis • 21 = Peripheral Chassis • 22 = Storage Chassis • 23 = Rack Mount Chassis • 24 = Sealed-Case PC. • 25 = Smart Phone • 26 = Tablet

Database Column	Details
WMICHassisTypeID	<i>Type:</i> integer. Nullable The identifier for the chassis type identified in WMI.
ResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing a computer role. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 128 characters) The text to display if the chassis type resource string has no translation.
IncludeInLicenseRec SecondUseDefault	<i>Type:</i> boolean Determines whether or not a second installation of an application on a computer of this chassis type (as well as on a primary computer assigned to the same end-user) may be counted as a legal second use under the Right of Second Use granted by some licenses. Currently, this field is used to group together chassis types that can be treated as "laptops" for this purpose.
SecondUseBitwiseValue	<i>Type:</i> integer Reserved for future use. Do not edit.

ConsolidatedLicenseUser Table

This table stores the data specific to a consolidated license user.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 147: Database columns for ConsolidatedLicenseUser table

Database Column	Details
ConsolidatedLicenseUserID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the consolidated license user.
LicenseUserID	<i>Type:</i> integer Foreign key to the LicenseUser table.
ConsolidatedGroupNumber	<i>Type:</i> integer The unique identifier showing which users are duplicates of one another.
ConsolidatedName	<i>Type:</i> text The name of the consolidated user. If consolidated by rules engine, this column stores the name of the user with the lowest LicenseUserID
ConsolidationTypeID	<i>Type:</i> integer Foreign key to the ConsolidationType table.

ConsolidationType Table

This table stores consolidation type.

Table 148: Database columns for ConsolidationType table

Database Column	Details
ConsolidationTypeID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the consolidation type.
ResourceName	<i>Type:</i> text (max 256 characters). Key. Nullable A localizable resource string representing a consolidation type. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the consolidation type resource string has no translation.

Contract Table

The Contract table contains a list of all the contracts in the system.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 149: Database columns for Contract table

Database Column	Details
ContractID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the contract.
ContractNo	<i>Type:</i> text (max 60 characters) The contract number assigned by the operator.
ContractName	<i>Type:</i> text (max 100 characters) A contract name assigned by the operator.
ContractTypeID	<i>Type:</i> integer. Key Identifies the type of contract. Foreign key to the ContractType table.
ContractStatusID	<i>Type:</i> integer Identifies the status of the contract. Foreign key to the ContractStatus table.
NeverExpires	<i>Type:</i> boolean If set to True, this contract never expires. If False, the contract expires at the date specified in the EndDate field.
StartDate	<i>Type:</i> datetime. Nullable The start date of the contract.
EndDate	<i>Type:</i> datetime. Nullable The end date of the contract.
PreExpiryDate	<i>Type:</i> datetime. Nullable The date at which a contract should be reviewed prior to its expiry date.
RenewalDate	<i>Type:</i> datetime. Nullable The date at which a contract is due to be renewed.
Price	<i>Type:</i> currency. Nullable The price of the contract.

Database Column	Details
PriceRateID	<p><i>Type:</i> integer. Nullable</p> <p>The currency rate to be applied to the above contract price. Foreign key to the CurrencyRate table.</p>
PeriodTypeID	<p><i>Type:</i> integer. Nullable</p> <p>The frequency with which the period payments are applicable. Foreign key to the PeriodType table.</p>
BuyoutCost	<p><i>Type:</i> currency. Nullable</p> <p>The buyout cost of the contract.</p>
BuyoutCostRateID	<p><i>Type:</i> integer. Nullable</p> <p>The currency rate to be applied to the above buyout cost. Foreign key to the CurrencyRate table.</p>
ManagerID	<p><i>Type:</i> integer. Key. Nullable</p> <p>The person who manages the contract. Foreign key to the ComplianceUser table.</p>
Comments	<p><i>Type:</i> text. Nullable</p> <p>Comments recorded about the contract.</p>
PeriodicPayment	<p><i>Type:</i> currency. Nullable</p> <p>The price of periodic payments associated with this contract.</p>
PeriodicPaymentRateID	<p><i>Type:</i> integer. Nullable</p> <p>The currency rate to be applied to the periodic payments figure above. Foreign key to the CurrencyRate table.</p>
VendorID	<p><i>Type:</i> integer. Key. Nullable</p> <p>The vendor with which the contract agreement has been made. Foreign key to the Vendor table.</p>
MasterContractID	<p><i>Type:</i> integer. Key. Nullable</p> <p>The contract that is the master of this contract. Foreign key to another contract in this Contract table.</p>
LocationID	<p><i>Type:</i> text (max 128 characters). Key. Nullable</p> <p>Any enterprise location associated with this contract. Foreign key to the GroupEx table.</p>
BusinessUnitID	<p><i>Type:</i> text (max 128 characters). Key. Nullable</p> <p>Any enterprise corporate unit associated with this contract. Foreign key to the GroupEx table.</p>

Database Column	Details
CostCenterID	<p><i>Type:</i> text (max 128 characters). Key. Nullable</p> <p>Any enterprise cost center associated with this contract. Foreign key to the GroupEx table.</p>
CategoryID	<p><i>Type:</i> text (max 128 characters). Key. Nullable</p> <p>Any category used in this enterprise that is associated with this contract. Foreign key to the GroupEx table.</p>
LicenseDowngradeEnabled	<p><i>Type:</i> boolean</p> <p>If this field is set to True, licenses can inherit downgrade rights from this contract. If False (the default), licenses cannot inherit downgrade rights.</p>
LicenseDowngradeToVersion	<p><i>Type:</i> boolean</p> <p>If this field is set to True, any license inheriting downgrade rights from this contract can cover all previous releases (with the same edition) of the primary application. If False, licenses inheriting downgrade rights may not downgrade to earlier versions.</p>
LicenseDowngradeToEdition	<p><i>Type:</i> boolean</p> <p>If this field is set to True, any license inheriting downgrade rights from this contract can cover all lower editions of this version of the primary application. If False, licenses inheriting downgrade rights may not downgrade to lower editions.</p>
LicenseUpgradeEnabled	<p><i>Type:</i> boolean</p> <p>If this field is set to True, licenses can inherit upgrade rights from this contract. If False (the default), licenses cannot inherit upgrade rights.</p>
LicenseUpgradeToVersion	<p><i>Type:</i> boolean</p> <p>If this field is set to True, any license inheriting upgrade rights from this contract can cover all later releases (with the same edition) of the primary application. If False, licenses inheriting upgrade rights may not upgrade to later versions.</p>
LicenseUpgradeUntil ContractExpiry	<p><i>Type:</i> boolean</p> <p>If this field is set to True, any license inheriting upgrade rights from this contract can cover all later releases (with the same edition) of the primary application, as long as they were released before the expiry date (EndDate) of the contract. If False, licenses inheriting upgrade rights do not take the application release date into consideration.</p>
GrantSecondUseToLicense	<p><i>Type:</i> boolean</p> <p>If this field is set to True, licenses can inherit the right of second use from this contract. If False (the default), licenses cannot inherit the right of second use.</p>

Database Column	Details
SecondUsageWorkLaptop	<p><i>Type:</i> boolean</p> <p>If this field is set to <code>True</code>, any license inheriting from this contract will confer the right of second use on a work laptop. If <code>False</code>, licenses inheriting from this contract will not confer the right of second use.</p>
SecondUsageAtHome	<p><i>Type:</i> boolean</p> <p>If this field is set to <code>True</code>, any license inheriting from this contract will confer the right of second use on a home computer, for the same end-user as the primary end-user of the license entitlement consumed at work. If <code>False</code>, licenses inheriting from this contract will not confer the right of second use on a home computer.</p>
GrantVirtualInstallsToLicense	<p><i>Type:</i> boolean</p> <p>If this field is set to <code>True</code>, licenses can inherit the virtual machine licensing rights from this contract. If <code>False</code> (the default), licenses cannot inherit virtual machine licensing rights.</p>
CoverInstallsOnVirtualMachines	<p><i>Type:</i> boolean</p> <p>If this field is set to <code>True</code>, any license inheriting virtual machine rights from this contract may be used to account for installations on virtual machines. If <code>False</code>, licenses inheriting virtual machine rights may only account for installations on physical machines.</p>
LimitNumberOfVirtualInstalls	<p><i>Type:</i> boolean</p> <p>If this field is set to <code>True</code>, there is a limit to the number of virtual machine installations that may be covered by any license inheriting virtual machine rights from this contract. If this field is <code>False</code>, one license entitlement may cover any use on virtual machines (typically within one host computer).</p>
NumberOfAllowedVirtualInstalls	<p><i>Type:</i> integer. Nullable</p> <p>If this contract confers the right for an inheriting license to cover installations on virtual machines, this field specifies how many installations per host are allowed before an additional license entitlement (or point) is consumed.</p>
LimitVirtualInstallsIncludesHost	<p><i>Type:</i> boolean</p> <p>If this field is <code>True</code>, the host operating system installations are included in the overall count of operating systems on the host when there is a limit on the number of allowed virtual installs for each license. If <code>False</code>, the host operating system is not considered when determining virtual install limits.</p>
UseHostProcessorInformation	<p><i>Type:</i> boolean</p> <p>If virtual installs are allowed, this field controls whether host information is used by an inheriting license when calculating the license points consumed.</p>

Database Column	Details
GrantLimitPointsToLicense	<p><i>Type:</i> boolean</p> <p>If this field is set to <code>True</code>, licenses can inherit the right of multiple use from this contract. If <code>False</code> (the default), licenses cannot inherit the right of multiple use.</p>
LimitNumberOfApplicationsEachLicensePointCovers	<p><i>Type:</i> boolean</p> <p>If this field is set to <code>True</code>, there is a limit, for any inheriting license, to the number of application installations allowed per license entitlement (or point). If this bit is <code>False</code> (the default), an inheriting license entitles you to any number of installations of software linked to this license on the one computer.</p>
NumberOfApplicationInstallsAllowedPerLicensePoint	<p><i>Type:</i> integer. Nullable</p> <p>Where the previous field is set to <code>True</code>, this column defines the limited number of application installations allowed per entitlement (or point).</p>
LimitNumberOfComputersUserLicenseCanBeInstalledOn	<p><i>Type:</i> boolean</p> <p>If this field is set to <code>True</code>, there is a limit, for an inheriting user-based license, to the number of computers that an end-user can use per entitlement (or point) consumed. If this field is <code>False</code> (the default), a single end-user is entitled to install related software for his/her own use on any number of computers.</p>
NumberOfComputersAllowedPerUserLicensePoint	<p><i>Type:</i> integer. Nullable</p> <p>Where the previous field is set to <code>True</code>, this column defines the limited number of application installations an end-user is allowed per entitlement (or point).</p>
InitialPlatformQuantity	<p><i>Type:</i> integer. Nullable</p> <p>The number of desktops covered by the Microsoft Enterprise Agreement platform license at the start of the agreement.</p>
PurchaseProgramID	<p><i>Type:</i> integer. Nullable</p> <p>Identifies the purchase program of contract. Foreign key to the <code>PurchaseProgram</code> table.</p>
MSSelectApplicationLevelID	<p><i>Type:</i> integer. Nullable</p> <p>Identifies the Microsoft Select level for applications. Foreign key to the <code>MSSelectLevel</code> table.</p>
MSSelectSystemLevelID	<p><i>Type:</i> integer. Nullable</p> <p>Identifies the Microsoft Select level for systems. Foreign key to the <code>MSSelectLevel</code> table.</p>

Database Column	Details
MSSelectServerLevelID	<i>Type:</i> integer. Nullable Identifies the Microsoft Select level for servers. Foreign key to the MSSelectLevel table.
CreationUser	<i>Type:</i> text (max 128 characters). Nullable The operator who created the record.
CreationDate	<i>Type:</i> datetime The date the record was created.
UpdatedUser	<i>Type:</i> text (max 128 characters). Nullable The operator who last updated the record.
UpdatedDate	<i>Type:</i> datetime. Nullable The date the record was last updated.
TotalValue	<i>Type:</i> currency. Nullable The total value of the contract.
TotalValueRateID	<i>Type:</i> integer. Nullable The rate for the total value. Foreign key to the CurrencyRate table.
MonthlyValue	<i>Type:</i> currency. Nullable The cost of the contract per month.
MonthlyValueRateID	<i>Type:</i> integer. Nullable The rate for the monthly cost. Foreign key to the CurrencyRate table.
ProjectID	<i>Type:</i> integer. Key. Nullable A project for the Contract. Foreign key to the Project table.
SecurityTypeID	<i>Type:</i> integer. Nullable The type of security to use when determining which operators have access to the contract. Foreign key to the SecurityType table.
PreviousContractID	<i>Type:</i> integer. Key. Nullable A link to a contract that this contract has replaced. Foreign key to the Contract table.
ContractStateID	<i>Type:</i> integer. Nullable The state of the contract. Foreign key to the ContractState table.
LastRenewedDate	<i>Type:</i> datetime. Nullable The date when the contract was last renewed.

Database Column	Details
LicenseConsumptionEnabled	<i>Type:</i> boolean If this field is set to <code>True</code> , licenses can inherit consumption rules from this contract. If <code>False</code> (the default), licenses cannot inherit consumption rules.
LicenseMobilityEnabled	<i>Type:</i> boolean If this field is set to <code>True</code> , licenses can inherit mobility rights from this contract. If <code>False</code> (the default), licenses cannot inherit mobility rights.
ProcessorLimitsEnabled	<i>Type:</i> boolean If this field is set to <code>True</code> , licenses can inherit rights related to processor limits from this contract. If <code>False</code> (the default), licenses cannot inherit rights related to processor limits.

ContractNote Table

ContractNote stores a list of notes attached to a contract.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 150: Database columns for ContractNote table

Database Column	Details
ContractNoteID	Type: integer. Key. Generated ID A unique identifier for the contract note.
ContractID	Type: integer. Key The contract that the note is for. Foreign key to the Contract table.
ShortDescription	Type: text (max 100 characters) In the user interface, this maps to the contract reference to which the note relates.
LongDescription	Type: text. Nullable The content of the note.
CreationUser	Type: text (max 128 characters) The operator who created the note.
CreationDate	Type: datetime The date of creation of the note.
UpdatedUser	Type: text (max 128 characters) The operator who last updated the note.
UpdatedDate	Type: datetime The date of the last update to the note.

ContractNotification Table

ContractNotification lists the notifications that need to be sent for a contract.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 151: Database columns for ContractNotification table

Database Column	Details
ContractNotificationID	Type: integer. Key. Generated ID A unique identifier for the contract notification.
ContractID	Type: integer. Key The contract this record is associated with. Foreign key to the Contract table.
NotificationInterval	Type: integer Defines how long before the contract notification is sent.
NotificationIntervalTypeID	Type: integer Defines the interval type used to work out how long before a contract notification is sent. Foreign key to the IntervalType table.
NotificationTypeID	Type: integer. Key Defines the type of notification (contract renewal or contract expiry). Foreign key to the NotificationType table.

ContractNotificationResponsibility Table

ContractNotificationResponsibility keeps track of which responsibility groups need to be notified for contract expiry or renewals.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 152: Database columns for ContractNotificationResponsibility table

Database Column	Details
ContractNotificationResponsibilityID	<i>Type:</i> integer. Key. Generated ID Unique identifier for contract notification responsibility groups.
ContractID	<i>Type:</i> integer. Key The contract generating notifications. Foreign key to the Contract table.
ResponsibilityTypeID	<i>Type:</i> integer. Key The responsibility type of the end-users receiving notifications about the contract. Foreign key to the ResponsibilityType table.
NotificationTypeID	<i>Type:</i> integer. Key The type of notification (renewal or expiry) that these responsibility groups should receive notifications for. Foreign key to the NotificationType table.

ContractProperty Table

ContractProperty defines extra custom properties for contracts of a specified type.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 153: Database columns for ContractProperty table

Database Column	Details
ContractPropertyID	Type: integer. Key. Generated ID Unique identifier for a contract property.
ContractTypeID	Type: integer. Key The type of contract to which this property may apply. Foreign key to the ContractType table.
PropertyName	Type: text (max 256 characters). Key The name of the custom property. A unique identifier for a resource string. Foreign key to the ComplianceResourceString table.
CustomPropertyDisplayXMLID	Type: integer. Nullable Reference to a record in the CustomPropertyDisplayXML table, describing how to show the property on a property dialog.

ContractPropertyValue Table

For each contract, ContractPropertyValue stores the values for the custom properties defined in ContractProperty.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 154: Database columns for ContractPropertyValue table

Database Column	Details
ContractPropertyValueID	Type: integer. Key. Generated ID A unique identifier for a property value.
ContractID	Type: integer. Key The individual contract to which this value applies. Foreign key to the Contract table.
ContractPropertyID	Type: integer. Key The property that contains this value. The contract should have the same type as the type associated with this property. Foreign key to the ContractProperty table.
PropertyValue	Type: text (max 4000 characters) The property value.
CreationUser	Type: text (max 128 characters). Nullable The operator who created the record.
CreationDate	Type: datetime The date the record was created.
UpdatedUser	Type: text (max 128 characters). Nullable The operator who last updated the record.
UpdatedDate	Type: datetime. Nullable The date the record was last updated.

ContractScopingData Table

ContractScoping links contracts to the enterprise groups to which they apply. Exactly one of GroupExID and CategoryID must be non-NULL.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 155: Database columns for ContractScopingData table

Database Column	Details
ContractID	Type: integer. Key The contract the scoping applies to. Foreign key to the Contract table.
GroupExID	Type: text (max 128 characters). Key. Nullable The enterprise group that the scoping applies to. Foreign key to the GroupEx table.
CategoryID	Type: text (max 128 characters). Key. Nullable The category that the scoping applies to. Foreign key to the Category table.

ContractSecurityUser Table

ContractSecurityUser stores a list of permissions granted to an operator for a contract with Restricted security.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 156: Database columns for ContractSecurityUser table

Database Column	Details
ContractID	Type: integer. Key The contract with Restricted security. Foreign key to the Contract table.
ActionClassID	Type: integer. Key The type of permission being granted to the operator. Foreign key to the ActionClass table.
ComplianceOperatorID	Type: integer. Key The operator that the permission is granted to. Foreign key to the ComplianceOperator table.

ContractState Table

ContractState holds the different states a contract can be in.

Table 157: Database columns for ContractState table

Database Column	Details
ContractStateID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each ContractState. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = Draft• 2 = Suspended• 3 = Active• 4 = Archived• 5 = Cancelled• 6 = Expired• 7 = Completed.
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a contract state. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the state resource string has no translation.</p>

ContractStatus Table

ContractStatus is a static table listing all contract status values in the system.

Table 158: Database columns for ContractStatus table

Database Column	Details
ContractStatusID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each ContractStatus. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = Active • 2 = Archived • 3 = Draft • 4 = Suspended • 5 = Cancelled • 6 = Expired • 7 = Completed.
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a contract status. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the status resource string has no translation.</p>

ContractType Table

ContractType is a static table listing all contract types in the system.

Table 159: Database columns for ContractType table

Database Column	Details
ContractTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each ContractType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = General • 2 = Lease • 3 = Hardware Maintenance and Support • 4 = Software License • 5 = Software Maintenance and Support • 6 = Blanket purchase • 7 = Consulting services • 8 = Insurance • 9 = Rent • 10 = Subscription • 11 = Microsoft Business and Services Agreement • 12 = Microsoft Select License Agreement • 13 = Microsoft Select Plus Agreement • 14 = Microsoft Select License Enrollment • 15 = Microsoft Select Plus Affiliate • 16 = Microsoft Enterprise Agreement • 17 = Microsoft Enterprise Subscription Agreement.
ContractTypeResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a contract type. Foreign key to the ComplianceResourceString table.</p>
ContractTypeDefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the type resource string has no translation.</p>

Database Column	Details
XMLFile	<p><i>Type:</i> text. Nullable</p> <p>The layout of the property dialog for this type of computer, stored in XML format.</p>
PathResourceName	<p><i>Type:</i> text (max 256 characters)</p> <p>The unique name of the localizable resource string representing the parent contract type under which this contract type should be displayed. Foreign key to the ComplianceResourceString table.</p>
PathDefaultValue	<p><i>Type:</i> text (max 256 characters)</p> <p>The default parent contract type text to display if the resource string has no translation.</p>
PurchaseProgramID	<p><i>Type:</i> integer. Nullable</p> <p>The default purchase program for this contract type.</p>
CanCreate	<p><i>Type:</i> boolean</p> <p>Whether the end-user can manually create contracts of this type.</p>

ContractUseRight Table

ContractUseRight contains licensing rules most of which can be set by PURL.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 160: Database columns for ContractUseRight table

Database Column	Details
ContractUseRightID	Type: integer. Key. Generated ID A unique identifier
ContractID	Type: integer. Key A unique identifier for a contract.
ReassignmentTimeLimit AppliesDevice	Type: boolean If 1 then the license cannot be reassigned for some period of time (example is Microsoft 90 day rule)
ReassignmentTimeLimit AppliesUser	Type: boolean If 1 then the license cannot be reassigned for some period of time (example is Microsoft 90 day rule)
ReassignmentTimeLimit Device	Type: integer. Nullable The period (in days) within which the license cannot be reassigned
ReassignmentTimeLimitUser	Type: integer. Nullable The period (in days) within which the license cannot be reassigned
LicenseMobilityApplies	Type: boolean 1 if eligible for bringing your own license to cloud environment
NumberOfOSEPerLicense	Type: integer. Nullable Number of OSE per license
NumberOfProcessorsPerOSE	Type: integer. Nullable Number of processors per OSE
TotalNumberOfCoresPerV MPerLicense	Type: integer. Nullable Total number of cores per VM per license
NumberOfCoresPerSocket	Type: integer. Nullable Number of cores per socket

Database Column	Details
ThirdPartyAccessAllowed	<p><i>Type:</i> boolean</p> <p>Access to applications is allowed to third party users. This field is defaulted to True</p>
AllowExternalRoamingUse	<p><i>Type:</i> boolean. Nullable</p> <p>Set this field to True if license allows external roaming use. This field is defaulted to False. This is applicable for both device and user licenses and is related to virtual application access. If 1, this license will consume 1 entitlement per each user. If 0, this license will consume 1 license per each user device. And, if NULL, ignore virtual application access. This can be used in conjunction with VirtualApplicationAccessMaximumUsagePeriod.</p>
MeasurementDate	<p><i>Type:</i> datetime. Nullable</p> <p>The date of the license measurment.</p>
ConsumptionUnit	<p><i>Type:</i> text. Nullable</p> <p>Unit description to describe the consumption amount.</p>
TargetOperatingSystem TypeID	<p><i>Type:</i> integer</p> <p>Type of Operating Systems to target</p>
VirtualApplication AccessMaximumUsage PeriodDevice	<p><i>Type:</i> integer. Nullable</p> <p>This is a rule for virtual application access. This is used in conjunction with the AllowExternalRoamingUse. For Device licenses, a license will consume 1 entitlement per each user device when used in period specified here.</p>
VirtualApplication AccessMaximumUsage PeriodUser	<p><i>Type:</i> integer. Nullable</p> <p>This is a rule for virtual application access. This is used in conjunction with the AllowExternalRoamingUse. For user licenses, if 1, this license will consume only when used in period specified here.</p>
AlwaysInstalled	<p><i>Type:</i> boolean</p> <p>If this field is True, this license is considered in to be used whenever it is allocated. If False, software usage is considered separately, and allocation merely defines the corporation's modelling of who is expected to consume entitlements.</p>
MinimumNumberOf LicensesPerVM	<p><i>Type:</i> integer</p> <p>When licensing a Virtual Hardware System with a MSServerCore license (LicenseTypeID = 33), consume license entitlements as though the virtual machine had at least this number of virtual threads.</p>
AllowIBMPVUSubCapacity FromNonILMT	<p><i>Type:</i> boolean</p> <p>If the license does not use host processor information (not full capacity), set this field to True to allow non-ILMT sub-capacity PVU consumption calculations to be used.</p>

Database Column	Details
NumberOfAllowedProcessorsPerHost	<i>Type:</i> integer. Nullable This field specifies how many processors per host are allowed before an additional license entitlement (or point) is consumed. Null provides the default of 1. Zero provides unlimited.
MinimumNumberOfProcessors	<i>Type:</i> integer The minimum number of processors that this license is for. This field is only used where the SoftwareLicenseType is MSServerProcessor (LicenseTypeID = 22).

ContractUseRightIBM Table

ContractUseRightIBM contains IBM licensing rules most of which can be set by PURL.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 161: Database columns for ContractUseRightIBM table

Database Column	Details
ContractUseRightIBMid	Type: integer. Key. Generated ID A unique identifier
ContractID	Type: integer. Key A unique identifier for a contract.
PVULimitApplies	Type: boolean If 1 then PVU limits apply
PVULimit	Type: integer. Nullable PVU limit

ContractVendor Table

ContractVendor stores the links between vendors and contracts.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 162: Database columns for ContractVendor table

Database Column	Details
ContractVendorID	Type: integer. Key. Generated ID A unique identifier for the link.
ContractID	Type: integer. Key The contract that the vendor is linked to. Foreign key to the Contract table.
VendorID	Type: integer. Key. Nullable The vendor that the contract is linked to. Foreign key to the Vendor table.
ThirdParty	Type: boolean Set this field to True if this vendor is third-party.

CurrencyRate Table

CurrencyRate stores the exchange rates assigned to any currency.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 163: Database columns for CurrencyRate table

Database Column	Details
CurrencyRateID	Type: integer. Key. Generated ID Unique identifier for each record.
SnapshotID	Type: integer. Key Snapshot associated with this exchange rate. Foreign key to the CurrencyRateSnapshot table.
CurrencyID	Type: integer. Key Currency associated with this exchange rate. Foreign key to the Currency table.
Rate	Type: decimal Exchange rate assigned to the currency for the selected snapshot.
UpdatedUser	Type: text (max 256 characters). Nullable Operator who last modified the record.
UpdatedDate	Type: datetime. Nullable Date that the record was last modified.

CurrencyRateSnapshot Table

Each record in CurrencyRateSnapshot represents a single currency snapshot.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 164: Database columns for CurrencyRateSnapshot table

Database Column	Details
CurrencyRateSnapshotID	<i>Type:</i> integer. Key. Generated ID Unique identifier for this record.
SnapshotName	<i>Type:</i> text (max 256 characters) Name of the currency snapshot.
SnapshotResourceID	<i>Type:</i> text (max 64 characters). Nullable The resource string containing the name of the snapshot to display on the user interface.
SnapshotDate	<i>Type:</i> datetime. Nullable Start date of the currency snapshot.
SnapshotReference CurrencyID	<i>Type:</i> integer. Nullable Reference currency used for this snapshot. Foreign key to the Currency table.
IsStandardRateSnapshot	<i>Type:</i> boolean. Key Set to True if this is the default standard rate snapshot, which is created for each FNMP installation.
UpdatedUser	<i>Type:</i> text (max 256 characters). Nullable Operator who last modified this record.
UpdatedDate	<i>Type:</i> datetime. Nullable Date this record was last modified.

CustomPropertyDisplayXML Table

CustomPropertyDisplayXML stores XML snippets with layout information for custom properties. The XML snippets in this table will be inserted into the default XML layout for the appropriate property dialog. Storing snippets in this table, rather than manually updating the default XML layout, ensures that custom properties will continue to be applied even after upgrading the product (since during a product upgrade, we typically overwrite all property display XML layout with the new defaults for that version of the product).

Table 165: Database columns for CustomPropertyDisplayXML table

Database Column	Details
CustomPropertyDisplayXMLID	<i>Type:</i> integer. Key. Generated ID A unique identifier for this XML snippet.
XMLSnippet	<i>Type:</i> text An XML snippet that describes how to show this property in the properties dialog.
InsertXPath	<i>Type:</i> text XPath which selects an XML node where the snippet will be inserted.
XMLInsertTypeID	<i>Type:</i> integer How to insert this property at the selected XPath node. Foreign key to the XMLInsertType table.
InsertOrder	<i>Type:</i> integer The order in which to insert the XML snippet for this property into the XML layout file. If this value is higher than another, it will be inserted after it. Useful when the XML snippet for this property is to be inserted inside another - for instance, if a property creates a tab or group.

DisplayXML Table

The static `DisplayXML` table stores the default XML code representing the property dialog layout for non-type-specific objects such as purchase orders, vendors and evidence. The XML files for type-specific entities (such as assets) are stored in the static type tables (such as `AssetType`) for those objects.

Table 166: Database columns for `DisplayXML` table

Database Column	Details
XMLType	<p><i>Type:</i> text (max 30 characters). Key</p> <p>A unique identifier for the type of object associated with the XML. Possible values are:</p> <ul style="list-style-type: none"> Contract (not in use any longer - the contract XML files are now stored in <code>ContractType</code>) Vendor VendorContact PurchaseOrder PurchaseOrderDetail SoftwareTitle FileEvidence InstallerEvidence User TermAndCondition Operator LicensePointsRuleSet.
XMLFile	<p><i>Type:</i> text. Nullable</p> <p>The layout of the property dialog for this type of entity, stored in XML format.</p>

Document Table

The Document table stores details of documents or files relating to assets, contracts, purchase orders, licenses and terms and conditions.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 167: Database columns for Document table

Database Column	Details
DocumentID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the document.
DocumentTypeID	<i>Type:</i> integer The way that the document is stored and referenced. Foreign key to the DocumentType table.
DocumentName	<i>Type:</i> text (max 500 characters) The name of the document.
DocumentFile	<i>Type:</i> image. Nullable The binary data for the document (if it is stored in the FlexNet Manager Suite database).
OpenWith	<i>Type:</i> text (max 500 characters). Nullable The program to attempt to open the document with.
DocumentDescription	<i>Type:</i> text (max 3000 characters) A description of the document.
PhysicalLocation	<i>Type:</i> text (max 500 characters). Nullable Physical location of a (possibly hard) copy of this document. NOTE: for compatibility with the FlexNet Manager Suite console, when the document type is 3 (Reference), the DocumentName column should be used instead, and this field set to null.
DocumentSize	<i>Type:</i> integer. Nullable Document size in bytes.
ContentType	<i>Type:</i> text (max 256 characters). Nullable The MIME-type of the document file.

Database Column	Details
AssetID	<i>Type:</i> integer. Key. Nullable The asset to which this document may be linked. Foreign key to the Asset table.
PurchaseOrderID	<i>Type:</i> integer. Key. Nullable The purchase order to which the document may be linked. Foreign key to the PurchaseOrder table.
PurchaseOrderDetailID	<i>Type:</i> integer. Key. Nullable The purchase order detail (or PO line) to which the document may be linked. Foreign key to the PurchaseOrderDetail table.
ContractID	<i>Type:</i> integer. Key. Nullable The contract to which the document may be linked. Foreign key to the Contract table.
SoftwareLicenseID	<i>Type:</i> integer. Nullable The license to which the document may be linked. Foreign key to the SoftwareLicense table.
ComplianceUserID	<i>Type:</i> integer. Key. Nullable The end-user to which the document may be linked. Foreign key to the ComplianceUser table.
AttachDate	<i>Type:</i> datetime The date and time this document was linked.
UserName	<i>Type:</i> text (max 256 characters) Operator who created the link between this document and the other object.
DocumentNoteID	<i>Type:</i> integer. Key. Nullable The note to which this document may be linked. Foreign key to the DocumentNote table.
ContractNoteID	<i>Type:</i> integer. Key. Nullable The contract note to which this document may be linked. Foreign key to the ContractNote table.
TermAndConditionID	<i>Type:</i> integer. Key. Nullable The term/condition to which this document may be linked. Foreign key to the TermAndCondition table.
SecurityTypeID	<i>Type:</i> integer. Key. Nullable Security type for this document (role-based or individual access). Foreign key to the SecurityType table.

Database Column	Details
FileType	<i>Type:</i> text (max 20 characters). Nullable The type of the file that has been uploaded, if any. This is used to provide full-text indexing.

DocumentHistory Table

The DocumentHistory table stores history of documents or files relating to assets, contracts, purchase orders, licenses, and terms and conditions.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 168: Database columns for DocumentHistory table

Database Column	Details
DocumentHistoryID	Type: integer. Key. Generated ID A unique identifier for the document history.
DocumentID	Type: integer. Key The corresponding document. Foreign key to the Document table.
DocumentTypeID	Type: integer The way that the document is stored and referenced. Foreign key to the DocumentType table.
DocumentName	Type: text (max 500 characters) The name of the document.
DocumentFile	Type: image. Nullable The binary data for the document (if it is stored in the FlexNet Manager Suite database).
OpenWith	Type: text (max 500 characters). Nullable The program to attempt to open the document with.
DocumentDescription	Type: text (max 3000 characters) A description of the document.
PhysicalLocation	Type: text (max 500 characters). Nullable Physical location of a (possibly hard) copy of this document. NOTE: for compatibility with the FlexNet Manager Suite console, when the document type is 3 (Reference), the DocumentName column should be used instead, and this field set to null.
DocumentSize	Type: integer. Nullable Document size in bytes.
ContentType	Type: text (max 256 characters). Nullable The MIME-type of the document file.

Database Column	Details
UserName	<i>Type:</i> text (max 256 characters) Operator who created the link between this document and the other object.
AttachDate	<i>Type:</i> datetime The date and time this document was linked to the other object.
FileType	<i>Type:</i> text (max 20 characters). Nullable The type of the file that has been uploaded, if any. This is used to provide full-text indexing.

DocumentNote Table

DocumentNote stores a list of notes attached to a document. The document itself is attached to a contract.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 169: Database columns for DocumentNote table

Database Column	Details
DocumentNoteID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the document note.
DocumentID	<i>Type:</i> integer The document that the note is for. Foreign key to the Document table.
ShortDescription	<i>Type:</i> text (max 100 characters) In the user interface, this maps to the document reference to which the note relates.
LongDescription	<i>Type:</i> text. Nullable The content of the note.
CreationUser	<i>Type:</i> text (max 128 characters) The operator who created the note.
CreationDate	<i>Type:</i> datetime The date of creation of the note.
UpdatedUser	<i>Type:</i> text (max 128 characters) The operator who last updated the note.
UpdatedDate	<i>Type:</i> datetime The date of the last update to the note.

DocumentType Table

DocumentType is a static value listing the alternative ways that a document can be saved in the database.

Table 170: Database columns for DocumentType table

Database Column	Details
DocumentTypeID	<i>Type:</i> integer. Key. Generated ID A unique identifier for each DocumentType. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• 1 = Document upload• 2 = File location• 3 = Physical location• 4 = URL.
ResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing a document type. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the type resource string has no translation.

Event Table

The Event table stores errors and events processed by the beacon, devices, rules etc.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 171: Database columns for Event table

Database Column	Details
EventID	Type: integer. Key. Generated ID Synthetic key for this table.
ActivityID	Type: integer. Key Foreign key to the Activity table.
EventUID	Type: unique identifier. Key UID to uniquely identify the event.
EventTypeID	Type: integer. Key Foreign key to the EventType table.
CreationDate	Type: datetime Date and time (UTC) when the Event was created.
SessionUID	Type: unique identifier. Key. Nullable UID to uniquely identify the the session.

EventLogCategory Table

The EventLogCategory table holds the different categories of events created by the system.

Table 172: Database columns for EventLogCategory table

Database Column	Details
EventLogCategoryID	<i>Type:</i> integer. Key. Generated ID A unique identifier for each EventLogCategory. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• 1 = Email Notification.
ResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing a event category. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 100 characters) A description of the event category.

EventLogDetail Table

The EventLogDetail table holds details of the events created by the system.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 173: Database columns for EventLogDetail table

Database Column	Details
EventLogDetailID	Type: integer. Key. Generated ID A unique identifier for an event detail.
EventLogSummaryID	Type: integer. Key The unique identifier for an event. Foreign key to the EventLogSummary table.
EventLogLevelID	Type: integer. Key The level of event. Foreign key to the EventLogLevel table.
MessageTime	Type: datetime. Key The time that the event was raised.
Message	Type: text (max 256 characters) The brief event message.
Details	Type: text. Nullable The full event message.
ParentEventLogDetailID	Type: integer. Key. Nullable The parent event log detail. Foreign key to another event log detail in this same EventLogDetail table.

EventLogLevel Table

The EventLogLevel table holds the different levels of events created by the system.

Table 174: Database columns for EventLogLevel table

Database Column	Details
EventLogLevelID	<i>Type:</i> integer. Key. Generated ID A unique identifier for each EventLogLevel. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• 1 = Information• 2 = Warning• 3 = Error.• 4 = Performance.
ResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing an event level. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 100 characters) A description of the event level.

EventLogStatus Table

The EventLogStatus table holds the different statuses of events created by the system.

Table 175: Database columns for EventLogStatus table

Database Column	Details
EventLogStatusID	<i>Type:</i> integer. Key. Generated ID A unique identifier for each EventLogStatus. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• 1 = In Progress• 2 = Success• 3 = Failed.
ResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing an event status. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 100 characters) A description of the event status.

EventLogSummary Table

The EventLogSummary table holds the top level summary of events created by the system.

Table 176: Database columns for EventLogSummary table

Database Column	Details
EventLogSummaryID	<i>Type:</i> integer. Key. Generated ID A unique identifier for an event.
StartTime	<i>Type:</i> datetime. Key The time that the event started.
EndTime	<i>Type:</i> datetime. Key. Nullable The time that the event finished.
EventLogCategoryID	<i>Type:</i> integer. Key The category of event. Foreign key to the EventLogCategory table.
EventName	<i>Type:</i> text (max 128 characters) Brief description of the event.
EventLogStatusID	<i>Type:</i> integer. Key The status of the event. Foreign key to the EventLogStatus table.

EventParameter Table

The EventParameter table stores the links between Activities and EventParameterTypes.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 177: Database columns for EventParameter table

Database Column	Details
EventParameterID	Type: integer. Key. Generated ID Primary key for the EventParameter table
EventID	Type: integer. Key A link to the Event table
EventParameterTypeID	Type: integer A link the the EventParameterType table. this value specifies which kind of object the EventParameter is linked to.
Value	Type: text stores the value of this parameter.

EventParameterType Table

The EventParameterType table stores details about the different types of Event Parameters.

Table 178: Database columns for EventParameterType table

Database Column	Details
EventParameterTypeID	<i>Type:</i> integer. Key. Generated ID Synthetic key for this table.
EventParameterTypeName	<i>Type:</i> text (max 256 characters). Key A short piece of text representing the Event Parameter. Internal use only- not to be displayed to the operator.
IsResourceString	<i>Type:</i> boolean A short piece of text representing the Event Parameter. Internal use only- not to be displayed to the operator.

EventSeverity Table

EventSeverity is a static table listing all of the severity levels that an event type can have.

Table 179: Database columns for EventSeverity table

Database Column	Details
EventSeverityID	Type: integer. Key. Generated ID
ResourceName	Type: text (max 256 characters). Key The unique name of the localizable resource string representing the EventSeverity record. Foreign key to the ComplianceResourceString table.
DefaultValue	Type: text (max 256 characters) The text to display if the state resource string has no translation.

EventTarget Table

The EventTarget table stores the links between Activities and other tables in the database.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 180: Database columns for EventTarget table

Database Column	Details
EventID	Type: integer. Key Link to the Event table
TargetTypeID	Type: integer. Key A link to the TargetType table. this value specifies which kind of object the Event is linked to.
TargetUID	Type: unique identifier. Key. Nullable used to attach the Event to its target. The target table depends on the TargetTypeID of the linked EventType.
TargetID	Type: integer. Nullable ID of the target. Referenced if the UID is not available.
TargetName	Type: text (max 128 characters). Nullable TargetName used to record the name of the target. Can be used when the UID or ID is not available.

EventType Table

The EventType table stores details about the different types of Events.

Table 181: Database columns for EventType table

Database Column	Details
EventTypeID	<i>Type:</i> integer. Key. Generated ID Synthetic key for this table.
EventTypeName	<i>Type:</i> text (max 256 characters). Key Short text representing the Event Type. Internal use only- not to be displayed to the operator.
EventSeverityID	<i>Type:</i> integer The severity of the Event. 1 = information, 2 = warning, 3 = error, 4 = critical.
EventMessageResource	<i>Type:</i> text (max 256 characters) A resource name used to look up a description for this Event
EventTypeStatusID	<i>Type:</i> integer. Key Foreign key to the EventTypeStatus table
ActivityTypeID	<i>Type:</i> integer. Key Foreign key to the ActivityType table

EventTypeStatus Table

The EventTypeStatus table stores progress stages for different processes.

Table 182: Database columns for EventTypeStatus table

Database Column	Details
EventTypeStatusID	Type: integer. Key. Generated ID Auto-generated status ID
EventTypeStatus ResourceName	Type: text (max 255 characters). Key Status name resource name
EventTypeStatusDefault Value	Type: text (max 255 characters). Nullable Default value for status

ILMTPVUCounts Table

This table allows the summarised PVU sub capacity numbers to be imported from ImportedILMTPVUCounts.”.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 183: Database columns for ILMTPVUCounts table

Database Column	Details
ILMTPVUCountsTableID	Type: integer. Key. Generated ID The ID of the ILMTPVUCounts Table
ComplianceComputerID	Type: integer. Key ID from the ComplianceComputer table.
TitleName	Type: text (max 512 characters). Key The name of the title these points apply to.
Publisher	Type: text (max 254 characters). Key The name of the publisher of the title these points apply to.
SubCapacityCores	Type: integer The number of sub-capacity licensable cores for the license on the computer.
FullCapacityCores	Type: integer The number of full-capacity licensable cores for the license on the computer.
SubCapacityPVU	Type: integer The number of sub-capacity PVU counts consumed for the license on the computer.
FullCapacityPVU	Type: integer The number of full-capacity PVU counts consumed for the license on the computer.
PeakSubCapacityPVU	Type: integer The peak number of sub-capacity PVU counts consumed for the license on the computer.
PeakFullCapacityPVU	Type: integer The peak number of full-capacity PVU counts consumed for the license on the computer.

ImportResolverErrorResult Table

The ImportResolverErrorResult table stores all resolver error message


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 184: Database columns for ImportResolverErrorResult table

Database Column	Details
ImportResolverErrorResultID	Type: integer. Key. Generated ID Auto-generated ID for ImportResolverErrorResult table
FileName	Type: text (max 255 characters) Name of the file
DateCreated	Type: datetime Date time where file was resolved.
ErrorMessage	Type: text. Nullable error message
ImportResolverTypeID	Type: integer. Key Foreign key to the ImportResolverType table

ImportResolverType Table

The ImportResolverType table stores all the resolver types.

Table 185: Database columns for ImportResolverType table

Database Column	Details
ImportResolverTypeID	<i>Type:</i> integer. Key. Generated ID Auto-generated ID for ImportResolverType table
ImportResolverTypeName	<i>Type:</i> text (max 255 characters). Key Name of the resolver
ImportResolverType Resource	<i>Type:</i> text (max 256 characters) A resource name used to look up a description for this resolver type

InstalledSoftwareAttribute Table

InstalledSoftwareAttribute stores the attribute values for each installation of an application. Reserved for future expansion.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 186: Database columns for InstalledSoftwareAttribute table

Database Column	Details
InstalledSoftwareID	<i>Type:</i> integer. Key The installation whose attribute value is being stored. Foreign key to the InstalledSoftware table.
AttributeID	<i>Type:</i> integer. Key The attribute whose value is being stored. Foreign key to the Attribute table.
Value	<i>Type:</i> text (max 400 characters) The value of this attribute of the installed application.

Instance Table

Instance stores information about database instances.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 187: Database columns for Instance table

Database Column	Details
InstanceID	<i>Type:</i> integer. Key. Generated ID A unique identifier for an instance.
ParentInstanceID	<i>Type:</i> integer. Key. Nullable The parent of the instance. Foreign key to another instance in the Instance table.
InstalledSoftwareID	<i>Type:</i> integer. Key. Nullable The installation associated with the instance. Foreign key to the InstalledSoftware table.
InstanceTypeID	<i>Type:</i> integer The type of this database instance. Foreign key to the InstanceType table
ComplianceComputerID	<i>Type:</i> integer. Key The host server running this database instance. Foreign key to the ComplianceComputer table.
SoftwareTitleID	<i>Type:</i> integer. Key The instance's application. Foreign key to the SoftwareTitle table
InstanceName	<i>Type:</i> text (max 256 characters). Key. Nullable The name of the database instance.
SerialNo	<i>Type:</i> text (max 256 characters). Nullable The serial number of the database instance.
InstallationPath	<i>Type:</i> text (max 512 characters). Nullable The installation path of the database instance.
BusinessApplicationName	<i>Type:</i> text (max 512 characters). Nullable The business application that uses the database instance.

Database Column	Details
IsLicensable	<p><i>Type:</i> boolean</p> <p>Set this to <code>False</code> if this instance does not require a license. The default is <code>True</code>, which means a license is required.</p>
IsLicensableForLicenseRec	<p><i>Type:</i> boolean</p> <p>Set this to <code>True</code> if this instance should be included in license reconciliation. <code>False</code> means that this instance will not be accounted for in license reconciliation.</p>
NeverDelete	<p><i>Type:</i> boolean</p> <p>When a computer does not return any inventory for a specified period of time, it may be deleted. Set this field to <code>True</code> to ensure that the instance record does not get deleted when there is no inventory.</p>
SoftwareLicenseID	<p><i>Type:</i> integer. Key. Nullable</p> <p>The software license covering this instance. Foreign key to the <code>SoftwareLicense</code> table.</p>
UsedInInventory	<p><i>Type:</i> boolean</p> <p>If the inventory importer detects that this database instance is used, it will set this field to <code>True</code>.</p>
UsedOverride	<p><i>Type:</i> boolean. Nullable</p> <p>An operator may manually specify whether this database instance is to be considered used (set this field to <code>True</code>), or not (set this field to <code>False</code>). This overrides the importer result (<code>UsedInInventory</code>) described above.</p>
InventorySourceTypeID	<p><i>Type:</i> integer</p> <p>Whether this instance has ever been reported in inventory, or has been manually created and maintained. Foreign key to the <code>ComplianceComputerInventorySourceType</code> table.</p>
AuditEvidenceDate	<p><i>Type:</i> datetime. Nullable</p> <p>Date and time the Oracle LMS audit evidence was collected by Flexera Inventory Manager</p>
CreationUser	<p><i>Type:</i> text (max 256 characters)</p> <p>The operator who created the database instance record.</p>
CreationDate	<p><i>Type:</i> datetime</p> <p>The date and time when this instance record was created.</p>
UpdatedUser	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>The operator who most recently updated the database instance record.</p>

Database Column	Details
UpdatedDate	<i>Type:</i> datetime The date and time when this instance record was last updated.

InstanceAttribute Table

InstanceAttribute stores the attribute values for each installed database instance.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 188: Database columns for InstanceAttribute table

Database Column	Details
InstanceID	<i>Type:</i> integer. Key The database instance whose attribute value is being stored. Foreign key to the Instance table.
AttributeID	<i>Type:</i> integer. Key The attribute whose value is being stored. Foreign key to the Attribute table.
Value	<i>Type:</i> text (max 400 characters) The value of this attribute of the database instance.

InstanceEnvironment Table

InstanceEnvironment is a static table listing the possible environments in which database instances may be deployed. For some vendors, the environment affects the costs of licensing the database instance.

Table 189: Database columns for InstanceEnvironment table

Database Column	Details
InstanceEnvironmentID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for an InstanceEnvironment. Possible values and the corresponding default names are:</p> <ul style="list-style-type: none">• 1 = Development• 2 = Test• 3 = Staging• 4 = Production• 5 = Other.
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing an instance environment. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the environment resource string has no translation.</p>

InstancePropertyValue Table

For each instance, InstancePropertyValue stores the values for the custom properties defined in InstanceTypeProperty.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 190: Database columns for InstancePropertyValue table

Database Column	Details
InstancePropertyValueID	<i>Type:</i> integer. Key. Generated ID A unique identifier for a property value.
InstanceID	<i>Type:</i> integer. Key The instance associated with this property. Foreign key to the Instance table.
InstanceTypePropertyID	<i>Type:</i> integer. Key The property whose value is being stored. The type of the instance should match the type that the property is associated with. Foreign key to the InstanceTypeProperty table.
PropertyValue	<i>Type:</i> text (max 4000 characters) The value of the property.
CreationUser	<i>Type:</i> text (max 128 characters). Nullable The operator who created the record.
CreationDate	<i>Type:</i> datetime The date and time when the record was created.
UpdatedUser	<i>Type:</i> text (max 128 characters). Nullable The operator who last updated the record.
UpdatedDate	<i>Type:</i> datetime. Nullable The date and time when the record was last updated.

InstanceRole Table

InstanceRole is a static table listing the possible roles of database instances. For some vendors, the role of the database instance affects the costs of licensing.

Table 191: Database columns for InstanceRole table

Database Column	Details
InstanceRoleID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for an InstanceRole. Possible values and the corresponding default names are:</p> <ul style="list-style-type: none">• 1 = None• 2 = Backup• 3 = Failover• 4 = Mirroring• 5 = Standby• 6 = Other• 7 = Primary.
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing an instance role. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the role resource string has no translation.</p>

InstanceType Table

InstanceType is a static table listing the possible types of database instance.

Table 192: Database columns for InstanceType table

Database Column	Details
InstanceTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for an InstanceType. Possible values and the corresponding default names are:</p> <ul style="list-style-type: none"> • 1 = General (for non-Oracle applications) • 2 = Oracle • 3 = Application (for instances created for non-Oracle applications manually flagged as Oracle). • 4 = Oracle EBS Server • 5 = Oracle EBS Module
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing an instance type. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the instance type resource string has no translation.</p>
XMLFile	<p><i>Type:</i> text. Nullable</p> <p>The layout of the property dialog for this type of instance, stored in XML format.</p>

InstanceTypeProperty Table

InstanceTypeProperty defines extra custom properties for instances of the specified type.

Table 193: Database columns for InstanceTypeProperty table

Database Column	Details
InstanceTypePropertyID	Type: integer. Key. Generated ID A unique identifier for each property.
PropertyName	Type: text (max 256 characters). Key The name of the property.
InstanceTypeID	Type: integer. Key Foreign key to the InstanceType table.
CustomPropertyDisplayXMLID	Type: integer. Nullable Foreign key to a record in the CustomPropertyDisplayXML table, describing how to show the property on a property dialog.

InstanceUser Table

InstanceUser links end-users in LicenseUser with a particular instance of a database for license counting purposes.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 194: Database columns for InstanceUser table

Database Column	Details
InstanceID	<i>Type:</i> integer. Key The instance used by the end-user. Foreign key to a database instance in the Instance table.
LicenseUserID	<i>Type:</i> integer. Key The end-user using the instance. Foreign key to the account name in the LicenseUser table.
Quantity	<i>Type:</i> integer The number of actual end-users of the database instance logging in to the Oracle database through this account. For example, if there is one "Shop Floor" account for all fork lift drivers, this field stores the number of individual drivers that must be accounted for.
AccountStatus	<i>Type:</i> text (max 256 characters). Nullable The current status of the end-user account.
CreationDate	<i>Type:</i> datetime. Nullable Date and time when the end-user was created.
LastLogonDate	<i>Type:</i> datetime. Nullable Date and time when the end-user last logged on.
DefaultTablespace	<i>Type:</i> text (max 256 characters). Nullable The default tablespace for an Oracle user.
TempTablespace	<i>Type:</i> text (max 256 characters). Nullable The temporary tablespace for an Oracle user.
IsManualUser	<i>Type:</i> boolean Whether or not the user was created manually (or through Oracle).

IntervalType Table

IntervalType stores the types of interval used by schedules and by terms and conditions.

Table 195: Database columns for IntervalType table

Database Column	Details
IntervalTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each IntervalType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = Day• 2 = Week• 3 = Month.
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing an interval type. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the type resource string has no translation.</p>

LicenseUser Table

The `LicenseUser` table lists account names (for end-users and other resources) that have been extracted from other products (such as Oracle databases). These external accounts cannot be reconciled with the end-users listed in the `ComplianceUser` table. Nevertheless, these accounts can be very important for licensing costs.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 196: Database columns for `LicenseUser` table

Database Column	Details
<code>LicenseUserID</code>	<i>Type:</i> integer. Key. Generated ID A unique identifier for an external end-user.
<code>LicenseUserLogin</code>	<i>Type:</i> text (max 400 characters). Key The user login extracted from the original listing (for example, from an Oracle database).
<code>Description</code>	<i>Type:</i> text (max 400 characters) The description is usually a group name.
<code>EmployeeNumber</code>	<i>Type:</i> text (max 256 characters). Nullable The employee number of the external end-user.
<code>FirstName</code>	<i>Type:</i> text (max 256 characters). Nullable The first name of the end-user extracted from the original listing.
<code>LastName</code>	<i>Type:</i> text (max 256 characters). Nullable The last name of the end-user extracted from the original listing.
<code>Email</code>	<i>Type:</i> text (max 400 characters). Nullable The email of the end-user extracted from the original listing.
<code>SAPClientCode</code>	<i>Type:</i> text (max 2 characters). Nullable The end-user's SAP client code, where applicable.
<code>SAPInstallationNumber</code>	<i>Type:</i> text (max 10 characters). Nullable The end-user's SAP installation number, where applicable.
<code>CostCenter</code>	<i>Type:</i> text (max 128 characters). Nullable The SAP cost center that the end-user belongs to
<code>LicenseUserTypeID</code>	<i>Type:</i> integer The type of external end-user. Foreign key to the <code>LicenseUserType</code> table.

LicenseUserConnection Table

ComplianceUserConnection stores a link between external end-users in LicenseUser which have been reported in inventory, and external IDs which can be used to identify them in their inventory sources. End-users reported in multiple inventory sources will appear multiple times in this table.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 197: Database columns for LicenseUserConnection table

Database Column	Details
LicenseUserID	Type: integer. Key A unique identifier for the external end-user. Foreign key to the LicenseUser table.
ComplianceConnectionID	Type: integer. Key. Nullable The inventory source where the end-user was reported. Foreign key to the ComplianceConnection table.
ExternalID	Type: big integer. Key A (hopefully unique) identifier for the end-user in the external inventory source.

LicenseUserExcluded Table

Similarly to the `LicenseUser` table, `LicenseUserExcluded` lists account names extracted from other products (such as Oracle databases); but these accounts are to be excluded from license counts. The accounts are listed in full here since it is possible that they do not already appear in the `LicenseUser` table. Any that do appear in both tables, matched on the login names, are excluded from license counts.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 198: Database columns for `LicenseUserExcluded` table

Database Column	Details
<code>LicenseUserExcludedID</code>	<p>Type: integer. Key. Generated ID</p> <p>A unique identifier for an excluded end-user.</p>
<code>LicenseUserLogin</code>	<p>Type: text (max 400 characters). Key</p> <p>The user login extracted from the original listing (for example, from an Oracle database). For the account to be excluded from license counts, this must exactly match a <code>LicenseUserLogin</code> from the <code>LicenseUser</code> table.</p>
<code>DefaultQuantity</code>	<p>Type: integer</p> <p>The number of actual users of the database instance logging in through this account. For example, a "SYSTEM" account may allow for a number of administrators to log in. In this table, the default quantity is zero. If this field is non-zero and the end-user matches a <code>LicenseUser</code> record, then in some cases, we may exclude this number of end-users from license counting, but include any further accounts covered by the <code>LicenseUser</code> record.</p>

LicenseUserType Table

LicenseUserType is a static table listing possible types of external end-users (in the LicenseUser table).

Table 199: Database columns for LicenseUserType table

Database Column	Details
LicenseUserTypeID	<i>Type:</i> integer. Key. Generated ID A unique identifier for each LicenseUserType. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• 1 = Default• 2 = Developer.
ResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing an external end-user type. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the type resource string has no translation.

LogFile Table

The LogFile table stores all the log file


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 200: Database columns for LogFile table

Database Column	Details
LogFileID	Type: integer. Key. Generated ID Primary key of the table LogFile
SessionUID	Type: unique identifier. Key Identified of the file
TaskStepID	Type: integer. Key. Nullable Foreign key to the TaskStep table
FileContent	Type: image holds the log file content
FileExtension	Type: text (max 10 characters) Extension of the file

MSEAARLSoftwareTitleEdition Table

MSEAARLSoftwareTitleEdition contains a list of available product editions for a Microsoft Enterprise Agreement.

Table 201: Database columns for MSEAARLSoftwareTitleEdition table

Database Column	Details
SoftwareRecognitionID	Type: text (max 32 characters). Key The factory unique ID (an MD5 digest) for the product edition in the Application Recognition Library.
IsPlatform	Type: boolean Whether this edition should be covered by the platform license.

MSSelectLevel Table

MSSelectLevel is a static table listing all Microsoft Select price levels.

Table 202: Database columns for MSSelectLevel table

Database Column	Details
MSSelectLevelID	<i>Type:</i> integer. Key. Generated ID A unique identifier for each MSSelectLevel. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• 1 = A• 2 = B• 3 = C• 4 = D
ResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing a price level. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 16 characters) The text to display if the price level resource string has no translation.
NumberOfPoints	<i>Type:</i> integer The umber of points that must be purchased to achieve the price level.

MSSelectPool Table

MSSelectPool is a static table listing all Microsoft Select pools.

Table 203: Database columns for MSSelectPool table

Database Column	Details
MSSelectPoolID	<i>Type:</i> integer. Key. Generated ID A unique identifier for each MSSelectPool. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• 1 = Applications• 2 = Systems• 3 = Servers
ResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing a pool. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 64 characters) The text to display if the pool resource string has no translation.

MobileDevice Table

MobileDevice extends the ComplianceComputer table to store mobile device related property values.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 204: Database columns for MobileDevice table

Database Column	Details
MobileDeviceID	<i>Type:</i> integer. Key. Generated ID A unique identifier for a MobileDevice Column use to specify clustered index.
ComplianceComputerID	<i>Type:</i> integer. Key A unique identifier for a MobileDevice. Foreign key to the ComplianceComputer table.
IMEI	<i>Type:</i> text (max 256 characters). Nullable IMEI value of the mobile device.
PhoneNo	<i>Type:</i> text (max 128 characters). Nullable Phone number of the mobile device.
EmailAddress	<i>Type:</i> text (max 256 characters). Nullable The stmp email account associated to a mobile device when the device is connected to ActiveSync.

NotificationItem Table

NotificationItem lists notifications that were sent to end-users.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 205: Database columns for NotificationItem table

Database Column	Details
NotificationItemID	Type: integer. Key. Generated ID A unique identifier for this notification.
NotificationTypeID	Type: integer. Key The type of notification to be sent. Foreign key to the NotificationType table.
NotificationDate	Type: datetime. Key The date the notification should be sent.
TaskID	Type: integer. Key. Nullable The task the notification is for, if any. Foreign key to the TermAndConditionTask table.
ContractID	Type: integer. Key. Nullable The contract the notification is for, if any. Foreign key to the Contract table.
ComplianceUserID	Type: integer. Key The end-user that is receiving the notification. Foreign key to the ComplianceUser table.
SentDate	Type: datetime. Key. Nullable The date the notification was actually sent.

NotificationTemplate Table

NotificationTemplate stores a list of email templates used to generate notification emails.

Table 206: Database columns for NotificationTemplate table

Database Column	Details
NotificationTemplateID	<i>Type:</i> integer. Key. Generated ID A unique identifier for each NotificationTemplate. The default templates provided are: <ul style="list-style-type: none">• -1 = Contract expiry notification template• -2 = Contract renewal notification template• -3 = Task due notification template• -4 = Task reminder notification template• -5 = Task escalation notification template.
FileName	<i>Type:</i> text (max 255 characters). Key The template's file name.
Content	<i>Type:</i> text. Nullable The template content.

NotificationType Table

NotificationType stores a list of notification types that can be sent to end-users.

Table 207: Database columns for NotificationType table

Database Column	Details
NotificationTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each NotificationType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = Contract Expiry (a notification sent to end-users responsible for a contract when it is due to expire)• 2 = Contract Renewal (a notification sent to end-users responsible for a contract when it is due for renewal)• 3 = Task Due (a notification sent to the end-user assigned to a task when it is due for completion)• 4 = Task Reminder (a notification sent to the end-user assigned to a task as a reminder that the task is nearing completion)• 5 = Task Escalation (a notification sent to the end-user assigned to receive escalations, typically when a task is not completed on time).
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a notification type. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the type resource string has no translation.</p>
NotificationTemplateID	<p><i>Type:</i> integer. Key. Nullable</p> <p>The template to use when sending notifications of this type. Foreign key to the NotificationTemplate table.</p>

OperatorManageState Table

The OperatorManageState table lists the possible states for managing who has responsibility for maintaining certain business data. This is for internal use.

Table 208: Database columns for OperatorManageState table

Database Column	Details
OperatorManageStateID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the operator management state of business data.
Name	<i>Type:</i> text (max 64 characters). Key A unique name for the state
DescriptionResourceName	<i>Type:</i> text (max 256 characters). Nullable The unique name of the localizable resource string representing the description of the state. Foreign key to the ComplianceResourceString table.
DescriptionDefaultValue	<i>Type:</i> text (max 256 characters) A string representing the default name of the state. Foreign key to the ComplianceResourceString table.
IsLocked	<i>Type:</i> boolean Is the data locked from edits by an operator.
IsModified	<i>Type:</i> boolean Is the data modified by an operator.
IsFactory	<i>Type:</i> boolean Is the data from the Reference ARL factory.
AutoUpdate	<i>Type:</i> boolean Is the data to be updated automatically.
Priority	<i>Type:</i> integer Is the data locked from edits by an operator.

OperatorTaskTypeSetting Table

The OperatorTaskTypeSetting table stores data related to background task type.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 209: Database columns for OperatorTaskTypeSetting table

Database Column	Details
OperatorTaskTypeSettingID	Type: integer. Key. Generated ID Auto-generated operator task type setting ID
ComplianceOperatorID	Type: integer. Key Foreign key to the ComplianceOperator table
ActivityTypeID	Type: integer. Key Foreign key to the ActivityType table
Enabled	Type: boolean Enabled flag for a setting

OracleInstance Table

OracleInstance stores key characteristics specific to instances of Oracle databases which may impact the cost of licensing.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 210: Database columns for OracleInstance table

Database Column	Details
InstanceID	<i>Type:</i> integer. Key The database instance whose attributes are being stored. Foreign key to the Instance table.
InstanceEnvironmentID	<i>Type:</i> integer The environment of the database instance. Foreign key to the InstanceEnvironment table.
InstanceRoleID	<i>Type:</i> integer The role of the database instance. Foreign key to the InstanceRole table.

PaymentSchedule Table

PaymentSchedule contains details of the payment schedules managed by FlexNet Manager Suite.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 211: Database columns for PaymentSchedule table

Database Column	Details
PaymentScheduleID	<i>Type:</i> integer. Key. Generated ID A unique identifier for a payment schedule.
ContractID	<i>Type:</i> integer. Key Identifies a contract to which this payment schedule applies. Foreign key to the Contract table.
PaymentScheduleTypeID	<i>Type:</i> integer Identifies the type of this payment schedule. Foreign key to the PaymentScheduleType table.
PaymentScheduleTermID	<i>Type:</i> integer Identifies the term of payment for this payment schedule. Foreign key to the PaymentScheduleTerm table.
PaymentScheduleCategoryID	<i>Type:</i> integer Identifies the category of this payment schedule. Foreign key to the PaymentScheduleCategory table.
Description	<i>Type:</i> text (max 100 characters) Name of this payment schedule.
StartDate	<i>Type:</i> datetime The date on which this payment schedule starts.
EndDate	<i>Type:</i> datetime. Nullable The date on which this payment schedule ends.
PeriodTypeID	<i>Type:</i> integer Identifies the period type of this payment schedule. Foreign key to the PeriodType table.

Database Column	Details
IncludeNewAssetsAndLicenses	<p><i>Type:</i> boolean</p> <p>If this field is set to <code>True</code>, then when a new asset or license is linked to the contract associated with this payment schedule, the item will also be linked to this payment schedule. If <code>False</code>, new items linked to the related contract are not automatically linked to the payment schedule (although a manual link can still be made).</p>
LeaseTerminationDate	<p><i>Type:</i> datetime. Nullable</p> <p>The termination date of this payment schedule's lease. Only applicable if the payment schedule type is <code>Lease</code>.</p>
LeaseTerminationReason	<p><i>Type:</i> text (max 100 characters). Nullable</p> <p>The reason this payment schedule's lease was terminated. Only applicable if the payment schedule type is <code>Lease</code>.</p>
LeaseNumber	<p><i>Type:</i> text (max 150 characters). Nullable</p> <p>The number of this payment schedule's lease. Only applicable if the payment schedule type is <code>Lease</code>.</p>
BuyoutCost	<p><i>Type:</i> currency. Nullable</p> <p>The buyout cost for this payment schedule's lease. Only applicable if the payment schedule type is <code>Lease</code>.</p>
BuyoutCostRateID	<p><i>Type:</i> integer. Nullable</p> <p>Identifies the currency rate to be applied to this payment schedule's lease buyout cost. Only applicable if the payment schedule type is <code>Lease</code>. Foreign key to the <code>CurrencyRate</code> table.</p>
PreviousPurchases	<p><i>Type:</i> integer. Nullable</p> <p>In the case of a Microsoft Enterprise Agreement renewal, the number of desktops covered by the associated platform license at the end of the previous Microsoft EA.</p>
Comment	<p><i>Type:</i> text. Nullable</p> <p>Operator's comments about this payment schedule.</p>
CreationUser	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>The operator who created the record.</p>
CreationDate	<p><i>Type:</i> datetime</p> <p>The date the payment schedule was created.</p>
UpdatedUser	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>The operator to make the last change to this record.</p>

Database Column	Details
UpdatedDate	<i>Type:</i> datetime The date the last change was made to this payment schedule record.

PaymentScheduleCategory Table

PaymentScheduleCategory is a static table listing categories that can be assigned to a payment schedule.

Table 212: Database columns for PaymentScheduleCategory table

Database Column	Details
PaymentScheduleCategoryID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each PaymentScheduleCategory. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = Fixed • 2 = License true up • 3 = Per hardware item • 4 = Per license quantity.
ResourceString	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a payment schedule category. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the category resource string has no translation.</p>

PaymentScheduleDetail Table

PaymentScheduleDetail lists all individual periods of a payment schedule.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 213: Database columns for PaymentScheduleDetail table

Database Column	Details
PaymentScheduleDetailID	<i>Type:</i> integer. Key. Generated ID Uniquely identifies this payment schedule period.
PaymentScheduleID	<i>Type:</i> integer. Key Identifies the payment schedule to which this period applies. Foreign key to the PaymentSchedule table.
PeriodCovered	<i>Type:</i> text (max 50 characters) A string describing the period to which this payment schedule period is applicable. This is a calculated field.
PeriodStartDate	<i>Type:</i> datetime. Key The date on which this payment schedule period starts.
PeriodEndDate	<i>Type:</i> datetime The date on which this payment schedule period ends.
DueDate	<i>Type:</i> datetime. Key. Nullable The date on which this payment is due.
PaymentScheduleDetailPaymentStatusID	<i>Type:</i> integer. Key Identifies the state type of this payment schedule. The default value 2 corresponds to an Incomplete status. Foreign key to the PaymentScheduleDetailPaymentStatus table.
PaymentDate	<i>Type:</i> datetime. Nullable Records the date the payment was made.
ActualAmount	<i>Type:</i> currency. Nullable The actual amount paid in this payment schedule period.
ActualAmountRateID	<i>Type:</i> integer. Nullable Identifies the currency rate to be applied to the amount paid in this payment schedule period. Foreign key to the CurrencyRate table.

Database Column	Details
EstimatedAmount	<i>Type:</i> currency. Nullable The estimated amount for this payment schedule period.
EstimatedAmountRateID	<i>Type:</i> integer. Nullable Identifies the currency rate to be applied to the estimated amount for this payment schedule period. Foreign key to the CurrencyRate table.
BudgetedAmount	<i>Type:</i> currency. Nullable The budgeted amount for this payment schedule period.
BudgetedAmountRateID	<i>Type:</i> integer. Nullable Identifies the currency rate to be applied to the budgeted amount for this payment schedule period. Foreign key to the CurrencyRate table.
Obligated	<i>Type:</i> boolean If this field is set to True, the payee is obligated to pay during this payment schedule period. If this bit is False (the default), payment can presumably be deferred.
Quantity	<i>Type:</i> integer. Nullable The quantity for this payment schedule period.
UnitPrice	<i>Type:</i> currency. Nullable The unit price for this payment schedule period.
UnitPriceRateID	<i>Type:</i> integer. Nullable Identifies the currency rate to be applied to the unit price for this payment schedule period. Foreign key to the CurrencyRate table.
SoftwareAssuranceUnit Price	<i>Type:</i> currency. Nullable The unit price for support (Software Assurance) for this payment schedule period.
SoftwareAssuranceUnit PriceRateID	<i>Type:</i> integer. Nullable Identifies the currency rate to be applied to the unit price for support in this payment schedule period. Foreign key to the CurrencyRate table.
Notes	<i>Type:</i> text. Nullable The notes field.
PeriodCoveredResourceName	<i>Type:</i> text (max 256 characters). Nullable The resource name used to describe the period to which this payment schedule period is applicable.

Database Column	Details
PeriodCoveredResource Parameters	<i>Type:</i> text (max 256 characters). Nullable The parameters used by the resource name used to describe the period to which this payment schedule period is applicable.

PaymentScheduleDetailPaymentStatus Table

PaymentScheduleDetailPaymentStatus is a static table listing the possible status values for payment schedules.

Table 214: Database columns for PaymentScheduleDetailPaymentStatus table

Database Column	Details
PaymentScheduleDetailPaymentStatusID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each PaymentScheduleDetailPaymentStatus. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = Complete• 2 = Incomplete• 3 = Not going to pay.
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a payment schedule status. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 256 characters)</p> <p>The text to display if the status resource string has no translation.</p>

PaymentScheduleTerm Table

PaymentScheduleTerm is a static table listing possible payment schedule terms (the timing of payments in relation to each payment period).

Table 215: Database columns for PaymentScheduleTerm table

Database Column	Details
PaymentScheduleTermID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each PaymentScheduleTerm. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = Pre-paid• 2 = At the end of each period• 3 = At the beginning of each period.
ResourceString	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a payment schedule term. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the term resource string has no translation.</p>

PaymentScheduleType Table

PaymentScheduleType is a static table listing possible payment schedule types.

Table 216: Database columns for PaymentScheduleType table

Database Column	Details
PaymentScheduleTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each PaymentScheduleType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = General • 2 = Lease • 3 = Hardware maintenance and support • 4 = Software license • 5 = Software maintenance and support • 6 = Consulting services • 7 = Insurance • 8 = Rent • 9 = Subscription • 10 = EA professional platform • 11 = EA other application.
ResourceString	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a payment schedule type. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the type resource string has no translation.</p>
XMLFile	<p><i>Type:</i> text. Nullable</p> <p>The layout of the property dialog for this type of payment schedule, stored in XML format.</p>

Project Table

Details about each Project.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 217: Database columns for Project table

Database Column	Details
ProjectID	Type: integer. Key. Generated ID A unique identifier for the project.
ProjectName	Type: text (max 100 characters). Key The name of the project.
Comments	Type: text. Nullable Comments recorded about the project.
CreationUser	Type: text (max 128 characters). Nullable The operator who created the record.
CreationDate	Type: datetime The date the record was created.
UpdatedUser	Type: text (max 128 characters). Nullable The operator who last updated the record.
UpdatedDate	Type: datetime. Nullable The date the record was last updated.

PurchaseOrder Table

The PurchaseOrder table contains a list of all the purchase orders in the system.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 218: Database columns for PurchaseOrder table

Database Column	Details
PurchaseOrderID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the purchase order.
PurchaseOrderNo	<i>Type:</i> text (max 50 characters). Key The purchase order number.
ShortDescription	<i>Type:</i> text (max 250 characters). Nullable A short description of the purchase order.
PurchaseOrderDate	<i>Type:</i> datetime The date recorded for the purchase order.
PurchaseOrderStatusID	<i>Type:</i> integer. Nullable The current state of the purchase order. Foreign key to the PurchaseOrderStatus table. The default value of 1 links to a “New” status.
PurchaseOrderTypeID	<i>Type:</i> integer. Nullable The type of the purchase order. Foreign key to the PurchaseOrderType table.
InvoiceNo	<i>Type:</i> text (max 50 characters). Nullable The invoice number that relates to the purchase order.
InvoiceDate	<i>Type:</i> datetime. Nullable The date on the invoice that relates to the purchase order.
TotalPrice	<i>Type:</i> currency. Nullable The total price of the purchase order.
TotalPriceRateID	<i>Type:</i> integer. Nullable The currency rate to be applied to this purchase order. Foreign key to the CurrencyRate table.
ShippingAndHandling	<i>Type:</i> currency. Nullable The amount of money spent on shipping and handling.

Database Column	Details
ShippingAndHandlingRateID	<p><i>Type:</i> integer. Nullable</p> <p>The currency rate to be applied to the shipping and handling costs related to this purchase order. Foreign key to the CurrencyRate table.</p>
SalesTax	<p><i>Type:</i> currency. Nullable</p> <p>The amount of sales tax paid as part of this purchase order.</p>
SalesTaxRateID	<p><i>Type:</i> integer. Nullable</p> <p>The currency rate to be applied to the sales tax related to this purchase order. Foreign key to the CurrencyRate table.</p>
AutoCalculateCostFromChildren	<p><i>Type:</i> boolean</p> <p>The default value of True indicates that the total price, shipping, and sales tax values should be calculated from the purchase order lines that are children of this purchase order. A value of False means that these values are manually inserted into this purchase order header.</p>
ShippingMethodID	<p><i>Type:</i> integer. Nullable</p> <p>The type shipping used to deliver the product. Foreign key to the ShippingMethod table.</p>
ShippingLocationID	<p><i>Type:</i> text (max 128 characters). Key. Nullable</p> <p>The location to which the ordered material is shipped. Foreign key to the GroupEx table.</p>
ShippingDate	<p><i>Type:</i> datetime. Nullable</p> <p>The date the ordered material was shipped.</p>
RequestNo	<p><i>Type:</i> text (max 60 characters). Nullable</p> <p>The request number for the purchase order.</p>
RequestDate	<p><i>Type:</i> datetime. Nullable</p> <p>The date the purchase order was requested.</p>
RequestedByID	<p><i>Type:</i> integer. Key. Nullable</p> <p>The person who requested the purchase order. Foreign key to the ComplianceUser table.</p>
AuthorizedByID	<p><i>Type:</i> integer. Key. Nullable</p> <p>The person who authorized the purchase order. Foreign key to the ComplianceUser table.</p>
ProcessedByID	<p><i>Type:</i> integer. Key. Nullable</p> <p>The person who processed the purchase order. Foreign key to the ComplianceUser table.</p>

Database Column	Details
Comments	<i>Type:</i> text. Nullable Comments recorded about the purchase order.
VendorID	<i>Type:</i> integer. Key. Nullable The vendor fulfilling this purchase order. Foreign key to the Vendor table.
ContractID	<i>Type:</i> integer. Key. Nullable Foreign key to the Contract table, identifying any existing contract related to this purchase order.
LocationID	<i>Type:</i> text (max 128 characters). Key. Nullable Any enterprise location associated with this purchase order. Foreign key to the GroupEx table.
BusinessUnitID	<i>Type:</i> text (max 128 characters). Key. Nullable Any corporate unit in the enterprise associated with this purchase order. Foreign key to the GroupEx table.
CostCenterID	<i>Type:</i> text (max 128 characters). Key. Nullable Any cost center in the enterprise associated with this purchase order. Foreign key to the GroupEx table.
CategoryID	<i>Type:</i> text (max 128 characters). Key. Nullable Any enterprise category associated with this purchase order. Foreign key to the GroupEx table.
CreationUser	<i>Type:</i> text (max 128 characters). Nullable The operator who created the record.
CreationDate	<i>Type:</i> datetime The date the record was created.
UpdatedUser	<i>Type:</i> text (max 128 characters). Nullable The operator who last updated the record.
UpdatedDate	<i>Type:</i> datetime. Nullable The date the record was last updated.

PurchaseOrderDetail Table

The PurchaseOrderDetail table contains a list of all the individual purchase order lines in the system.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 219: Database columns for PurchaseOrderDetail table

Database Column	Details
PurchaseOrderDetailID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the purchase order line.
PurchaseOrderID	<i>Type:</i> integer. Key The parent purchase order to which this line belongs. Foreign key to the PurchaseOrder table.
PurchaseOrderDetailParentID	<i>Type:</i> integer. Nullable When a purchase order line is nested as a child of another, this link identifies the parent. Foreign key to another purchase order line in this PurchaseOrderDetail table.
ItemDescription	<i>Type:</i> text (max 250 characters) A description of the item ordered in this PO line.
SequenceNumber	<i>Type:</i> integer. Key The sequence number of the PO line in the overall purchase order.
PartNo	<i>Type:</i> text (max 100 characters). Nullable Deprecated, use LicensePartNo.
Quantity	<i>Type:</i> integer. Nullable The quantity of items purchased in this PO line.
QuantityPerUnit	<i>Type:</i> integer. Nullable Where the purchase order refers to software licenses, this is the quantity of license included in per unit of this purchase order.
EffectiveQuantity	<i>Type:</i> integer. Nullable The license entitlements brought in by this purchase. If the total for this column would exceed the maximum allowable for int, then the total will be reduced to this number.

Database Column	Details
LicenseQuantity	<p><i>Type:</i> integer. Nullable</p> <p>Where the purchase order refers to software licenses, this is the number of license entitlements conferred by the item ordered in this line. This is distinct from the purchase quantity on the line item. For example, it would be possible to order "Qty 50 of XYZ license 10-pack", which would mean a Quantity field of 50 and a LicenseQuantity of 500.</p>
LicensePartNo	<p><i>Type:</i> text (max 100 characters). Key. Nullable</p> <p>The part number or SKU of the item ordered in this PO line.</p>
UnitPrice	<p><i>Type:</i> currency. Nullable</p> <p>The unit price of items ordered on this PO line.</p>
UnitPriceRateID	<p><i>Type:</i> integer. Nullable</p> <p>The currency rate to be applied to the above unit price. Foreign key to the CurrencyRate table.</p>
SalesTax	<p><i>Type:</i> currency. Nullable</p> <p>The amount of sales tax paid on this PO line item. May be left null if sales tax is only entered on the purchase order header.</p>
SalesTaxRateID	<p><i>Type:</i> integer. Nullable</p> <p>The currency rate to be applied to the above sales tax. Foreign key to the CurrencyRate table.</p>
TotalPrice	<p><i>Type:</i> currency. Nullable</p> <p>The total price of items in this PO line.</p>
TotalPriceRateID	<p><i>Type:</i> integer. Nullable</p> <p>The currency rate to be applied to the above total price. Foreign key to the CurrencyRate table.</p>
AutoCalculateTotal	<p><i>Type:</i> boolean</p> <p>Set this field to True (the default) for the total price to be calculated automatically as $(UnitPrice * Quantity) + ShippingAndHandling + SalesTax$. If False, the operator must enter the total manually.</p>
ShippingAndHandling	<p><i>Type:</i> currency. Nullable</p> <p>The amount of money spent on shipping and handling.</p>
ShippingAndHandlingRateID	<p><i>Type:</i> integer. Nullable</p> <p>The currency rate to be applied to the above shipping and handling costs. Foreign key to the CurrencyRate table.</p>

Database Column	Details
InheritPOContractID	<p><i>Type:</i> boolean. Key</p> <p>A bit which, if set to 1 (the default), means that the following contract ID is inherited from the parent purchase order.</p>
ContractID	<p><i>Type:</i> integer. Key. Nullable</p> <p>A link to a contract related to this PO line. Foreign key to the Contract table.</p>
InheritPOShippingDetails	<p><i>Type:</i> boolean</p> <p>Set this field to True (the default) for the following shipping details to be inherited from the parent purchase order. If False, an operator has to complete the following details manually.</p>
ShippingDate	<p><i>Type:</i> datetime. Nullable</p> <p>The date the product was shipped.</p>
ShippingMethodID	<p><i>Type:</i> integer. Nullable</p> <p>The delivery method used to deliver the item ordered in this PO line. Foreign key to the ShippingMethod table.</p>
ShippingLocationID	<p><i>Type:</i> text (max 128 characters). Key. Nullable</p> <p>The location to which the item is shipped. Foreign key to the GroupEx table.</p>
MaintenanceOrService Agreement	<p><i>Type:</i> boolean</p> <p>Set this field to True when this PO line includes maintenance or another type of service agreement. If False (the default), there is no maintenance or other service agreement associated with this PO line.</p>
EffectiveDate	<p><i>Type:</i> datetime. Nullable</p> <p>The effective date for the Purchase Order Line.</p>
ExpiryDate	<p><i>Type:</i> datetime. Nullable</p> <p>The expiry date for the Purchase Order Line.</p>
InheritPOEnterpriseGroups	<p><i>Type:</i> boolean</p> <p>Set this field to True (the default) for the following enterprise groups to be inherited from the parent purchase order. If False, an operator has to complete the following details manually.</p>
LocationID	<p><i>Type:</i> text (max 128 characters). Key. Nullable</p> <p>Any enterprise location associated with this PO line. Foreign key to the GroupEx table.</p>
BusinessUnitID	<p><i>Type:</i> text (max 128 characters). Key. Nullable</p> <p>Any corporate unit within the enterprise associated with this PO line. Foreign key to the GroupEx table.</p>

Database Column	Details
CostCenterID	<p><i>Type:</i> text (max 128 characters). Key. Nullable</p> <p>Any enterprise cost center associated with this PO line. Foreign key to the GroupEx table.</p>
CategoryID	<p><i>Type:</i> text (max 128 characters). Key. Nullable</p> <p>Any category used within the enterprise associated with this PO line. Foreign key to the GroupEx table.</p>
InheritPOProcessDetails	<p><i>Type:</i> boolean</p> <p>Set this field to True (the default) for the following process details to be inherited from the parent purchase order. If False, an operator has to complete the following details manually.</p>
RequestNo	<p><i>Type:</i> text (max 60 characters). Nullable</p> <p>The request number for the PO line.</p>
RequestDate	<p><i>Type:</i> datetime. Nullable</p> <p>The date the related product was requested.</p>
RequestedByID	<p><i>Type:</i> integer. Key. Nullable</p> <p>The person who requested the purchase order line. Foreign key to the ComplianceUser table.</p>
AuthorizedByID	<p><i>Type:</i> integer. Key. Nullable</p> <p>The person who authorized the purchase order line. Foreign key to the ComplianceUser table.</p>
ProcessedByID	<p><i>Type:</i> integer. Key. Nullable</p> <p>The person who processed the purchase order line. Foreign key to the ComplianceUser table.</p>
Comments	<p><i>Type:</i> text. Nullable</p> <p>Comments recorded about the purchase order line.</p>
InheritPOInvoiceDetails	<p><i>Type:</i> boolean</p> <p>Set this field to True (the default) for the following invoicing details to be inherited from the parent purchase order. If False, an operator has to complete the following details manually.</p>
InvoiceNo	<p><i>Type:</i> text (max 50 characters). Nullable</p> <p>The invoice number relating to this PO line.</p>
InvoiceDate	<p><i>Type:</i> datetime. Nullable</p> <p>The invoice date for the purchase order line.</p>

Database Column	Details
OrderedProduct	<i>Type:</i> text (max 256 characters). Nullable A description of the item ordered in this PO line.
CreationUser	<i>Type:</i> text (max 128 characters). Nullable The operator who created the record.
CreationDate	<i>Type:</i> datetime The date the record was created.
UpdatedUser	<i>Type:</i> text (max 128 characters). Nullable The operator who last updated the record.
UpdatedDate	<i>Type:</i> datetime. Nullable The date the record was last updated.
ExternalID	<i>Type:</i> text (max 32 characters). Nullable A text field where an operator may record the ID of the PO line in any external system it was imported from.
PurchaseOrderDetailTypeID	<i>Type:</i> integer. Key The type of the PO line. Foreign key to the PurchaseOrderDetailType table.
MSSelectPoolID	<i>Type:</i> integer. Nullable Identifies the Microsoft Select pool. Foreign key to the MSSelectPool table.
MSSelectPoints	<i>Type:</i> decimal. Nullable The number of points consumed by this purchase.
AutoAcceptRecommendation	<i>Type:</i> boolean Set this field to True to automatically accept recommendation calculated for this purchase order line in Link Licenses node.
SoftwareSkuID	<i>Type:</i> integer. Key. Nullable The SKU that was recognized. This value is optional. Foreign key to the SoftwareSku table.
PurchaseOrderDetail StatusID	<i>Type:</i> integer The current state of the purchase order details. Foreign key to the PurchaseOrderDetailStatus table. The default value of 1 links to a "New" status.
PublisherID	<i>Type:</i> integer. Nullable The publisher of this line item. This value is optional. Foreign key to the Vendor table.

PurchaseOrderDetailProperty Table

PurchaseOrderDetailProperty defines extra custom properties for all purchase order lines.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 220: Database columns for PurchaseOrderDetailProperty table

Database Column	Details
PurchaseOrderDetailPropertyID	Type: integer. Key. Generated ID Unique identifier for a purchase order line property.
PropertyName	Type: text (max 256 characters). Key The name of the custom property. Foreign key to the ComplianceResourceString table.
CustomPropertyDisplayXMLID	Type: integer. Nullable Reference to a record in the CustomPropertyDisplayXML table, describing how to show the property on a property dialog.

PurchaseOrderDetailPropertyValue Table

For each purchase order line, PurchaseOrderDetailPropertyValue stores the values for the custom properties defined in PurchaseOrderDetailProperty.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 221: Database columns for PurchaseOrderDetailPropertyValue table

Database Column	Details
PurchaseOrderDetail PropertyValueID	Type: integer. Key. Generated ID A unique identifier for a property value.
PurchaseOrderDetailID	Type: integer. Key The purchase order line associated with the property. Foreign key to the PurchaseOrderDetail table
PurchaseOrderDetail PropertyID	Type: integer. Key the property whose value is being stored. Foreign key to the PurchaseOrderDetailProperty table
PropertyValue	Type: text (max 4000 characters) The property value.
CreationUser	Type: text (max 128 characters). Nullable The operator who created the record.
CreationDate	Type: datetime The date the record was created.
UpdatedUser	Type: text (max 128 characters). Nullable The operator who last updated the record.
UpdatedDate	Type: datetime. Nullable The date the record was last updated.

PurchaseOrderDetailStatus Table

PurchaseOrderDetailStatus is a static table listing the possible states for purchase order details, broadly tracking the associated business processes.

Table 222: Database columns for PurchaseOrderDetailStatus table

Database Column	Details
PurchaseOrderDetailStatusID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each PurchaseOrderDetailStatus Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = New • 2 = Pending • 3 = Completed • 4 = Cancelled
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a purchase order status. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the status resource string has no translation.</p>

PurchaseOrderDetailType Table

PurchaseOrderDetailType is a static table listing the possible types of purchase order line item.

Table 223: Database columns for PurchaseOrderDetailType table

Database Column	Details
PurchaseOrderDetailTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each PurchaseOrderDetailType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = Not set• 2 = Software• 3 = Hardware• 4 = Service• 5 = Other• 6 = Software upgrade• 7 = Software maintenance• 8 = Disk kit• 9 = Hardware maintenance• 10 = Software Baseline• 11 = Software subscription.
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a purchase order line item type. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the type resource string has no translation.</p>

PurchaseOrderProperty Table

PurchaseOrderProperty defines extra custom properties for all purchase orders.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 224: Database columns for PurchaseOrderProperty table

Database Column	Details
PurchaseOrderPropertyID	Type: integer. Key. Generated ID Unique identifier for a purchase order property.
PropertyName	Type: text (max 256 characters). Key The name of the property.
CustomPropertyDisplayXMLID	Type: integer. Nullable Foreign key to a record in the CustomPropertyDisplayXML table, describing how to show the property on a property dialog.

PurchaseOrderPropertyValue Table

For each purchase order, PurchaseOrderPropertyValue stores the values for the custom properties defined in PurchaseOrderProperty.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 225: Database columns for PurchaseOrderPropertyValue table

Database Column	Details
PurchaseOrderProperty ValueID	Type: integer. Key. Generated ID A unique identifier for a property value.
PurchaseOrderID	Type: integer. Key The purchase order associated with this property. Foreign key to the PurchaseOrder table.
PurchaseOrderPropertyID	Type: integer. Key The property whose value is being stored. Foreign key to the PurchaseOrderProperty table.
PropertyValue	Type: text (max 4000 characters) The property value.
CreationUser	Type: text (max 128 characters). Nullable The operator who created the record.
CreationDate	Type: datetime The date the record was created.
UpdatedUser	Type: text (max 128 characters). Nullable The operator who last updated the record.
UpdatedDate	Type: datetime. Nullable The date the record was last updated.

PurchaseOrderStatus Table

PurchaseOrderStatus is a static table listing the possible states for purchase orders, broadly tracking the associated business processes.

Table 226: Database columns for PurchaseOrderStatus table

Database Column	Details
PurchaseOrderStatusID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each PurchaseOrderStatus. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = New• 2 = Completed• 3 = Cancelled• 4 = Sent to approver• 5 = Sent to vendor• 6 = Item received.
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a purchase order status. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the status resource string has no translation.</p>

PurchaseOrderType Table

PurchaseOrderType is a static table listing the possible types of purchase order. Reserved for future expansion.

Table 227: Database columns for PurchaseOrderType table

Database Column	Details
PurchaseOrderTypeID	<i>Type:</i> integer. Key. Generated ID A unique identifier for each PurchaseOrderType. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• 1 = None.
ResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing a purchase order type. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the type resource string has no translation.

PurchaseProgram Table

PurchaseProgram is a static table listing all known contract purchase programs.

Table 228: Database columns for PurchaseProgram table

Database Column	Details
PurchaseProgramID	<p>Type: integer. Key. Generated ID</p> <p>A unique identifier for each PurchaseProgram. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = Microsoft Select Agreement • 2 = Microsoft Enterprise Agreement • 3 = Microsoft Open Agreement • 4 = Adobe Cumulative Licensing Program • 5 = Adobe Transactional Licensing Program • 6 = Adobe Site License Program • 7 = Acronis Licensing Program • 8 = Attachmate Volume Purchase Account • 9 = Business Objects Open Licensing Program • 10 = CA Master License Program • 11 = CA Open License Program • 12 = Citrix Easy Licensing Program • 13 = Citrix Enterprise License Program • 14 = Citrix Open Licensing Program • 15 = Citrix Premium Licensing Program • 16 = Corel Contractual License • 17 = Corel Transactional Licensing • 18 = IBM Passport Advantage • 19 = McAfee TSP Licensing Program • 20 = Novell Corporate License Agreement • 21 = Novell Master License Agreement • 22 = Novell Volume License Agreement • 23 = Symantec Elite • 24 = Symantec Express • 25 = Symantec Open Licensing Program • 26 = Symantec Rewards

Database Column	Details
	<ul style="list-style-type: none"> • 27 = Symantec Volume Licensing Program • 28 = VMware Purchasing Program • 29 = Macromedia Volume License Program • 30 = Symantec Enterprise Option • 31 = Symantec Enterprise VPA. • 32 = Oracle Master Agreement • 33 = Oracle Unlimited Agreement • 34 = Oracle License and Services Agreement • 35 = Adobe Enterprise Term Licensing Agreement • 36 = Microsoft Products and Services Agreement • 37 = IBM Passport Advantage Express • 38 = IBM Enterprise License Agreement • 39 = IBM Enterprise Software and Services Option
Name	<i>Type:</i> text (max 100 characters). Key The display name of the purchase program.
PublisherName	<i>Type:</i> text (max 64 characters). Key The name of publisher under which this purchase program applies.
Code	<i>Type:</i> text (max 16 characters). Key A short code used to represent this purchase program.

QuerySnapshot Table

QuerySnapshot holds the snapshot of data for a report


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 229: Database columns for QuerySnapshot table

Database Column	Details
QuerySnapshotID	Type: integer. Key. Generated ID A unique identifier for a query snapshot.
QueryContext	Type: text (max 200 characters). Key The query context to partition different queries.
ComplianceSavedSearchID	Type: integer. Key. Nullable The query definition this snapshot is for. Foreign key to the ComplianceSavedSearch table.
ComplianceOperatorID	Type: integer. Key The operator who ran the report. Foreign key to the ComplianceOperator table.
SnapshotName	Type: text (max 200 characters) Name of snapshot.
SnapshotSchema	Type: XML Schema of snapshot.
SnapshotDate	Type: datetime Date and time of snapshot (UTC)
SnapshotBuildTime	Type: big integer Number of milliseconds taken to build the snapshot.
SnapshotRows	Type: big integer Number of rows in the snapshot.

RelationType Table

RelationType is a static table containing types of relationship between objects

Table 230: Database columns for RelationType table

Database Column	Details
RelationTypeID	<i>Type:</i> integer. Key. Generated ID A unique identifier for each RelationType. Possible values and the corresponding default strings are: <ul style="list-style-type: none">1 = VMware ESX host managed by vCenter
ResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing a relation type. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 256 characters) The text to display if the type resource string has no translation.
ImporterString	<i>Type:</i> text (max 100 characters). Key The text value provided by adapters when importing relation type.

ResponsibilityType Table

ResponsibilityType is a static table listing possible end-user responsibilities.

Table 231: Database columns for ResponsibilityType table

Database Column	Details
ResponsibilityTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for an end-user's title or responsibility. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = Blank • 2 = Owner • 3 = Signatory • 4 = Contract Manager • 5 = Point of Contact • 6 = Negotiator • 7 = Interested Party.
ResourceString	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a user responsibility. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the responsibility resource string has no translation.</p>

RestrictedAccessType Table

RestrictedAccessType is a static table holding access types

Table 232: Database columns for RestrictedAccessType table

Database Column	Details
RestrictedAccessTypeID	<i>Type:</i> integer. Key. Generated ID A unique identifier for a type of access. Values are: <ul style="list-style-type: none">• 1 = All users• 2 = Accessible only to creator
RestrictedAccessTypeName	<i>Type:</i> text (max 512 characters). Key Access type name.

RulesEngineRuleDefinition Table

This table stores rule definitions used for consolidating users.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 233: Database columns for RulesEngineRuleDefinition table

Database Column	Details
RuleDefinitionID	Type: integer. Key. Generated ID A unique identifier for the rule definition.
RuleDefinitionName	Type: text (max 128 characters) Name of the rule.
RuleTypeID	Type: integer Foreign key to the rule type.
RuleDefinition	Type: text The rule definition XML used to build the rule statement used by the rules engine.
IsActive	Type: boolean Whether or not this rule is active for execution.
CreationUser	Type: text (max 256 characters) The user who created the system landscape.
CreationDate	Type: datetime The data and time the system landscape was created.
UpdatedUser	Type: text (max 256 characters) The last user who update the system landscape.
UpdatedDate	Type: datetime The date and time the system landscape was last updated.

RulesEngineRuleType Table

This table stores the available rule types used for rulesengine.

Table 234: Database columns for RulesEngineRuleType table

Database Column	Details
RuleTypeID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the rule type.
TypeName	<i>Type:</i> text (max 100 characters). Key A unique name for the rule type.
TitleResourceName	<i>Type:</i> text (max 256 characters). Nullable A localizable resource string representing a rule type. Foreign key to the ComplianceResourceString table.
TitleDefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the rule type resource string has no translation.
RuleTemplate	<i>Type:</i> text The template used to build a rule for the rules engine.
DefaultRuleDefinition	<i>Type:</i> text. Nullable Default rule definition for newly created rule

SecurityType Table

SecurityType lists the types of security model that can be used to determine access to a contract or document.

Table 235: Database columns for SecurityType table

Database Column	Details
SecurityTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each SecurityType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = Public (security is controlled by the operator's roles) • 2 = Restricted (security is controlled by an access control list of account names).
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a security type. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the type resource string has no translation.</p>

SerialNumberBlackList Table

SerialNumberBlackList stores a blacklist of invalid serial numbers.

Table 236: Database columns for SerialNumberBlackList table

Database Column	Details
SerialNumberBlackListID	Type: integer. Key. Generated ID The unique identifier for a blacklisted serial number.
SerialNo	Type: text (max 100 characters). Key The blacklisted serial number.

SessionUIDBeacon Table

The SessionUIDBeacon table stores the task’s SessionUID and the beacon where the task is running .


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 237: Database columns for SessionUIDBeacon table

Database Column	Details
SessionUID	Type: unique identifier. Key Unique task run identifier
BeaconID	Type: integer. Key Beacon where the task’s session ran

ShippingMethod Table

ShippingMethod is a static table listing possible delivery methods. Reserved for future expansion.

Table 238: Database columns for ShippingMethod table

Database Column	Details
ShippingMethodID	<i>Type:</i> integer. Key. Generated ID A unique identifier for each ShippingMethod. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• 1 = None.
ResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing a shipping method. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the shipping method resource string has no translation.

SoftwareLicenseContractPaymentSchedule Table

SoftwareLicenseContractPaymentSchedule links a payment schedule to a software license, via a link from that software license to a contract.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 239: Database columns for SoftwareLicenseContractPaymentSchedule table

Database Column	Details
SoftwareLicenseContractID	Type: integer. Key Identifies a link between a software license and a contract. Foreign key to the SoftwareLicenseContract table.
PaymentScheduleID	Type: integer. Key Identifies a payment schedule. Foreign key to the PaymentSchedule table.

SystemShutdown Table

A row in this table indicates that the system is being taken down, and is used to show a warning to users.

Table 240: Database columns for SystemShutdown table

Database Column	Details
SystemShutdownID	<i>Type:</i> integer. Key. Generated ID Synthetic key for this table.
MessageResourceName	<i>Type:</i> text (max 256 characters). Nullable A resource name used to look up a message to show to the operator
StartTime	<i>Type:</i> datetime The time the shutdown is scheduled to begin
EndTime	<i>Type:</i> datetime The estimated time that the shutdown will end

TaskExecutionStatus Table

The TaskExecutionStatus table stores progress data for rules and background tasks.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 241: Database columns for TaskExecutionStatus table

Database Column	Details
TaskExecutionStatusID	Type: integer. Key. Generated ID Auto-generated task execution status ID
SessionUID	Type: unique identifier. Key Unique task run identifier
TaskName	Type: text (max 255 characters). Key The name of task.
ActivityTypeID	Type: integer. Key Foreign key to the ActivityType table
DateStarted	Type: datetime. Nullable Start date and time for a task.
DateCompleted	Type: datetime. Nullable Completion date and time for a task.
EventTypeStatusID	Type: integer. Key Foreign key to the EventTypeStatus table
BeaconRuleID	Type: integer. Key. Nullable Foreign key to the BeaconRule table
ScheduledTriggerDateTick	Type: big integer. Key. Nullable Executed date time in Tick.
BeaconID	Type: integer. Key. Nullable Beacon where the task is executing.
BeaconPolicyRevision Number	Type: integer. Nullable Beacon policy revision number
OperatorLogin	Type: text (max 255 characters). Nullable Login of the operator who started task.

TaskExecutionStatusStep Table

The TaskExecutionStatusStep table stores progress data for rule or background task steps.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 242: Database columns for TaskExecutionStatusStep table

Database Column	Details
TaskExecutionStatusStepID	<i>Type:</i> integer. Key. Generated ID Auto-generated task step execution status ID
TaskExecutionStatusID	<i>Type:</i> integer. Key Foreign key to TaskExecutionStatus table.
TaskStepID	<i>Type:</i> integer. Key The ID of task step.
BeaconRuleActionPropertyID	<i>Type:</i> integer. Key. Nullable The ID of rule action subtask.
DateStarted	<i>Type:</i> datetime. Nullable Start date and time for a step.
DateCompleted	<i>Type:</i> datetime. Nullable Completion date and time for a step.
EventTypeStatusID	<i>Type:</i> integer. Key Foreign key to the EventTypeStatus table
BeaconUID	<i>Type:</i> unique identifier. Key. Nullable Beacon ID.
EventTypeID	<i>Type:</i> integer. Key. Nullable Foreign key to the EventType table
EventID	<i>Type:</i> integer. Key. Nullable Foreign key to the Event table
Location	<i>Type:</i> text (max 255 characters). Nullable Server name where operation was performed.
TaskParameters	<i>Type:</i> XML. Nullable parameters for the task step.

TaskStep Table

The TaskStep table stores task steps.

Table 243: Database columns for TaskStep table

Database Column	Details
TaskStepID	<i>Type:</i> integer. Key. Generated ID Auto-generated task step ID
ActivityTypeID	<i>Type:</i> integer. Key Foreign key to the ActivityType table
TaskStepResourceName	<i>Type:</i> text (max 255 characters). Key Task step name resource name
TaskStepDefaultValue	<i>Type:</i> text (max 255 characters) Task step name default value
TaskStepOrder	<i>Type:</i> integer Task step order index

TaskStepEventType Table

The TaskStepEventType table stores eventType related to the taskStep.

Table 244: Database columns for TaskStepEventType table

Database Column	Details
TaskStepID	Type: integer. Key Foreign key to the TaskStep table
EventTypeID	Type: integer. Key Foreign key to the EventType table

TermAndCondition Table

TermAndCondition stores a list of terms and conditions related to a contract.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 245: Database columns for TermAndCondition table

Database Column	Details
TermAndConditionID	Type: integer. Key. Generated ID A unique identifier for the term/condition.
TermAndConditionTypeID	Type: integer. Key The type of term/condition. Foreign key to TermAndConditionType table.
Description	Type: text (max 100 characters). Key A description assigned by the operator.
DocReference	Type: text (max 100 characters). Nullable A text reference to a document for this term/condition.
Comments	Type: text. Nullable Comments about this term/condition.
BeginDate	Type: datetime. Nullable The start date for this term or condition.
EndDate	Type: datetime. Nullable The end date for this term or condition.
ContractID	Type: integer. Key The contract to which this term/condition applies. Foreign key to the Contract table.
CreationUser	Type: text (max 128 characters). Nullable The operator who created the record.
CreationDate	Type: datetime The date the term/condition was created.
UpdatedUser	Type: text (max 128 characters). Nullable The name of the operator who last updated the term/condition.

Database Column	Details
UpdatedDate	<i>Type:</i> datetime. Nullable The date the record was last updated.
EmailComplianceUserID	<i>Type:</i> integer. Key. Nullable A user who may be emailed according to conditions on this term/condition. Foreign key to the ComplianceUser table.
EmailIntervalTypeID	<i>Type:</i> integer. Key. Nullable The interval type for EmailInterval. Foreign key to the IntervalType table.
EmailInterval	<i>Type:</i> integer. Nullable The interval used when sending emails.
ReminderIntervalTypeID	<i>Type:</i> integer. Key. Nullable The interval type for ReminderInterval. Foreign key to the IntervalType table.
ReminderInterval	<i>Type:</i> integer. Nullable The interval used when sending reminders.
EscalationCompliance UserID	<i>Type:</i> integer. Key. Nullable A user who may be emailed if the term/condition needs to be escalated. Foreign key to the ComplianceUser table.
EscalationIntervalTypeID	<i>Type:</i> integer. Key. Nullable The interval type for EscalationInterval. Foreign key to the IntervalType table.
EscalationInterval	<i>Type:</i> integer. Nullable The interval used when sending escalation messages.
Auditable	<i>Type:</i> boolean Boolean to indicate whether the term/condition is auditable.

TermAndConditionTask Table

TermAndConditionTask holds extra information about a task.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 246: Database columns for TermAndConditionTask table

Database Column	Details
ComplianceTaskID	<i>Type:</i> integer. Key The task this extra information applies to. Foreign key to the ComplianceTask table.
Completed	<i>Type:</i> boolean Set this field to True if this task has been completed.
CompletionDate	<i>Type:</i> datetime. Nullable The date of completion of the task.
ComplianceUserID	<i>Type:</i> integer. Key. Nullable The end-user this task is assigned to. Foreign key to the ComplianceUser table.
Notes	<i>Type:</i> text. Nullable Notes or comments related to the task.

TermAndConditionType Table

TermAndConditionType stores a list of types of different terms/conditions that may be associated with contracts.

Table 247: Database columns for TermAndConditionType table

Database Column	Details
TermAndConditionTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each TermAndConditionType. The default values and corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = Acceptance Period• 2 = Price Change• 3 = Cancellation• 4 = Renewal• 5 = Expiry• 6 = Review• 7 = Limitation.
TermAndConditionType ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a term/condition type. Foreign key to the ComplianceResourceString table.</p>
TermAndConditionType DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the type resource string has no translation.</p>
ManageSoftType	<p><i>Type:</i> boolean</p> <p>If set to True, this field indicates that this term and condition type was created by FlexNet Manager Suite and should not be deleted or edited. If False, the type has been created by an operator, and may be modified.</p>

UserNameBlacklist Table

UserNameBlacklist stores a list of excluded accounts that will not be imported into FlexNet Manager Suite. If an end-user with account name matching a record in UserNameBlacklist already exists in FlexNet Manager Suite, that end-user will not be included in compliance calculations and will not appear in many of the end-user lists.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 248: Database columns for UserNameBlacklist table

Database Column	Details
UserNameBlacklistID	Type: integer. Key. Generated ID A unique identifier for the blacklisted account.
UserName	Type: text (max 64 characters). Key A blacklisted account name. May contain wildcards (% , _). End-users whose domain\SAM account name match this value will be excluded from compliance calculations.

VMEnabledState Table

VMEnabledState is a static table listing the possible operational states of a virtual machine.

Table 249: Database columns for VMEnabledState table

Database Column	Details
VMEnabledStateID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each VMEnabledState. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = Started• 2 = Stopped• 3 = Suspended• 4 = Unknown.
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a virtual machine operational state. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the operational state resource string has no translation.</p>

VMHostManagedBySoftware Table

VMHostManagedBySoftware stores relationships between management software and VM hosts it manages. The RelationTypeID specifies the context of these relationships


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 250: Database columns for VMHostManagedBySoftware table

Database Column	Details
VMHostManagedBySoftwareID	Type: integer. Key. Generated ID The primary key of VMHostManagedBySoftware.
InstalledSoftwareID	Type: integer. Key A unique identifier of an InstalledSoftware.
RelationTypeID	Type: integer. Key The type of relationship between management software and the VM hosts. Foreign key to the RelationType table.
ComplianceComputerID	Type: integer. Key A unique identifier of a ComplianceComputer.

VMPool Table

VMPool contains information about virtual machine pools (logical groups of VMs or partitions).



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 251: Database columns for VMPool table

Database Column	Details
VMPoolID	Type: integer. Key. Generated ID A unique identifier for a virtual machine pool.
PoolName	Type: text (max 100 characters). Key The name of the pool.
PoolFriendlyName	Type: text (max 256 characters) The friendly name of the pool.
Path	Type: text (max 1000 characters) The full path of the pool (including parent pool names).
VXObjectID	Type: text (max 256 characters). Nullable The ID of the virtual machine folder (pool) in Virtual Center.
NextChild	Type: integer One more than the number of children this pool has.
PoolPathID	Type: text (max 128 characters) A numerical representation of the path of this pool, constructed from VMPoolID values (something like: "1.2.").
HostComplianceComputerID	Type: integer. Key. Nullable A link to the host computer that this pool exists on. This is a foreign key to the ComplianceComputer table.
VMPoolTypeID	Type: integer. Key The type of pool. Foreign key to the VMPoolType table.
VirtualMachineID	Type: integer. Nullable If this pool is a virtual machine or partition itself, this is a link to that virtual machine or partition. Foreign key to the VirtualMachine table.
NumberOfProcessors	Type: decimal. Nullable The number of processors in this pool.

Database Column	Details
NumberOfCores	Type: decimal. Nullable The number of cores in this pool.

VMPoolType Table

VMPoolType is a static table listing the possible types of a virtual machine pool.

Table 252: Database columns for VMPoolType table

Database Column	Details
VMPoolTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for a VMPoolType. Possible values and the corresponding default names are:</p> <ul style="list-style-type: none">• 1 = Folder• 2 = Data Center• 3 = Compute Resource• 4 = Host System• 5 = Resource Pool• 6 = Virtual Machine• 7 = Physical Shared Pool• 8 = Virtual Shared Pool• 9 = LPAR• 10 = RSET• 11 = Cluster Compute Resource.
VTypeID	<p><i>Type:</i> text (max 32 characters)</p> <p>The type of the virtual machine folder in Virtual Center.</p>
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a pool type. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the pool type resource string has no translation.</p>

VMSourceType Table

VMSourceType is a static table used to define possible virtual machine inventory source values (that is, whether the properties were created manually or reported by the compliance importer).

Table 253: Database columns for VMSourceType table

Database Column	Details
VMSourceTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each VMSourceType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = Manual (the virtual machine properties were manually created and have not been updated by the compliance importer)• 2 = VM Host (the virtual machine's host recently reported inventory and updated these virtual machine properties).
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a virtual machine source type. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the source type resource string has no translation.</p>

VMState Table

VMState is a static table listing the possible relationships between a virtual machine and a physical (inventoried) computer.

Table 254: Database columns for VMState table

Database Column	Details
VMStateID	<p>Type: integer. Key. Generated ID</p> <p>A unique identifier for each VMState. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = Linked (the virtual machine is linked to an inventoried or manually created computer)• 2 = Unlinked (the virtual machine is only linked to a “light” computer, automatically created from the host computer’s inventory)• 3 = Duplicated (the virtual machine has a duplicate UUID and is not linked to an inventoried or manually created computer).
ResourceName	<p>Type: text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a virtual machine state. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p>Type: text (max 100 characters)</p> <p>The text to display if the state resource string has no translation.</p>

VMType Table

VMType is a static table listing the possible types of virtual machine or partition.

Table 255: Database columns for VMType table

Database Column	Details
VMTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for a VMType. Possible values and the corresponding default names are:</p> <ul style="list-style-type: none"> • 1 = VMware • 2 = Hyper-V • 3 = LPAR • 4 = WPAR • 5 = nPar • 6 = vPar • 7 = SRP • 8 = Zone • 9 = Unknown. • 10 = Oracle VM
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a virtual machine or partition type. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the type resource string has no translation.</p>

Vendor Table

The Vendor table contains a list of all the vendors in the system.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 256: Database columns for Vendor table

Database Column	Details
VendorID	Type: integer. Key. Generated ID A unique identifier for the vendor.
VendorName	Type: text (max 64 characters). Key The name of the vendor.
VendorPreviousName	Type: text (max 64 characters). Nullable Any earlier name that the vendor was previously known as.
BusinessPhoneNumber	Type: text (max 30 characters). Nullable The business phone number of the vendor.
FaxPhoneNumber	Type: text (max 30 characters). Nullable The fax number of the vendor.
Address_Street	Type: text (max 200 characters). Nullable The street address of the vendor.
Address_City	Type: text (max 200 characters). Nullable The city of the vendor.
Address_State	Type: text (max 200 characters). Nullable The state or province of the vendor.
Address_ZIP	Type: text (max 20 characters). Nullable The ZIP or postal code of the vendor.
Address_Country	Type: text (max 100 characters). Nullable The country of the vendor.
Address2_Street	Type: text (max 200 characters). Nullable The second street address of the vendor, if applicable.
Address2_City	Type: text (max 200 characters). Nullable The second city of the vendor.

Database Column	Details
Address2_State	<i>Type:</i> text (max 200 characters). Nullable The second state or province of the vendor.
Address2_ZIP	<i>Type:</i> text (max 20 characters). Nullable The second ZIP or postal code of the vendor.
Address2_Country	<i>Type:</i> text (max 100 characters). Nullable The second country of the vendor.
WebSite	<i>Type:</i> text (max 200 characters). Nullable The web site of the vendor.
Email	<i>Type:</i> text (max 200 characters). Nullable The email address of the vendor.
ParentVendorID	<i>Type:</i> integer. Nullable A link to a vendor's parent vendor. Foreign key to another vendor record in this Vendor table. Vendor hierarchies are not currently implemented.
CreationUser	<i>Type:</i> text (max 128 characters). Nullable The operator who created the record.
CreationDate	<i>Type:</i> datetime The date the record was created.
UpdatedUser	<i>Type:</i> text (max 128 characters). Nullable The operator who last updated the record.
UpdatedDate	<i>Type:</i> datetime. Nullable The date the record was last updated.
AutomaticallyAccept Purchases	<i>Type:</i> boolean Whether purchases from this vendor should have their license linking recommendations in the EntitlementRecommendation table automatically accepted.

VendorContact Table

VendorContact contains a list of all the vendor contacts, or individuals employed by the vendor with whom this enterprise has contact.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 257: Database columns for VendorContact table

Database Column	Details
VendorContactID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the contact.
UserTitleID	<i>Type:</i> integer. Nullable The title of the contact's name. Foreign key to the UserTitle table.
FirstName	<i>Type:</i> text (max 128 characters) The first name of the contact.
MiddleName	<i>Type:</i> text (max 128 characters). Nullable The middle name(s) of the contact.
LastName	<i>Type:</i> text (max 128 characters). Nullable The last name name of the contact.
UserSuffixID	<i>Type:</i> integer. Nullable The suffix to the name of the contact.
JobTitle	<i>Type:</i> text (max 128 characters). Nullable The job title of the contact.
VendorID	<i>Type:</i> integer. Key A link to the contact's parent vendor. Foreign key to the Vendor table.
BusinessPhoneNumber	<i>Type:</i> text (max 30 characters). Nullable The business phone number of the contact.
MobilePhoneNumber	<i>Type:</i> text (max 30 characters). Nullable The mobile phone number of the contact.
FaxPhoneNumber	<i>Type:</i> text (max 30 characters). Nullable The fax number of the contact.

Database Column	Details
Address_Street	<i>Type:</i> text (max 200 characters). Nullable The street address of the contact.
Address_City	<i>Type:</i> text (max 200 characters). Nullable The city of the contact.
Address_State	<i>Type:</i> text (max 200 characters). Nullable The state or province of the contact.
Address_ZIP	<i>Type:</i> text (max 20 characters). Nullable The ZIP or postal code of the contact.
Address_Country	<i>Type:</i> text (max 100 characters). Nullable The country of the contact.
Address2_Street	<i>Type:</i> text (max 200 characters). Nullable The second street address of the contact, if applicable.
Address2_City	<i>Type:</i> text (max 200 characters). Nullable The second city of the contact.
Address2_State	<i>Type:</i> text (max 200 characters). Nullable The second state or province of the contact.
Address2_ZIP	<i>Type:</i> text (max 20 characters). Nullable The second ZIP or postal code of the contact.
Address2_Country	<i>Type:</i> text (max 100 characters). Nullable The second country of the contact.
Email	<i>Type:</i> text (max 200 characters). Nullable The email address of the contact.
Messenger	<i>Type:</i> text (max 200 characters). Nullable The instant messenger address of the contact.
Comments	<i>Type:</i> text. Nullable Comments recorded about the contact.
CreationUser	<i>Type:</i> text (max 128 characters). Nullable The operator who created the record.
CreationDate	<i>Type:</i> datetime The date the record was created.
UpdatedUser	<i>Type:</i> text (max 128 characters). Nullable The operator who last updated the record.

Database Column	Details
UpdatedDate	Type: datetime. Nullable The date the record was last updated.

VendorProperty Table

VendorProperty defines extra custom properties for all vendors.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 258: Database columns for VendorProperty table

Database Column	Details
VendorPropertyID	Type: integer. Key. Generated ID Unique identifier for a vendor property.
PropertyName	Type: text (max 256 characters). Key The name of the custom property. Foreign key to the ComplianceResourceString table.
CustomPropertyDisplayXMLID	Type: integer. Nullable Reference to a record in the CustomPropertyDisplayXML table, describing how to show the property on a property dialog.

VendorPropertyValue Table

For each vendor, VendorPropertyValue stores the values for the custom properties defined in VendorProperty.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 259: Database columns for VendorPropertyValue table

Database Column	Details
VendorPropertyValueID	Type: integer. Key. Generated ID A unique identifier for a property value.
VendorID	Type: integer. Key The vendor associated with this property. Foreign key to the Vendor table.
VendorPropertyID	Type: integer. Key The property whose value is being stored. Foreign key to the VendorProperty table.
PropertyValue	Type: text (max 4000 characters) The property value.
CreationUser	Type: text (max 128 characters). Nullable The operator who created the record.
CreationDate	Type: datetime The date the record was created.
UpdatedUser	Type: text (max 128 characters). Nullable The operator who last updated the record.
UpdatedDate	Type: datetime. Nullable The date the record was last updated.

VirtualMachine Table

VirtualMachine stores extra information for computers identified as virtual machines or hardware partitions.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 260: Database columns for VirtualMachine table

Database Column	Details
VirtualMachineID	<i>Type:</i> integer. Key. Generated ID A unique identifier for virtual machine or partition properties associated with a computer.
HostComplianceComputerID	<i>Type:</i> integer. Key. Nullable The virtual machines or partition's host computer. Foreign key to the ComplianceComputer table.
ComplianceComputerID	<i>Type:</i> integer. Key The computer associated with these virtual machine or partition properties. Computer in the ComplianceComputer table.
VMTypeID	<i>Type:</i> integer The type of virtual machine or partition. Foreign key to the VMType table.
UUID	<i>Type:</i> text (max 256 characters). Nullable The UUID (Universally Unique Identifier) of the virtual machine. Used to match virtual machine properties to their associated ComplianceComputer.
VMName	<i>Type:</i> text (max 256 characters). Nullable The name of the virtual machine or partition.
VMLocation	<i>Type:</i> text (max 256 characters). Nullable The location of the virtual machine on the file system.
GuestFullName	<i>Type:</i> text (max 256 characters). Nullable The configured operating system for the guest.
FriendlyName	<i>Type:</i> text (max 256 characters). Nullable The friendly name of the virtual machine or partition.
VCObjectID	<i>Type:</i> text (max 256 characters). Nullable The ID of the virtual machine in Virtual Center.

Database Column	Details
TotalMemory	<i>Type:</i> big integer. Nullable The total memory of the virtual machine (in bytes).
VMStateID	<i>Type:</i> integer The state of the virtual machine, related to whether it is linked to a computer or not. Foreign key to the VMState table.
VMPoolID	<i>Type:</i> integer. Nullable The resource pool that the virtual machine belongs to. Foreign key to the VMPool table.
CPUUsage	<i>Type:</i> integer. Nullable The maximum CPU usage of the Virtual Machine (measured in MHz).
MemoryUsage	<i>Type:</i> big integer. Nullable The maximum memory usage of the Virtual Machine (in bytes).
VMEabledStateID	<i>Type:</i> integer The operational state of the virtual machine (powered on, off, and so on). Foreign key to the VMEabledState table.
VMSourceTypeID	<i>Type:</i> integer Whether the virtual machine properties are manually entered or created from inventory. Foreign key to the VMSourceType table.
CreationUser	<i>Type:</i> text (max 256 characters) The operator who created this record.
CreationDate	<i>Type:</i> datetime The date/time when this record was created.
UpdatedUser	<i>Type:</i> text (max 256 characters). Nullable The operator who last updated this record.
UpdatedDate	<i>Type:</i> datetime The date/time when this record was last updated.
AffinityEnabled	<i>Type:</i> boolean Set this to True if this VM is unable to move to different host computers.
LocatedInCloud	<i>Type:</i> boolean 1 - if the virtual machine is hosted in a cloud environment
ServiceProvider	<i>Type:</i> text (max 250 characters). Nullable Cloud provider (data center)

Database Column	Details
CPUAffinity	<i>Type:</i> text (max 256 characters). Nullable Contains the CPU Affinity value for virtual machines (Host Logical processors)
CoreAffinity	<i>Type:</i> text (max 256 characters). Nullable Contains the Core Affinity value for virtual machine
PartitionID	<i>Type:</i> text (max 100 characters). Nullable Partition ID generated and used by the managing virtualization platform
PartitionNumber	<i>Type:</i> integer. Nullable Number of this partition
IsHostAssignedManually	<i>Type:</i> boolean Was the virtual machine assigned to its host manually? This prevents unlinking of the virtual machine.

XMLInsertType Table

XMLInsertType is a static table storing how custom property XML snippets will be inserted into the default property display layout XML file.

Table 261: Database columns for XMLInsertType table

Database Column	Details
XMLInsertTypeID	<p>Type: integer. Key. Generated ID</p> <p>A unique identifier for each XMLInsertType. Possible values are:</p> <ul style="list-style-type: none">• 1 = Before (the new snippet needs to go before the existing XML element)• 2 = After (the new snippet needs to go after the existing XML element)• 3 = Replace (the new snippet needs to replace the existing XML element)• 4 = First child (the new snippet needs to be added as the first child of the existing XML element)• 5 = Last child (the new snippet needs to be added as the last child of the existing XML element).
TypeDescription	<p>Type: text (max 50 characters). Key</p> <p>A description of the insert type.</p>

Compliance.Logic.Discovery Tables

The complete set of database tables documented here includes:

- ASN1Object table (see [ASN1Object Table](#))
- DeviceRole table (see [DeviceRole Table](#))
- DiscoveredDevice table (see [DiscoveredDevice Table](#))
- DiscoveredDeviceCalculatedMember table (see [DiscoveredDeviceCalculatedMember Table](#))
- DiscoveredDeviceParent table (see [DiscoveredDeviceParent Table](#))
- DiscoveredDeviceSNMPInfo table (see [DiscoveredDeviceSNMPInfo Table](#))
- DiscoveredDeviceVDIBrokerInfo table (see [DiscoveredDeviceVDIBrokerInfo Table](#))
- DiscoveredDeviceVDIInfo table (see [DiscoveredDeviceVDIInfo Table](#))
- DiscoveredDeviceVirtualizationInfo table (see [DiscoveredDeviceVirtualizationInfo Table](#))
- KnownOracleListener table (see [KnownOracleListener Table](#))
- KnownOracleService table (see [KnownOracleService Table](#))
- Site table (see [Site Table](#))
- SiteSubnet table (see [SiteSubnet Table](#))
- VirtualizationProductName table (see [VirtualizationProductName Table](#))

ASN1Object Table

Stores a mapping from a ASN ObjectID (OID) to a type of device.

Table 262: Database columns for ASN1Object table

Database Column	Details
OID	Type: text (max 128 characters). Key ASN object identifier.
Description	Type: text (max 512 characters) The fully expanded text version of the object identifier.
ObjectRole	Type: integer. Nullable What role does the device perform?

DeviceRole Table

The role of a network device.

Table 263: Database columns for DeviceRole table

Database Column	Details
DeviceRoleID	<i>Type:</i> integer. Key. Generated ID The id of the device role.
Description	<i>Type:</i> text (max 64 characters). Key The name of the device role. Possible id and name pairs are: <ul style="list-style-type: none">• 0 = Computer• 1 = Workstation• 2 = Server• 3 = Printer• 4 = Switch• 5 = Router• 6 = Hub• 7 = NetworkDevice• 8 = Vendor.

DiscoveredDevice Table

A DiscoveredDevice is a loose record of the discovery of a device on a network, using any of a number of discovery methods. As such, the same device may be found in more than one way (see DuplicateID which may be able to track this fact if known), or by more than one distinguishing feature. Accordingly this table has a somewhat unsatisfactory primary key!



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 264: Database columns for DiscoveredDevice table

Database Column	Details
DeviceID	Type: integer. Key. Generated ID Auto-generated identity number.
DeviceUID	Type: unique identifier. Key A unique external identifier for the device.
DuplicateID	Type: integer. Key. Nullable Reference to another discovery record for this device, if known.
ComputerID	Type: integer. Key. Nullable FlexNet Manager Suite computer id, if known
DeviceName	Type: text (max 64 characters). Key. Nullable NetBIOS name for computers or any name for other devices, if known.
DNSFullName	Type: text (max 256 characters). Key. Nullable Fully qualified DNS name, if known.
NTDomainName	Type: text (max 256 characters). Key. Nullable NT domain name, if known.
IPAddress	Type: text (max 64 characters). Key. Nullable IP address of the device.
IPSubnet	Type: text (max 64 characters). Nullable IP subnet that contains the node.
IPSubnetMask	Type: text (max 64 characters). Nullable IP subnet mask for the subnet contains the device.

Database Column	Details
PhysicalAddress	<p><i>Type:</i> text (max 64 characters). Key. Nullable</p> <p>Network adapter physical address of the node. Can be a MAC address or token ring address.</p>
DeviceRole	<p><i>Type:</i> integer. Nullable</p> <p>What role does the device perform?</p> <ul style="list-style-type: none"> • NULL = unknown • 0 = Computer (don't know if server or workstation) • 1 = Workstation • 2 = Server • 3 = Printer • 4 = Switch • 5 = Router • 6 = Hub
OperatingSystem	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>Operating system of the node, if it is a computer.</p>
IsManaged	<p><i>Type:</i> integer. Key. Nullable</p> <p>Is the device to be managed by FlexNet Manager Suite? 0 = no, 1 = yes, NULL = unknown.</p>
Description	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>Customer-entered description of the device.</p>
SystemDescription	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>This field is currently unused.</p>
SystemLocation	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>This field is currently unused.</p>
SystemContact	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>This field is currently unused.</p>
FirstDiscovered	<p><i>Type:</i> datetime</p> <p>The date and time that the node was first discovered.</p>
LastUpdate	<p><i>Type:</i> datetime</p> <p>The last time the node was checked or updated.</p>

Database Column	Details
LastDataSourceName	<i>Type:</i> text (max 128 characters). Key. Nullable A name that identifies where the discovery information came from (for example: physical location, server, and so on).
LastDataSourceType	<i>Type:</i> text (max 32 characters). Key. Nullable The type of data source (for example: Excel, Fluke, NM, Text).
OpenPortsTCP	<i>Type:</i> text (max 512 characters). Nullable The comma-delimited list of TCP ports which were found to be open on scan.
OpenPortsUDP	<i>Type:</i> text (max 512 characters). Nullable The comma-delimited list of UDP ports which were found to be open on scan.
ScannedOperatingSystem	<i>Type:</i> text (max 512 characters). Nullable The IP scan tool's best guess at the operating system. This is based on corner cases in the behavior of the network protocol stack.
ScannedOsType	<i>Type:</i> text (max 512 characters). Nullable OS Type, as reported by scan tool.
ScannedOsVendor	<i>Type:</i> text (max 512 characters). Nullable OS Vendor, as reported by scan tool.
ScannedOsFamily	<i>Type:</i> text (max 512 characters). Nullable OS family, as reported by scan tool.
ScannedOsGen	<i>Type:</i> text (max 512 characters). Nullable OS Generation(Versions), as reported by scan tool.
ScannedMacAddress	<i>Type:</i> text (max 64 characters). Nullable MAC Address, as reported by scan tool.
ScannedMacVendor	<i>Type:</i> text (max 512 characters). Nullable MAC Vendor, as reported by scan tool.
SQLDiscoveredBy	<i>Type:</i> text (max 128 characters). Nullable The discovery tool used to discover SQL Server.
SQLPorts	<i>Type:</i> text (max 128 characters). Nullable The ports where SQL Server has been discovered.
IPAddressInt	<i>Type:</i> big integer. Key. Nullable Integer representation of IPAddress column.

DiscoveredDeviceCalculatedMember Table

Stores summary strings of DiscoveredDevice details that are expensive to calculate on demand.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 265: Database columns for DiscoveredDeviceCalculatedMember table

Database Column	Details
DeviceID	Type: integer. Key Device identity number.
IsOracle	Type: boolean. Nullable Have we discovered Oracle on this machine?
OracleListeners	Type: text (max 512 characters). Nullable A summary string representing any known Oracle Listeners, and the port they can be contacted on.
OracleServices	Type: text (max 512 characters). Nullable A summary string representing any known Oracle Services.
IsSQL	Type: boolean. Nullable Have we discovered SQL Server on this machine?
IsVDI	Type: boolean. Nullable Is this machine a virtual desktop?
IsVDIBroker	Type: boolean. Nullable Have we discovered a VDI broker on this machine?

DiscoveredDeviceParent Table

Records any parent child relationships between DiscoveredDevice records.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 266: Database columns for DiscoveredDeviceParent table

Database Column	Details
DeviceID	Type: integer. Key The child DiscoveredDevice ID
ParentDeviceID	Type: integer. Key The parent DiscoveredDevice ID

DiscoveredDeviceSNMPInfo Table

Records any SNMP information discovered for a DiscoveredDevice.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 267: Database columns for DiscoveredDeviceSNMPInfo table

Database Column	Details
DeviceID	Type: integer. Key Device identity number.
SNMP_snmpCommunityString	Type: text (max 256 characters). Nullable The SNMP Community String that was used for obtaining SNMP MIBs. This and all following SNMP attributes are defined in RFC1907 and others available from the IETF websites.
SNMP_sysDescr	Type: text (max 256 characters). Nullable A textual description of the device. This value should include the full name and version identification of the system's hardware type, software operating-system, and networking software.
SNMP_sysObjectID	Type: text (max 256 characters). Nullable The vendor's authoritative identification of the network management subsystem contained in the entity. This value is allocated within the SMI enterprises subtree (1.3.6.1.4.1) and provides an easy and unambiguous means for determining 'what kind of device' is being managed. For example, if vendor 'Flintstones, Inc.' was assigned the subtree 1.3.6.1.4.1.4242, it could assign the identifier 1.3.6.1.4.1.4242.1.1 to its 'Fred Router'.
SNMP_sysObjectIDSymbolic	Type: text (max 256 characters). Nullable The symbolic representation of the same value as sysObjectID.
SNMP_sysUpTime	Type: big integer. Nullable The time (in hundredths of a second) since the network management portion of the system was last re-initialized.
SNMP_sysContact	Type: text (max 256 characters). Nullable The textual identification of the contact person for this managed node, together with information on how to contact this person.
SNMP_sysName	Type: text (max 256 characters). Nullable An administratively-assigned name for this managed node. By convention, this is the node's fully-qualified domain name.

Database Column	Details
SNMP_sysLocation	<i>Type:</i> text (max 256 characters). Nullable The physical location of this node (for example, 'telephone closet, 3rd floor').
SNMP_sysServices	<i>Type:</i> integer. Nullable a bitmask indicating at which of the seven OSI protocol levels the system provides services (physical=1, TCP = 8, applications = 64, etc)
SNMP_ipForwarding	<i>Type:</i> integer. Nullable Set to 1 if the device forwards IP packets, 2 otherwise.

DiscoveredDeviceVDIBrokerInfo Table

Records any VDI information discovered for a DiscoveredDevice.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 268: Database columns for DiscoveredDeviceVDIBrokerInfo table

Database Column	Details
DeviceID	Type: integer. Key Device identity number.
VDISiteName	Type: text (max 256 characters). Key. Nullable The Site to which this VDI Broker belongs.
BrokerType	Type: text (max 256 characters). Key The type of VDI broker found.

DiscoveredDeviceVDIInfo Table

Records any VDI information discovered for a DiscoveredDevice.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 269: Database columns for DiscoveredDeviceVDIInfo table

Database Column	Details
DeviceID	Type: integer. Key Device identity number.
VDIGroupName	Type: text (max 256 characters). Nullable The Desktop Group to which this VDI belongs.
VDITemplateName	Type: text (max 256 characters). Nullable The template from which this VDI device was cloned.
VDISiteName	Type: text (max 256 characters). Key. Nullable The Site to which this VDI belongs.
BrokerType	Type: text (max 256 characters). Key. Nullable The type of broker that serves up this VDI belongs.
BrokerMachineName	Type: text (max 64 characters). Nullable NetBIOS name for the VDI broker.
BrokerDomainName	Type: text (max 256 characters). Nullable NT domain name of the broker.
BrokerIPAddress	Type: text (max 256 characters). Nullable The IP of the broker.
IsPersistent	Type: boolean Whether or not the VDI device is a persistent one.

DiscoveredDeviceVirtualizationInfo Table

Records any virtualization server information discovered for a DiscoveredDevice.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 270: Database columns for DiscoveredDeviceVirtualizationInfo table

Database Column	Details
DeviceID	Type: integer. Key Device identity number.
Protocol	Type: text (max 16 characters). Nullable The protocol by which the virtualization API is accessed on the device.
Port	Type: integer The TCP port used by the protocol.
APIType	Type: text (max 32 characters). Nullable The reported API type.
APIVersion	Type: text (max 16 characters). Nullable The supported version of the API.
ProductNameID	Type: integer The reported product name.
ProductVersion	Type: text (max 16 characters). Nullable The reported product version.

KnownOracleListener Table

Records any discovered Oracle listeners a DiscoveredDevice is providing.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 271: Database columns for KnownOracleListener table

Database Column	Details
KnownOracleListenerID	Type: integer. Key. Generated ID Unique id for the known listener.
DeviceID	Type: integer. Key Device identity number.
Port	Type: integer. Key Port for this listener.
Name	Type: text (max 128 characters) The name of the service provided by the device.
Version	Type: text (max 32 characters) The version of the service provided by the device.
ManuallyAdded	Type: boolean Boolean field specifying whether the KnownService record has been manually added by the user.
DiscoveredRemotely	Type: boolean True means this listener is discovered using remote discovery, false otherwise
DiscoveredLocally	Type: boolean True means this listener is discovered using local discovery, false otherwise
DiscoveredViaTNSNames	Type: boolean True means this listener is discovered from a TNSNames file on a beacon

KnownOracleService Table

Records any discovered Oracle services (databases) on a DiscoveredDevice


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 272: Database columns for KnownOracleService table

Database Column	Details
KnownOracleServiceID	Type: integer. Key. Generated ID Unique id for the known Oracle service.
KnownOracleListenerID	Type: integer. Key. Nullable Listener identity number.
DeviceID	Type: integer. Key Network device identity number.
Name	Type: text (max 128 characters). Key The name of the service provided by the device.
ManuallyAdded	Type: boolean Boolean field specifying whether the KnownService record has been manually added by the user.
DiscoveredRemotely	Type: boolean True means this service is discovered using remote discovery, false otherwise
DiscoveredLocally	Type: boolean True means this service is discovered using local discovery, false otherwise
DiscoveredViaTNSNames	Type: boolean True means this service is discovered from a TNSNames file on a beacon

Site Table

The Site table contains data about network locations (sites)


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 273: Database columns for Site table

Database Column	Details
SiteID	Type: integer. Key. Generated ID The ID for the Site
Name	Type: text (max 256 characters). Key The name of the Site
AutoPopulated	Type: boolean Specifies whether the row was populated automatically(1) or manually(0).
Enabled	Type: boolean Specifies whether the row will be used when mapping domains and devices to Locations

SiteSubnet Table

The Subnet table contains data about subnets in a location.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 274: Database columns for SiteSubnet table

Database Column	Details
SubnetID	Type: integer. Key. Generated ID The ID for the Subnet
IPSubnet	Type: text (max 64 characters). Key The IPSubnet of the Subnet
IPSubnetBits	Type: tiny integer. Key The number of bits in the IPSubnet
SiteID	Type: integer. Key SiteID of the Site in which the Subnet resides
AutoPopulated	Type: boolean Specifies whether the row was populated automatically(1) or manually(0).
Enabled	Type: boolean Specifies whether the row will be used when mapping domains and devices to Locations
IPAddressRangeFrom	Type: big integer. Key Specifies whether the row will be used when mapping domains and devices to Locations
IPAddressRangeTo	Type: big integer. Key Specifies whether the row will be used when mapping domains and devices to Locations

VirtualizationProductName Table

Stores unique virtualization server software names for a DiscoveredDevice.

Table 275: Database columns for VirtualizationProductName table

Database Column	Details
VirtualizationProduct NameID	Type: integer. Key. Generated ID Device identity number.
ProductName	Type: text (max 256 characters). Key The reported product name.

Compliance.Logic.Licensing Tables

The complete set of database tables documented here includes:

- AccessEvidence table (see [AccessEvidence Table](#))
- AccessEvidenceEx table (see [AccessEvidenceEx Table](#))
- AccessEvidenceMatchCount table (see [AccessEvidenceMatchCount Table](#))
- AccessMode table (see [AccessMode Table](#))
- AccessedSoftware table (see [AccessedSoftware Table](#))
- AccessedSoftwareOccurrence table (see [AccessedSoftwareOccurrence Table](#))
- AccessingDevice table (see [AccessingDevice Table](#))
- AccessingDeviceSnapshot table (see [AccessingDeviceSnapshot Table](#))
- AccessingUser table (see [AccessingUser Table](#))
- AccessingUserSnapshot table (see [AccessingUserSnapshot Table](#))
- ClientAccessSourceType table (see [ClientAccessSourceType Table](#))
- ClientAccessedAccessEvidence table (see [ClientAccessedAccessEvidence Table](#))
- ClientAccessedAccessOccurrence table (see [ClientAccessedAccessOccurrence Table](#))
- Cluster table (see [Cluster Table](#))
- ClusterComputer table (see [ClusterComputer Table](#))
- ClusterHostAffinityRule table (see [ClusterHostAffinityRule Table](#))
- ClusterHostAffinityRuleType table (see [ClusterHostAffinityRuleType Table](#))
- ClusterNodeType table (see [ClusterNodeType Table](#))
- ClusterType table (see [ClusterType Table](#))
- ComplianceComputerSnapshot table (see [ComplianceComputerSnapshot Table](#))
- ComplianceComputerTag table (see [ComplianceComputerTag Table](#))
- ComplianceUserSnapshot table (see [ComplianceUserSnapshot Table](#))
- ComplianceUserTag table (see [ComplianceUserTag Table](#))
- DatabaseMutex table (see [DatabaseMutex Table](#))
- EndOfSupportLife table (see [EndOfSupportLife Table](#))
- EndOfSupportLifeName table (see [EndOfSupportLifeName Table](#))
- EntitlementRecommendation table (see [EntitlementRecommendation Table](#))

- EntitlementRecommendationState table (see [EntitlementRecommendationState Table](#))
- EntitlementTransaction table (see [EntitlementTransaction Table](#))
- EntitlementTransactionOtherCandidate table (see [EntitlementTransactionOtherCandidate Table](#))
- EntitlementTransactionState table (see [EntitlementTransactionState Table](#))
- EntitlementTransactionType table (see [EntitlementTransactionType Table](#))
- EvidenceExistenceRule table (see [EvidenceExistenceRule Table](#))
- EvidenceStatus table (see [EvidenceStatus Table](#))
- FNMEAFeature table (see [FNMEAFeature Table](#))
- FNMEALicensedFeature table (see [FNMEALicensedFeature Table](#))
- FileEvidenceCompany table (see [FileEvidenceCompany Table](#))
- FileEvidenceEx table (see [FileEvidenceEx Table](#))
- FileEvidenceFile table (see [FileEvidenceFile Table](#))
- FileEvidenceLanguage table (see [FileEvidenceLanguage Table](#))
- FileEvidenceMatchCount table (see [FileEvidenceMatchCount Table](#))
- FileEvidencePath table (see [FileEvidencePath Table](#))
- GroupSnapshot table (see [GroupSnapshot Table](#))
- ImporterRun table (see [ImporterRun Table](#))
- ImporterStepValidationIssue table (see [ImporterStepValidationIssue Table](#))
- ImporterStepValidationIssueType table (see [ImporterStepValidationIssueType Table](#))
- InstalledFileEvidence table (see [InstalledFileEvidence Table](#))
- InstalledInstallerAttribute table (see [InstalledInstallerAttribute Table](#))
- InstalledInstallerEvidence table (see [InstalledInstallerEvidence Table](#))
- InstalledInstanceReplacement table (see [InstalledInstanceReplacement Table](#))
- InstalledSoftwareData table (see [InstalledSoftwareData Table](#))
- InstalledSoftwareRemoval table (see [InstalledSoftwareRemoval Table](#))
- InstalledSoftwareReplacement table (see [InstalledSoftwareReplacement Table](#))
- InstalledSoftwareUsageData table (see [InstalledSoftwareUsageData Table](#))
- InstalledWMIEvidence table (see [InstalledWMIEvidence Table](#))
- InstallerEvidence table (see [InstallerEvidence Table](#))
- InstallerEvidenceEx table (see [InstallerEvidenceEx Table](#))

- [InstallerEvidenceMatchCount](#) table (see [InstallerEvidenceMatchCount Table](#))
- [InstallerEvidenceType](#) table (see [InstallerEvidenceType Table](#))
- [LicenseBreachReason](#) table (see [LicenseBreachReason Table](#))
- [LicenseDefinitionTitle](#) table (see [LicenseDefinitionTitle Table](#))
- [LicenseDefinitionType](#) table (see [LicenseDefinitionType Table](#))
- [LicenseDefinitionUsageRight](#) table (see [LicenseDefinitionUsageRight Table](#))
- [LicenseMeasurement](#) table (see [LicenseMeasurement Table](#))
- [LicenseSimulation](#) table (see [LicenseSimulation Table](#))
- [LicenseSimulationBreachStatus](#) table (see [LicenseSimulationBreachStatus Table](#))
- [LicenseSimulationChangeType](#) table (see [LicenseSimulationChangeType Table](#))
- [LicenseSimulationHWDDetails](#) table (see [LicenseSimulationHWDDetails Table](#))
- [LicenseSimulationLicenseDetails](#) table (see [LicenseSimulationLicenseDetails Table](#))
- [LicenseSimulationResults](#) table (see [LicenseSimulationResults Table](#))
- [LicenseSimulationRowType](#) table (see [LicenseSimulationRowType Table](#))
- [LicenseSimulationSWDetails](#) table (see [LicenseSimulationSWDetails Table](#))
- [LicenseSimulationScenario](#) table (see [LicenseSimulationScenario Table](#))
- [LicenseStatus](#) table (see [LicenseStatus Table](#))
- [NewFileEvidence](#) table (see [NewFileEvidence Table](#))
- [OracleLegacyLicenseType](#) table (see [OracleLegacyLicenseType Table](#))
- [PODetailProcess](#) table (see [PODetailProcess Table](#))
- [PeriodType](#) table (see [PeriodType Table](#))
- [ProcessAction](#) table (see [ProcessAction Table](#))
- [ProcessState](#) table (see [ProcessState Table](#))
- [ReconcileAccessedSoftwareData](#) table (see [ReconcileAccessedSoftwareData Table](#))
- [ReconcileInstalledSoftwareData](#) table (see [ReconcileInstalledSoftwareData Table](#))
- [ReconcileInstalledSoftwareUsageData](#) table (see [ReconcileInstalledSoftwareUsageData Table](#))
- [ReconcileInterestingBundleAccessComputer](#) table (see [ReconcileInterestingBundleAccessComputer Table](#))
- [ReconcileInterestingBundleInstallComputer](#) table (see [ReconcileInterestingBundleInstallComputer Table](#))
- [ReconcileInterestingLicenses](#) table (see [ReconcileInterestingLicenses Table](#))
- [ReconcileInterestingTitles](#) table (see [ReconcileInterestingTitles Table](#))

- ReconcileSoftwareAccessDeviceLicensePointsConsumedData table (see [ReconcileSoftwareAccessDeviceLicensePointsConsumedData Table](#))
- ReconcileSoftwareAccessUserLicensePointsConsumedData table (see [ReconcileSoftwareAccessUserLicensePointsConsumedData Table](#))
- ReconcileSoftwareLicenseComputerProblem table (see [ReconcileSoftwareLicenseComputerProblem Table](#))
- ReconcileSoftwareLicenseCoresConsumedData table (see [ReconcileSoftwareLicenseCoresConsumedData Table](#))
- ReconcileSoftwareLicenseGroupPointsConsumedData table (see [ReconcileSoftwareLicenseGroupPointsConsumedData Table](#))
- ReconcileSoftwareLicenseILMTPointsConsumedData table (see [ReconcileSoftwareLicenseILMTPointsConsumedData Table](#))
- ReconcileSoftwareLicensePointsConsumedData table (see [ReconcileSoftwareLicensePointsConsumedData Table](#))
- ReconcileSoftwareLicensePointsConsumedReason table (see [ReconcileSoftwareLicensePointsConsumedReason Table](#))
- ReconcileSoftwareLicenseProcessorData table (see [ReconcileSoftwareLicenseProcessorData Table](#))
- ReconcileSoftwareLicenseSecondUseMappingData table (see [ReconcileSoftwareLicenseSecondUseMappingData Table](#))
- ReconcileSoftwareUserLicensePointsConsumedData table (see [ReconcileSoftwareUserLicensePointsConsumedData Table](#))
- ReconcileVirtualMachineLayer table (see [ReconcileVirtualMachineLayer Table](#))
- RegistryEvidence table (see [RegistryEvidence Table](#))
- RegistryEvidenceHive table (see [RegistryEvidenceHive Table](#))
- RegistryEvidenceKey table (see [RegistryEvidenceKey Table](#))
- RegistryEvidenceValue table (see [RegistryEvidenceValue Table](#))
- RelatedInstalledInstallerEvidence table (see [RelatedInstalledInstallerEvidence Table](#))
- RelatedInstalledInstallerEvidenceSourceMap table (see [RelatedInstalledInstallerEvidenceSourceMap Table](#))
- RelatedInstalledSoftwareData table (see [RelatedInstalledSoftwareData Table](#))
- SAPSoftwareLicense table (see [SAPSoftwareLicense Table](#))
- SAPSoftwareLicenseType table (see [SAPSoftwareLicenseType Table](#))
- SAPSpecialVersion table (see [SAPSpecialVersion Table](#))
- ServicePack table (see [ServicePack Table](#))
- ServicePackName table (see [ServicePackName Table](#))

- SoftwareAccessDeviceLicensePointsConsumedData table (see [SoftwareAccessDeviceLicensePointsConsumedData Table](#))
- SoftwareAccessMode table (see [SoftwareAccessMode Table](#))
- SoftwareAccessUserLicensePointsConsumedData table (see [SoftwareAccessUserLicensePointsConsumedData Table](#))
- SoftwareLicense table (see [SoftwareLicense Table](#))
- SoftwareLicenseAllocation table (see [SoftwareLicenseAllocation Table](#))
- SoftwareLicenseAllocationStatus table (see [SoftwareLicenseAllocationStatus Table](#))
- SoftwareLicenseAllocationUserType table (see [SoftwareLicenseAllocationUserType Table](#))
- SoftwareLicenseBreachReasonData table (see [SoftwareLicenseBreachReasonData Table](#))
- SoftwareLicenseChangeEvent table (see [SoftwareLicenseChangeEvent Table](#))
- SoftwareLicenseChangeEventReason table (see [SoftwareLicenseChangeEventReason Table](#))
- SoftwareLicenseChangeEventSource table (see [SoftwareLicenseChangeEventSource Table](#))
- SoftwareLicenseComplianceStatus table (see [SoftwareLicenseComplianceStatus Table](#))
- SoftwareLicenseComputerProblemData table (see [SoftwareLicenseComputerProblemData Table](#))
- SoftwareLicenseComputerProblemType table (see [SoftwareLicenseComputerProblemType Table](#))
- SoftwareLicenseConnection table (see [SoftwareLicenseConnection Table](#))
- SoftwareLicenseContract table (see [SoftwareLicenseContract Table](#))
- SoftwareLicenseCoresConsumedData table (see [SoftwareLicenseCoresConsumedData Table](#))
- SoftwareLicenseCreation table (see [SoftwareLicenseCreation Table](#))
- SoftwareLicenseDefinition table (see [SoftwareLicenseDefinition Table](#))
- SoftwareLicenseDuration table (see [SoftwareLicenseDuration Table](#))
- SoftwareLicenseExemptionReason table (see [SoftwareLicenseExemptionReason Table](#))
- SoftwareLicenseExemptionRole table (see [SoftwareLicenseExemptionRole Table](#))
- SoftwareLicenseGroupAllocationReportingType table (see [SoftwareLicenseGroupAllocationReportingType Table](#))
- SoftwareLicenseGroupAssignmentHistory table (see [SoftwareLicenseGroupAssignmentHistory Table](#))
- SoftwareLicenseGroupAssignmentHistoryType table (see [SoftwareLicenseGroupAssignmentHistoryType Table](#))
- SoftwareLicenseGroupBreachStatus table (see [SoftwareLicenseGroupBreachStatus Table](#))
- SoftwareLicenseGroupPointsConsumedData table (see [SoftwareLicenseGroupPointsConsumedData Table](#))
- SoftwareLicenseILMTPointsConsumedData table (see [SoftwareLicenseILMTPointsConsumedData Table](#))

- SoftwareLicenseKey table (see [SoftwareLicenseKey Table](#))
- SoftwareLicenseKeyType table (see [SoftwareLicenseKeyType Table](#))
- SoftwareLicenseMetric table (see [SoftwareLicenseMetric Table](#))
- SoftwareLicensePartitioningDefault table (see [SoftwareLicensePartitioningDefault Table](#))
- SoftwareLicensePoints table (see [SoftwareLicensePoints Table](#))
- SoftwareLicensePointsConsumedData table (see [SoftwareLicensePointsConsumedData Table](#))
- SoftwareLicensePointsConsumedReasonData table (see [SoftwareLicensePointsConsumedReasonData Table](#))
- SoftwareLicensePointsConsumedReasonType table (see [SoftwareLicensePointsConsumedReasonType Table](#))
- SoftwareLicensePointsDefault table (see [SoftwareLicensePointsDefault Table](#))
- SoftwareLicensePointsRule table (see [SoftwareLicensePointsRule Table](#))
- SoftwareLicensePointsRuleSet table (see [SoftwareLicensePointsRuleSet Table](#))
- SoftwareLicenseProcessorPointsData table (see [SoftwareLicenseProcessorPointsData Table](#))
- SoftwareLicenseProduct table (see [SoftwareLicenseProduct Table](#))
- SoftwareLicensePropertyValue table (see [SoftwareLicensePropertyValue Table](#))
- SoftwareLicenseProposalStatus table (see [SoftwareLicenseProposalStatus Table](#))
- SoftwareLicensePurchaseType table (see [SoftwareLicensePurchaseType Table](#))
- SoftwareLicenseReservation table (see [SoftwareLicenseReservation Table](#))
- SoftwareLicenseReservationNecessityCheckResult table (see [SoftwareLicenseReservationNecessityCheckResult Table](#))
- SoftwareLicenseReservationStatus table (see [SoftwareLicenseReservationStatus Table](#))
- SoftwareLicenseReservationType table (see [SoftwareLicenseReservationType Table](#))
- SoftwareLicenseScopeTag table (see [SoftwareLicenseScopeTag Table](#))
- SoftwareLicenseScopeTagType table (see [SoftwareLicenseScopeTagType Table](#))
- SoftwareLicenseScoping table (see [SoftwareLicenseScoping Table](#))
- SoftwareLicenseSecondUseMappingData table (see [SoftwareLicenseSecondUseMappingData Table](#))
- SoftwareLicenseSnapshot table (see [SoftwareLicenseSnapshot Table](#))
- SoftwareLicenseTierType table (see [SoftwareLicenseTierType Table](#))
- SoftwareLicenseType table (see [SoftwareLicenseType Table](#))
- SoftwareLicenseTypeChangeProposal table (see [SoftwareLicenseTypeChangeProposal Table](#))
- SoftwareLicenseTypePriority table (see [SoftwareLicenseTypePriority Table](#))
- SoftwareLicenseTypeProperty table (see [SoftwareLicenseTypeProperty Table](#))

- SoftwareLicenseUseRight table (see [SoftwareLicenseUseRight Table](#))
- SoftwareLicenseUseRightIBM table (see [SoftwareLicenseUseRightIBM Table](#))
- SoftwareLicenseUseRightName table (see [SoftwareLicenseUseRightName Table](#))
- SoftwareLicenseUseRightProposal table (see [SoftwareLicenseUseRightProposal Table](#))
- SoftwareLifeCycle table (see [SoftwareLifeCycle Table](#))
- SoftwareRecognition table (see [SoftwareRecognition Table](#))
- SoftwareSKULookup table (see [SoftwareSKULookup Table](#))
- SoftwareSku table (see [SoftwareSku Table](#))
- SoftwareTitle table (see [SoftwareTitle Table](#))
- SoftwareTitleAccessEvidence table (see [SoftwareTitleAccessEvidence Table](#))
- SoftwareTitleAction table (see [SoftwareTitleAction Table](#))
- SoftwareTitleClassification table (see [SoftwareTitleClassification Table](#))
- SoftwareTitleEdition table (see [SoftwareTitleEdition Table](#))
- SoftwareTitleEx table (see [SoftwareTitleEx Table](#))
- SoftwareTitleFileEvidence table (see [SoftwareTitleFileEvidence Table](#))
- SoftwareTitleHierarchy table (see [SoftwareTitleHierarchy Table](#))
- SoftwareTitleHierarchyEx table (see [SoftwareTitleHierarchyEx Table](#))
- SoftwareTitleInstallerEvidence table (see [SoftwareTitleInstallerEvidence Table](#))
- SoftwareTitleLicense table (see [SoftwareTitleLicense Table](#))
- SoftwareTitleLicenseProposal table (see [SoftwareTitleLicenseProposal Table](#))
- SoftwareTitleLicenseProposalAction table (see [SoftwareTitleLicenseProposalAction Table](#))
- SoftwareTitleLicenseReason table (see [SoftwareTitleLicenseReason Table](#))
- SoftwareTitleOracle table (see [SoftwareTitleOracle Table](#))
- SoftwareTitleProduct table (see [SoftwareTitleProduct Table](#))
- SoftwareTitleProperty table (see [SoftwareTitleProperty Table](#))
- SoftwareTitlePropertyValue table (see [SoftwareTitlePropertyValue Table](#))
- SoftwareTitlePublisher table (see [SoftwareTitlePublisher Table](#))
- SoftwareTitleRegistryEvidence table (see [SoftwareTitleRegistryEvidence Table](#))
- SoftwareTitleSuite table (see [SoftwareTitleSuite Table](#))
- SoftwareTitleSuiteEx table (see [SoftwareTitleSuiteEx Table](#))

- SoftwareTitleType table (see [SoftwareTitleType Table](#))
- SoftwareTitleVersion table (see [SoftwareTitleVersion Table](#))
- SoftwareTitleVersionServicePack table (see [SoftwareTitleVersionServicePack Table](#))
- SoftwareTitleWMIEvidence table (see [SoftwareTitleWMIEvidence Table](#))
- SoftwareUserLicensePointsConsumedData table (see [SoftwareUserLicensePointsConsumedData Table](#))
- SoftwareUserLicensePointsConsumedSuggested table (see [SoftwareUserLicensePointsConsumedSuggested Table](#))
- SoftwareUserLicensePointsConsumedSuggestedHistory table (see [SoftwareUserLicensePointsConsumedSuggestedHistory Table](#))
- SoftwareUserLicensePointsHistory table (see [SoftwareUserLicensePointsHistory Table](#))
- Tag table (see [Tag Table](#))
- TargetOperatingSystemType table (see [TargetOperatingSystemType Table](#))
- VDI table (see [VDI Table](#))
- VDIEndPointAccess table (see [VDIEndPointAccess Table](#))
- VDIGroup table (see [VDIGroup Table](#))
- VDISite table (see [VDISite Table](#))
- VDI Template table (see [VDITemplate Table](#))
- VDIUser table (see [VDIUser Table](#))
- WMIEvidence table (see [WMIEvidence Table](#))
- WMIEvidenceMatchCount table (see [WMIEvidenceMatchCount Table](#))

AccessEvidence Table

AccessEvidence lists software access evidence that is used to identify that a particular item of software (defined in the SoftwareTitle table) has been accessed on a computer.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 276: Database columns for AccessEvidence table

Database Column	Details
AccessEvidenceID	Type: integer. Key. Generated ID A unique identifier for an software access evidence record.
DisplayName	Type: text (max 256 characters). Key The display name of the software as reported by the software access evidence.
Version	Type: text (max 72 characters). Key The version of the software as reported by the software access evidence.
Edition	Type: text (max 50 characters). Key The edition of the software as reported by the software access evidence.
Publisher	Type: text (max 200 characters). Key The publisher of the software as reported by the installer evidence.
OperatorManageStateID	Type: integer. Key The management responsibility for this information. Foreign key to the OperatorManageState table.
Ignored	Type: boolean Set this field to True if the access evidence is not used for application recognition.
IsShared	Type: boolean

AccessEvidenceEx Table

The AccessEvidenceEx table contains additional information on the access evidence managed by FlexNet Manager Suite.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 277: Database columns for AccessEvidenceEx table

Database Column	Details
AccessEvidenceID	Type: integer. Key A unique identifier for an access evidence record.
OperatorManageStateID	Type: integer. Nullable The management responsibility for this information. Foreign key to the OperatorManageState table.
Ignored	Type: boolean. Nullable Set this field to True if the access evidence is not used for application recognition.

AccessEvidenceMatchCount Table

AccessEvidenceMatchCount tracks the number of times that each access evidence (rule) has been detected as installed and recorded in the data source. A separate count is kept for each access evidence rule, and for each data source.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 278: Database columns for AccessEvidenceMatchCount table

Database Column	Details
AccessEvidenceMatchCountID	<i>Type:</i> integer. Key. Generated ID A synthetic unique identifier is required, since ComplianceConnectionID, being nullable, cannot be included in the primary key.
AccessEvidenceID	<i>Type:</i> integer. Key The access evidence which is being matched. Foreign key to the AccessEvidence table.
ComplianceConnectionID	<i>Type:</i> integer. Key. Nullable The data source where the match is occurring. Foreign key to the ComplianceConnection table.
MatchedCount	<i>Type:</i> integer The number of installed access evidence records in this data source matching this access evidence rule.
InstallCount	<i>Type:</i> integer The number of physical application installations recognized in this data source using this access evidence rule.

AccessMode Table

The AccessMode table holds the available states an application can be considered accessed.

Table 279: Database columns for AccessMode table

Database Column	Details
AccessModeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each AccessMode. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = Local• 2 = App-V• 3 = XenApp• 4 = XenDesktop• 5 = VMware View• 6 = Office 365
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing an access mode. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the access mode resource string has no translation.</p>

AccessedSoftware Table

AccessedSoftware lists all the access records of an application from a device.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 280: Database columns for AccessedSoftware table

Database Column	Details
AccessedSoftwareID	Type: big integer. Key. Generated ID A unique identifier for an accessed software record.
AccessingUserID	Type: integer. Key. Nullable An identifier for a accessing user record. Foreign key to the AccessingUser table.
AccessingDeviceID	Type: integer. Key. Nullable An identifier for a accessing device record. Foreign key to the AccessingDevice table.
SoftwareTitleID	Type: integer. Key The software that is being accessed. Foreign key to the SoftwareTitle table.
SoftwareLicenseID	Type: integer. Key. Nullable The link to the license this access has been counted against. Foreign key to the SoftwareLicense table.
SoftwareLicenseAllocationID	Type: integer. Key. Nullable The link to the license allocation this access has consumed. Foreign key to the SoftwareLicenseAllocation table.
ConsumedCount	Type: integer. Nullable The number of this installation consumed on the license.
IsLicensed	Type: boolean Set this field to True when this access is licensed.
LastAccessDate	Type: datetime. Nullable Last access date recorded for this software access.
LastInventoryDate	Type: datetime. Nullable Last time access inventory was collected for this software access.

Database Column	Details
PointsCalculated	Type: integer The number of calculated points this installation consumes.

AccessedSoftwareOccurrence Table

AccessedSoftwareOccurrence lists access Occurrences for accessed software.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 281: Database columns for AccessedSoftwareOccurrence table

Database Column	Details
AccessedSoftwareID	Type: big integer. Key An identifier for an accessed software. Foreign key to the AccessedSoftware
ServerComputerID	Type: integer. Key An identifier for a server record. Foreign key to the ComplianceComputer table.
AccessDate	Type: datetime. Nullable Date on which access has occurred.
LicenseDate	Type: datetime. Key Date which will be used for licensing purpose.
InventoryDate	Type: datetime. Key Date on which inventory occurrence was recorded.
AccessCount	Type: integer Number of accessed occurred on this date.

AccessingDevice Table

AccessingDevice stores information about devices which are accessing a software on the server.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 282: Database columns for AccessingDevice table

Database Column	Details
AccessingDeviceID	Type: integer. Key. Generated ID A unique identifier for a AccessingDevice
ComplianceComputerID	Type: integer. Key. Nullable An identifier for a compliance computer record. Foreign key to the ComplianceComputer table.
IPAddress	Type: text (max 256 characters). Key. Nullable IP address of the of the device.
ComputerName	Type: text (max 256 characters). Key. Nullable Computer name.
SerialNo	Type: text (max 100 characters). Nullable The serial number of the computer.
Domain	Type: text (max 100 characters). Nullable The domain name of the computer.

AccessingDeviceSnapshot Table

The AccessingDeviceSnapshot table lists all the snapshotted accessing devices.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 283: Database columns for AccessingDeviceSnapshot table

Database Column	Details
AccessingDeviceID	Type: integer. Key A unique identifier for a AccessingDevice.
ComplianceComputerID	Type: integer. Nullable An identifier for a compliance computer record. Foreign key to the ComplianceComputerSnapshot table.
IPAddress	Type: text (max 256 characters). Nullable IP address of the of the device.
ComputerName	Type: text (max 256 characters). Nullable Computer name.
LicenseMeasurementID	Type: integer. Key The snapshot ID. Foreign key to the LicenseMeasurement table.

AccessingUser Table

AccessingUser stores information about users which are accessing a software on the server.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 284: Database columns for AccessingUser table

Database Column	Details
AccessingUserID	Type: integer. Key. Generated ID A unique identifier for a AccessingUser
ComplianceUserID	Type: integer. Key. Nullable An identifier for a compliance user record. Foreign key to the ComplianceUser table.
UserName	Type: text (max 256 characters). Key Username of the end user.
DomainName	Type: text (max 100 characters). Key. Nullable Domain name of the end user.

AccessingUserSnapshot Table

The AccessingUserSnapshot table lists all the snapshotted accessing users.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 285: Database columns for AccessingUserSnapshot table

Database Column	Details
AccessingUserID	Type: integer. Key A unique identifier for a AccessingUser.
ComplianceUserID	Type: integer. Nullable An identifier for a compliance user record. Foreign key to the ComplianceUserSnapshot table.
UserName	Type: text (max 256 characters) Username of the end user.
DomainName	Type: text (max 100 characters). Nullable Domain name of the end user.
LicenseMeasurementID	Type: integer. Key The snapshot ID. Foreign key to the LicenseMeasurement table.

ClientAccessSourceType Table

ClientAccessSourceType is a static table listing the types of client access source type that can be used to determine whether the evidence is collection from which source.

Table 286: Database columns for ClientAccessSourceType table

Database Column	Details
ClientAccessSourceTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each ClientAccessSourceType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = Unknown • 2 = UAL • 3 = Exchange • 4 = Lync • 5 = SCCM • 6 = Manual • 7 = SharePoint
TypeResourceString	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a client access source type. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the type resource string has no translation.</p>
ImporterString	<p><i>Type:</i> text (max 100 characters). Key</p> <p>The text value provided by adapters when importing client access source type.</p>

ClientAccessedAccessEvidence Table

ClientAccessedAccessEvidence lists access evidences from user and device that occurred on a server computer.

 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 287: Database columns for ClientAccessedAccessEvidence table

Database Column	Details
ClientAccessedAccessEvidenceID	Type: big integer. Key. Generated ID A unique identifier for a ClientAccessedAccessEvidence
AccessEvidenceID	Type: integer. Key An identifier for an access evidence record. Foreign key to the AccessEvidence table.
AccessingUserID	Type: integer. Key. Nullable An identifier for a accessing user record. Foreign key to the AccessingUser table.
AccessingDeviceID	Type: integer. Key. Nullable An identifier for a accessing device record. Foreign key to the AccessingDevice table.
ServerComputerID	Type: integer. Key An identifier for a server record. Foreign key to the ComplianceComputer table.
MaxAccessCount	Type: integer. Nullable Maximum access count recorded for this evidence.
LastAccessCount	Type: integer. Nullable Last access count recorded for this evidence.
LastAccessDate	Type: datetime. Nullable Last access date recorded for this evidence.
LastInventoryDate	Type: datetime. Nullable Last time access inventory was collected for this evidence.
ClientAccessSourceTypeID	Type: integer. Key Referencing to the client access source type.

ClientAccessedAccessOccurrence Table

ClientAccessedAccessOccurrence lists access Occurrences for accessed access evidence.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 288: Database columns for ClientAccessedAccessOccurrence table

Database Column	Details
ClientAccessedAccessEvidenceID	Type: big integer. Key An identifier for an accessed access evidence. Foreign key to the ClientAccessedAccessEvidence
AccessDate	Type: datetime. Nullable Date on which access has occurred.
InventoryDate	Type: datetime. Key Date on which inventory occurrence was recorded.
LicenseDate	Type: datetime. Key Date which will be used for licensing purpose.
AccessCount	Type: integer Number of accessed occurred on this date.

Cluster Table

The Cluster table stores information about a logical group of computers which form a cluster.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 289: Database columns for Cluster table

Database Column	Details
ClusterID	Type: integer. Key. Generated ID A unique identifier for the cluster.
ParentClusterID	Type: integer. Key. Nullable An optional link back to a parent cluster.
ExternalName	Type: text (max 256 characters). Nullable The identifier of the cluster in the external cluster management system.
Name	Type: text (max 256 characters). Key The user-visible name of the cluster.
Namespace	Type: text (max 256 characters). Key. Nullable The name of the domain or datacenter containing the cluster.
ClusterTypeID	Type: integer. Key Foreign key to the ClusterType table.
ComplianceComputer InventorySourceTypeID	Type: integer Whether this cluster has ever been reported in inventory, or has been manually created and maintained. Foreign key to the ComplianceComputerInventorySourceType table.
InventoryDate	Type: datetime. Nullable The date the computer last had inventory reported.
UpdatedUser	Type: text (max 128 characters). Nullable The name of the operator who last updated the computer details.
UpdatedDate	Type: datetime. Nullable The date the record was last updated.
CreationUser	Type: text (max 128 characters). Nullable The operator who created the record.

Database Column	Details
CreationDate	<i>Type:</i> datetime The date the cluster was created.
InventoryAgent	<i>Type:</i> text (max 64 characters). Nullable The name of the person or tool that performed the last inventory.
DRS	<i>Type:</i> boolean. Nullable Whether Distributed Resource Scheduler (DRS) is enabled
DPM	<i>Type:</i> boolean. Nullable Whether Distributed Power Management (DPM) is enabled

ClusterComputer Table

The ClusterComputer table stores information about the relationship of computers to a cluster.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 290: Database columns for ClusterComputer table

Database Column	Details
ClusterComputerID	Type: integer. Key. Generated ID A unique identifier for the cluster computer.
ClusterID	Type: integer. Key Foreign key to the Cluster table.
ComplianceComputerID	Type: integer. Key Foreign key to the ComplianceComputer table.
ClusterNodeTypeID	Type: integer Foreign key to the ClusterNodeType table.
ComplianceComputerInventorySourceTypeID	Type: integer Whether this cluster computer relationship has ever been reported in inventory, or has been manually created and maintained. Foreign key to the ComplianceComputerInventorySourceType table.

ClusterHostAffinityRule Table

The ClusterHostAffinityRule table stores rules that define whether there is affinity between different VM groups and host groups within a cluster.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 291: Database columns for ClusterHostAffinityRule table

Database Column	Details
ClusterHostAffinityRuleID	Type: integer. Key. Generated ID A unique identifier for each ClusterHostAffinityRule.
ClusterHostAffinityRuleTypeID	Type: integer A unique identifier indicating a type of Cluster Host Affinity Rule.
Name	Type: text (max 256 characters). Key The name assigned to an affinity rule.
HostGroupClusterID	Type: integer The unique identifier of the host group to which the affinity rule applies. Foreign key to the Cluster table.
VMGroupClusterID	Type: integer The unique identifier of the VM group to which the affinity rule applies. Foreign key to the Cluster table.
ClusterID	Type: integer. Key Foreign key to the Cluster table.
ComplianceComputerInventorySourceTypeID	Type: integer Whether this cluster host affinity rule has ever been reported in inventory, or has been manually created and maintained. Foreign key to the ComplianceComputerInventorySourceType table.

ClusterHostAffinityRuleType Table

ClusterHostAffinityRuleType is a static table listing all of the types of cluster host affinity rules.

Table 292: Database columns for ClusterHostAffinityRuleType table

Database Column	Details
ClusterHostAffinityRuleTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each ClusterHostAffinityRuleType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = must run on (VMs in the LHS group MUST run on hosts specified in the RHS group)• 2 = must not run on (VMs in the LHS group MUST NOT run on any of the hosts specified in the RHS group)
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing the type of a cluster host affinity rule. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the type resource string has no translation.</p>

ClusterNodeType Table

ClusterNodeType is a static table listing all of the roles a computer can have in a cluster.

Table 293: Database columns for ClusterNodeType table

Database Column	Details
ClusterNodeTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each ClusterNodeType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = Active (a node that is powered on and in use.)• 2 = Passive (a node that is powered on but not in use unless an active node fails over to it)• 3 = Hot (an active node–IBM nomenclature)• 4 = Warm (a passive node–IBM nomenclature)• 5 = Cold (a node that is powered off–IBM nomenclature)
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a cluster node type. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the type resource string has no translation.</p>

ClusterType Table

ClusterType is a static table listing all of the types of a cluster.

Table 294: Database columns for ClusterType table

Database Column	Details
ClusterTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each ClusterType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = vMotion (a mobility cluster based on VMWare ESX technology) • 2 = Hyper-V (a mobility cluster based on Microsoft's Hyper-V virtualization technology) • 5 = Oracle VM (a cluster based on Oracle VM virtualization technology)
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a cluster type. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the type resource string has no translation.</p>
XMLFile	<p><i>Type:</i> text. Nullable</p> <p>The layout of the property dialog for this type of cluster, stored in XML format.</p>

ComplianceComputerSnapshot Table

The ComplianceComputerSnapshot table lists all the snapshotted computers.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 295: Database columns for ComplianceComputerSnapshot table

Database Column	Details
ComplianceComputerID	<i>Type:</i> integer. Key The snapshotted ComplianceComputerID.
ComputerName	<i>Type:</i> text (max 256 characters). Nullable The snapshotted computer name.
Domain	<i>Type:</i> text (max 256 characters). Nullable The snapshotted computer domain name.
LocationID	<i>Type:</i> text (max 128 characters). Key. Nullable The snapshotted LocationID.
BusinessUnitID	<i>Type:</i> text (max 128 characters). Key. Nullable The snapshotted BusinessUnitID.
CostCenterID	<i>Type:</i> text (max 128 characters). Key. Nullable The snapshotted CostCenterID.
CategoryID	<i>Type:</i> text (max 128 characters). Key. Nullable The snapshotted CategoryID.
LicenseMeasurementID	<i>Type:</i> integer. Key The snapshot ID. Foreign key to the LicenseMeasurement table.

ComplianceComputerTag Table

Reserved for future development.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 296: Database columns for ComplianceComputerTag table

Database Column	Details
ComplianceComputerID	Type: integer. Key Foreign key to the ComplianceComputer table
TagID	Type: integer. Key Foreign key to the Tag table.

ComplianceUserSnapshot Table

The ComplianceUserSnapshot table lists all the users for each snapshot.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 297: Database columns for ComplianceUserSnapshot table

Database Column	Details
ComplianceUserID	Type: integer. Key The snapshotted ComplianceUserID.
UserName	Type: text (max 256 characters). Nullable The snapshotted user name.
Domain	Type: text (max 256 characters). Nullable The snapshotted user domain name.
LocationID	Type: text (max 128 characters). Key. Nullable The snapshotted LocationID.
BusinessUnitID	Type: text (max 128 characters). Key. Nullable The snapshotted BusinessUnitID.
CostCenterID	Type: text (max 128 characters). Key. Nullable The snapshotted CostCenterID.
CategoryID	Type: text (max 128 characters). Key. Nullable The snapshotted CategoryID.
LicenseMeasurementID	Type: integer. Key The snapshot ID. Foreign key to the LicenseMeasurement table.

ComplianceUserTag Table

Reserved for future use.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 298: Database columns for ComplianceUserTag table

Database Column	Details
ComplianceUserID	Type: integer. Key Foreign key to the ComplianceUser table.
TagID	Type: integer. Key Foreign key to the Tag table.

DatabaseMutex Table

The DatabaseMutex table lists all current database mutexes.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 299: Database columns for DatabaseMutex table

Database Column	Details
DatabaseMutexID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the database mutex.
Name	<i>Type:</i> text (max 256 characters). Key The name of the mutex.

EndOfSupportLife Table

Table 300: Database columns for EndOfSupportLife table

Database Column	Details
EndOfSupportLifeID	<i>Type:</i> integer. Key. Generated ID A unique identifier.
SoftwareLifeCycleID	<i>Type:</i> integer. Key The software life cycle this EOSL belongs to. Foreign key to the SoftwareLifeCycle table.
EndOfSupportLifeNameID	<i>Type:</i> integer. Key The name of the EOSL. Foreign key to the EndOfSupportLifeName table.
EndDate	<i>Type:</i> datetime. Nullable The support end date.
Notes	<i>Type:</i> text. Nullable Notes for this end of support life

EndOfSupportLifeName Table

Table 301: Database columns for EndOfSupportLifeName table

Database Column	Details
EndOfSupportLifeNameID	<i>Type:</i> integer. Key. Generated ID A unique identifier for EOSL name.
Name	<i>Type:</i> text (max 256 characters). Key The EOSL's name

EntitlementRecommendation Table

EntitlementRecommendation is a table listing all of the recommendations that have been made to link entitlements to licenses.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 302: Database columns for EntitlementRecommendation table

Database Column	Details
EntitlementRecommendationID	<i>Type:</i> integer. Key. Generated ID A unique identifier for this recommendation.
SoftwareLicenseID	<i>Type:</i> integer. Key. Nullable The license affected by this recommendation, null if a new license is being created. Foreign key to the SoftwareLicense table.
SoftwareLicenseDefinitionID	<i>Type:</i> integer. Key. Nullable The license definition of the new license being created. Foreign key to the SoftwareLicenseDefinition table.
SoftwareLicenseDefinition	<i>Type:</i> text. Nullable Encrypted XML definition of the customised license being created if any.
MaintenanceDefinition	<i>Type:</i> text. Nullable Encrypted XML definition of the maintenance being applied to the license associated with this recommendation.
ContractID	<i>Type:</i> integer. Key. Nullable The contract affected by this recommendation, if any. Foreign key to the Contract table.
MaintenanceContractID	<i>Type:</i> integer. Nullable The contract providing maintenance for this recommendation, if any. Foreign key to the Contract table.
ProcessActionID	<i>Type:</i> integer. Key. Nullable The action that is recommended by this recommendation. Foreign key to the ProcessAction table.
EntitlementRecommendationStateID	<i>Type:</i> integer. Nullable The state that the recommendation is in. Foreign key to the EntitlementRecommendationState table.

Database Column	Details
CreationUser	<i>Type:</i> text (max 128 characters). Nullable The operator who created the record.
CreationDate	<i>Type:</i> datetime The date the record was created.
UpdatedUser	<i>Type:</i> text (max 128 characters). Nullable The operator who last updated the record.
UpdatedDate	<i>Type:</i> datetime. Nullable The date the record was last updated.
DoTransferSoftware LicenseAllocations	<i>Type:</i> boolean. Nullable Indicates whether to transfer Group Assignments and Allocations when performing an upgrade and all the entitlements are transferred to the new license.

EntitlementRecommendationState Table

EntitlementRecommendationState is a static table listing all of the states a entitlement recommendation or transaction can be in.

Table 303: Database columns for EntitlementRecommendationState table

Database Column	Details
EntitlementRecommendationStateID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each EntitlementRecommendationState. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = Automatically recommended • 2 = Manually created • 3 = Edited by an operator • 4 = Accepted by an operator or automatically • 5 = Rolled back by an operator • 6 = Deferred by an operator • 7 = Failed to be accepted.
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing the entitlement recommendation's state. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 256 characters)</p> <p>The text to display if the state resource string has no translation.</p>

EntitlementTransaction Table

EntitlementTransaction is a table listing all of the recommendations that have been made to link entitlements to licenses.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 304: Database columns for EntitlementTransaction table

Database Column	Details
EntitlementTransactionID	<i>Type:</i> integer. Key. Generated ID A unique identifier for this transaction.
Entitlement RecommendationID	<i>Type:</i> integer. Key. Nullable The recommendation this transaction is related to if any. Foreign key to the EntitlementRecommendation table.
SoftwareLicenseID	<i>Type:</i> integer. Key. Nullable The license affected by this recommendation. If a new license is being created from a recommendation but the recommendation is pending, the value of this field is null. The license identified depends on the EntitlementTransactionType. For a recommendation, this could be the license being updated (the “from” license) or it could be the new license (the “to” license). Foreign key to the SoftwareLicense table.
PurchaseOrderDetailID	<i>Type:</i> integer. Key. Nullable The purchase order line associated with this transaction. Foreign key to the PurchaseOrderDetail table.
Adjustment	<i>Type:</i> integer. Nullable The (potentially partial) amount of the purchased license quantity that is being applied to the license.
OtherCandidates	<i>Type:</i> boolean. Nullable Whether there were other licenses which could have been recommended.
EntitlementTransaction TypeID	<i>Type:</i> integer. Nullable The type of the transaction. Foreign key to the EntitlementTransactionType table.
Entitlement RecommendationStateID	<i>Type:</i> integer. Key. Nullable The state that the transaction is in. Foreign key to the EntitlementRecommendationState table.

Database Column	Details
IsDeferred	<i>Type:</i> boolean Flags the entitlement transaction whether it is deferred for later processing.
TransactionUser	<i>Type:</i> text (max 128 characters). Nullable The operator who last updated the record.
TransactionDate	<i>Type:</i> datetime. Nullable The date the record was last updated.
PreviousMaintenance Definition	<i>Type:</i> text. Nullable Encrypted XML definition of the maintenance previously applied to the license associated with this transaction.
PreviousMaintenance ContractID	<i>Type:</i> integer. Nullable The ID of the contract previously giving maintenance to the license associated with this transaction. Foreign key to the Contract table.
LicenseNameMatched	<i>Type:</i> boolean Indicates whether or not there was a license name match.
PrimaryApplicationMatched	<i>Type:</i> boolean Indicates whether or not there was a primary application match.
AnyApplicationMatched	<i>Type:</i> boolean Indicates whether or not there was a match on any application.
MaintenanceSettings Matched	<i>Type:</i> boolean Indicates whether or not there was a match based on maintenance settings.
EnterpriseGroupMatched	<i>Type:</i> boolean Indicates whether or not there was a match based on enterprise groups.
NumberOfVersionsDifferent	<i>Type:</i> integer Indicated the number of versions between the version being upgraded to from the version being upgraded from.
EntitlementTransaction StateID	<i>Type:</i> integer The state of the transaction. Foreign key to the EntitlementTransactionState table.
AdjustmentDefault	<i>Type:</i> integer. Nullable The default amount of the purchased license quantity that is being applied to the license.

Database Column	Details
AllowMaintenanceGap	<p><i>Type:</i> boolean</p> <p>Will determine if the end users will be alerted about a gap in maintenance for this purchase. If this is set to 0, then an alert will be generated if a gap is detected. if it is set to 1, then no alert will be generated.</p>

EntitlementTransactionOtherCandidate Table

EntitlementTransactionOtherCandidate is a table listing all of the other possible license recommendations that have been made to for entitlements.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 305: Database columns for EntitlementTransactionOtherCandidate table

Database Column	Details
EntitlementTransactionOtherCandidateID	<i>Type:</i> integer. Key. Generated ID A unique identifier for this possible candidate.
EntitlementTransactionID	<i>Type:</i> integer. Key The entitlement the recommendation belongs to.
SoftwareLicenseID	<i>Type:</i> integer. Key The license affected by this recommendation.
UpgradeFrom	<i>Type:</i> boolean Indicates whether this license was a candidate to upgrade from or not.
LicenseNameMatched	<i>Type:</i> boolean Indicates whether or not there was a license name match.
PrimaryApplicationMatched	<i>Type:</i> boolean Indicates whether or not there was a primary application match.
AnyApplicationMatched	<i>Type:</i> boolean Indicates whether or not there was a match on any application.
MaintenanceSettingsMatched	<i>Type:</i> boolean Indicates whether or not there was a match based on maintenance settings.
EnterpriseGroupMatched	<i>Type:</i> boolean Indicates whether or not there was a match based on enterprise groups.
NumberOfVersionsDifferent	<i>Type:</i> integer Indicated the number of versions between the version being upgraded to from the version being upgraded from.

EntitlementTransactionState Table

EntitlementTransactionState is a static table listing all of the states that can be associated with purchased entitlements.

Table 306: Database columns for EntitlementTransactionState table

Database Column	Details
EntitlementTransactionStateID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each EntitlementTransactionState. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = Enabled• 2 = Disabled• 3 = Always enabled• 4 = Not contributing.
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing the enabled state of the transaction. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 256 characters)</p> <p>The text to display if the type resource string has no translation.</p>

EntitlementTransactionType Table

EntitlementTransactionType is a static table listing all of the types of transactions that can be performed associating purchased entitlements to a license.

Table 307: Database columns for EntitlementTransactionType table

Database Column	Details
EntitlementTransactionTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each EntitlementTransactionType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = Purchased entitlements added to license • 2 = Purchased entitlements removed from license • 3 = Purchased entitlements taken from this license for upgrade purposes • 4 = Entitlements adjusted manually on the license by an operator • 5 = Maintenance entitlements adjusted on the license. • 6 = Maintenance entitlements adjusted manually on the license. • 7 = Upgrade entitlements adjusted manually on the license.
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing the type of transaction. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 256 characters)</p> <p>The text to display if the type resource string has no translation.</p>

EvidenceExistenceRule Table

EvidenceExistenceRule is a static table listing the rules to be applied to file evidence and its relationship to a software (application) title.

Table 308: Database columns for EvidenceExistenceRule table

Database Column	Details
EvidenceExistenceRuleID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>Unique identifier for each EvidenceExistenceRule. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = Required (the file evidence must be present for the title to be considered installed)• 2 = Not for recognition (not used for recognizing application installations - the presence of this file evidence does not guarantee installation of the title)• 3 = Not allowed (if the file evidence is present, the title is not installed).• 4 = At least one (the presence of any of the file evidence identified this way is enough for the title to be considered installed).
RuleResourceString	<p><i>Type:</i> text (max 50 characters). Key</p> <p>The unique name of the localizable resource string representing an evidence rule. Foreign key to the ComplianceResourceString table.</p>
RuleDefaultString	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the rule resource string has no translation.</p>

EvidenceStatus Table

The collection of status values for installation evidence.

Table 309: Database columns for EvidenceStatus table

Database Column	Details
EvidenceStatusID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for an evidence status. Possible values (and associated default names) are:</p> <ul style="list-style-type: none">• 1 = Active• 2 = Inactive• 3 = Unassigned• 4 = Ignored• 5 = Assigned.
StatusResourceString	<p><i>Type:</i> text (max 50 characters). Key</p> <p>The name of the resource string containing the text to display on the user interface.</p>
StatusDefaultString	<p><i>Type:</i> text (max 100 characters)</p> <p>The value to display if there is no resource string available for this status.</p>

FNMEAFeature Table

FNMEAFeature records additional license features, associated with a specific license, that have been imported from FlexNet Manager for Engineering Applications.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 310: Database columns for FNMEAFeature table

Database Column	Details
FNMEAFeatureID	Type: integer. Key. Generated ID A unique identifier for the FNM-EA feature record.
Name	Type: text (max 256 characters) Name of the feature.
Version	Type: text (max 60 characters). Nullable Version of the feature.
PublisherID	Type: integer. Nullable The publisher of the license associated with this feature. Foreign key to the Vendor table.
NumberPurchased	Type: integer The quantity of purchased feature entities.
NumberInstalled	Type: integer The quantity of software installations accounted for by this feature.
SoftwareLicense ComplianceStatusID	Type: integer The compliance status of the license associated with this feature. Defaults to Compliant. Foreign key to the SoftwareLicenseComplianceStatus table.

FNMEALicensedFeature Table

FNMEALicensedFeature associated imported FlexNet Manager for Engineering Applications features with software licenses.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 311: Database columns for FNMEALicensedFeature table

Database Column	Details
FNMEAFeatureID	Type: integer. Key The feature associated with a license. Foreign key to the FNMEAFeature table.
SoftwareLicenseID	Type: integer. Key The license associated with a feature. Foreign key to the SoftwareLicense table.
QuantityPerLicense	Type: integer The quantity of feature entitlements per associated license purchased.
ProductID	Type: text (max 256 characters). Key The external identifier of the product the linked feature is a part of.
ComplianceConnectionID	Type: integer. Key An identifier for the data source the product has been imported from.

FileEvidenceCompany Table

FileEvidenceCompany contains the company names appearing in the headers of files used as evidence that an application is installed.

Table 312: Database columns for FileEvidenceCompany table

Database Column	Details
FileEvidenceCompanyID	Type: integer. Key. Generated ID A unique identifier for this company.
Company	Type: text (max 100 characters). Key The name of the company.

FileEvidenceEx Table

The FileEvidenceEx table contains additional information on the file evidence managed by FlexNet Manager Suite.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 313: Database columns for FileEvidenceEx table

Database Column	Details
FileEvidenceID	Type: integer. Key A unique identifier for an file evidence record.
OperatorManageStateID	Type: integer. Nullable The management responsibility for this information. Foreign key to the OperatorManageState table.
Ignored	Type: boolean. Nullable Set this field to True if the file evidence is not used for application recognition.

FileEvidenceFile Table

FileEvidenceFile contains the names of the files used as evidence that an application is installed.

Table 314: Database columns for FileEvidenceFile table

Database Column	Details
FileEvidenceFileID	Type: integer. Key. Generated ID A unique identifier for the file.
FileName	Type: text (max 256 characters). Key The name of the file.

FileEvidenceLanguage Table

FileEvidenceLanguage contains the language names appearing in headers of files used as evidence that an application is installed.

Table 315: Database columns for FileEvidenceLanguage table

Database Column	Details
FileEvidenceLanguageID	<i>Type:</i> integer. Key. Generated ID A unique identifier for this language.
Language	<i>Type:</i> text (max 200 characters). Key The name of the language.

FileEvidenceMatchCount Table

FileEvidenceMatchCount tracks the number of times that each file evidence (rule) has been detected as installed and recorded in the data source. A separate count is kept for each file evidence rule, and for each data source.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 316: Database columns for FileEvidenceMatchCount table

Database Column	Details
FileEvidenceMatchCountID	Type: integer. Key. Generated ID A synthetic unique identifier is required, since ComplianceConnectionID, being nullable, cannot be included in the primary key.
FileEvidenceID	Type: integer. Key The file evidence rule being matched. Foreign key to the NewFileEvidence table.
ComplianceConnectionID	Type: integer. Key. Nullable The data source where the match is occurring. Foreign key to the ComplianceConnection table.
MatchedCount	Type: integer The number of installed files in this data source matching this file evidence rule.
InstallCount	Type: integer The number of physical application installations recognized in this data source using this file evidence rule.

FileEvidencePath Table

FileEvidencePath contains the file paths to files used as evidence that an application is installed.

Table 317: Database columns for FileEvidencePath table

Database Column	Details
FileEvidencePathID	<i>Type:</i> integer. Key. Generated ID A unique identifier for this path.
FilePath	<i>Type:</i> text (max 400 characters). Key The content of the file path.

GroupSnapshot Table

The GroupSnapshot table lists all the snapshotted groups.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 318: Database columns for GroupSnapshot table

Database Column	Details
GroupID	Type: integer. Key The snapshotted GroupID.
GroupExID	Type: text (max 128 characters). Key The snapshotted GroupExID.
Path	Type: text (max 500 characters) The snapshotted Path.
LicenseMeasurementID	Type: integer. Key The snapshot ID. Foreign key to the LicenseMeasurement table.

ImporterRun Table

The ImporterRun table lists all previously run imports.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 319: Database columns for ImporterRun table

Database Column	Details
ImporterRunID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the import run.
LicenseMeasurementID	<i>Type:</i> integer. Key. Nullable The LicenseMeasurementID if a license reconcile was performed. Foreign key to the LicenseMeasurement table.
StartDate	<i>Type:</i> datetime. Nullable The time the import was started.
EndDate	<i>Type:</i> datetime. Nullable The time the import was completed.
ImportSourcesAppliedDate	<i>Type:</i> datetime. Nullable If non-licensing writers ran and completed successfully, this field will be set to the date/time of their completion. In effect, it records the application of data from the importer staging tables in to the core tables. This is the case even if the record as a whole is marked as a failure, as the writers processing will have already completed.
Arguments	<i>Type:</i> text (max 1024 characters) The command line arguments to the import.
RunAs	<i>Type:</i> text (max 1024 characters) The user who performed the import.
Comment	<i>Type:</i> text (max 1024 characters). Nullable Comments related to the import.
EventLogSummaryID	<i>Type:</i> integer. Key. Nullable The EventLogSummaryID for the import. Foreign key to the EventLogSummary table.
Success	<i>Type:</i> boolean. Key. Nullable Determines whether the import completed successfully.

ImporterStepValidationIssue Table

The ImporterStepValidationIssue table lists any validation issues that occurred during an import, that the user may need to review.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 320: Database columns for ImporterStepValidationIssue table

Database Column	Details
ImporterStepValidationIssueID	Type: integer. Key. Generated ID A unique identifier for the import validation.
ImporterRunID	Type: integer. Key Foreign key to the ImporterRun table.
ComplianceConnectionID	Type: integer. Key Foreign key to the ComplianceConnection table.
ProcedureName	Type: text (max 256 characters). Nullable The procedure that contains the issue.
StepName	Type: text (max 512 characters). Nullable The step that contains the issue.
RowSkipped	Type: boolean Source to object validation issue specifying if row skipped.
ColErrorReason	Type: integer. Nullable Source to object validation issue specifying reason for error on particular row.
ColumnName	Type: text (max 128 characters). Nullable Column name of the failed source to object validation issue.
RowNumber	Type: big integer. Nullable Row number of the failed source to object validation issue.
AffectedItem	Type: text (max 512 characters). Nullable An optional description for any further related item.
ImporterStepValidationIssueTypeID	Type: integer. Nullable Foreign key to the ImporterStepValidationIssueType table.

Database Column	Details
OccurrenceDate	Type: datetime. Nullable The time the issue was raised.

ImporterStepValidationIssueType Table

ImporterStepValidationIssueType is a static table listing all of the validation issues that can occur on a ComplianceConnection.

Table 321: Database columns for ImporterStepValidationIssueType table

Database Column	Details
ImporterStepValidationIssueTypeID	Type: integer. Key. Generated ID
ResourceName	Type: text (max 256 characters). Key The unique name of the localizable resource string representing the ImporterStepValidationIssueType record. Foreign key to the ComplianceResourceString table.
DefaultValue	Type: text (max 256 characters) The text to display if the state resource string has no translation.

InstalledFileEvidence Table

InstalledFileEvidence lists file evidence that has been installed on a computer.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 322: Database columns for InstalledFileEvidence table

Database Column	Details
FileEvidenceID	<i>Type:</i> integer. Key An identifier for a file evidence record. Foreign key to the NewFileEvidence table.
ComplianceComputerID	<i>Type:</i> integer. Key The managed computer on which this evidence was found. Foreign key to the ComplianceComputer table.
AccessModeID	<i>Type:</i> integer. Key The state an application was considered accessed. Foreign key to the AccessMode table.

InstalledInstallerAttribute Table

InstalledInstallerAttribute installer evidence attributes that exist on a computer.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 323: Database columns for InstalledInstallerAttribute table

Database Column	Details
InstallerEvidenceID	Type: integer. Key An identifier for an installer evidence record. Foreign key to the InstallerEvidence table.
ComplianceComputerID	Type: integer. Key An identifier for a computer record. Foreign key to the ComplianceComputer table.
InstanceName	Type: text (max 256 characters). Key. Nullable The name of the instance on the computer where this installer evidence was found.
AttributeID	Type: integer. Key The installer evidence attribute. Foreign key to the Attribute table.
Value	Type: text The value of the attribute.

InstalledInstallerEvidence Table

InstalledInstallerEvidence lists installer evidence that has been installed on a computer.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 324: Database columns for InstalledInstallerEvidence table

Database Column	Details
InstallerEvidenceID	<i>Type:</i> integer. Key An identifier for an installer evidence record. Foreign key to the InstallerEvidence table.
ComplianceComputerID	<i>Type:</i> integer. Key An identifier for a computer record. Foreign key to the ComplianceComputer table.
InstanceName	<i>Type:</i> text (max 256 characters). Key. Nullable The name of the instance on the computer where this installer evidence was found.
InstallDate	<i>Type:</i> datetime. Nullable The install date of the installer evidence.
DiscoveryDate	<i>Type:</i> datetime. Nullable The date that the installer evidence was first seen.
AccessModeID	<i>Type:</i> integer. Key The state an application was considered accessed. Foreign key to the AccessMode table.

InstalledInstanceReplacement Table

InstalledInstanceReplacement tracks the particular installations instances where a software suite replaced the installation record of its member application.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 325: Database columns for InstalledInstanceReplacement table

Database Column	Details
InstanceID	Type: integer. Key The installation instance of the software suite. Foreign key to the Instance table.
ReplacedSoftwareTitleID	Type: integer. Key Software title that has been replaced by its parent suite. Foreign key to the SoftwareTitle table.

InstalledSoftwareData Table

InstalledSoftware lists all the installations of an application (as defined in the SoftwareTitle table).


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 326: Database columns for InstalledSoftwareData table

Database Column	Details
InstalledSoftwareID	<i>Type:</i> integer. Key. Generated ID A unique identifier for an installed software record.
ComplianceComputerID	<i>Type:</i> integer. Key The computer on which the software is installed. Foreign key to the ComplianceComputer table.
SoftwareTitleID	<i>Type:</i> integer. Key The software that is installed. Foreign key to the SoftwareTitle table.
IsUsed	<i>Type:</i> boolean Set this field to True if the software title is installed according to usage thresholds in the SoftwareTitle table.
SoftwareLicenseID	<i>Type:</i> integer. Key. Nullable The link to the license this install has been counted against. Foreign key to the SoftwareLicense table.
SoftwareLicenseAllocationID	<i>Type:</i> integer. Key. Nullable The link to the license allocation this installation has consumed. Foreign key to the SoftwareLicenseAllocation table.
IsLicensed	<i>Type:</i> boolean Set this field to True when this installation is licensed.
PointsUsed	<i>Type:</i> integer. Nullable The number of points this installation consumes on a points-based license.
RawPointsUsed	<i>Type:</i> integer. Nullable The number of points this installation consumes on a points-based license before exemptions are considered.
InstallDate	<i>Type:</i> datetime. Nullable The install date of the software.

Database Column	Details
DiscoveryDate	<i>Type:</i> datetime. Nullable The date that the software was first seen.
LastUsedDate	<i>Type:</i> datetime. Nullable The date that the software was last used.
PointsCalculated	<i>Type:</i> integer The number of calculated points this installation consumes.

InstalledSoftwareRemoval Table

InstalledSoftwareRemoval table keeps track of software titles that have been recognised, but then removed due to precedence. This is typically because a higher quality (more specific) title has been found.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 327: Database columns for InstalledSoftwareRemoval table

Database Column	Details
InstalledSoftwareID	Type: integer. Key Installation record for lower quality title. Foreign key to the InstalledSoftware table.
RemovedSoftwareTitleID	Type: integer. Key Software title whose installation is now being ignored due to the presence of a higher quality title. Foreign key to the SoftwareTitle table.

InstalledSoftwareReplacement Table

InstalledSoftwareReplacement tracks which individual application installation records have (ever) been subsumed by recognition of their parent software suite installed on the same computer. Only the suite and its member application are linked here.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 328: Database columns for InstalledSoftwareReplacement table

Database Column	Details
InstalledSoftwareID	Type: integer. Key The suite's installation record. Foreign key to the InstalledSoftware table.
ReplacedSoftwareTitleID	Type: integer. Key The software title that has been replaced by its parent suite. Foreign key to the SoftwareTitle table.

InstalledSoftwareUsageData Table

InstalledSoftwareUsage records the end-users who are using a piece of software installed on a computer.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 329: Database columns for InstalledSoftwareUsageData table

Database Column	Details
InstalledSoftwareUsageID	Type: integer. Key. Generated ID The unique identifier for this record.
ComplianceUserID	Type: integer. Key. Nullable The end-user using the application. Foreign key to the ComplianceUser table.
SoftwareLicenseID	Type: integer. Nullable The license that covers this installation. Foreign key to the SoftwareLicense table.
SoftwareLicenseAllocationID	Type: integer. Key. Nullable A link to any individual allocation that this installation consumes. Foreign key to the SoftwareLicenseAllocation table.
IsLicensed	Type: boolean Set this field to True if this usage is licensed.
UsageSessions	Type: integer The number of sessions for (or times that the application was used by) this end-user on this computer.
UsageActiveTime	Type: integer The amount of time this application was in active use (in the foreground) for this end-user on this computer.
ComplianceComputerID	Type: integer. Key The application. Foreign key to the ComplianceComputer table.
SoftwareTitleID	Type: integer. Key The application. Foreign key to the SoftwareTitle table.
LastUsedDate	Type: datetime. Nullable The date that the installed software was last used.

Database Column	Details
AccessModeID	Type: integer. Key The date that the installed software was last used.

InstalledWMIEvidence Table

InstalledWMIEvidence lists WMI evidence that has been installed on a computer.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 330: Database columns for InstalledWMIEvidence table

Database Column	Details
WMIEvidenceID	Type: integer. Key An identifier for a WMI evidence record. Foreign key to the WMIEvidence table.
ComplianceComputerID	Type: integer. Key An identifier for a computer record. Foreign key to the ComplianceComputer table.
AccessModeID	Type: integer. Key The state an application was considered accessed. Foreign key to the AccessMode table.
InstanceName	Type: text (max 256 characters). Key The name of the WMI class instance used in the source connection for the WMI evidence

InstallerEvidence Table

InstallerEvidence lists installer evidence that is used to identify that a particular item of software (defined in the SoftwareTitle table) has been installed on a computer.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 331: Database columns for InstallerEvidence table

Database Column	Details
InstallerEvidenceID	Type: integer. Key. Generated ID A unique identifier for an installer evidence record.
InstallerEvidenceTypeID	Type: integer. Key Identifies the type of installer evidence. Defaults to MSI. Foreign key to the InstallerEvidenceType table.
DisplayName	Type: text (max 256 characters). Key The display name of the software as reported by the installer evidence.
Version	Type: text (max 72 characters). Key The version of the software as reported by the installer evidence.
Publisher	Type: text (max 200 characters). Key The publisher of the software as reported by the installer evidence.
OperatorManageStateID	Type: integer. Key The management responsibility for this information. Foreign key to the OperatorManageState table.
Ignored	Type: boolean Set this field to True if the installer evidence is not used for application recognition.
IsShared	Type: boolean

InstallerEvidenceEx Table

The `InstallerEvidenceEx` table contains additional information on the installer evidence managed by FlexNet Manager Suite.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 332: Database columns for `InstallerEvidenceEx` table

Database Column	Details
<code>InstallerEvidenceID</code>	<i>Type:</i> integer. Key A unique identifier for an installer evidence record.
<code>OperatorManageStateID</code>	<i>Type:</i> integer. Nullable The management responsibility for this information. Foreign key to the <code>OperatorManageState</code> table.
<code>Ignored</code>	<i>Type:</i> boolean. Nullable Set this field to <code>True</code> if the installer evidence is not used for application recognition.

InstallerEvidenceMatchCount Table

InstallerEvidenceMatchCount tracks the number of times that each installer evidence (rule) has been detected as installed and recorded in the data source. A separate count is kept for each installer evidence rule, and for each data source.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 333: Database columns for InstallerEvidenceMatchCount table

Database Column	Details
InstallerEvidenceMatchCountID	Type: integer. Key. Generated ID A synthetic unique identifier is required, since ComplianceConnectionID, being nullable, cannot be included in the primary key.
InstallerEvidenceID	Type: integer. Key The installer evidence which is being matched. Foreign key to the InstallerEvidence table.
ComplianceConnectionID	Type: integer. Key. Nullable The data source where the match is occurring. Foreign key to the ComplianceConnection table.
MatchedCount	Type: integer The number of installed installer evidence records in this data source matching this installer evidence rule.
InstallCount	Type: integer The number of physical application installations recognized in this data source using this installer evidence rule.

InstallerEvidenceType Table

InstallerEvidenceType is a static table listing the types of installer evidence that can be used to determine whether an item of software has been installed.

Table 334: Database columns for InstallerEvidenceType table

Database Column	Details
InstallerEvidenceTypeID	<p>Type: integer. Key. Generated ID</p> <p>A unique identifier for each InstallerEvidenceType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = Any • 2 = Add/Remove Programs • 3 = Software ID Tag • 4 = MSI • 5 = Unknown • 6 = ILMT • 7 = RPM • 8 = OS X App • 9 = LPP • 10 = SDUX • 11 = SUNPKG • 12 = IA • 13 = BEA • 14 = ISMP • 15 = IPS • 16 = ADDM • 17 = OracleEBSModule • 18 = BDNA • 19 = FlexeraID • 20 = DPKG • 21 = App-V • 22 = OUI • 23 = IIM • 24 = DSPMQ • 25 = VMware • 26 = HPUD

Database Column	Details
	<ul style="list-style-type: none">• 27 = SaaS• 28 = UniversalApplication
TypeResourceString	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing an installer evidence type. Foreign key to the ComplianceResourceString table.
TypeDefaultString	<i>Type:</i> text (max 100 characters) The text to display if the type resource string has no translation.
ImporterString	<i>Type:</i> text (max 100 characters) The text value provided by adapters when importing installer evidence.

LicenseBreachReason Table

LicenseBreachReason is a static table holding the collection of reasons why a license can be in breach.

Table 335: Database columns for LicenseBreachReason table

Database Column	Details
LicenseBreachReasonID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each LicenseBreachReason. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = Installed Greater Than Purchased • 2 = Child License In Breach • 3 = Install Linked to License has Invalid Sockets • 4 = Software License Does Not Meet Minimums • 5 = Software License Has Expired • 6 = Unlicensed Component Installed • 7 = Peak Consumed Quantity Greater Than Purchased • 8 = Nested License In Breach • 9 = Supplementary Product Exceeds Ratio.
BreachResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a breach reason. Foreign key to the ComplianceResourceString table.</p>
BreachDefaultValue	<p><i>Type:</i> text (max 512 characters)</p> <p>The text to display if the reason resource string has no translation.</p>

LicenseDefinitionTitle Table

LicenseDefinitionTitle associates software license definitions with their related applications.

Table 336: Database columns for LicenseDefinitionTitle table

Database Column	Details
SoftwareLicense DefinitionID	<i>Type:</i> integer. Key The license definition. Foreign key to the SoftwareLicenseDefinition table.
SoftwareRecognitionID	<i>Type:</i> text (max 100 characters). Key The encrypted FlexNet Manager Suite factory unique ID for the linked application in the Application Recognition Library.

LicenseDefinitionType Table

LicenseDefinitionType is a static table listing supported software license definition types, which are used to distinguish records downloaded from the Product Use Rights Library.

Table 337: Database columns for LicenseDefinitionType table

Database Column	Details
LicenseDefinitionTypeID	<i>Type:</i> integer. Key. Generated ID A unique identifier for a definition type. Possible values (and associated default names) are: <ul style="list-style-type: none">• 1 = License• 2 = Product• 3 = Usage Right.
TypeName	<i>Type:</i> text (max 100 characters). Key Unique internal name for this definition type.

LicenseDefinitionUsageRight Table

LicenseDefinitionUsageRight associates software license definitions and Application Recognition Library software applications to recommended usage rights.

Table 338: Database columns for LicenseDefinitionUsageRight table

Database Column	Details
LicenseDefinitionFactoryUID	Type: text (max 100 characters). Key The encrypted factory unique ID for a license definition or ARL application.
UsageRightFactoryUID	Type: text (max 100 characters). Key The encrypted factory unique ID for a usage right template.
IsPrimary	Type: boolean Is the software application a primary application to the recommended usage rights?
IsBundle	Type: boolean Is the recommended usage rights a bundle?
IsRelatedByEdition	Type: boolean Is the recommended usage rights is related to this primary application by the edition?

LicenseMeasurement Table

The LicenseMeasurement table is used to store license measurement snapshots.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 339: Database columns for LicenseMeasurement table

Database Column	Details
LicenseMeasurementID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the license measurement.
MeasurementCode	<i>Type:</i> text (max 128 characters) The unique code for this measurement.
MeasurementTime	<i>Type:</i> datetime. Key The date and time this measurement was started.
MeasurementEndTime	<i>Type:</i> datetime. Nullable The date and time this measurement was completed.
Success	<i>Type:</i> boolean Determines whether the measurement completed successfully.
Description	<i>Type:</i> text (max 50 characters) The description of this measurement.
IsPartial	<i>Type:</i> boolean Indicate whether this licence run was a partial run or not.

LicenseSimulation Table

A LicenseSimulation is made up of an initial scenario, and a cloned version of this scenario. The user can modify the rows in this cloned scenario.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 340: Database columns for LicenseSimulation table

Database Column	Details
LicenseSimulationID	Type: integer. Key. Generated ID Unique ID for the LicenseSimulation table.
LicenseSimulationScenarioID	Type: integer. Key Foreign key to the LicenseSimulationScenario table.
LastModified	Type: datetime The last time this simulation was modified.
ComplianceOperatorID	Type: integer. Key The compliance operator responsible for this scenario
DisplayName	Type: text (max 256 characters). Nullable The name given to this simulation by the owner/operator.
DisplayRateID	Type: integer. Nullable The rate to be used to display all price values in this simulation. Foreign key to the CurrencyRate table. If null, then the user’s default can be used.

LicenseSimulationBreachStatus Table

LicenseSimulationBreachStatus is a static table listing all of the breach states a license can be in, once it is modelled in a Simulation.

Table 341: Database columns for LicenseSimulationBreachStatus table

Database Column	Details
LicenseSimulation BreachStatusID	<i>Type:</i> integer. Key. Generated ID A unique identifier for each LicenseSimulationBreachStatus. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• 1 = Still compliant• 2 = Still in breach• 3 = Now compliant• 4 = Now in breach.
ResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing breach status in a license simulation. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the type resource string has no translation.

LicenseSimulationChangeType Table

LicenseSimulationChangeType is a static table listing all the types of operations that can be applied as changes to simulation data

Table 342: Database columns for LicenseSimulationChangeType table

Database Column	Details
LicenseSimulation ChangeTypeID	<p>Type: integer. Key. Generated ID</p> <p>A unique identifier for each LicenseSimulationChangeType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = Unchanged• 2 = Added• 3 = Deleted• 4 = Modified• 5 = Moved.
ResourceName	<p>Type: text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a computer role. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p>Type: text (max 100 characters)</p> <p>The text to display if the type resource string has no translation.</p>

LicenseSimulationHWDetails Table

LicenseSimulationHWDetails stores a complete snapshot of hardware data for simulations. The LicenseSimulationScenario associated with each record could be an original snapshot of data, or a user modifiable scenario.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 343: Database columns for LicenseSimulationHWDetails table

Database Column	Details
LicenseSimulationHWDetailsID	Type: integer. Key. Generated ID A unique identifier for a hardware item that is part of a simulation scenario.
LicenseSimulationScenarioID	Type: integer. Key The simulation scenario this hardware item is part of. Foreign key to the LicenseSimulationScenario table.
Name	Type: text (max 256 characters). Nullable The friendly name for this hardware item.
LicenseSimulationRowTypeID	Type: integer The type of hardware for this item.
Manufacturer	Type: text (max 128 characters). Nullable The manufacturer of this hardware item. Typically applies to a virtualisation server.
ModelNo	Type: text (max 128 characters). Nullable The model number of this hardware item. Typically applies to a virtualisation server.
ChassisNumber	Type: text (max 128 characters). Nullable The chassis number of this hardware item. Typically applies to a virtualisation server.
SerialNo	Type: text (max 100 characters). Nullable The serial number of this hardware item. Typically applies to a virtualisation server or physical machine.
ProcessorType	Type: text (max 256 characters). Nullable The processor type of this hardware item.

Database Column	Details
MaxClockSpeed	<i>Type:</i> integer. Nullable The maximum clock speed of this hardware item.
PurchaseDate	<i>Type:</i> datetime. Nullable The date this hardware item was purchased on, if it has an associated Asset.
NumSockets	<i>Type:</i> integer. Nullable The number of physical CPU sockets of this hardware item.
PoolTypeID	<i>Type:</i> integer. Nullable The type of pool technology of this hardware item. Typically applies to resource pools. Foreign key to the VMPoolType table.
VMTypeID	<i>Type:</i> integer. Nullable The type of virtual machine technology of this hardware item. Typically applies to virtual machines. Foreign key to the VMType table.
OperatingSystem	<i>Type:</i> text (max 128 characters). Nullable The operating system running on this hardware item.
NumProcessors	<i>Type:</i> decimal. Nullable The number of processors available to this hardware item.
NumCores	<i>Type:</i> decimal. Nullable The number of cores available to this hardware item.
NumThreads	<i>Type:</i> integer. Nullable The number of threads available to this hardware item.
ParentLicense SimulationHWDetailsID	<i>Type:</i> integer. Key. Nullable The parent hardware item of this item.
HostLicenseSimulationH WDetailsID	<i>Type:</i> integer. Nullable The host hardware item of this item.
ComplianceComputerID	<i>Type:</i> integer. Key. Nullable The actual computer record for this hardware item. Foreign key to the ComplianceComputer table.
VMLayerID	<i>Type:</i> integer. Key. Nullable Internal unique identifier used when populating hardware items to create a new simulation.
LicenseSimulation ChangeTypeID	<i>Type:</i> integer Tracks the state of the hardware item, as it gets modified by the simulation user. Foreign key to the LicenseSimulationChangeType table.

Database Column	Details
ClusterID	<i>Type:</i> integer. Nullable The hardware cluster to which this computer belongs, if any. Foreign key to the Cluster table.
AffinityEnabled	<i>Type:</i> boolean Whether this VM is locked to its current host computer.
CoreAffinity	<i>Type:</i> text (max 256 characters). Nullable Contains the Core Affinity value for virtual machine

LicenseSimulationLicenseDetails Table

LicenseSimulationLicenseDetails stores properties associated with each license included in a simulation scenario. The LicenseSimulationScenario associated with each record could be an original snapshot of data, or a user modifiable scenario.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 344: Database columns for LicenseSimulationLicenseDetails table

Database Column	Details
LicenseSimulation LicenseDetailsID	Type: integer. Key. Generated ID A unique identifier for a license item that is part of a simulation scenario.
OriginalLicense SimulationLicense DetailsID	Type: integer. Nullable The original version of this license, that has not been modified by a simulation user.
LicenseSimulation ScenarioID	Type: integer. Key The simulation scenario this software license is part of. Foreign key to the LicenseSimulationScenario table.
SoftwareLicenseID	Type: integer. Key The software license for this simulation license. Foreign key to the SoftwareLicense table.
UnitPrice	Type: currency. Nullable The unit price associated with this license.
UnitPriceRateID	Type: integer. Nullable The rate for the total value. Foreign key to the CurrencyRate table.
LicenseSimulation ChangeTypeID	Type: integer Tracks the state of the software license, as it gets modified by the simulation user. Foreign key to the LicenseSimulationChangeType table.

LicenseSimulationResults Table

LicenseSimulationResults stores points consumed by each item in a simulation scenario against each license included in the simulation scenario.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 345: Database columns for LicenseSimulationResults table

Database Column	Details
LicenseSimulationHW DetailsID	Type: integer. Key The hardware item for this license simulation result. Foreign key to the LicenseSimulationHWDetails table.
LicenseSimulation ScenarioID	Type: integer. Key The scenario for this license simulation result. Foreign key to the LicenseSimulationScenario table.
SoftwareLicenseID	Type: integer. Key The software license for this license simulation result. Foreign key to the SoftwareLicense table.
InstalledCount	Type: decimal The number of processors/cores on which a software title licensed by the license is installed.
UsedCount	Type: decimal The number of processors/cores on which a software title licensed by the license is used.
CapacityCount	Type: decimal The number of processors/cores that apply to a software license under full capacity counting rules.
IsCapped	Type: boolean Does this layer implement hard partitioning for this license?
PointsFactor	Type: decimal The number of points consumed per processor/core on this computer for this license.
PointsConsumed	Type: decimal. Nullable The number of processor/core points required to cover the above InstalledCount.

Database Column	Details
PointsUsed	<i>Type:</i> decimal. Nullable The number of processor/core points required to cover the above UsedCount.
CapacityPointsConsumed	<i>Type:</i> decimal. Nullable The number of processor/core points required to cover the above CapacityCount.
PointsCalculated	<i>Type:</i> decimal The number of calculated points this installation consumes.
Overridden	<i>Type:</i> boolean Is this simulation result derived from an overridden consumption via allocation.

LicenseSimulationRowType Table

LicenseSimulationRowType is a static table listing all types of rows that can be displayed in the Simulation UI. Entries in the LicenseSimulationSWDetails table are assumed to be type 4 (Software installation)

Table 346: Database columns for LicenseSimulationRowType table

Database Column	Details
LicenseSimulationRowTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each LicenseSimulationRowType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = Host • 2 = Shared pool • 3 = Virtual Machine • 4 = Software installation • 5 = Physical machine.
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing the type of a row in a license simulation. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the type resource string has no translation.</p>

LicenseSimulationSWDetails Table

LicenseSimulationSWDetails stores a complete snapshot of software data for simulations. The LicenseSimulationHWDetails record associated with each LicenseSimulationSWDetails record could be part of an original snapshot of data, or a user modifiable scenario.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 347: Database columns for LicenseSimulationSWDetails table

Database Column	Details
LicenseSimulationSWDetailsID	Type: integer. Key. Generated ID A unique identifier for a software installation that is part of a simulation scenario.
LicenseSimulationHWDetailsID	Type: integer. Key The hardware item that this software title is installed on. Foreign key to the LicenseSimulationHWDetails table.
LicenseSimulationScenarioID	Type: integer. Key The simulation scenario this software installation is part of. Foreign key to the LicenseSimulationScenario table.
OriginalLicenseSimulationSWDetailsID	Type: integer. Key. Nullable The original version of this software installation, that has not been modified by a simulation user.
Name	Type: text (max 512 characters) The friendly name of this software installation.
SoftwareTitleID	Type: integer. Key The software title that is installed here. Foreign key to the SoftwareTitle table.
SoftwareLicenseID	Type: integer. Key The software license that this install is assigned to. Foreign key to the SoftwareLicense table.
LicenseSimulationChangeTypeID	Type: integer Tracks the state of the software installation, as it gets modified by the simulation user. Foreign key to the LicenseSimulationChangeType table.

Database Column	Details
IsUsed	<i>Type:</i> boolean Set this field to True if the software title is installed according to usage thresholds in the SoftwareTitle table.

LicenseSimulationScenario Table

A LicenseSimulationScenario is a set of hardware and software inventory details that are recorded at a particular point in time. A scenario can be modified by the user for the purposes of simulation.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 348: Database columns for LicenseSimulationScenario table

Database Column	Details
LicenseSimulationScenarioID	Type: integer. Key. Generated ID Unique ID for the LicenseSimulationScenario table.
OriginalLicenseSimulationScenarioID	Type: integer. Nullable The original (unmodified) scenario that a user-modifiable scenario was based on

LicenseStatus Table

LicenseStatus is a static table storing the collection of possible license states.

Table 349: Database columns for LicenseStatus table

Database Column	Details
LicenseStatusID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each LicenseStatus. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = Active• 2 = Retired• 3 = In Stock• 4 = Purchased• 5 = Received.
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a license status. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the status resource string has no translation.</p>

NewFileEvidence Table

NewFileEvidence identifies files used as evidence that an application (defined in the SoftwareTitle table) has been installed on a computer. File evidence may have wildcards, so each record in this table should be considered a rule, which one or more physical files on a computer may match.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 350: Database columns for NewFileEvidence table

Database Column	Details
FileEvidenceID	Type: integer. Key. Generated ID A unique identifier for a file evidence record.
FileEvidenceFileID	Type: integer. Key The file name. Foreign key to the FileEvidenceFile table.
FileEvidenceCompanyID	Type: integer. Key The company publishing the software. Foreign key to the FileEvidenceCompany table.
FileEvidencePathID	Type: integer. Key. Nullable The file path where the file was located. Foreign key to the FileEvidencePath table.
FileEvidenceLanguageID	Type: integer. Key. Nullable The language identified in the file header. Foreign key to the FileEvidenceLanguage table.
FileVersion	Type: text (max 100 characters). Key The version number of the file used as evidence of software installation.
ProductName	Type: text (max 200 characters). Nullable The product name in the file header.
ProductVersion	Type: text (max 200 characters). Nullable The product version number in the file header.
Description	Type: text (max 200 characters). Key The description in the file header.
FileSize	Type: integer. Key. Nullable The size of the file.

Database Column	Details
OperatorManageStateID	<i>Type:</i> integer. Key The management responsibility for this information. Foreign key to the OperatorManageState table.
Ignored	<i>Type:</i> boolean Set this field to True to indicate that this file evidence is ignored for application recognition.
IsShared	<i>Type:</i> boolean

OracleLegacyLicenseType Table

OracleLegacyLicenseType lists some of the legacy Oracle license types.

Table 351: Database columns for OracleLegacyLicenseType table

Database Column	Details
OracleLegacyLicenseTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each OracleLegacyLicenseType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = Named User• 2 = Named User Network license• 3 = Named User Single Server• 4 = Named User Multi Server• 5 = Concurrent Device• 6 = Concurrent Device Network License• 7 = UPU• 8 = Developer• 9 = Developer Network License• 10 = Concurrent User• 11 = Concurrent User Network License• 12 = Application Specific Full User Licensing• 13 = Embedded Software License• 14 = Site.
OracleLegacyLicenseTypeResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing an Oracle legacy license type. Foreign key to the ComplianceResourceString table.</p>
OracleLegacyLicenseTypeDefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the type resource string has no translation.</p>

PODetailProcess Table

PODetailProcess records the processing steps taken when applying upgrades to software installations. The newly-purchased upgrade license is linked here to the original license being upgraded.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 352: Database columns for PODetailProcess table

Database Column	Details
PurchaseOrderDetailID	<i>Type:</i> integer. Key The purchase order line that defines this upgrade. Foreign key to the PurchaseOrderDetail table.
FromSoftwareLicenseID	<i>Type:</i> integer. Key. Nullable The original software license to which an upgrade is being applied. Foreign key to the SoftwareLicense table.
ToSoftwareLicenseID	<i>Type:</i> integer. Key. Nullable The upgrade license referenced in the PO line and permitting the installation of the software upgrade. Foreign key to the SoftwareLicense table.
ProcessActionID	<i>Type:</i> integer The processing action taken with respect to this upgrade. Defaults to Defer. Foreign key to the ProcessAction table.
ProcessStateID	<i>Type:</i> integer. Key The resulting process state of the upgrade. Foreign key to the ProcessState table.
CreationDate	<i>Type:</i> datetime The date this record was created.

PeriodType Table

PeriodType is a static table holding a collection of supported time periods to indicate the frequency of license charge-backs.

Table 353: Database columns for PeriodType table

Database Column	Details
PeriodTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each PeriodType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = None• 2 = Weekly• 3 = Monthly• 4 = Quarterly• 5 = Yearly• 6 = Lump Sum.
PeriodTypeResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a period type. Foreign key to the ComplianceResourceString table.</p>
PeriodTypeDefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the type resource string has no translation.</p>

ProcessAction Table

ProcessAction is a static table holding a collection of possible actions that can be applied while processing a SKU, with a special focus on processing software license upgrades.

Table 354: Database columns for ProcessAction table

Database Column	Details
ProcessActionID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each ProcessAction. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = Link to existing license • 2 = Create new from SKU • 3 = Create new from PO line • 4 = Upgrade license: Link to existing license and upgrade from existing license • 5 = Upgrade license: Link to existing license and select upgrade from license • 6 = Upgrade license: Link to new license created from SKU and select upgrade from license • 7 = Remove from list • 8 = Upgrade license: Link to new license created from PO line and select upgrade from license • 9 = Create new from SKU with fixed maintenance • 10 = Create new from PO line with fixed maintenance • 11 = Create new from SKU with unlimited maintenance • 12 = Create new from PO line with unlimited maintenance • 13 = Create new from SKU with maintenance from contract • 14 = Create new from PO line with maintenance from contract • 15 = Apply contract maintenance to an existing license • 16 = Apply fixed maintenance to an existing license • 17 = Apply unlimited maintenance to an existing license • 18 = Apply contract maintenance to an existing license by SKU • 19 = Apply fixed maintenance to an existing license by SKU • 20 = Apply unlimited maintenance to an existing license by SKU • 21 = Apply contract maintenance to a non-existent license for SKU • 22 = Apply fixed maintenance to a non-existent license for SKU • 23 = Apply unlimited maintenance to a non-existent license for SKU

Database Column	Details
	<ul style="list-style-type: none"> • 24 = Upgrade license: Link to existing license and upgrade from existing license with contract maintenance • 25 = Upgrade license: Link to existing license and upgrade from existing license with fixed maintenance • 26 = Upgrade license: Link to existing license and upgrade from existing license with unlimited maintenance • 27 = Upgrade license: Link to existing license and select upgrade from license with contract maintenance • 28 = Upgrade license: Link to existing license and select upgrade from license with fixed maintenance • 29 = Upgrade license: Link to existing license and select upgrade from license with unlimited maintenance • 30 = Upgrade license: Link to new license created from SKU and select upgrade from license with contract maintenance • 31 = Upgrade license: Link to new license created from SKU and select upgrade from license with fixed maintenance • 32 = Upgrade license: Link to new license created from SKU and select upgrade from license with unlimited maintenance • 33 = Upgrade license: Link to new license created from PO line and select upgrade from license with contract maintenance • 34 = Upgrade license: Link to new license created from PO line and select upgrade from license with fixed maintenance • 35 = Upgrade license: Link to new license created from PO line and select upgrade from license with unlimited maintenance • 36 = Apply maintenance to a contract • 37 = No recommendation • 38 = Create a new license • 39 = Create a new license with a maintenance contract • 40 = Create a new license with fixed maintenance • 41 = Create a new license with unlimited maintenance • 42 = Add entitlements to a license • 43 = Add entitlements to a license with a maintenance contract

Database Column	Details
	<ul style="list-style-type: none"> • 44 = Add entitlements to a license with fixed maintenance • 45 = Add entitlements to a license with unlimited maintenance • 46 = Upgrade to a new license • 47 = Upgrade to a new license with a maintenance contract • 48 = Upgrade to a new license with fixed maintenance • 49 = Upgrade to a new license with unlimited maintenance • 50 = Upgrade to an existing license • 51 = Upgrade to an existing license with a maintenance contract • 52 = Upgrade to an existing license with fixed maintenance • 53 = Upgrade to an existing license with unlimited maintenance • 54 = Apply maintenance from a contract to an existing license • 55 = Apply fixed maintenance to an existing license • 56 = Apply unlimited maintenance to an existing license
ProcessActionResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing an action. Foreign key to the ComplianceResourceString table.</p>
ProcessActionDefaultValue	<p><i>Type:</i> text (max 256 characters)</p> <p>The text to display if the action resource string has no translation.</p>

ProcessState Table

ProcessState is a static table holding the collection of processing states that a purchase order line containing a SKU can be left in.

Table 355: Database columns for ProcessState table

Database Column	Details
ProcessStateID	<i>Type:</i> integer. Key. Generated ID A unique identifier for each ProcessState. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• 1 = Unprocessed• 2 = Processed• 3 = Deferred• 4 = Discarded.
ProcessStateResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing a processing state. Foreign key to the ComplianceResourceString table.
ProcessStateDefaultValue	<i>Type:</i> text (max 256 characters) The text to display if the state resource string has no translation.

ReconcileAccessedSoftwareData Table

A list of all the accesses of an application, or item of software (as defined in the SoftwareTitle table).


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 356: Database columns for ReconcileAccessedSoftwareData table

Database Column	Details
AccessedSoftwareID	Type: big integer. Key A unique identifier for an accessed software record.
ServerComputerID	Type: integer. Key The server computer on which the software is available. Foreign key to the ComplianceComputer table.
AccessingUserID	Type: integer. Key. Nullable The user who accessed the software. Foreign key to the AccessingUser table.
ComplianceUserID	Type: integer. Nullable The compliance user who accessed the software. Foreign key to the ComplianceUser table.
AccessingDeviceID	Type: integer. Key. Nullable The device from which the software is accessed. Foreign key to the AccessingDevice table.
ComplianceComputerID	Type: integer. Nullable The compliance computer from which the software is accessed. Foreign key to the ComplianceComputer table.
SoftwareTitleID	Type: integer. Key The software that is accessed. Foreign key to the SoftwareTitle table.
IsUsed	Type: boolean Set this field to True if the software title is accessed according to usage thresholds in the SoftwareTitle table.
SoftwareLicenseID	Type: integer. Key. Nullable The link to the license this access has been counted against. Foreign key to the SoftwareLicense table.

Database Column	Details
SoftwareLicense AllocationID	<i>Type:</i> integer. Key. Nullable The link to the license allocation this access has consumed. Foreign key to the SoftwareLicenseAllocation table.
IsLicensed	<i>Type:</i> boolean Set this field to True when this access is licensed.
PointsUsed	<i>Type:</i> integer. Nullable The number of this accesses consumed on license.
LastUsedDate	<i>Type:</i> datetime. Nullable The last used date of the application by client.
PointsCalculated	<i>Type:</i> integer The number of calculated points this installation consumes.

ReconcileInstalledSoftwareData Table

A list of all the installations of an application, or item of software (as defined in the SoftwareTitle table).


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 357: Database columns for ReconcileInstalledSoftwareData table

Database Column	Details
InstalledSoftwareID	Type: integer. Key A unique identifier for an installed software record.
ComplianceComputerID	Type: integer. Key The computer on which the software is installed. Foreign key to the ComplianceComputer table.
SoftwareTitleID	Type: integer. Key The software that is installed. Foreign key to the SoftwareTitle table.
IsUsed	Type: boolean. Key Set this field to True if the software title is installed according to usage thresholds in the SoftwareTitle table.
SoftwareLicenseID	Type: integer. Key. Nullable The link to the license this install has been counted against. Foreign key to the SoftwareLicense table.
SoftwareLicenseAllocationID	Type: integer. Key. Nullable The link to the license allocation this installation has consumed. Foreign key to the SoftwareLicenseAllocation table.
IsLicensed	Type: boolean Set this field to True when this installation is licensed.
PointsUsed	Type: integer. Nullable The number of points this installation consumes on a points-based license.
RawPointsUsed	Type: integer. Nullable The number of points this installation consumes on a points-based license before exemptions are considered.

Database Column	Details
AccessModeID	<i>Type:</i> integer. Key The access mode that indicates why this computer was associated with this software title.
LastUsedDate	<i>Type:</i> datetime. Nullable The date of the installed software was last used.
PointsCalculated	<i>Type:</i> integer The number of calculated points this installation consumes.

ReconcileInstalledSoftwareUsageData Table

This is a staging table for InstalledSoftwareUsage that is used during license reconciliation process, to store calculated values, and then bulk update the main table.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 358: Database columns for ReconcileInstalledSoftwareUsageData table

Database Column	Details
ComplianceUserID	Type: integer. Key. Nullable The end-user using the application. Foreign key to the ComplianceUser table.
SoftwareLicenseID	Type: integer. Nullable The license that covers this installation. Foreign key to the SoftwareLicense table.
SoftwareLicenseAllocationID	Type: integer. Key. Nullable A link to any individual allocation that this installation consumes. Foreign key to the SoftwareLicenseAllocation table.
IsLicensed	Type: boolean Set this field to True if this usage is licensed.
UsageSessions	Type: integer The number of sessions for (or times that the application was used by) this end-user on this computer.
UsageActiveTime	Type: integer The amount of time this application was in active use (in the foreground) for this end-user on this computer.
ComplianceComputerID	Type: integer. Key The application. Foreign key to the ComplianceComputer table.
SoftwareTitleID	Type: integer. Key The application. Foreign key to the SoftwareTitle table.
LastUsedDate	Type: datetime. Nullable The last used date of the application.
AccessModeID	Type: integer. Key The date that the installed software was last used.

ReconcileInterestingBundleAccessComputer Table

A list of all computers with bundlable accesses for licenses that are interesting to the current execution of license reconcile.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 359: Database columns for ReconcileInterestingBundleAccessComputer table

Database Column	Details
SoftwareLicenseID	Type: integer. Key The unique identifier for a bundle software license that is interesting to an execution of reconcile.
AccessingDeviceID	Type: integer. Key. Nullable The unique identifier for a accessing device that could consume a bundle software license that is interesting to an execution of reconcile.
AccessingUserID	Type: integer. Key. Nullable The unique identifier of the accessing user that could consume a bundle software license that is interesting to an execution of reconcile.
ComplianceComputerID	Type: integer. Key. Nullable The unique identifier for a computer that could consume a bundle software license that is interesting to an execution of reconcile.
ComplianceUserID	Type: integer. Key. Nullable The unique identifier of the primary user for a computer that could consume a bundle software license that is interesting to an execution of reconcile.
NumProducts	Type: integer The number of products covered by this license that are accessed on this computer.

ReconcileInterestingBundleInstallComputer Table

A list of all computers with bundlable installs for licenses that are interesting to the current execution of license reconcile.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 360: Database columns for ReconcileInterestingBundleInstallComputer table

Database Column	Details
SoftwareLicenseID	Type: integer. Key The unique identifier for a bundle software license that is interesting to an execution of reconcile.
ComplianceComputerID	Type: integer. Key The unique identifier for a computer that could consume a bundle software license that is interesting to an execution of reconcile.
ComplianceUserID	Type: integer. Key. Nullable The unique identifier of the primary user for a computer that could consume a bundle software license that is interesting to an execution of reconcile.
NumProducts	Type: integer The number of products covered by this license that are installed on this computer.

ReconcileInterestingLicenses Table

A list of all licenses that are interesting to the current execution of license reconcile.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 361: Database columns for ReconcileInterestingLicenses table

Database Column	Details
SoftwareLicenseID	Type: integer. Key The unique identifier for a software license that is interesting to an execution of reconcile.

ReconcileInterestingTitles Table

A list of all titles that are interesting to the current execution of license reconcile.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 362: Database columns for ReconcileInterestingTitles table

Database Column	Details
SoftwareTitleID	Type: integer. Key The unique identifier for a software title that is interesting to an execution of reconcile.

ReconcileSoftwareAccessDeviceLicensePointsConsumedData Table

This is a staging table for SoftwareAccessDeviceLicensePointsConsumed that is used during license reconciliation process, to store calculated values, and then bulk update the main table.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 363: Database columns for ReconcileSoftwareAccessDeviceLicensePointsConsumedData table

Database Column	Details
AccessingDeviceID	Type: integer. Key. Nullable The accessing device under examination. Foreign key to the AccessingDevice table.
ComplianceComputerID	Type: integer. Key. Nullable The compliance computer under examination. Foreign key to the ComplianceComputer table.
SoftwareLicenseID	Type: integer. Key The license being assessed. Foreign key to the SoftwareLicense table.
LicensesUsed	Type: integer How many of the points consumed are for installations actually being used.
CalculatedConsumption	Type: integer The calculated consumption value for this license assignment before exemptions or overrides are considered.

ReconcileSoftwareAccessUserLicensePointsConsumedData Table

This is a staging table for SoftwareAccessUserLicensePointsConsumed that is used during license reconciliation process, to store calculated values, and then bulk update the main table.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 364: Database columns for ReconcileSoftwareAccessUserLicensePointsConsumedData table

Database Column	Details
AccessingUserID	Type: integer. Key. Nullable The accessing user under examination. Foreign key to the AccessingUser table.
ComplianceUserID	Type: integer. Key. Nullable The Compliance user under examination. Foreign key to the ComplianceUser table.
SoftwareLicenseID	Type: integer. Key The license being assessed. Foreign key to the SoftwareLicense table.
LicensesUsed	Type: integer How many of the points consumed are for installations actually being used.
CalculatedConsumption	Type: integer The calculated consumption value for this license assignment before exemptions or overrides are considered.

ReconcileSoftwareLicenseComputerProblem Table

ReconcileSoftwareLicenseComputerProblem is a license reconciliation staging table for the SoftwareLicenseComputerProblemData table.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 365: Database columns for ReconcileSoftwareLicenseComputerProblem table

Database Column	Details
SoftwareLicenseID	Type: integer. Key The software license. Foreign key to the SoftwareLicense table.
ComplianceComputerID	Type: integer. Key The computer consuming license entitlements. Foreign key to the ComplianceComputer table.
SoftwareLicense ComputerProblemTypeID	Type: integer The type of problem this computer’s inventory causes for a given license. For example, core-based licenses require accurate inventory of processor core counts to determine ther compliance status. Foreign key to the SoftwareLicenseComputerProblemType table.

ReconcileSoftwareLicenseCoresConsumedData Table

This is a staging table for SoftwareLicenseCoresConsumedData that stores values calculated by license reconciliation. The main table is populated at the end of license reconciliation by a single bulk update.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 366: Database columns for ReconcileSoftwareLicenseCoresConsumedData table

Database Column	Details
ComplianceComputerID	Type: integer. Key The computer under examination. Foreign key to the ComplianceComputer table.
SoftwareLicenseID	Type: integer. Key The license being assessed. Foreign key to the SoftwareLicense table.
CoresConsumed	Type: integer The number of cores that have contributed to license point consumption for the license on the computer.
CalculatedConsumption	Type: integer The calculated consumption value for this license assignment before exemptions or overrides are considered.

ReconcileSoftwareLicenseGroupPointsConsumedData Table

This serves as a staging table for SoftwareLicenseGroupPointsConsumed during reconciliation process.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 367: Database columns for ReconcileSoftwareLicenseGroupPointsConsumedData table

Database Column	Details
SoftwareLicenseID	Type: integer. Key The license that owns the pre-calculated totals for a group. Foreign key to the SoftwareLicense table.
GroupTypeID	Type: integer. Key Type of the group(Location, Cost center, etc)
GroupExID	Type: text (max 128 characters). Key. Nullable The group where the local and rolledup values are calculated. Foreign key to the GroupEx table.
RolledUpNumberConsumed	Type: integer The sum of points consumed of the current group and of all its child groups.
LocalNumberConsumed	Type: integer The sum of points consumed of the current group
RolledUpNumberUsed	Type: integer The sum of used points f the current group and of all its child groups.
LocalNumberUsed	Type: integer The sum of used points of the current group
RolledUpNumberPurchased	Type: integer The rolled up purchase counts of the license.
LocalNumberPurchased	Type: integer The local purchase counts of the license
RolledUpNumberCalculated	Type: integer The sum of points calculated for the current group and of all its child groups.

Database Column	Details
LocalNumberCalculated	Type: integer The sum of points calculated for the current group.

ReconcileSoftwareLicenseILMTPointsConsumedData Table

This is a staging table for SoftwareLicenseILMTPointsConsumed that is used during license reconciliation process, to store calculated values, and then bulk update the main table.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 368: Database columns for ReconcileSoftwareLicenseILMTPointsConsumedData table

Database Column	Details
ComplianceComputerID	Type: integer. Key The computer under examination. Foreign key to the ComplianceComputer table.
SoftwareLicenseID	Type: integer. Key The license being assessed. Foreign key to the SoftwareLicense table.
CoreCount	Type: integer The number of licensable cores for the license on the computer.
PVUCount	Type: integer The number of PVU counts consumed for the license on the computer.
PeakPVUCount	Type: integer The number of PVU counts consumed for the license on the computer at the time where the peak for this license occurred.
ProductCount	Type: integer The number of products that are consuming same license.
CalculatedConsumption	Type: integer The calculated consumption value for this license assignment before exemptions or overrides are considered.

ReconcileSoftwareLicensePointsConsumedData Table

This is a staging table for SoftwareLicensePointsConsumed that is used during license reconciliation process, to store calculated values, and then bulk update the main table.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 369: Database columns for ReconcileSoftwareLicensePointsConsumedData table

Database Column	Details
ComplianceComputerID	Type: integer. Key The computer under examination. Foreign key to the ComplianceComputer table.
SoftwareLicenseID	Type: integer. Key The license being assessed. Foreign key to the SoftwareLicense table.
LicensesConsumed	Type: integer The number of entitlements (or points) consumed for the license on the computer.
CalculatedConsumption	Type: integer The calculated consumption value for this license assignment before exemptions or overrides are considered.
LicensesUsed	Type: integer How many of the points consumed are for installations actually being used.

ReconcileSoftwareLicensePointsConsumedReasonTable

This is a staging table for SoftwareLicensePointsConsumedReasonData that is used during license reconciliation process, to store calculated values, and then bulk update the main table.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 370: Database columns for ReconcileSoftwareLicensePointsConsumedReason table

Database Column	Details
ComplianceComputerID	Type: integer. Key The computer under examination. Foreign key to the ComplianceComputer table.
SoftwareLicenseID	Type: integer. Key The license being assessed. Foreign key to the SoftwareLicense table.
ReasonTypeID	Type: integer. Key The reason for the points to be consumed here. Foreign key to the SoftwareLicensePointsConsumedReasonType table.

ReconcileSoftwareLicenseProcessorData Table

This serves as an intermediate table during reconciliation process to store the number of processors (or cores) on which licensed software is installed and used for each computer, and the calculated points.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 371: Database columns for ReconcileSoftwareLicenseProcessorData table

Database Column	Details
ComplianceComputerID	Type: integer. Key The host computer under examination. Foreign key to the ComplianceComputer table.
SoftwareLicenseID	Type: integer. Key The license being assessed. Foreign key to the SoftwareLicense table.
VMLayerID	Type: integer. Key. Nullable The virtual machine layer under examination. Foreign key to the ReconcileVirtualMachineLayer table.
IsHost	Type: boolean. Key Does this refer to the top layer for this host?
IsCapped	Type: boolean Does this layer implement hard partitioning for this license?
InstalledCount	Type: decimal The number of processors/cores on which a software title licensed by the license is installed.
UsedCount	Type: decimal The number of processors/cores on which a software title licensed by the license is used.
CapacityCount	Type: decimal The number of processors/cores that apply to a software title licensed by the license under full capacity counting rules.
PointsFactor	Type: decimal The number of points consumed per processor/core on this computer.

Database Column	Details
InstalledPoints	<i>Type:</i> integer The number of processor/core points required to cover the above InstalledCount.
UsedPoints	<i>Type:</i> integer The number of processor/core points required to cover the above UsedCount.
CapacityPoints	<i>Type:</i> integer The number of processor/core points required to cover the above CapacityCount.
CalculatedConsumption	<i>Type:</i> integer The calculated consumption value for this license assignment before exemptions or overrides are considered.
Overridden	<i>Type:</i> boolean Whether this consumption value was the result of an override.

ReconcileSoftwareLicenseSecondUseMappingData Table

This is a staging table for SoftwareLicenseSecondUseMapping that is used during license reconciliation process, to store calculated values, and then bulk update the main table.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 372: Database columns for ReconcileSoftwareLicenseSecondUseMappingData table

Database Column	Details
SoftwareLicenseID	Type: integer. Key The license conferring the right of second use. Foreign key to the SoftwareLicense table.
DesktopComputerID	Type: integer. Key The desktop or primary computer on which the related software is installed. Foreign key to the ComplianceComputer table.
SecondUseComputerID	Type: integer. Key The laptop or second computer covered by this license's right of second use, relative to the installation on the primary computer tracked in the previous field. Foreign key to the ComplianceComputer table.
TotalLicenseGrabs	Type: integer For internal use only. Temporary storage for calculations of overlapping second use and multiple install rights.
IsExternalRoamingLink	Type: boolean Is this a second use link or is it actually an 'external roaming' right?

ReconcileSoftwareUserLicensePointsConsumedData Table

This is a staging table for SoftwareUserLicensePointsConsumed that is used during license reconciliation process, to store calculated values, and then bulk update the main table.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 373: Database columns for ReconcileSoftwareUserLicensePointsConsumedData table

Database Column	Details
ComplianceUserID	Type: integer. Key The end-user. Foreign key to the ComplianceUser table.
SoftwareLicenseID	Type: integer. Key The license. Foreign key to the SoftwareLicense table.
LicensesConsumed	Type: integer The number of points (or entitlements) consumed for the license by the end-user.
LicensesUsed	Type: integer How many of the points consumed are for installations that are actually being used.
CalculatedConsumption	Type: integer The calculated consumption value for this license assignment before exemptions or overrides are considered.
LicenseMeasurementID	Type: integer. Key. Nullable The associated SAP license measurement snapshot, where appropriate. Foreign key to the LicenseMeasurement table.

ReconcileVirtualMachineLayer Table

This serves as an intermediate table during reconciliation process to store virtual machines, pools and hosts in a generalized tree structure.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 374: Database columns for ReconcileVirtualMachineLayer table

Database Column	Details
VMLayerID	<i>Type:</i> integer. Key A unique identifier for a ReconcileVirtualMachineLayer.
HostComplianceComputerID	<i>Type:</i> integer. Key The host computer on which the layer resides, or the computer itself. Foreign key to the ComplianceComputer table.
VMPoolID	<i>Type:</i> integer. Key. Nullable The identifier of the virtual pool containing this VM, or the pool itself. Foreign key to the VMPool table.
VMPoolTypeID	<i>Type:</i> integer. Nullable The type of this VM pool. Foreign key to the VMPoolType table.
VirtualMachineID	<i>Type:</i> integer. Key. Nullable The identifier of this virtual machine. Foreign key to the VirtualMachine table.
VMTypeID	<i>Type:</i> integer. Nullable The type of this virtual machine. Foreign key to the VMType table.
ParentVMPoolID	<i>Type:</i> integer. Nullable The identifier of the parent VM pool of this pool. Foreign key to the VMPool table.
ParentVMLayerID	<i>Type:</i> integer. Key. Nullable The parent layer. Foreign key to the ReconcileVirtualMachineLayer table.
ComplianceComputerID	<i>Type:</i> integer. Key. Nullable The identifier of the computer running inside this virtual machine. Foreign key to the ComplianceComputer table.
Name	<i>Type:</i> text (max 256 characters). Nullable The name of the layer (host/pool/VM).

Database Column	Details
PartialNumberOfProcessors	<i>Type:</i> decimal. Nullable The fractional processor count available to this computer.
NumberOfProcessors	<i>Type:</i> decimal. Nullable The processor count for this computer.
NumberOfCores	<i>Type:</i> decimal. Nullable The core count for this computer.
Depth	<i>Type:</i> integer. Key The number of layers between this and the host computer.

RegistryEvidence Table

Reserved for future expansion.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 375: Database columns for RegistryEvidence table

Database Column	Details
RegistryEvidenceID	Type: integer. Key. Generated ID A unique identifier for a software registry evidence record.
RegistryEvidenceHiveID	Type: integer. Key The registry hive for the registry evidence.
RegistryEvidenceKeyID	Type: integer. Key The registry key for the registry evidence.
RegistryEvidenceValueID	Type: integer. Key The value of the registry evidence.
RegistryData	Type: text (max 400 characters). Key The data contained in the registry value for the registry evidence.
Ignored	Type: boolean If True this registry evidence is ignored for application recognition.
IsShared	Type: boolean

RegistryEvidenceHive Table

Reserved for future use.

Table 376: Database columns for RegistryEvidenceHive table

Database Column	Details
RegistryEvidenceHiveID	Type: integer. Key. Generated ID Unique identifier for a registry hive.
RegistryHive	Type: text (max 50 characters). Key The registry hive for the registry evidence.

RegistryEvidenceKey Table

Reserved for future use.

Table 377: Database columns for RegistryEvidenceKey table

Database Column	Details
RegistryEvidenceKeyID	<i>Type:</i> integer. Key. Generated ID Unique identifier for a registry key.
RegistryKey	<i>Type:</i> text (max 200 characters). Key The registry key for the registry evidence.

RegistryEvidenceValue Table

Reserved for future use.

Table 378: Database columns for RegistryEvidenceValue table

Database Column	Details
RegistryEvidenceValueID	Type: integer. Key. Generated ID Unique identifier for a registry value
RegistryValue	Type: text (max 50 characters). Key The registry value for the registry evidence.

RelatedInstalledInstallerEvidence Table

RelatedInstalledInstallerEvidence table holds parent-child relationship between installer evidence.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 379: Database columns for RelatedInstalledInstallerEvidence table

Database Column	Details
RelatedInstalled InstallerEvidenceID	<i>Type:</i> integer. Key. Generated ID A synthetic unique identifier
ParentInstallerEvidenceID	<i>Type:</i> integer. Key An parent identifier for an installer evidence record. Foreign key to the InstallerEvidence table.
ParentCompliance ComputerID	<i>Type:</i> integer. Key An parent identifier for a computer record. Foreign key to the ComplianceComputer table.
ParentAccessModeID	<i>Type:</i> integer. Key The state an application was considered accessed. Foreign key to the AccessMode table.
ChildInstallerEvidenceID	<i>Type:</i> integer. Key An child identifier for an installer evidence record. Foreign key to the InstallerEvidence table.
ChildComplianceComputerID	<i>Type:</i> integer. Key An child identifier for a computer record. Foreign key to the ComplianceComputer table.
ChildAccessModeID	<i>Type:</i> integer. Key The state an application was considered accessed. Foreign key to the AccessMode table.
IsCharged	<i>Type:</i> boolean. Key The identifier used in the source connection to determine the pricing relation between parent and child installer evidence (specifies if it is charged = 1 or free = 0).
ConfidenceLevel	<i>Type:</i> integer. Nullable Confidence level for each bundled installer evidence (as a percentage).

RelatedInstalledInstallerEvidenceSourceMap Table

RelatedInstalledInstallerEvidenceSourceMap Maps related installed installer evidence to the evidence source type.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 380: Database columns for RelatedInstalledInstallerEvidenceSourceMap table

Database Column	Details
RelatedInstalled InstallerEvidence SourceMapID	Type: integer. Key. Generated ID A synthetic unique identifier
RelatedInstalled InstallerEvidenceID	Type: integer. Key An identifier for an related installer evidence record. Foreign key to the RelatedInstalledInstallerEvidence table.
ComplianceConnectionID	Type: integer. Key The inventory source where the end-user was reported. Foreign key to the ComplianceConnection table.

RelatedInstalledSoftwareData Table

RelatedInstalledSoftware stores parent-child relationship among application installations. This is used for modelling application bundling.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 381: Database columns for RelatedInstalledSoftwareData table

Database Column	Details
RelatedInstalledSoftwareID	<i>Type:</i> integer. Key. Generated ID Unique identifier for this record.
ParentInstalledSoftwareID	<i>Type:</i> integer. Key The parent installed application. Foreign key to the InstalledSoftware table.
ChildInstalledSoftwareID	<i>Type:</i> integer. Key The child installed application. Foreign key to the InstalledSoftware table.
IsCharged	<i>Type:</i> boolean. Key The identifier used in the source connection to determine the pricing relation between parent and child installer evidence (specifies if it is charged = 1 or free = 0).
ConfidenceLevel	<i>Type:</i> integer. Nullable Confidence level for each bundled installer evidence (as a percentage).

SAPSoftwareLicense Table

SAPSoftwareLicense stores additional SAP-specific licensing information for SAP licenses.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 382: Database columns for SAPSoftwareLicense table

Database Column	Details
SoftwareLicenseID	<i>Type:</i> integer. Key The SAP license. Foreign key to the SoftwareLicense table.
SAPServerName	<i>Type:</i> text (max 256 characters). Nullable The name of the SAP server. Should match the ComputerName of the record in the ComplianceComputer table which corresponds to the computer on which SAP is installed.
SAPBaseLicenseTypeID	<i>Type:</i> integer The SAP base license type, coming from the first pair of symbols in the “xx-xx-xx” license code. Foreign key to the SAPSoftwareLicenseType table.
SAPSpecialVersionID	<i>Type:</i> integer The SAP special version (language, country, etc.), coming from the second pair of symbols in the “xx-xx-xx” license type code. Foreign key to the SAPSoftwareLicenseType table.
SAPSurchargeID	<i>Type:</i> integer The SAP surcharge special version, coming from the third pair of symbols in the “xx-xx-xx” license code. Foreign key to the SAPSoftwareLicenseType table
SAPLicenseCode	<i>Type:</i> text (max 32 characters) The SAP license code, consisting of the license type, special version and surcharge.
HasUsage	<i>Type:</i> boolean Set this field to True if this license contains SAP usage/optimization information.
Description	<i>Type:</i> text (max 512 characters). Nullable A decription of the SAP license.

SAPSoftwareLicenseType Table

SAPSoftwareLicenseType lists the SAP base license types and special versions, and is part of the full “xx-xx-xx” code.

 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 383: Database columns for SAPSoftwareLicenseType table

Database Column	Details
SAPSoftwareLicenseTypeID	Type: integer. Key. Generated ID A unique identifier for this SAP base license type.
LicenseCode	Type: text (max 32 characters). Key The unique code for this license type - one of the “xx” parts of the full “xx-xx-xx” code.
SAPSpecialVersionID	Type: integer. Key. Nullable If this is a base license type, this field is NULL (and the LicenseCode comes from the first “xx” part of the full “xx-xx-xx” code). Otherwise, it is a special SAP version (the LicenseCode comes from the second or third “xx” part), and is foreign key to the SAPSpecialVersion table.
DescriptionResourceName	Type: text (max 256 characters). Nullable The unique name of the localizable resource string representing the license code description. Foreign key to the ComplianceResourceString table.
DescriptionDefaultValue	Type: text (max 256 characters) The text to display if the license code resource string has no translation.

SAPSpecialVersion Table

SAPSpecialVersion lists the types of special versions, indicating which part of the “xx-xx-xx” code the SAP software license type comes from.

Table 384: Database columns for SAPSpecialVersion table

Database Column	Details
SAPSpecialVersionID	<i>Type:</i> integer. Key. Generated ID A unique identifier for each SAPSpecialVersion. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• 1 = Generic special version• 2 = Surcharge special version.
InternalDescription	<i>Type:</i> text (max 50 characters) Internal description for developers.

ServicePack Table

Table 385: Database columns for ServicePack table

Database Column	Details
ServicePackID	<i>Type:</i> integer. Key. Generated ID A unique identifier for an ARL published service pack.
ServicePackUID	<i>Type:</i> integer. Key Factory generated identifier.
ServicePackNameID	<i>Type:</i> integer. Key Name of the service pack published by software publisher. Foreign key to the ServicePackName table.
ReleaseDate	<i>Type:</i> datetime. Nullable The availability date.
EndOfSupportDate	<i>Type:</i> datetime. Nullable The end of availability date.
Notes	<i>Type:</i> text. Nullable Notes for this service pack

ServicePackName Table

Table 386: Database columns for ServicePackName table

Database Column	Details
ServicePackNameID	Type: integer. Key. Generated ID A unique identifier for service pack.
Name	Type: text (max 256 characters). Key The service pack name

SoftwareAccessDeviceLicensePointsConsumedData Table

SoftwareAccessDeviceLicensePointsConsumed records how many license entitlements have been consumed for a given license by a given accessing device.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 387: Database columns for SoftwareAccessDeviceLicensePointsConsumedData table

Database Column	Details
AccessingDeviceID	<i>Type:</i> integer. Key. Nullable The accessing device under examination. Foreign key to the AccessingDevice table.
ComplianceComputerID	<i>Type:</i> integer. Key. Nullable The compliance computer under examination. Foreign key to the ComplianceComputer table.
SoftwareLicenseID	<i>Type:</i> integer. Key The license being assessed. Foreign key to the SoftwareLicense table.
LicensesUsed	<i>Type:</i> integer How many of the points consumed are for installations actually being used.
LicenseMeasurementID	<i>Type:</i> integer. Key The license measurement ID. Foreign key to the LicenseMeasurement table.
CalculatedConsumption	<i>Type:</i> integer The calculated consumption value for this license assignment before exemptions or overrides are considered.

SoftwareAccessMode Table

The SoftwareAccessMode table holds the states an application has been accessed.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 388: Database columns for SoftwareAccessMode table

Database Column	Details
SoftwareAccessModeID	Type: integer. Key. Generated ID The primary key of the SoftwareAccessMode table.
AccessModeID	Type: integer. Key The access mode for the application. Foreign key to the AccessMode table.
InstalledSoftwareID	Type: integer. Key The installed software title to which the access mode applies. Foreign key to the InstalledSoftware table
IsACL	Type: boolean. Key Determines whether the software access mode record came from ACL data.

SoftwareAccessUserLicensePointsConsumedData Table

SoftwareAccessUserLicensePointsConsumed records how many license entitlements have been consumed for a given license by a given accessing user.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 389: Database columns for SoftwareAccessUserLicensePointsConsumedData table

Database Column	Details
AccessingUserID	Type: integer. Key. Nullable The accessing user under examination. Foreign key to the AccessingUser table.
ComplianceUserID	Type: integer. Key. Nullable The compliance user under examination. Foreign key to the ComplianceUser table.
SoftwareLicenseID	Type: integer. Key The license being assessed. Foreign key to the SoftwareLicense table.
LicensesUsed	Type: integer How many of the points consumed are for installations actually being used.
LicenseMeasurementID	Type: integer. Key The license measurement ID. Foreign key to the LicenseMeasurement table.
CalculatedConsumption	Type: integer The calculated consumption value for this license assignment before exemptions or overrides are considered.

SoftwareLicense Table

SoftwareLicense contains details of the software licenses managed by FlexNet Manager Suite.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 390: Database columns for SoftwareLicense table

Database Column	Details
SoftwareLicenseID	Type: integer. Key. Generated ID A unique identifier for a software license.
ParentLicenseID	Type: integer. Key. Nullable The id of any bundle that this license is a part of.
Name	Type: text (max 256 characters). Key Name of the license.
Version	Type: text (max 60 characters). Key. Nullable Version of the license.
Edition	Type: text (max 60 characters). Nullable Edition of the license.
LicenseTypeID	Type: integer. Key The license type. Foreign key to the SoftwareLicenseType table.
SoftwareLicenseMetricID	Type: integer. Nullable Custom licensing metric for this license. Foreign key to the SoftwareLicenseMetric table.
DurationID	Type: integer The duration of this license. Foreign key to the SoftwareLicenseDuration table.
SoftwareLicense ComplianceStatusID	Type: integer The compliance status of this license. Foreign key to the SoftwareLicenseComplianceStatus table. Defaults to "Compliant".
LicenseStatusID	Type: integer The status of this license. Foreign key to the LicenseStatus table.

Database Column	Details
SoftwareLicensePurchaseTypeID	<i>Type:</i> integer. Nullable The kind of purchase. Foreign key to the SoftwareLicensePurchaseType table.
VendorID	<i>Type:</i> integer. Key. Nullable The vendor from whom the license was purchased. Foreign key to the Vendor table.
PublisherID	<i>Type:</i> integer. Key. Nullable The software publisher associated with this license. Foreign key to the Vendor table.
ManagerID	<i>Type:</i> integer. Key. Nullable The manager of this license. Foreign key to the ComplianceUser table.
PartNo	<i>Type:</i> text (max 100 characters). Nullable The publisher's part number for this license.
SerialNumber	<i>Type:</i> text (max 256 characters). Nullable The serial number of the license.
LicenseKeyTypeID	<i>Type:</i> integer The type of license keys managed on this license. Foreign key to the SoftwareLicenseKeyType table. Defaults to "No key".
LicenseKey	<i>Type:</i> text (max 256 characters). Nullable The multiple-use license key of the license. Only used when the license key type is a multi-use key (for example, an Enterprise key used to cover multiple installs).
RequestNo	<i>Type:</i> text (max 60 characters). Nullable The request number for the license.
AcquisitionModeID	<i>Type:</i> integer The method of acquisition used for the asset this license covers. Defaults to Purchased. Foreign key to the AcquisitionMode table.
PurchaseOrderNumber	<i>Type:</i> text (max 50 characters). Nullable The purchase order number which was used to purchase the license.
PurchaseOrderDate	<i>Type:</i> datetime. Nullable The original purchase order date for the license.
PurchasePrice	<i>Type:</i> currency. Nullable The initial purchase price of the license.

Database Column	Details
PurchasePriceRateID	<p><i>Type:</i> integer. Nullable</p> <p>The currency rate applied to the purchase price of the license. Foreign key to the CurrencyRate table.</p>
ChargeBackPrice	<p><i>Type:</i> currency. Nullable</p> <p>Amount to be charged for each computer on which the license is installed.</p>
ChargeBackPriceRateID	<p><i>Type:</i> integer. Nullable</p> <p>The currency rate applied to the charge-back price. Foreign key to the CurrencyRate table.</p>
ChargeBackPeriodTypeID	<p><i>Type:</i> integer</p> <p>The frequency with which the charge back price is charged. Defaults to None. Foreign key to the PeriodType table.</p>
ExpiryDate	<p><i>Type:</i> datetime. Nullable</p> <p>The date this license expires. A NULL value means the license does not expire.</p>
DeliveryDate	<p><i>Type:</i> datetime. Nullable</p> <p>The date this license became active. A NULL value means the license is inactive.</p>
RetirementDate	<p><i>Type:</i> datetime. Nullable</p> <p>The date this license was retired. A NULL value means the license is active.</p>
WarrantyExpiryDate	<p><i>Type:</i> datetime. Nullable</p> <p>The date the warranty on this license expires. This refers to a warranty Contract associated with the license.</p>
NumberOfProcessors	<p><i>Type:</i> integer</p> <p>The number of processors that this license is for. This field is only used where the SoftwareLicenseType is Device (Processor-Limited) (LicenseTypeID = 11).</p>
NumberOfCores	<p><i>Type:</i> integer</p> <p>The number of cores per processor that this license is for. This field is only used where the SoftwareLicenseType is Device (Core-Limited) (LicenseTypeID = 14).</p>
NumberOfSockets	<p><i>Type:</i> integer</p> <p>The number of sockets that this license is for. The value zero is reserved to mean unlimited. This field is only used where the SoftwareLicenseType is Oracle Processor (LicenseTypeID = 16) or Oracle Named User Plus (LicenseTypeID = 17).</p>

Database Column	Details
MinimumNumberOfProcessors	<p><i>Type:</i> integer</p> <p>The minimum number of processors that this license is for. This field is only used where the SoftwareLicenseType is Microsoft Server Processor (LicenseTypeID = 22).</p>
MinimumNumberOfLicensesPerVM	<p><i>Type:</i> integer</p> <p>When licensing a Virtual Hardware System with a Microsoft Server Core license (LicenseTypeID = 33), consume license entitlements as though the virtual machine had at least this number of virtual threads.</p>
MSPool	<p><i>Type:</i> text (max 120 characters). Nullable</p> <p>The name of the Microsoft license pool to which the license belongs.</p>
MSPoints	<p><i>Type:</i> integer</p> <p>The points value of each installed version of this license, for use when calculating Microsoft licensing reports. This field is only valid when the MSPool field is set.</p>
WarrantyTypeID	<p><i>Type:</i> integer</p> <p>The type of warranty for the license. Defaults to None. Foreign key to the AssetWarrantyType table.</p>
EndOfLifeRecipient	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>The person or organization who received the asset associated with this license when it was disposed of.</p>
EndOfLifeReasonID	<p><i>Type:</i> integer</p> <p>The reason the asset was associated with this license was disposed of. Foreign key to the EndOfLifeReason table.</p>
ResalePrice	<p><i>Type:</i> currency. Nullable</p> <p>The amount the asset associated with this license was sold for.</p>
ResalePriceRateID	<p><i>Type:</i> integer. Nullable</p> <p>The currency rate to be applied to the sale price of the asset associated with this license.</p>
CreationUser	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>The operator who created this license.</p>
CreationDate	<p><i>Type:</i> datetime</p> <p>The date and time the license was created.</p>
UpdatedUser	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>The operator who last updated this license.</p>

Database Column	Details
UpdatedDate	<i>Type:</i> datetime. Nullable The date and time the license was last updated.
Comments	<i>Type:</i> text. Nullable Comments about the license recorded by an operator. This field may also be used for storing license keys.
NumberPurchased	<i>Type:</i> integer The quantity of purchased license entitlements.
NumberInstalled	<i>Type:</i> integer The quantity of software installations accounted for by this license. This value is calculated and updated during the data import process, based on the software inventory details imported.
NumberCalculated	<i>Type:</i> integer The calculated consumption value for this license.
ResourceUnitsConsumed	<i>Type:</i> decimal The quantity consumed of a resource relevant to this license. The type of resource is identified by the associated <code>SoftwareLicenseMetric</code> . On the IBM Resource Value Unit license type this will have a points rule set applied to it to calculate the final license consumption value.
PeakConsumed	<i>Type:</i> integer The peak quantity of software installations accounted for by this license. This value is a high-water mark of the Consumed entitlements for the license.
AdditionalBulkUsers Regular	<i>Type:</i> integer A number of regular users associated with this license in addition to those specified individually in <code>SoftwareLicenseAllocation</code> . For IBM User Value Unit licenses this will have a points rule set applied to it to calculate the final license consumption value.
AdditionalBulkUsers Infrequent	<i>Type:</i> integer A number of infrequent users associated with this license in addition to those specified individually in <code>SoftwareLicenseAllocation</code> . For IBM User Value Unit licenses this will have an infrequent user multiplier and points rule set applied to it to calculate the final license consumption value.
AdditionalBulkUsers External	<i>Type:</i> integer A number of external users associated with this license in addition to those specified individually in <code>SoftwareLicenseAllocation</code> . For IBM User Value Unit licenses this will have an external user multiplier and points rule set applied to it to calculate the final license consumption value.

Database Column	Details
UserMultiplierInfrequent	<i>Type:</i> decimal The fraction of a regular user's consumption to use for infrequent users.
UserMultiplierExternal	<i>Type:</i> decimal The fraction of a regular user's consumption to use for external users.
NumberUsed	<i>Type:</i> integer The number of software installations covered by this license that are actually being used.
NumberAllocated	<i>Type:</i> integer The quantity of license entitlements allocated to individual end-users or computers.
NumberAssigned	<i>Type:</i> integer The quantity of license entitlements that have been assigned to enterprise groups.
NumberOverridden	<i>Type:</i> integer The quantity of overridden consumption allocated to individual end-users or computers.
LastCalculatedNUPMinimum	<i>Type:</i> integer. Nullable The last calculated minimum for Oracle Named User Plus licenses.
AlwaysInstalled	<i>Type:</i> boolean If this field is True, this license is considered in to be used whenever it is allocated. If False, software usage is considered separately, and allocation merely defines the corporation's modelling of who is expected to consume entitlements.
LocationID	<i>Type:</i> text (max 128 characters). Key. Nullable Any enterprise location linked to this license. Foreign key to the GroupEx table.
BusinessUnitID	<i>Type:</i> text (max 128 characters). Key. Nullable Any enterprise corporate unit linked to this license. Foreign key to the GroupEx table.
CostCenterID	<i>Type:</i> text (max 128 characters). Key. Nullable Any cost center in the enterprise that is linked to this license. Foreign key to the GroupEx table.
CategoryID	<i>Type:</i> text (max 128 characters). Key. Nullable Any enterprise category associated with this license. Foreign key to the GroupEx table.

Database Column	Details
CoverInstallsOnVirtual Machines	<p><i>Type:</i> boolean</p> <p>This is known in the UI as “Enable special handling for virtual machines”.</p> <p>Its effect usually includes enabling sub-capacity licensing of virtual installs and/or capping of license consumption at the host level, but its exact effect depends on the specific license type.</p> <p>For license types that expose additional virtualization properties, this property must be set for the other properties to be used.</p>
LimitNumberOfVirtual Installs	<p><i>Type:</i> boolean</p> <p>If this field is <code>True</code>, there is a limit to the number of installations on virtual machines that can be covered by each license entitlement. If <code>False</code>, one license entitlement may cover use on any number of virtual machines (typically on one host computer).</p>
NumberOfAllowedVirtual Installs	<p><i>Type:</i> integer. Nullable</p> <p>If the license covers installations on virtual machines, this field specifies how many installations per host are allowed before an additional license entitlement (or point) is consumed.</p>
LimitVirtualInstalls IncludesHost	<p><i>Type:</i> boolean</p> <p>If this field is <code>True</code>, the host operating system installations are included in the overall count of operating systems on the host when there is a limit on the number of allowed virtual installs for each license. If <code>False</code>, the host operating system is not considered when determining virtual install limits.</p>
NumberOfAllowed ProcessorsPerHost	<p><i>Type:</i> integer. Nullable</p> <p>This field specifies how many processors per host are allowed before an additional license entitlement (or point) is consumed. Null provides the default of 1. Zero provides unlimited.</p>
UseHostProcessor Information	<p><i>Type:</i> boolean</p> <p>If virtual installs are allowed, set this field to <code>True</code> if host information should be used when calculating license points consumed.</p>
AllowIBMPVUSubCapacity FromNonILMT	<p><i>Type:</i> boolean</p> <p>If the license does not use host processor information (not full capacity), set this field to <code>True</code> to allow non-ILMT sub-capacity PVU consumption calculations to be used.</p>
LimitNumberOf ApplicationsEach LicensePointCovers	<p><i>Type:</i> boolean</p> <p>If this field is <code>True</code>, there is a limit on the number of application installations allowed per license entitlement (or point). If <code>False</code> (the default), then a license entitles you to any number of installations of software linked to this license on the one computer.</p>

Database Column	Details
NumberOfApplication InstallsAllowedPer LicensePoint	<i>Type:</i> integer. Nullable Where the previous field is set to True, this field defines the limited number of application installations allowed per entitlement (or point).
LimitNumberOfComputers UserLicenseCanBe InstalledOn	<i>Type:</i> boolean If this field is True, there is a limit to the number of computers that a user-based license can be linked to per entitlement (or point) consumed. If False (the default), a single end-user is entitled to install related software for his/her own use on any number of computers.
NumberOfComputers AllowedPerUserLicense Point	<i>Type:</i> integer. Nullable Where the previous field is set to True, this field defines the limited number of application installations an end-user is allowed per entitlement (or point).
MinimumNumberOfUsers	<i>Type:</i> integer The minimum number of users allowed for the license. This is used for Oracle Named User Plus licenses.
MinimumNumberOfUsers MultipliedByProcessors	<i>Type:</i> boolean Whether the previous field a fixed value for the license or it is a multiple of the number of processor points consumed by the license. This is used for Oracle Named User Plus licenses.
SecondUsageWorkLaptop	<i>Type:</i> boolean If this field is True, the license confers the right of second use on a work laptop. If False, there is no right of second use allowed on a work laptop.
SecondUsageAtHome	<i>Type:</i> boolean If this field is True, the license confers the right of second use on a home computer by the same end-user as the primary end-user of the license entitlement consumed at work. If False (the default), there is no right of second use allowed on a home computer.
MultiUseInheritFrom Contract	<i>Type:</i> boolean Set this field to True if the license should inherit the values for right of multiple use from a contract.
MultiUseInheritFrom ContractID	<i>Type:</i> integer. Nullable If the previous field is True, this is the contract that right of multiple use is inherited from. Foreign key to Contract table.
SecondUsageInheritFrom Contract	<i>Type:</i> boolean Set this field to True if the license should inherit the values for right of second use from a contract.

Database Column	Details
SecondUsageInheritFromContractID	<p><i>Type:</i> integer. Nullable</p> <p>If the previous field is True, this is the contract that right of second use is inherited from. Foreign key to Contract table.</p>
CoverInstallsOnVMInheritFromContract	<p><i>Type:</i> boolean</p> <p>Set this field to True if the license should inherit virtual machine rights from a contract.</p>
CoverInstallsOnVMInheritFromContractID	<p><i>Type:</i> integer. Nullable</p> <p>If the previous field is True, this is the contract that virtual machine rights are inherited from. Foreign key to Contract table.</p>
AutoManageTitles	<p><i>Type:</i> boolean</p> <p>Set this field to True if the license should have its application links automatically managed for upgrade and downgrade rights. When this field is False, the operator must manually manage links between this license and any applications.</p>
DowngradeOnlyToVersionLegacy	<p><i>Type:</i> text (max 60 characters). Nullable</p> <p>A repository for backward-compatible custom data.</p>
UpgradeOnlyToVersionLegacy	<p><i>Type:</i> text (max 60 characters). Nullable</p> <p>A repository for backward-compatible custom data.</p>
TrueUp	<p><i>Type:</i> boolean</p> <p>Set this field to True if the license is a true-up license (and so never goes into breach).</p>
OracleLegacyLicenseTypeID	<p><i>Type:</i> integer. Key. Nullable</p> <p>The specific Oracle legacy license type, where appropriate. Foreign key to the OracleLegacyLicenseType table.</p>
GroupAllocationTypeID	<p><i>Type:</i> integer. Key</p> <p>Allocations of entitlements under any license can be made to only one type of enterprise group, specified here. Foreign key to the GroupType table.</p>
GroupAllocationReportingTypeID	<p><i>Type:</i> integer. Key</p> <p>Determines when enterprise groups will be considered to have breached their allocations of entitlements under this license. Foreign key to the SoftwareLicenseGroupAllocationReportingType table.</p>
GroupAllocationComplianceLevel	<p><i>Type:</i> integer. Nullable</p> <p>Determines the depth level of groups to be used for calculating the breach status for a license.</p>

Database Column	Details
CannotManuallyUpdateGroupAssignments	<p><i>Type:</i> boolean</p> <p>Set this field to True if the operator must make group assignments through a Assign License Entitlements dialog box. If False, changes can be made directly in the license properties pages.</p>
CalculateCompliance	<p><i>Type:</i> boolean</p> <p>When this field is True (the default), and the associated SoftwareLicenseType also has its CalculateCompliance field set to True (true for most license types), license consumption must be calculated from imported inventory. When False, the compliance state must be imported, not calculated.</p>
IsSharableToLibrary	<p><i>Type:</i> boolean</p> <p>Set this field to True (the default) if the license is sharable to the downloadable FlexNet Manager Suite ARL library.</p>
CopyEditionAndVersion	<p><i>Type:</i> boolean</p> <p>Set this field to True (the default) if edition and version should be automatically copied to the license from the primary application.</p>
SoftwareLicenseTierTypeID	<p><i>Type:</i> integer. Key. Nullable</p> <p>Type of the tier, for Tiered Device license type only. Foreign key to the SoftwareLicenseTierType table.</p>
SoftwareLicenseTierCode	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>The actual tier of the license, corresponding to the tier type. For Tiered Device license type only.</p>
ImportedFromFNMEA	<p><i>Type:</i> boolean</p> <p>Set this to True if this license was imported from FlexNet Manager for Engineering Applications.</p>
SoftwareLicensePointsRuleSetID	<p><i>Type:</i> integer. Key. Nullable</p> <p>The points rule set used to calculate compliance for this license. Foreign key to the SoftwareLicensePointsRuleSet table.</p>
BaselineQuantity	<p><i>Type:</i> integer. Nullable</p> <p>The baseline value for this license</p>
BaselineDate	<p><i>Type:</i> datetime. Nullable</p> <p>The date at which the baseline applies.</p>

Database Column	Details
AlternateNon InventoriedUsers	<p><i>Type:</i> integer. Nullable</p> <p>Number of non-inventoried users who are consuming this license. For Oracle Named User Plus and Oracle Application User licenses, this acts as an alternate mean to specify user consumption in the case where no instance users are available from inventory. The number of non-inventoried users are added to the number of unique users found from inventory when number installed and number used are calculated in license reconcile.</p>
InheritLicenseMobility FromContract	<p><i>Type:</i> boolean</p> <p>Set this field to True if this license inherits its license mobility rights from a contract. If False (the default), license mobility rights must be configured directly on the license properties.</p>
InheritLicenseMobility FromContractID	<p><i>Type:</i> integer. Nullable</p> <p>If the previous field is True, this is the contract that mobility rights are inherited from. Foreign key to the Contract table.</p>
InheritLicense ConsumptionFromContract	<p><i>Type:</i> boolean</p> <p>Set this field to True if this license inherits its license consumption rules from a contract. If False (the default), license consumption rules must be configured directly on the license properties.</p>
InheritLicense ConsumptionFrom ContractID	<p><i>Type:</i> integer. Nullable</p> <p>If the previous field is True, this is the contract that license consumption rules are inherited from. Foreign key to the Contract table.</p>
InheritProcessorLimits FromContract	<p><i>Type:</i> boolean</p> <p>Set this field to True if this license inherits its processor limits rights from a contract. If False (the default), license processor limits rights must be configured directly on the license properties.</p>
InheritProcessorLimits FromContractID	<p><i>Type:</i> integer. Nullable</p> <p>If the previous field is True, this is the contract that processor limits rights are inherited from. Foreign key to the Contract table.</p>
AllowMaintenanceToExpire	<p><i>Type:</i> boolean</p> <p>If the value True, maintenance added to license will not be renewed. If this flag is set, use rights for this license will be automatically updated once the maintenance expires.</p>
AutoSynchronized	<p><i>Type:</i> boolean</p> <p>If the value is True the license information will be synchronized with the information from the source connection.</p>

Database Column	Details
UseRightsAutoUpdated	<i>Type:</i> boolean If the value True, the use rights of this license has been automatically updated when all the maintenace expired. Else, use rights has not been updated.

SoftwareLicenseAllocation Table

SoftwareLicenseAllocation records the allocations of individual computers, end-users, enterprise groups or instances to licenses.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 391: Database columns for SoftwareLicenseAllocation table

Database Column	Details
SoftwareLicenseAllocationID	Type: integer. Key. Generated ID A unique identifier for the license allocation record.
SoftwareLicenseID	Type: integer. Key The license that has been allocated. Foreign key to the SoftwareLicense table.
ComplianceComputerID	Type: integer. Key. Nullable The computer to which the license is allocated. Foreign key to the ComplianceComputer table.
ComplianceUserID	Type: integer. Key. Nullable The end-user to which the license is allocated. Foreign key to the ComplianceUser table.
InstanceID	Type: integer. Key. Nullable The instance to which the license is allocated. Foreign key to the Instance table.
GroupExID	Type: text (max 128 characters). Key. Nullable The enterprise group to which the license is assigned. Foreign key to the GroupEx table.
LicenseUserID	Type: integer. Key. Nullable The external end-user to whom the license is allocated. Foreign key to the LicenseUser table.
AccessingUserID	Type: integer. Key. Nullable The external accessing user to whom the license is allocated. Foreign key to the AccessingUser table.

Database Column	Details
SoftwareLicense AllocationUserTypeID	<i>Type:</i> integer. Key. Nullable Indicates for user allocations whether they are a regular user or some special type of user for this license. Foreign key to the SoftwareLicenseAllocationUserType table.
NumberAllocated	<i>Type:</i> integer. Nullable The number of license entitlements assigned. This is used for group assignments.
NumberUsed	<i>Type:</i> integer. Nullable The number of license entitlements where the application is recorded as being used.
SoftwareLicense AllocationStatusID	<i>Type:</i> integer. Nullable Indicates the status of an allocation. Foreign key to the SoftwareLicenseAllocationStatus table.
SoftwareLicenseKeyID	<i>Type:</i> integer. Key. Nullable The software license key that is allocated to this end-user/computer. Foreign key to the SoftwareLicenseKey table.
SoftwareLicense ExemptionReasonID	<i>Type:</i> integer. Key. Nullable The reason why this allocation is exempted from consuming a license entitlement. Foreign key to the SoftwareLicenseExemptionReason table.

SoftwareLicenseAllocationStatus Table

SoftwareLicenseAllocationStatus is a static table storing a collection of status values for a license allocation.

Table 392: Database columns for SoftwareLicenseAllocationStatus table

Database Column	Details
SoftwareLicenseAllocationStatusID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each SoftwareLicenseAllocationStatus. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = Allocated• 2 = Awaiting Inventory• 3 = Permanent• 4 = Unallocated.
StatusResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing an allocation status. Foreign key to the ComplianceResourceString table.</p>
StatusDefaultValue	<p><i>Type:</i> text (max 50 characters)</p> <p>The text to display if the status resource string has no translation.</p>

SoftwareLicenseAllocationUserType Table

SoftwareLicenseAllocationUserType is a static table storing a collection of user type values for a license allocation.

Table 393: Database columns for SoftwareLicenseAllocationUserType table

Database Column	Details
SoftwareLicense	<i>Type:</i> integer. Key. Generated ID
AllocationUserID	A unique identifier for each SoftwareLicenseAllocationUserType. Possible values and the corresponding default strings are: <ul style="list-style-type: none"> • 1 = Normal • 2 = Infrequent • 3 = External.
UserTypeResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing a user allocation type. Foreign key to the ComplianceResourceString table.
UserTypeDefaultValue	<i>Type:</i> text (max 50 characters) The text to display if the user type resource string has no translation.

SoftwareLicenseBreachReasonData Table

SoftwareLicenseBreachReasonData identifies the reasons why non-compliant software licenses are in this state.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 394: Database columns for SoftwareLicenseBreachReasonData table

Database Column	Details
SoftwareLicenseID	Type: integer. Key The software license. Foreign key to the SoftwareLicense table.
LicenseBreachReasonID	Type: integer. Key The license breach reason. Foreign key to the LicenseBreachReason table.
LicenseMeasurementID	Type: integer. Key The license measurement ID. Foreign key to the LicenseMeasurement table.

SoftwareLicenseChangeEvent Table

The SoftwareLicenseChangeEvent table holds the details of all license change events.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 395: Database columns for SoftwareLicenseChangeEvent table

Database Column	Details
ComplianceEventID	<i>Type:</i> integer. Key A unique identifier and foreign key to the ComplianceEvent table.
SoftwareLicenseID	<i>Type:</i> integer. Key The license involved in the change event. Foreign key to the SoftwareLicense table.
SoftwareTitleID	<i>Type:</i> integer. Key The software title that needs to be added or removed. Foreign key to the SoftwareTitle table.
SoftwareLicenseChangeEventSourceID	<i>Type:</i> integer What caused the event. Foreign key to the SoftwareLicenseChangeEventSource table.
SoftwareLicenseChangeEventReasonID	<i>Type:</i> integer The type of event. Foreign key to the SoftwareLicenseChangeEventReason table.
SoftwareTitleLicenseReasonID	<i>Type:</i> integer. Nullable When a software title has been added to a license, the reason it has been added (ie because upgrade rights allow it, for example). Foreign key to the SoftwareTitleLicenseReason table.

SoftwareLicenseChangeEventReason Table

SoftwareLicenseChangeEventReason is a static table holding all the valid reasons why a license change event was generated.

Table 396: Database columns for SoftwareLicenseChangeEventReason table

Database Column	Details
SoftwareLicenseChangeEventReasonID	<i>Type:</i> integer. Key. Generated ID A unique identifier for each SoftwareLicenseChangeEventReason. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• 1 = Add Application• 2 = Remove Application.
ChangeEventReasonResourceString	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing a change event reason. Foreign key to the ComplianceResourceString table.
ChangeEventReasonDefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the reason resource string has no translation.

SoftwareLicenseChangeEventSource Table

SoftwareLicenseChangeEventSource is a static table holding all the valid sources of license change events.

Table 397: Database columns for SoftwareLicenseChangeEventSource table

Database Column	Details
SoftwareLicenseChangeEventSourceID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each SoftwareLicenseChangeEventSource. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = ARL • 2 = Software License • 3 = Software Title (the application properties) • 4 = Contract • 5 = Version (changing the relative priorities or weights of application versions linked to a license) • 6 = Edition (changing the relative priorities or weights of application editions linked to a license).
ChangeEventSourceResourceString	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a change event source. Foreign key to the ComplianceResourceString table.</p>
ChangeEventSourceDefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>Default value for a license change event source if the source resource has no translation.</p>

SoftwareLicenseComplianceStatus Table

SoftwareLicenseComplianceStatus is a static table listing valid compliance states for a license.

Table 398: Database columns for SoftwareLicenseComplianceStatus table

Database Column	Details
SoftwareLicense ComplianceStatusID	<i>Type:</i> integer. Key. Generated ID A unique identifier for each SoftwareLicenseComplianceStatus. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• 1 = Compliant• 2 = In Breach• 3 = Unknown• 4 = Not Tracked.
StatusResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing a compliance status. Foreign key to the ComplianceResourceString table.
StatusDefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the status resource string has no translation.

SoftwareLicenseComputerProblemData Table

SoftwareLicenseComputerProblemData identifies the problems with individual ComplianceComputers that contributed to an associated license having an unknown compliance status. For example, some license types caculate entitlement consumption based on the number of processor cores present in a computer, but that detail is not available from Microsoft SCCM before version 2012, so computers from this inventory source will cause associated licenses to have unknown compliance status.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 399: Database columns for SoftwareLicenseComputerProblemData table

Database Column	Details
SoftwareLicenseID	Type: integer. Key The software license. Foreign key to the SoftwareLicense table.
ComplianceComputerID	Type: integer. Key The computer consuming license entitlements. Foreign key to the ComplianceComputer table.
SoftwareLicense ComputerProblemTypeID	Type: integer The type of problem this computer’s inventory causes for a given license. For example, core-based licenses require accurate inventory of processor core counts to determine ther compliance status. Foreign key to the SoftwareLicenseComputerProblemType table.
LicenseMeasurementID	Type: integer. Key The license measurement ID. Foreign key to the LicenseMeasurement table.

SoftwareLicenseComputerProblemType Table

SoftwareLicenseComputerProblemType is a static table holding the collection of problems that a computer can have which might cause a particular type of license to have an unknown compliance status.

Table 400: Database columns for SoftwareLicenseComputerProblemType table

Database Column	Details
SoftwareLicense	Type: integer. Key. Generated ID
ComputerProblemTypeID	A unique identifier for each SoftwareLicenseComputerProblemType. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• 1 = Core count missing from inventory• 2 = Processor count missing from inventory• 3 = Socket count missing from inventory• 4 = Thread count missing from inventory.
ProblemTypeResourceName	Type: text (max 256 characters). Key The unique name of the localizable resource string representing a problem type. Foreign key to the ComplianceResourceString table.
ProblemTypeDefaultValue	Type: text (max 512 characters) The text to display if the problem type resource string has no translation.

SoftwareLicenseConnection Table

SoftwareLicenseConnection stores a link between software licenses in SoftwareLicense which have been reported in inventory, and external IDs which can be used to identify them in their inventory sources.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 401: Database columns for SoftwareLicenseConnection table

Database Column	Details
SoftwareLicenseID	Type: integer. Key A unique identifier for the software license. Foreign key to the SoftwareLicense table.
ComplianceConnectionID	Type: integer. Key The inventory source where the software license was reported. Foreign key to the ComplianceConnection table.
ExternalLicenseID	Type: big integer. Key A (hopefully unique) identifier for the software license in the external inventory source.

SoftwareLicenseContract Table

SoftwareLicenseContract links licenses to related contracts.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 402: Database columns for SoftwareLicenseContract table

Database Column	Details
SoftwareLicenseContractID	<i>Type:</i> integer. Key. Generated ID A unique identifier for this record.
SoftwareLicenseID	<i>Type:</i> integer. Key The license to which the contract is related. Foreign key to the SoftwareLicense table.
ContractID	<i>Type:</i> integer. Key The contract related to the license. Foreign key to the Contract table.

SoftwareLicenseCoresConsumedData Table

SoftwareLicenseCoresConsumedData records how many cores have contributed to license point consumption for a given license by a given computer.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 403: Database columns for SoftwareLicenseCoresConsumedData table

Database Column	Details
ComplianceComputerID	<i>Type:</i> integer. Key The computer under examination. Foreign key to the ComplianceComputer table.
SoftwareLicenseID	<i>Type:</i> integer. Key The license being assessed. Foreign key to the SoftwareLicense table.
CoresConsumed	<i>Type:</i> integer The number of cores that have contributed to license point consumption for the license on the computer.
LicenseMeasurementID	<i>Type:</i> integer. Key The license measurement ID. Foreign key to the LicenseMeasurement table.
CalculatedConsumption	<i>Type:</i> integer The calculated consumption value for this license assignment before exemptions or overrides are considered.

SoftwareLicenseCreation Table

SoftwareLicenseCreation records which SKU definition was used to create a software license.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 404: Database columns for SoftwareLicenseCreation table

Database Column	Details
SoftwareLicenseCreationID	Type: integer. Key. Generated ID A unique identifier for this record.
SoftwareLicenseID	Type: integer. Key The software license created. Foreign key to the SoftwareLicense table.
SoftwareSkuID	Type: integer. Key. Nullable The SKU that was recognized. This value is optional, as the software license could have been created directly using a definition selected by the operator, without a SKU being used as the link. Foreign key to the SoftwareSku table.
SoftwareLicenseDefinitionID	Type: integer. Key The license definition used to create the software license. Foreign key to the SoftwareLicenseDefinition table.
LicenseDefinitionVersion	Type: integer. Key Which version of the license definition was used to create the software license.

SoftwareLicenseDefinition Table

SoftwareLicenseDefinition maps SKUs to the license definitions and applications that it relates to.

Table 405: Database columns for SoftwareLicenseDefinition table

Database Column	Details
SoftwareLicense DefinitionID	<i>Type:</i> integer. Key. Generated ID A unique identifier for this record.
LicenseDefinition FactoryUID	<i>Type:</i> text (max 30 characters). Key The FlexNet Manager Suite factory unique identifier for this record.
NonMaintenanceLicense DefinitionFactoryUID	<i>Type:</i> text (max 30 characters). Key. Nullable The FlexNet Manager Suite factory without maintenance for this record.
LicenseDefinitionTypeID	<i>Type:</i> integer. Key The license definition type. Foreign key to the LicenseDefinitionType table.
LicenseDefinition	<i>Type:</i> text The license definition. Contains information relevant to license creation and application links.
ProductName	<i>Type:</i> text (max 2000 characters) When a license is created using this definition, this will be its license name.
ProductVersion	<i>Type:</i> text (max 2000 characters) When a license is created using this definition, this will be its license version.
ProductPublisher	<i>Type:</i> text (max 2000 characters) When a license is created using this definition, this will be its license publisher.
LicenseTypeID	<i>Type:</i> integer. Key This definition will create a license of this type. Foreign key to the LicenseType table.
IsUpgrade	<i>Type:</i> boolean Set this field to True if this definition will create an upgrade license. If this field is False, this definition creates a standard license.
Version	<i>Type:</i> integer. Key The current version of this SKU definition.

Database Column	Details
PreviousVersion	<i>Type:</i> integer. Key. Nullable The version of the SKU definition prior to the current version.
CreationDate	<i>Type:</i> datetime The date that this record was created.
UpdatedDate	<i>Type:</i> datetime. Nullable The date that this record was last updated.

SoftwareLicenseDuration Table

The collection of durations for which a license can be active.

Table 406: Database columns for SoftwareLicenseDuration table

Database Column	Details
SoftwareLicenseDurationID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for a license duration. Possible values (and associated default names) are:</p> <ul style="list-style-type: none"> • 1 = Perpetual • 2 = TimeLimited • 3 = Subscription.
DurationResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The name of the resource string containing the text to display on the user interface.</p>
DurationDefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The value to display if there is no resource string available for this status</p>

SoftwareLicenseExemptionReason Table

The collection of types exemption reasons that may be associated with software license allocations.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 407: Database columns for SoftwareLicenseExemptionReason table

Database Column	Details
SoftwareLicenseExemptionReasonID	<p>Type: integer. Key. Generated ID</p> <p>A unique identifier for each SoftwareLicenseExemptionReason. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = Alpha, beta, early support program• 2 = Backup, disaster recovery• 3 = Component of a non-PVU licensed offering• 4 = Component is not compatible with the server or agent system• 5 = Development• 6 = Evaluation, trial• 7 = Fail-over• 8 = Not eligible for PVU licensing• 9 = Other• 10 = Second use• 11 = Test• 12 = Covered by related product• 13 = Covered by virtual application access• 14 = No usage for virtual application within specified time limit
ResourceName	<p>Type: text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing an exemption reason. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p>Type: text (max 100 characters)</p> <p>The text to display if the type resource string has no translation.</p>

SoftwareLicenseExemptionRole Table

SoftwareLicenseExemptionRole table holds information on role exemption rule for licenses. Contains many to many relationship between licenses and device roles.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 408: Database columns for SoftwareLicenseExemptionRole table

Database Column	Details
SoftwareLicenseExemptionRoleID	Type: integer. Key. Generated ID A unique identifier for the license exemption role record.
SoftwareLicenseID	Type: integer. Key The license that has role exemption rule. Foreign key to the SoftwareLicense table.
ExemptionRoleID	Type: integer. Key The device role that is exempted from license consumption. Foreign key to the ComplianceComputerRole table.
ExemptionLimit	Type: integer. Nullable The number of devices that can be exempted, having an exempted role.

SoftwareLicenseGroupAllocationReportingType Table

SoftwareLicenseGroupAllocationReportingType stores the set of tests that can be used to determine whether a license is in "group breach" for one or more of its associated enterprise groups.

Table 409: Database columns for SoftwareLicenseGroupAllocationReportingType table

Database Column	Details
SoftwareLicenseGroupAllocationReportingTypeID	<i>Type:</i> integer. Key. Generated ID A unique identifier for each SoftwareLicenseGroupAllocationReportingType. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• 0 = None• 1 = Consumed Exceeds Purchased• 2 = Consumed Exceeds Assigned.
ResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing a group breach test type. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 256 characters) The text to display if the type resource string has no translation.

SoftwareLicenseGroupAssignmentHistory Table

SoftwareLicenseGroupAssignmentHistory is used to keep track of changes made to assignments of software license entitlements to enterprise groups.

 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 410: Database columns for SoftwareLicenseGroupAssignmentHistory table

Database Column	Details
SoftwareLicenseGroupAssignmentHistoryID	Type: integer. Key. Generated ID A unique identifier for the history record.
GroupExID	Type: text (max 128 characters). Key This is the primary group that had a change of assignments. Foreign key to the GroupEx table.
FromGroupExID	Type: text (max 128 characters). Key. Nullable If assignments were transferred, this is the source group who had assignments taken away. Foreign key to the GroupEx table.
FromGroupExPath	Type: text (max 500 characters). Nullable The path of the group that assignments were transferred from. This field is used to display the group name (at the time that the transfer took place) when showing history after the group has been deleted.
HistoryDate	Type: datetime The date of the change.
SoftwareLicenseID	Type: integer. Key The license for which entitlements are being assigned. Foreign key to the SoftwareLicense table.
UserName	Type: text (max 60 characters) The operator who made the change.
Comments	Type: text (max 2000 characters). Nullable Comments recorded about the change.
NumberAdded	Type: integer The number of assignments added to or removed from the group.
Total	Type: integer The progressive total of assignments to the group following this change.

Database Column	Details
SoftwareLicenseGroup	Type: integer. Key
AssignmentHistoryTypeID	The type of history record. This records the kind of change that was made (eg, a flat increase/decrease of the assignment count, a transfer, and so on). Foreign key to the SoftwareLicenseGroupAssignmentHistoryType table.

SoftwareLicenseGroupAssignmentHistoryType Table

SoftwareLicenseGroupAssignmentHistoryType stores a collection of the types of history record that can be stored in the SoftwareLicenseGroupAssignmentHistory table.

Table 411: Database columns for SoftwareLicenseGroupAssignmentHistoryType table

Database Column	Details
SoftwareLicenseGroupAssignmentHistoryTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each SoftwareLicenseGroupAssignmentHistoryType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = Manual (manual increase/decrease of the group assignment quantity) • 2 = ManualDialog (manual increase/decrease of the group assignment quantity, using the Assign License Entitlements dialog_ • 3 = Transfer (a transfer of entitlements from one enterprise group to another) • 4 = ClearAssignments (the Clear Assignments button has been used to remove all entitlements from a group) • 5 = AssignPurchased (the Assign Purchases button has been used to copy purchases within the group to the group assignment total) • 6 = ChangeGroupType (assignments have been cleared because the group assignment type has been changed).
ResourceName	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>The unique name of the localizable resource string representing a history type. Foreign key to the ComplianceResourceString table.</p>
SoftwareLicenseGroupAssignmentHistoryTypeName	<p><i>Type:</i> text (max 64 characters). Key</p> <p>A description of the history type.</p>
DefaultValue	<p><i>Type:</i> text (max 50 characters)</p> <p>The text to display if the type resource string has no translation.</p>

SoftwareLicenseGroupBreachStatus Table

SoftwareLicenseGroupBreachStatus stores the collection of possible outcomes of group breach testing.

Table 412: Database columns for SoftwareLicenseGroupBreachStatus table

Database Column	Details
SoftwareLicenseGroupBreachStatusID	<i>Type:</i> integer. Key. Generated ID A unique identifier for each SoftwareLicenseGroupBreachStatus. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• 0 = Ignored• 1 = Not In Group Breach• 2 = In Group Breach.
ResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing a group breach status. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 256 characters) The text to display if the status resource string has no translation.

SoftwareLicenseGroupPointsConsumedData Table

SoftwareLicenseGroupPointsConsumed records the licenses pre-calculated local and rolledup totals for groups.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 413: Database columns for SoftwareLicenseGroupPointsConsumedData table

Database Column	Details
SoftwareLicenseID	Type: integer. Key The license that owns the pre-calculated totals for a group. Foreign key to the SoftwareLicense table.
GroupTypeID	Type: integer. Key Type of the group(Location, Cost center, etc)
GroupExID	Type: text (max 128 characters). Key. Nullable The group where the local and rolledup values are calculated. Foreign key to the GroupEx table.
RolledUpNumberConsumed	Type: integer The sum of points consumed of the current group and of all its child groups.
LocalNumberConsumed	Type: integer The sum of points consumed of the current group
RolledUpNumberUsed	Type: integer The sum of used points f the current group and of all its child groups.
LocalNumberUsed	Type: integer The sum of used points of the current group
RolledUpNumberPurchased	Type: integer The rolled up purchase counts of the license.
LocalNumberPurchased	Type: integer The local purchase counts of the license
LicenseMeasurementID	Type: integer. Key The license measurement ID. Foreign key to the LicenseMeasurement table.
RolledUpNumberCalculated	Type: integer The sum of points calculated for the current group and of all its child groups.

Database Column	Details
LocalNumberCalculated	Type: integer The sum of points calculated for the current group.

SoftwareLicenseILMTPointsConsumedData Table

SoftwareLicenseILMTPointsConsumed records how many PVU counts and their corresponding core counts have been consumed for a given license by a given computer.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 414: Database columns for SoftwareLicenseILMTPointsConsumedData table

Database Column	Details
ComplianceComputerID	<i>Type:</i> integer. Key The computer under examination. Foreign key to the ComplianceComputer table.
SoftwareLicenseID	<i>Type:</i> integer. Key The license being assessed. Foreign key to the SoftwareLicense table.
CoreCount	<i>Type:</i> integer The number of licensable cores for the license on the computer.
PVUCount	<i>Type:</i> integer The number of PVU counts consumed for the license on the computer.
PeakPVUCount	<i>Type:</i> integer The number of PVU counts consumed for the license on the computer at the time where the peak for this license occurred.
LicenseMeasurementID	<i>Type:</i> integer. Key The license measurement ID. Foreign key to the LicenseMeasurement table.
CalculatedConsumption	<i>Type:</i> integer The calculated consumption value for this license assignment before exemptions or overrides are considered.

SoftwareLicenseKey Table

The SoftwareLicenseKey table contains installation keys that are linked to software licenses.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 415: Database columns for SoftwareLicenseKey table

Database Column	Details
SoftwareLicenseKeyID	Type: integer. Key. Generated ID A unique identifier for this license key.
SoftwareLicenseID	Type: integer. Key The software license that this installation key belongs to. Foreign key to the SoftwareLicense table.
KeyValue	Type: text (max 400 characters). Key The installation key value.

SoftwareLicenseKeyType Table

The collection of types of installation keys that may be associated with software licenses.

Table 416: Database columns for SoftwareLicenseKeyType table

Database Column	Details
SoftwareLicenseTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each SoftwareLicenseKeyType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = No keys • 2 = One (multi-install) key per license • 3 = One (multi-install) key per application • 4 = One (single-install) key per installation. • 5 = One (multi-install) key per installation.
KeyTypeResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a license key type. Foreign key to the ComplianceResourceString table.</p>
KeyTypeDefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the type resource string has no translation.</p>

SoftwareLicenseMetric Table

SoftwareLicenseMetric holds the pre-defined list of licensing custom metrics.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 417: Database columns for SoftwareLicenseMetric table

Database Column	Details
SoftwareLicenseMetricID	<p>Type: integer. Key. Generated ID</p> <p>A unique identifier for each SoftwareLicenseMetric. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = \$M cost of goods sold • 2 = \$M freight under management • 3 = \$M in revenue • 4 = \$M revenue under management • 5 = Active Oracle node • 6 = Cluster • 7 = Compensated individual • 8 = Connector • 9 = Developer • 10 = Drive • 11 = Electronic order line • 12 = Employees • 13 = Expense report • 14 = External connector • 15 = External recipient • 16 = Field technician • 17 = Floating user • 18 = Form • 19 = Front end GB • 20 = Front end TB • 21 = FTE student • 22 = Gateway • 23 = Gigabyte • 24 = Guest • 25 = Host • 26 = Internet connector

Database Column	Details
	<ul style="list-style-type: none"> • 27 = IP • 28 = Mailbox • 29 = OSE • 30 = Partner organization • 31 = Person • 32 = Per 1000 invoice lines • 33 = Per 1000 records • 34 = Per rule set • 35 = Per tape drive • 36 = Port • 37 = Record • 38 = Server bundle • 39 = Service order line • 40 = Storage domain • 41 = Terabyte • 42 = Tiered NAS device • 43 = Tivoli management point • 44 = Trainee • 45 = Transaction • 46 = UPK module • 47 = Folio download • 48 = Document • 49 = Per 1000 minutes • 50 = Exam • 51 = Support incidents • 52 = Time • 53 = Recipient • 54 = Employees + non employees

Database Column	Details
	<ul style="list-style-type: none"> • 100 (Oracle Processor) = Cores • 101 (Oracle NUP) = Cores • 102 (Oracle Processor) = Sockets • 103 (Oracle NUP) = Sockets • 150 (IBM RVU) = Million Service Units • 151 (IBM RVU) = Messages • 152 (IBM RVU) = Engines • 153 (IBM RVU) = Terabytes • 154 (IBM RVU) = Tape Drives • 155 (IBM RVU) = Gigabytes • 156 (IBM RVU) = Premium Income \$US Billions (1 Resource Per US\$500M, rounded up to nearest US\$500M) • 157 (IBM RVU) = Capital Asset Value (\$US Billions) • 158 (IBM RVU) = Activated Processor Cores • 159 (IBM RVU) = Pages Per Month • 160 (IBM RVU) = Soft Goods & Services Entities • 161 (IBM RVU) = Manufactured Goods Entities • 162 (IBM RVU) = Assets & Commodities Entities • 163 (IBM RVU) = Locations Entities and Trading Partners & Parties Entities • 164 (IBM RVU) = Client Devices • 165 (IBM RVU) = Server Devices • 166 (IBM RVU) = Annual Web Sessions • 167 (IBM RVU) = 1,000 Web Interactions • 168 (IBM RVU) = 1,000,000 Data Source Records • 169 (IBM RVU) = 1,000,000 Monthly Server Calls • 170 (IBM RVU) = 1,000,000 Subscribers • 171 (IBM RVU) = 10,000 Records • 172 (IBM RVU) = 100 Records • 173 (IBM RVU) = 100,000 Records

Database Column	Details
	<ul style="list-style-type: none"> • 174 (IBM RVU) = Assets • 175 (IBM RVU) = Authorized Retail, Host, and Mobile Sites • 176 (IBM RVU) = Conversion Units • 177 (IBM RVU) = Enterprise Identifiers • 178 (IBM RVU) = Managed Devices • 179 (IBM RVU) = Records • 180 (IBM RVU) = Resources • 181 (IBM RVU) = Revenue \$US Billions • 182 (IBM RVU) = Secondary Sites • 183 (IBM RVU) = Servers • 184 (IBM RVU) = Transportation Events Per Calendar Month • 185 (IBM RVU) = Value Units • 186 (IBM RVU) = Virtual Servers • 187 (IBM RVU) = Web Pages.
SoftwareLicenseTypeID	<p><i>Type:</i> integer. Key</p> <p>The software license type to which this metric applies. Foreign key to the SoftwareLicenseType table.</p>
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a licensing metric. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the ResourceName has no translation.</p>

SoftwareLicensePartitioningDefault Table

SoftwareLicensePartitioningDefault contains the sub-capacity licensing rules: the types of virtual machines/partitions and pools which each license type treats as “hard” (able to put a hard limit on processor usage).

Table 418: Database columns for SoftwareLicensePartitioningDefault table

Database Column	Details
SoftwareLicenseTypeID	Type: integer. Key The software license type to which this rule applies. Foreign key to the SoftwareLicenseType table.
VMTypeID	Type: integer. Key. Nullable A virtual machine/partition type that is “hard” for the purposes of this license type. Foreign key to the VMType table.
VMPoolTypeID	Type: integer. Key. Nullable A virtual machine/partition pool type that is “hard” for the purposes of this license type. Foreign key to the VMPoolType table.

SoftwareLicensePoints Table

The SoftwareLicensePoints table holds the criteria for points-based licenses.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 419: Database columns for SoftwareLicensePoints table

Database Column	Details
SoftwareLicensePointsID	Type: integer. Key. Generated ID A unique identifier for a software license criterion.
SoftwareLicenseID	Type: integer. Key The license to which this information applies. Foreign key to the SoftwareLicense table.
ProcessorType	Type: text (max 256 characters). Key The type of processor a computer must have for this criterion to apply, such as "AMD" or "Intel".
ComputerModelNo	Type: text (max 128 characters). Key The model number a computer must have for this criterion to apply, such as "IBM PS701" or "IBM JS12".
MinCores	Type: integer. Key The minimum number of processor cores a computer must have for this criterion to apply.
MaxCores	Type: integer. Key The maximum number of processor cores a computer must have for this criterion to apply.
MinProcessors	Type: integer. Key The minimum number of processors a computer must have for this criterion to apply.
MaxProcessors	Type: integer. Key The maximum number of processors a computer must have for this criterion to apply.
MinSockets	Type: integer. Key The minimum number of processor sockets a computer must have for this criterion to apply.

Database Column	Details
MaxSockets	<i>Type:</i> integer. Key The maximum number of processor sockets a computer must have for this criterion to apply.
MinCoresPerSocket	<i>Type:</i> integer. Key The minimum number of processor cores per socket a computer must have for this criterion to apply.
MaxCoresPerSocket	<i>Type:</i> integer. Key The maximum number of processor cores per socket a computer must have for this criterion to apply.
Points	<i>Type:</i> decimal The points value per core or processor.

SoftwareLicensePointsConsumedData Table

SoftwareLicensePointsConsumed records how many license entitlements have been consumed for a given license by a given computer.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 420: Database columns for SoftwareLicensePointsConsumedData table

Database Column	Details
ComplianceComputerID	<i>Type:</i> integer. Key The computer under examination. Foreign key to the ComplianceComputer table.
SoftwareLicenseID	<i>Type:</i> integer. Key The license being assessed. Foreign key to the SoftwareLicense table.
LicensesConsumed	<i>Type:</i> integer The number of entitlements (or points) consumed for the license on the computer.
CalculatedConsumption	<i>Type:</i> integer The calculated consumption value for this license assignment before exemptions or overrides are considered.
LicensesUsed	<i>Type:</i> integer How many of the points consumed are for installations actually being used.
LicenseMeasurementID	<i>Type:</i> integer. Key The license measurement ID. Foreign key to the LicenseMeasurement table.

SoftwareLicensePointsConsumedReasonData Table

This table stores information about why an entry in SoftwareLicensePointsConsumed exists.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 421: Database columns for SoftwareLicensePointsConsumedReasonData table

Database Column	Details
ComplianceComputerID	Type: integer. Key The computer under examination. Foreign key to the ComplianceComputer table.
SoftwareLicenseID	Type: integer. Key The license being assessed. Foreign key to the SoftwareLicense table.
ReasonTypeID	Type: integer The reason for the points to be consumed here. Foreign key to the SoftwareLicensePointsConsumedReasonType table.
LicenseMeasurementID	Type: integer. Key The license measurement ID. Foreign key to the LicenseMeasurement table.

SoftwareLicensePointsConsumedReasonType Table

SoftwareLicensePointsConsumedReasonType stores all the different important attributes that can be stored against a SoftwareLicensePointsConsumed record.

Table 422: Database columns for SoftwareLicensePointsConsumedReasonType table

Database Column	Details
ReasonTypeID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the SoftwareLicensePointsConsumedReasonType table.
ReasonResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing the reason a license was linked to a title. Foreign key to the ComplianceResourceString table.
ReasonDefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the reason resource string has no translation.

SoftwareLicensePointsDefault Table

The SoftwareLicensePointsDefault table stores a collection of default license points associated with a particular license type.

Table 423: Database columns for SoftwareLicensePointsDefault table

Database Column	Details
SoftwareLicensePointsDefaultID	<i>Type:</i> integer. Key. Generated ID A unique identifier for a default points record.
SoftwareLicenseTypeID	<i>Type:</i> integer. Key The software license type to which this points record applies. Foreign key to the SoftwareLicenseType table.
ProcessorType	<i>Type:</i> text (max 256 characters) The type of processor a computer must have for this criterion to apply, such as "AMD" or "Intel".
ComputerModelNo	<i>Type:</i> text (max 128 characters) The model number a computer must have for this criterion to apply, such as "IBM PS701" or "IBM JS12".
MinCores	<i>Type:</i> integer The minimum number of processor cores a computer must have for this criterion to apply.
MaxCores	<i>Type:</i> integer The maximum number of processor cores a computer must have for this criterion to apply.
MinProcessors	<i>Type:</i> integer The minimum number of processors a computer must have for this criterion to apply.
MaxProcessors	<i>Type:</i> integer The maximum number of processors a computer must have for this criterion to apply.
MinSockets	<i>Type:</i> integer The minimum number of processor sockets a computer must have for this criterion to apply.
MaxSockets	<i>Type:</i> integer The maximum number of processor sockets a computer must have for this criterion to apply.

Database Column	Details
MinCoresPerSocket	<i>Type:</i> integer The minimum number of processor cores per socket a computer must have for this criterion to apply.
MaxCoresPerSocket	<i>Type:</i> integer The maximum number of processor cores per socket a computer must have for this criterion to apply.
Points	<i>Type:</i> decimal The points value per core or processor.
DateEffective	<i>Type:</i> datetime. Nullable The date from which these default values are effective. This is used to group sets of rows into sets.
Description	<i>Type:</i> text (max 1024 characters). Nullable A description of the points rules.

SoftwareLicensePointsRule Table

The SoftwareLicensePointsRule table stores individual license points rules (mapping of criteria to point value) belonging to a given points rule set.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 424: Database columns for SoftwareLicensePointsRule table

Database Column	Details
SoftwareLicensePointsRuleID	Type: integer. Key. Generated ID A unique identifier for a points rule record.
SoftwareLicensePointsRuleSetID	Type: integer. Key The set to which this rule applies. Foreign key to the SoftwareLicensePointsRuleSet table.
IsCustom	Type: boolean. Key True if the rule is managed by the customer (versus by the ARL).
Description	Type: text (max 1024 characters). Nullable A human-readable description or identifier for the rule.
Points	Type: decimal. Key The points value per core, processor, user, or other resource metric.
ProcessorType	Type: text (max 256 characters) The type of processor a computer must have for this criterion to apply, such as "AMD" or "Intel".
ComputerModelNo	Type: text (max 128 characters) The model number a computer must have for this criterion to apply, such as "IBM PS701" or "IBM JS12".
MinCores	Type: integer The minimum number of processor cores a computer must have for this criterion to apply.
MaxCores	Type: integer The maximum number of processor cores a computer must have for this criterion to apply.

Database Column	Details
MinProcessors	<i>Type:</i> integer The minimum number of processors a computer must have for this criterion to apply.
MaxProcessors	<i>Type:</i> integer The maximum number of processors a computer must have for this criterion to apply.
MinSockets	<i>Type:</i> integer The minimum number of processor sockets a computer must have for this criterion to apply.
MaxSockets	<i>Type:</i> integer The maximum number of processor sockets a computer must have for this criterion to apply.
MinCoresPerSocket	<i>Type:</i> integer The minimum number of processor cores per socket a computer must have for this criterion to apply.
MaxCoresPerSocket	<i>Type:</i> integer The maximum number of processor cores per socket a computer must have for this criterion to apply.
MinResource	<i>Type:</i> decimal. Key The minimum resource value for an IBM RVU license for this criterion to apply.
MaxResource	<i>Type:</i> decimal. Key The maximum resource value for an IBM RVU license for this criterion to apply.
MinUsers	<i>Type:</i> integer. Key The minimum number of users relevant to an IBM UVU license for this criterion to apply.
MaxUsers	<i>Type:</i> integer. Key The maximum number of users relevant to an IBM UVU license for this criterion to apply.
MinClockSpeed	<i>Type:</i> integer The minimum value of the highest frequency of fastest processor, measured in megahertz, for this criterion to apply.
MaxClockSpeed	<i>Type:</i> integer The maximum value of the highest frequency of fastest processor, measured in megahertz, for this criterion to apply.

Database Column	Details
MinPurchaseDate	<i>Type:</i> datetime. Nullable The earliest date on which the asset must have been purchased for this criterion to apply.
MaxPurchaseDate	<i>Type:</i> datetime. Nullable The latest date on which the asset must have been purchased for this criterion to apply.
IsShared	<i>Type:</i> boolean

SoftwareLicensePointsRuleSet Table

The SoftwareLicensePointsRuleSet table stores named sets of points rules associated with a particular license type.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 425: Database columns for SoftwareLicensePointsRuleSet table

Database Column	Details
SoftwareLicensePointsRuleSetID	Type: integer. Key. Generated ID A unique identifier for a points rule set record.
SoftwareLicenseTypeID	Type: integer. Key The software license type to which this set applies. Foreign key to the SoftwareLicenseType table.
Description	Type: text (max 256 characters). Key. Nullable A human-readable description or identifier for the set.
IsShared	Type: boolean

SoftwareLicenseProcessorPointsData Table

Stores the number of processors/cores on which points-based licensed software is installed and used, and the corresponding points and factors.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 426: Database columns for SoftwareLicenseProcessorPointsData table

Database Column	Details
ComplianceComputerID	Type: integer. Key The computer under examination. Foreign key to the ComplianceComputerSnapshot table.
SoftwareLicenseID	Type: integer. Key The license being assessed. Foreign key to the SoftwareLicenseSnapshot table.
InstalledCount	Type: decimal The number of processors/cores on which a software title licensed by the license is installed.
UsedCount	Type: decimal The number of processors/cores on which a software title licensed by the license is used.
CapacityCount	Type: decimal The number of processors/cores that apply to a software title licensed by the license under full capacity counting rules.
PointsFactor	Type: decimal The number of points consumed per processor/core on this computer for this license.
InstalledPoints	Type: integer The number of processor/core points required to cover the above InstalledCount.
UsedPoints	Type: integer The number of processor/core points required to cover the above UsedCount.

Database Column	Details
CapacityPoints	<i>Type:</i> integer The number of processor/core points required to cover the above CapacityCount.
LicenseMeasurementID	<i>Type:</i> integer. Key The license measurement ID. Foreign key to the LicenseMeasurement table.
CalculatedConsumption	<i>Type:</i> integer The calculated consumption value for this license assignment before exemptions or overrides are considered.
Overridden	<i>Type:</i> boolean Whether this consumption value was the result of an override.

SoftwareLicenseProduct Table

SoftwareLicenseProduct contains the set of SoftwareTitleProducts covered by a SoftwareLicense. Their product specific use rights on this license are also covered.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 427: Database columns for SoftwareLicenseProduct table

Database Column	Details
SoftwareLicenseProductID	Type: integer. Key. Generated ID A unique identifier for a software license product.
SoftwareLicenseID	Type: integer. Key License whose property value is being stored. Foreign key to the SoftwareLicense table
SoftwareTitleProductID	Type: integer. Key. Nullable The product covered by this license. Foreign key to the SoftwareTitleProduct table.
CurrentSoftwareTitleID	Type: integer. Nullable Identifies the current application for this product on this license (which may change over time as upgrade rights are applied). Foreign key to the SoftwareTitle table.
Supplementary	Type: boolean Whether this product on this license is supplementary (counted for consumption) or not.
MeasuredForCompliance	Type: boolean Whether this product on this license is measured for compliance breaches.
ProductRatio	Type: integer If this product is supplementary on the license, the number of entitlements consumed related to the entitlements consumed for the parent product.
ParentProductRatio	Type: integer If this product is supplementary on the license, the number of entitlements consumed related to the entitlements consumed for the supplementary product.

Database Column	Details
InheritDowngradeFromContract	<p><i>Type:</i> boolean</p> <p>Set this field to <code>True</code> if this license inherits its downgrade rights from a contract. If <code>False</code> (the default), downgrade rights must be configured directly on the license properties.</p>
InheritDowngradeFromContractID	<p><i>Type:</i> integer. Nullable</p> <p>If the previous field is <code>True</code>, this is the contract that downgrade rights are inherited from. Foreign key to the Contract table.</p>
InheritUpgradeFromContract	<p><i>Type:</i> boolean</p> <p>Set this field to <code>True</code> if this license inherits its upgrade rights from a contract. If <code>False</code> (the default), upgrade rights must be configured directly on the license properties.</p>
InheritUpgradeFromContractID	<p><i>Type:</i> integer. Nullable</p> <p>If the previous field is <code>True</code>, this is the contract that downgrade rights are inherited from. Foreign key to the Contract table.</p>
DowngradeEnabled	<p><i>Type:</i> boolean</p> <p>If this field is <code>True</code>, this license can cover previous releases, or lower editions, of applications linked to this license. If this field is <code>False</code> (the default), there is no downgrade right conferred by this license.</p>
DowngradeToVersion	<p><i>Type:</i> boolean</p> <p>If this field is <code>True</code>, the license covers previous releases (with the same edition) of the primary application. If this field is <code>False</code> (the default), earlier versions of the primary application are not covered by downgrade rights.</p>
DowngradeToVersionID	<p><i>Type:</i> integer. Nullable</p> <p>If the previous field is <code>True</code> and the value of this field is <code>NULL</code>, downgrade rights cover all earlier releases (with the same edition) of the primary application. If not <code>NULL</code>, downgrade rights cover all versions of the primary application down to and including this version. Foreign key to the SoftwareTitleVersion table.</p>
DowngradeToEdition	<p><i>Type:</i> boolean</p> <p>If this field is <code>True</code>, the license covers lower editions (with the same version) of the primary application. If this field is <code>False</code> (the default), lower editions of the primary application are not covered by downgrade rights.</p>

Database Column	Details
DowngradeToEditionID	<p><i>Type:</i> integer. Nullable</p> <p>If the previous field is True and the value of this field is NULL, downgrade rights cover all lower editions (with the same version) of the primary application. If not NULL, downgrade rights cover all editions of the primary application down to and including this edition. Foreign key to the SoftwareTitleEdition table.</p>
UpgradeEnabled	<p><i>Type:</i> boolean</p> <p>If this field is True, the license can cover future releases (with the same edition) of the primary application. If this bit is False (the default), there is no upgrade right conferred by this license.</p>
UpgradeToVersion	<p><i>Type:</i> boolean</p> <p>If this field is True, the license covers later releases (with the same edition) of the primary application. If this field is False (the default), later versions of the primary application are not covered by upgrade rights.</p>
UpgradeToVersionID	<p><i>Type:</i> integer. Nullable</p> <p>If the previous field is True and the value of this field is NULL, upgrade rights cover all later version (with the same edition) of the primary application. If not NULL, upgrade rights cover all versions of the primary application up to and including this version. Foreign key to the SoftwareTitleEdition table.</p>
UpgradeUntil	<p><i>Type:</i> boolean</p> <p>If this bit is 1, the upgrade right covers future releases of applications that get linked to this license, provided that the release date of each version is before (or on) a specified date. If this bit is zero (the default), the upgrade right is not date limited.</p>
UpgradeUntilDate	<p><i>Type:</i> datetime. Nullable</p> <p>If this field is set, only applications released before this date are covered by upgrade rights.</p>

SoftwareLicensePropertyValue Table

For each end-user, SoftwareLicensePropertyValue stores the values for the custom properties defined in SoftwareLicenseTypeProperty.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 428: Database columns for SoftwareLicensePropertyValue table

Database Column	Details
SoftwareLicense PropertyValueID	Type: integer. Key. Generated ID A unique identifier for a property value.
SoftwareLicenseType PropertyID	Type: integer. Key The property whose value is being stored. The type of the license should match the type that the property is associated with. Foreign key to the SoftwareLicenseTypeProperty table.
SoftwareLicenseID	Type: integer. Key License whose property value is being stored. Foreign key to the SoftwareLicense table
PropertyValue	Type: text (max 4000 characters) The property value.
CreationUser	Type: text (max 128 characters). Nullable The operator who created the record.
CreationDate	Type: datetime The date the record was created.
UpdatedUser	Type: text (max 128 characters). Nullable The operator who last updated the record.
UpdatedDate	Type: datetime. Nullable The date the record was last updated.

SoftwareLicenseProposalStatus Table

SoftwareLicenseProposalStatus is a static table listing all of the states that a license change proposal can be in.

Table 429: Database columns for SoftwareLicenseProposalStatus table

Database Column	Details
SoftwareLicenseProposalStatusID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each SoftwareLicenseProposalStatus. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = Pending• 2 = Accepted• 3 = Ignored
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing the license change proposal state. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 256 characters)</p> <p>The text to display if the state resource string has no translation.</p>

SoftwareLicensePurchaseType Table

SoftwareLicensePurchaseType holds a list of purchase types for licenses.

Table 430: Database columns for SoftwareLicensePurchaseType table

Database Column	Details
SoftwareLicense PurchaseTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each SoftwareLicensePurchaseType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = Volume • 2 = Shrink Wrap • 3 = OEM • 4 = Subscription.
SoftwareLicense PurchaseTypeResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a purchase type. Foreign key to the ComplianceResourceString table.</p>
SoftwareLicense PurchaseTypeDefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the type resource string has no translation.</p>

SoftwareLicenseReservation Table

The SoftwareLicenseReservation table lists all reservations for a license entitlement for an application.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 431: Database columns for SoftwareLicenseReservation table

Database Column	Details
SoftwareLicense ReservationID	Type: integer. Key. Generated ID A unique identifier for this reservation.
SoftwareTitleID	Type: integer. Key The application being reserved. Foreign key to the SoftwareTitle table.
SoftwareLicenseID	Type: integer. Key. Nullable The license affected by this reservation, null if any license for the application can be consumed. Foreign key to the SoftwareLicense table.
ComplianceComputerID	Type: integer. Key The computer making the reservation. Foreign key to the ComplianceComputer table.
ComplianceUserID	Type: integer. Key. Nullable The user making the reservation. Foreign key to the ComplianceUser table.
PointsReserved	Type: integer The number of points this reservation will ultimately consume.
CreationUser	Type: text (max 128 characters). Nullable The operator who created the record.
CreationDate	Type: datetime The date the record was created.
SoftwareLicense ReservationTypeID	Type: integer The type of reservation.
SoftwareLicense ReservationStatusID	Type: integer Stores the status of the reservation

SoftwareLicenseReservationNecessityCheckResult Table

The SoftwareLicenseReservationNecessityCheckResult table saves the results of the necessity to do software license reservation for a license entitlement for an application.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 432: Database columns for SoftwareLicenseReservationNecessityCheckResult table

Database Column	Details
SoftwareLicenseReservationNecessityCheckResultID	Type: integer. Key. Generated ID A unique identifier for this reservation necessity check result.
SoftwareTitleID	Type: integer. Key The application being reserved. Foreign key to the SoftwareTitle table.
SoftwareLicenseID	Type: integer. Key. Nullable The license affected by this reservation, null if any license for the application can be consumed. Foreign key to the SoftwareLicense table.
ComplianceComputerID	Type: integer. Key The computer making the reservation. Foreign key to the ComplianceComputer table.
ComplianceUserID	Type: integer. Key. Nullable The user making the reservation. Foreign key to the ComplianceUser table.
HasSecondUseRight	Type: boolean No reservation is actually needed because of second use right.
HasUpgradeDowngradeRight	Type: boolean No reservation is actually needed because of upgrade/downgrade right
HasExemptionByDeviceRole	Type: boolean No reservation is actually needed because of exemption by device role.
CreationUser	Type: text (max 128 characters). Nullable The operator who created the record.
CreationDate	Type: datetime The date the record was created.

SoftwareLicenseReservationStatus Table

The collection of status values for reservation.

Table 433: Database columns for SoftwareLicenseReservationStatus table

Database Column	Details
SoftwareLicense ReservationStatusID	Type: integer. Key. Generated ID A unique identifier for the reservation status id
SoftwareLicense ReservationStatusName	Type: text (max 128 characters) The name of the reservation status.

SoftwareLicenseReservationType Table

The collection of status values for reservation types.

Table 434: Database columns for SoftwareLicenseReservationType table

Database Column	Details
SoftwareLicense ReservationTypeID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the reservation type id
SoftwareLicense ReservationTypeName	<i>Type:</i> text (max 128 characters) The name of the reservation type.

SoftwareLicenseScopeTag Table

Reserved for future development.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 435: Database columns for SoftwareLicenseScopeTag table

Database Column	Details
SoftwareLicenseID	Type: integer. Key Foreign key to the SoftwareLicense table.
TagID	Type: integer. Key Foreign key to the Tag table.
ScopeTagTypeID	Type: integer. Key Foreign key to the SoftwareLicenseScopeTagType table.

SoftwareLicenseScopeTagType Table

Reserved for future development.

Table 436: Database columns for SoftwareLicenseScopeTagType table

Database Column	Details
ScopeTagTypeID	<i>Type:</i> integer. Key. Generated ID A unique ID for this record.
TypeDescription	<i>Type:</i> text (max 50 characters). Key The text value for this type.

SoftwareLicenseScoping Table

SoftwareLicenseScoping links software licenses to enterprise groups, to restrict the rights granted by the licenses to the selected group and its descendents (license scoping).


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 437: Database columns for SoftwareLicenseScoping table

Database Column	Details
SoftwareLicenseID	Type: integer. Key The scoped license. Foreign key to the SoftwareLicense table.
GroupExID	Type: text (max 128 characters). Key The enterprise group that this license is restricted to. Any children of this enterprise group are also included in the scope of the license. Foreign key to the GroupEx table.

SoftwareLicenseSecondUseMappingData Table

SoftwareLicenseSecondUseMapping maps pairs of desktop computers and laptop computers against each license conferring the right of second use and covering installations on these computers.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 438: Database columns for SoftwareLicenseSecondUseMappingData table

Database Column	Details
SoftwareLicenseID	<i>Type:</i> integer. Key The license conferring the right of second use. Foreign key to the SoftwareLicense table.
DesktopComputerID	<i>Type:</i> integer. Key The desktop or primary computer on which the related software is installed. Foreign key to the ComplianceComputer table.
SecondUseComputerID	<i>Type:</i> integer. Key The laptop or second computer covered by this license's right of second use, relative to the installation on the primary computer tracked in the previous field. Foreign key to the ComplianceComputer table.
TotalLicenseGrabs	<i>Type:</i> integer For internal use only. Temporary storage for calculations of overlapping second use and multiple install rights.
IsExternalRoamingLink	<i>Type:</i> boolean Is this a second use link or is it actually an 'external roaming' right?

SoftwareLicenseSnapshot Table

The SoftwareLicenseSnapshot table lists all the snapshotted software licenses.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 439: Database columns for SoftwareLicenseSnapshot table

Database Column	Details
SoftwareLicenseID	Type: integer. Key The snapshotted SoftwareLicenseID.
Name	Type: text (max 256 characters) The snapshotted license name.
LicenseTypeID	Type: integer. Key The license type. Foreign key to the SoftwareLicenseType table.
SoftwareLicense ComplianceStatusID	Type: integer. Nullable The compliance status of this license. Foreign key to the SoftwareLicenseComplianceStatus table. Defaults to "Compliant".
Consumed	Type: integer. Nullable The snapshotted license consumed count.
PurchaseQuantity	Type: integer. Nullable The snapshotted license purchase quantity.
PurchasePrice	Type: currency. Nullable The initial purchase price of the license.
PurchasePriceRateID	Type: integer. Nullable The currency rate applied to the purchase price of the license. Foreign key to the CurrencyRate table.
LicenseMeasurementID	Type: integer. Key The snapshot ID. Foreign key to the LicenseMeasurement table.
NumberUsed	Type: integer. Nullable The snapshotted license number used count.
LastCalculatedNUPMinimum	Type: integer. Nullable The snapshotted license last calculated minimum for Oracle Named User Plus licenses.

Database Column	Details
CalculatedConsumed	<i>Type:</i> integer The calculated consumption value for this license.

SoftwareLicenseTierType Table

SoftwareLicenseTierType is a static table listing the tier types that a software license can have. Used for Tiered Device license type.

Table 440: Database columns for SoftwareLicenseTierType table

Database Column	Details
SoftwareLicenseTierTypeID	<i>Type:</i> integer. Key. Generated ID A unique identifier for each SoftwareLicenseTierType. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• 1 = Generic• 2 = Per Processor• 3 = Symantec Server• 4 = Symantec Processor Type• 5 = Symantec Installed Operating System.
TierTypeResourceName	<i>Type:</i> text (max 256 characters). Key. Nullable The unique name of the localizable resource string representing a tier type. Foreign key to the ComplianceResourceString table.
TierTypeDefaultValue	<i>Type:</i> text (max 256 characters) The text to display if the type resource string has no translation.
TierCodeValidationRegEx	<i>Type:</i> text (max 256 characters). Nullable The regular expression used to validate the tier code.
TierCodeValidationMsg ResourceName	<i>Type:</i> text (max 256 characters). Nullable The unique name of the localizable resource string representing the message shown when tier code validation fails. Foreign key to the ComplianceResourceString table.
TierCodeValidationMsg DefaultValue	<i>Type:</i> text (max 256 characters). Nullable The text to display if the resource string (for the message shown when tier code validation fails) has no translation.

SoftwareLicenseType Table

SoftwareLicenseType holds the collection of all valid license types.

Table 441: Database columns for SoftwareLicenseType table

Database Column	Details
SoftwareLicenseTypeID	<p>Type: integer. Key. Generated ID</p> <p>A unique identifier for each SoftwareLicenseType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = Enterprise • 2 = Device • 3 = Node-Locked • 4 = User • 5 = Concurrent User • 6 = Appliance • 7 = Client Server • 8 = OEM • 9 = Evaluation • 10 = Run-Time • 11 = Device (Processor-Limited) • 12 = Site • 13 = Named User • 14 = Device (Core-Limited) • 15 = Core Points • 16 = Oracle Processor • 17 = Oracle Named User Plus • 18 = Processor Points • 19 = Oracle Legacy • 20 = Enterprise Agreement • 21 = SAP Named User • 22 = Microsoft Server Processor • 23 = CAL Legacy • 24 = Tiered Device • 25 = IBM Processor Value Unit • 26 = IBM Authorized User

Database Column	Details
	<ul style="list-style-type: none"> • 27 = IBM Concurrent User • 28 = IBM Floating User • 29 = Custom Metric • 30 = Processor • 31 = IBM Resource Value Unit • 32 = IBM User Value Unit • 33 = Microsoft Server Core • 34 = Oracle User • 35 = SAP Package • 36 = Microsoft SCCM Client Device • 37 = Microsoft SCCM Client User • 38 = Microsoft Developer Network • 39 = Microsoft Device CAL • 40 = Microsoft User CAL
TypeResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a license type. Foreign key to the ComplianceResourceString table.</p>
TypeDefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the type resource string has no translation.</p>
XMLFile	<p><i>Type:</i> text. Nullable</p> <p>The layout of the property dialog for this type of computer, stored in XML format.</p>
CustomProcedureName	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>The stored procedure used to assign licenses for this license type.</p>
DoesLicenseAllowUser Allocations	<p><i>Type:</i> boolean</p> <p>Set this field to True if the license supports allocations to individual end-users. When False, it cannot be allocated to end-users.</p>

Database Column	Details
DoesLicenseAllow ComputerAllocations	<p><i>Type:</i> boolean</p> <p>Set this field to True if the license supports allocations to individual computers. When it is False, it cannot be allocated to computers. (Note that for a custom license type, both this and the previous field may be set at the same time.)</p>
DoesLicenseAllow VirtualApplications	<p><i>Type:</i> boolean</p> <p>Set this field to True if the license supports virtual applications. When it is False, it cannot be consumed by virtual applications. (Note that virtual applications have AccessModeID > 1.)</p>
CanConvertToAndFromType	<p><i>Type:</i> boolean</p> <p>Set this field to True if an operator is allowed to change the type of this license after it has been created. This field also determines whether this license type is included in the list of types that can be converted to. Oracle licenses, for example, cannot be converted to or from.</p>
ExclusionReasonName	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>The unique name of the localizable resource string representing the reason why an installation linked to a license of this type may appear in the Unlicensed Installs node. Foreign key to the ComplianceResourceString table.</p>
ExclusionReasonDefault	<p><i>Type:</i> text (max 500 characters)</p> <p>The text to display if the reason resource string has no translation.</p>
IncludeInSQLAssignment	<p><i>Type:</i> boolean</p> <p>Set this field to True if licenses of this type should be processed during the SQL part of the license reconciliation process.</p>
CalculateCompliance	<p><i>Type:</i> boolean</p> <p>When this field is True (the default), and a SoftwareLicense of this type also has its CalculateCompliance field set to True (the default), that license must have its consumption calculated from imported inventory. When False, the compliance state of licenses with this type must be imported or otherwise set manually, not calculated.</p>
ReconcileAsSoftware LicenseTypeID	<p><i>Type:</i> integer. Nullable</p> <p>If specified, treat this license type as if it were another for license reconciliation purposes. Foreign key to another type in this SoftwareLicenseType table.</p>
Enabled	<p><i>Type:</i> boolean</p> <p>Indicates whether this license type is enabled</p>

SoftwareLicenseTypeChangeProposal Table

The SoftwareLicenseTypeChangeProposal table is used to store a proposed change of type for a particular software license. The changes have been inferred from changes to the license definition used to create the software license.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 442: Database columns for SoftwareLicenseTypeChangeProposal table

Database Column	Details
SoftwareLicenseType ChangeProposalID	Type: integer. Key. Generated ID Primary key for the SoftwareLicenseTypeChangeProposal table.
SoftwareLicenseID	Type: integer. Key Foreign key to the SoftwareLicense table.
SoftwareLicense DefinitionID	Type: integer Foreign key to the SoftwareLicenseDefinition table.
LicenseDefinitionVersion	Type: integer The version of the license definition that has been used for these proposed changes.
SoftwareLicenseUse RightNameID	Type: integer The proposed use right being changed on the software license.
SoftwareLicenseTypeID	Type: integer. Key The proposed license type for the software license.
OldSoftwareLicenseTypeID	Type: integer The existing license type for the software license.
SoftwareLicense ProposalStatusID	Type: integer The state of this software license change proposal.
Conflicted	Type: boolean Whether this license type change proposal conflicts with another type proposed for the same license.
CreationUser	Type: text (max 128 characters). Nullable The operator who created the record.

Database Column	Details
CreationDate	<i>Type:</i> datetime The date the record was created.
UpdatedUser	<i>Type:</i> text (max 128 characters). Nullable The operator who updated the record.
UpdatedDate	<i>Type:</i> datetime. Nullable The date the record was updated.

SoftwareLicenseTypePriority Table

SoftwareLicenseTypePriority holds the priority order of license types.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 443: Database columns for SoftwareLicenseTypePriority table

Database Column	Details
SoftwareLicenseTypeID	Type: integer. Key The software license type to which this priority applies. Foreign key to the SoftwareLicenseType table.
CompliancePriority	Type: integer The priority order of the license type when calculating compliance. Licenses with higher priority will be consumed first.

SoftwareLicenseTypeProperty Table

SoftwareLicenseTypeProperty defines extra custom properties for all end-users.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 444: Database columns for SoftwareLicenseTypeProperty table

Database Column	Details
SoftwareLicenseType PropertyID	Type: integer. Key. Generated ID A unique identifier for an individual property.
PropertyName	Type: text (max 256 characters). Key The name of the property.
SoftwareLicenseTypeID	Type: integer. Key License type with which this property is associated. Foreign key to the LicenseType table.
CustomPropertyDisplayXMLID	Type: integer. Nullable Foreign key to a record in the CustomPropertyDisplayXML table, describing how to show the property on a property dialog.

SoftwareLicenseUseRight Table

SoftwareLicenseUseRight contains licensing rules most of which can be set by PURL.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 445: Database columns for SoftwareLicenseUseRight table

Database Column	Details
SoftwareLicenseUseRightID	<i>Type:</i> integer. Key. Generated ID A unique identifier
SoftwareLicenseID	<i>Type:</i> integer. Key A unique identifier for a software license.
ReassignmentTimeLimitApplies	<i>Type:</i> boolean If 1 then the license cannot be reassigned for some period of time (example is Microsoft 90 day rule)
ReassignmentTimeLimit	<i>Type:</i> integer. Nullable The period (in days) within which the license cannot be reassigned
LicenseMobilityApplies	<i>Type:</i> boolean 1 if eligible for bringing your own license to cloud environment
NumberOfOSEPerLicense	<i>Type:</i> integer. Nullable Number of OSE per license
NumberOfProcessorsPerOSE	<i>Type:</i> integer. Nullable Number of processors per OSE
TotalNumberOfCoresPerVMPerLicense	<i>Type:</i> integer. Nullable Total number of cores per VM per license
NumberOfCoresPerSocket	<i>Type:</i> integer. Nullable Number of cores per socket
ThirdPartyAccessAllowed	<i>Type:</i> boolean Access to applications is allowed to third party users. This field is defaulted to True
PURLComment	<i>Type:</i> text. Nullable Additional information provided by PURL

Database Column	Details
AllowExternalRoamingUse	<p><i>Type:</i> boolean. Nullable</p> <p>Set this field to True if license allows external roaming use. This field is defaulted to False. This is applicable for both device and user licenses and is related to virtual application access. If 1, this license will consume 1 entitlement per each user. If 0, this license will consume 1 license per each user device. And, if NULL, ignore virtual application access. This can be used in conjunction with VirtualApplicationAccessMaximumUsagePeriod.</p>
MeasurementDate	<p><i>Type:</i> datetime. Nullable</p> <p>The date of the license measurment.</p>
ConsumptionUnit	<p><i>Type:</i> text. Nullable</p> <p>Unit description to describe the consumption amount.</p>
TargetOperatingSystem TypeID	<p><i>Type:</i> integer</p> <p>Type of Operating Systems to target</p>
VirtualApplication AccessMaximumUsagePeriod	<p><i>Type:</i> integer. Nullable</p> <p>This is a rule for virtual application access. This is used in conjunction with the AllowExternalRoamingUse. For Device licenses, a license will consume 1 entitlement per each user device when used in period specified here. For user licenses, if 1, this license will consume only when used in period specified here.</p>
ExemptCALs	<p><i>Type:</i> boolean</p> <p>If the value True, clients accessing servers that consume this license will be exempted from CAL (no CALs required). Only applicable to Microsoft Server Processor, Microsoft Server Core and Device license types.</p>

SoftwareLicenseUseRightIBM Table

SoftwareLicenseUseRightIBM contains IBM licensing rules most of which can be set by PURL.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 446: Database columns for SoftwareLicenseUseRightIBM table

Database Column	Details
SoftwareLicenseUseRightIBMID	Type: integer. Key. Generated ID A unique identifier
SoftwareLicenseID	Type: integer. Key A unique identifier for a software license.
PVULimitApplies	Type: boolean If 1 then PVU limits apply
PVULimit	Type: integer. Nullable PVU limit

SoftwareLicenseUseRightName Table

SoftwareLicenseUseRightName is a static table listing all of the use rights that can be applied to a software license.

Table 447: Database columns for SoftwareLicenseUseRightName table

Database Column	Details
SoftwareLicenseUse RightNameID	<p>Type: integer. Key. Generated ID</p> <p>A unique identifier for each SoftwareLicenseUseRightName. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = License type • 2 = Cover installs on virtual machines • 3 = Limit number of virtual installs • 4 = Number of allowed virtual installs • 5 = Limit virtual installs includes host • 6 = Use host processor information • 7 = Allow IBM PVU sub-capacity from non ILMT • 8 = Limit number of applications each license point covers • 9 = Number of application installs allowed per license point • 10 = Limit number of computers user license can be installed on • 11 = Number of computers allowed per license point • 12 = Minimum number of users • 13 = Minimum number of users multiplied by processors • 14 = Second usage work laptop • 15 = Second usage at home • 16 = Downgrade enabled • 17 = Downgrade to version • 18 = Downgrade to version ID • 19 = Downgrade to edition • 20 = Downgrade to edition ID • 21 = Upgrade enabled • 22 = Upgrade to version • 23 = Upgrade to version ID • 24 = Upgrade until • 25 = Upgrade until date • 26 = Reassignment time limit applies

Database Column	Details
	<ul style="list-style-type: none"> • 27 = Reassignment time limit • 28 = License mobility applies • 29 = Number of OSE per license • 30 = Number of processors per OSE • 31 = Total number of cores per VM per license • 32 = Number of cores per socket • 33 = Third party access allowed • 34 = PURL comment • 35 = Allow external roaming use • 36 = Measurement date • 37 = Consumption unit • 38 = PVU limit applies • 39 = PVU limit • 40 = Points rule set • 41 = Minimum number of processors • 42 = Minimum number of licenses per virtual machine • 43 = Number of sockets • 44 = User multiplier external • 45 = User multiplier infrequent • 46 = Exempted roles • 47 = Exempted role limit • 48 = Measure for compliance • 49 = Ratio from primary • 50 = Ratio to primary
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing the proposed action. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 256 characters)</p> <p>The text to display if the state resource string has no translation.</p>

SoftwareLicenseUseRightProposal Table

The SoftwareLicenseUseRightProposal table is used to store a summary of use right changes to a particular software license. The changes have been inferred from changes to the license definition used to create the software license.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 448: Database columns for SoftwareLicenseUseRightProposal table

Database Column	Details
SoftwareLicenseUseRightProposalID	Type: integer. Key. Generated ID Primary key for the SoftwareLicenseUseRightProposal table.
SoftwareLicenseID	Type: integer. Key Foreign key to the SoftwareLicense table.
SoftwareLicenseDefinitionID	Type: integer Foreign key to the SoftwareLicenseDefinition table.
LicenseDefinitionVersion	Type: integer The version of the license definition that has been used for these proposed changes.
SoftwareLicenseUseRightNameID	Type: integer. Key The proposed use right being changed on the software license.
SoftwareTitleProductID	Type: integer. Key. Nullable Foreign key to the SoftwareTitleProduct table.
Enabled	Type: boolean. Key. Nullable Is this use right being enabled?
MD5Value	Type: text (max 32 characters). Key. Nullable The MD5 of Value in Hex.
Value	Type: text (max 4000 characters). Nullable The proposed value for this use right.
OldValue	Type: text (max 4000 characters). Nullable The existing value for this use right.
RelatedID	Type: integer. Nullable The database ID of the proposed object associated with this use right.

Database Column	Details
OldRelatedID	<i>Type:</i> integer. Nullable The database ID of the old object associated with this use right.
SoftwareLicense ProposalStatusID	<i>Type:</i> integer The state of this software license change proposal.
Conflicted	<i>Type:</i> boolean Whether this license type change proposal conflicts with another type proposed for the same license.
ContractInherited	<i>Type:</i> boolean Whether this license type change proposal is for a use right currently inherited from contract by the license.
CreationUser	<i>Type:</i> text (max 128 characters). Nullable The operator who created the record.
CreationDate	<i>Type:</i> datetime The date the record was created.
UpdatedUser	<i>Type:</i> text (max 128 characters). Nullable The operator who updated the record.
UpdatedDate	<i>Type:</i> datetime. Nullable The date the record was updated.

SoftwareLifeCycle Table

Table 449: Database columns for SoftwareLifeCycle table

Database Column	Details
SoftwareLifeCycleID	<i>Type:</i> integer. Key. Generated ID A unique identifier for an ARL published software life cycle.
SoftwareLifeCycleUID	<i>Type:</i> text (max 64 characters). Key Factory generated identifier
Name	<i>Type:</i> text (max 350 characters) Name of the software life cycle published by software publisher
AvailabilityDate	<i>Type:</i> datetime. Nullable The availability date.
EndOfAvailabilityDate	<i>Type:</i> datetime. Nullable The end of availability date.

SoftwareRecognition Table

Table 450: Database columns for SoftwareRecognition table

Database Column	Details
SoftwareRecognitionID	<i>Type:</i> text (max 30 characters). Key Factory generated identity.
UpdateMode	<i>Type:</i> text (max 20 characters). Nullable Update behavior.
LastCollectiveUpdated	<i>Type:</i> datetime. Nullable Last updated datetime by ARL on all software titles and evidence
LastLinkUpdated	<i>Type:</i> datetime. Nullable Last updated datetime by ARL on the software title links
LastRecordUpdated	<i>Type:</i> datetime. Nullable Last updated datetime by ARL on the software title or evidence records. To know which record this column refers to, see TypeOfID.
LastCollectiveChecksum	<i>Type:</i> integer. Nullable Last collective checksum on successful ARL update
LastLinkChecksum	<i>Type:</i> integer. Nullable Last link checksum on successful ARL update
LastRecordChecksum	<i>Type:</i> integer. Nullable Last record checksum on successful ARL update. To know which record this column refers to, see TypeOfID.
LastCollectiveUpdateResult	<i>Type:</i> integer. Nullable Last collective ARL update result
LastLinkUpdateResult	<i>Type:</i> integer. Nullable Last ARL link update result
LastRecordUpdateResult	<i>Type:</i> integer. Nullable Last ARL record update result
RecordAdoptedByARL	<i>Type:</i> boolean When an existing customer record is updated by the ARL, this flag will be set
SoftwareTitleID	<i>Type:</i> integer. Key. Nullable The related SoftwareTitle

Database Column	Details
ChildSoftwareTitleID	Type: integer. Key. Nullable The related child SoftwareTitle
SoftwareTitleProductID	Type: integer. Key. Nullable The related SoftwareTitleProduct
SoftwareTitleVersionID	Type: integer. Key. Nullable The related SoftwareTitleVersion
SoftwareTitleEditionID	Type: integer. Key. Nullable The related SoftwareTitleEdition
SoftwareTitlePublisherID	Type: integer. Key. Nullable The related SoftwareTitlePublisher
FileEvidenceID	Type: integer. Key. Nullable The related FileEvidence
InstallerEvidenceID	Type: integer. Key. Nullable The related InstallerEvidence
WMIEvidenceID	Type: integer. Key. Nullable The related WMIEvidence
AccessEvidenceID	Type: integer. Key. Nullable The related AccessEvidence
RegistryEvidenceID	Type: integer. Nullable The related registry WMIEvidence
SoftwareLicensePointsDefaultID	Type: integer. Key. Nullable The related SoftwareLicensePointsDefault
SoftwareLicensePointsRuleSetID	Type: integer. Key. Nullable The related SoftwareLicensePointsRuleSet
SoftwareLicensePointsRuleID	Type: integer. Key. Nullable The related SoftwareLicensePointsRule
TypeOfID	Type: text (max 32 characters). Key The type of the last updated ARL record

SoftwareSKULookup Table

SoftwareSKULookup maps licenses imported from external source to SKU published by FNMS

Table 451: Database columns for SoftwareSKULookup table

Database Column	Details
SoftwareSKULookupID	<i>Type:</i> integer. Key. Generated ID A unique identifier for this record.
SourceType	<i>Type:</i> text (max 32 characters). Key
LookupName	<i>Type:</i> text (max 128 characters). Key
SKU	<i>Type:</i> text (max 100 characters) Holds the SKU value.

SoftwareSku Table

SoftwareSku defines all software SKU (stock-keeping unit) numbers.

Table 452: Database columns for SoftwareSku table

Database Column	Details
SoftwareSkuID	<i>Type:</i> integer. Key. Generated ID A unique identifier for a software SKU.
SKUFactoryUID	<i>Type:</i> text (max 30 characters). Key A FlexNet Manager Suite factory unique ID for this SKU.
SKU	<i>Type:</i> text (max 100 characters). Key Holds the SKU value.
SKUDefinition	<i>Type:</i> text Encrypted data that describes this SKU.
SoftwareLicense DefinitionID	<i>Type:</i> integer. Key SKU license definition. Used to create new licenses and link them to applications. Foreign key to the SoftwareLicenseDefinition table.
SoftwareSkuTypeID	<i>Type:</i> integer. Key For internal use only. A numerical representation of the type of SKU.
MaintenanceTypeID	<i>Type:</i> integer For internal use only. A numerical representation of the maintenance type (if any) of the SKU.
Version	<i>Type:</i> integer. Key The current version of the SKU definition.
PreviousVersion	<i>Type:</i> integer. Key. Nullable The version of the SKU definition prior to the current version.
CreationDate	<i>Type:</i> datetime The date that this SKU definition was created.
UpdatedDate	<i>Type:</i> datetime. Nullable The date that this SKU definition was last updated.

SoftwareTitle Table

The SoftwareTitle table contains the application titles managed by FlexNet Manager Suite.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 453: Database columns for SoftwareTitle table

Database Column	Details
SoftwareTitleID	Type: integer. Key. Generated ID A unique identifier for a software record.
SoftwareTitleTypeID	Type: integer. Key The application type. Foreign key to the SoftwareTitleType table.
SoftwareTitleProductID	Type: integer. Key The application product, which also may specify a publisher. Foreign key to the SoftwareTitleProduct table.
SoftwareTitleVersionID	Type: integer. Key. Nullable The application version. Foreign key to the SoftwareTitleVersion table.
SoftwareTitleEditionID	Type: integer. Key. Nullable The application edition. Foreign key to the SoftwareTitleEdition table.
OperatorManageStateID	Type: integer. Key The management responsibility for this information. Foreign key to the OperatorManageState table.
FullName	Type: text (max 512 characters) By default, the full name of the application is the concatenation of the product, version, and edition fields. The operator may overwrite this with any preferred value.
SoftwareTitle ClassificationID	Type: integer. Nullable The classification of the title. Defaults to None. Foreign key to the SoftwareTitleClassification table.
IsMonitoringSessions	Type: boolean Set this field to True if sessions are being monitored.

Database Column	Details
UsageSessions	<p><i>Type:</i> integer</p> <p>An application is considered used if it is opened more than this many times within the monitoring period.</p>
IsMonitoringActiveTime	<p><i>Type:</i> boolean</p> <p>Set this field to True if active time is being monitored.</p>
UsageActiveTime	<p><i>Type:</i> integer</p> <p>An application is considered used if the application active time (time it is in the foreground) exceeds this value during the monitoring period.</p>
UsagePeriod	<p><i>Type:</i> integer</p> <p>The period in months over which to consider usage.</p>
Comments	<p><i>Type:</i> text. Nullable</p> <p>Stores any comments an operator wants to make about a particular application title.</p>
SKU	<p><i>Type:</i> text (max 200 characters). Nullable</p> <p>Deprecated: now use LicensePartNo of the PurchaseOrderDetail table. Stock Keeping Unit (SKU) for the application.</p>
CategoryID	<p><i>Type:</i> text (max 128 characters). Key. Nullable</p> <p>Any enterprise category associated with this application title. Foreign key to the GroupEx table.</p>
IsLicensable	<p><i>Type:</i> boolean</p> <p>Set this field to True if this application needs a license. If False, the application doesn't need a license.</p>
ReleaseDate	<p><i>Type:</i> datetime. Nullable</p> <p>The date the application was released.</p>
IsSharableToLibrary	<p><i>Type:</i> boolean</p> <p>Set this field to True if the application is sharable to the FlexNet Manager Suite ARL library.</p>
AutoManageLicensePriority	<p><i>Type:</i> boolean</p> <p>Set this field to True if the application should automatically manage the priority of attached licenses.</p>
TitleRequiresStrict Matching	<p><i>Type:</i> boolean</p> <p>Set this field to True if the application should use stricter matching rules, requiring all evidence of all types to be present.</p>

Database Column	Details
SupportedUntil	<i>Type:</i> datetime. Nullable The date the application will be supported
ExtendedSupportUntil	<i>Type:</i> datetime. Nullable The date the application will be supported, in extended case
SoftwareTitleActionID	<i>Type:</i> integer A categorization for the application in the enterprise. Defaults to New.Foreign key to the SoftwareTitleAction table.
HasInstalls	<i>Type:</i> boolean If this field is True this application has at least one installation. If False, the application has no installations.
SoftwareLifeCycleID	<i>Type:</i> integer. Key. Nullable Foreign key to the SoftwareLifeCycle table.
HasCustomEndOfSupportLife	<i>Type:</i> boolean. Nullable Set this field to indicate custom end of support life for this application.
CustomEndOfSupportLife Date	<i>Type:</i> datetime. Nullable Custom end of support life date.
IsShared	<i>Type:</i> boolean

SoftwareTitleAccessEvidence Table

SoftwareTitleAccessEvidence links software (application) titles to access evidence.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 454: Database columns for SoftwareTitleAccessEvidence table

Database Column	Details
SoftwareTitleID	<i>Type:</i> integer. Key The software title to which the access evidence is related. Foreign key to the SoftwareTitle table.
AccessEvidenceID	<i>Type:</i> integer. Key The access evidence related to the software title. Foreign key to the AccessEvidence table.
IsLocal	<i>Type:</i> boolean If this field is <code>False</code> , the link has come from the ARL. If it is <code>True</code> , then the link has been created by an operator.
IsShared	<i>Type:</i> boolean

SoftwareTitleAction Table

SoftwareTitleAction is a static table listing action outcomes for the application in the enterprise.

Table 455: Database columns for SoftwareTitleAction table

Database Column	Details
SoftwareTitleActionID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each SoftwareTitleAction. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = Unmanaged (recently created application, not yet categorized)• 2 = Authorized (application is authorized for use in the enterprise)• 3 = Unauthorized (application is not authorized for use)• 4 = Ignored (application will not be tracked by the enterprise)• 5 = Inactive (application is not in use in the enterprise).• 6 = Deferred (application installed in enterprise but marked for later attention).
ActionResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing an action outcome. Foreign key to the ComplianceResourceString table.</p>
ActionDefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the action outcome resource string has no translation.</p>

SoftwareTitleClassification Table

SoftwareTitleClassification is a static table listing the possible classifications for software titles.

Table 456: Database columns for SoftwareTitleClassification table

Database Column	Details
SoftwareTitle ClassificationID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each SoftwareTitleClassification. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = Shareware • 2 = Freeware • 3 = Commercial • 4 = Update • 5 = Malware • 6 = Beta • 7 = XRated • 8 = None • 9 = Component.
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing an application classification. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the classification resource string has no translation.</p>

SoftwareTitleEdition Table

A list of application editions, which must be unique for a given product. Examples include “Ultimate”, “Professional” and “32 bit”.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 457: Database columns for SoftwareTitleEdition table

Database Column	Details
SoftwareTitleEditionID	Type: integer. Key. Generated ID The unique identifier for an edition.
SoftwareTitleProductID	Type: integer. Key The edition’s product. Foreign key to the SoftwareTitleProduct table.
EditionName	Type: text (max 50 characters). Key The text for this application edition.
EditionWeight	Type: decimal Edition weight (for ordering, so we know which editions are upgrades/ downgrades of other editions).
IsLocal	Type: boolean If this field is False, the edition has come from the ARL. If it is True, then the edition has been created by an operator.
IsShared	Type: boolean

SoftwareTitleEx Table

The SoftwareTitleEx table contains additional information on the application titles managed by FlexNet Manager Suite.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 458: Database columns for SoftwareTitleEx table

Database Column	Details
SoftwareTitleID	<i>Type:</i> integer. Key A unique identifier for a software record.
OperatorManageStateID	<i>Type:</i> integer. Nullable The management responsibility for this information. Foreign key to the OperatorManageState table.
AutoManageLicensePriority	<i>Type:</i> boolean. Nullable Set this field to True if the application should automatically manage the priority of attached licenses.
IsMonitoringSessions	<i>Type:</i> boolean. Nullable Set this field to True if sessions are being monitored.
UsageSessions	<i>Type:</i> integer. Nullable An application is considered used if it is opened more than this many times within the monitoring period.
IsMonitoringActiveTime	<i>Type:</i> boolean. Nullable Set this field to True if active time is being monitored.
UsageActiveTime	<i>Type:</i> integer. Nullable An application is considered used if the application active time (time it is in the foreground) exceeds this value during the monitoring period.
UsagePeriod	<i>Type:</i> integer. Nullable The period in months over which to consider usage.
SoftwareTitleActionID	<i>Type:</i> integer. Key. Nullable A categorization for the application in the enterprise. Defaults to New.Foreign key to the SoftwareTitleAction table.

Database Column	Details
HasInstalls	<i>Type:</i> boolean. Nullable If this field is True this application has at least one installation. If False, the application has no installations.
HasCustomEndOfSupportLife	<i>Type:</i> boolean. Nullable Set this field to indicate custom end of support life for this application.
CustomEndOfSupportLife Date	<i>Type:</i> datetime. Nullable Custom end of support life date.

SoftwareTitleFileEvidence Table

SoftwareTitleFileEvidence links software (application) titles to file evidence.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 459: Database columns for SoftwareTitleFileEvidence table

Database Column	Details
SoftwareTitleID	<i>Type:</i> integer. Key The application title to which the file evidence is related. Foreign key to the SoftwareTitle table.
FileEvidenceID	<i>Type:</i> integer. Key The file evidence related to the software title. Foreign key to the FileEvidence table.
EvidenceExistenceRuleID	<i>Type:</i> integer The evidence existence rule related to the software title. Foreign key to the EvidenceExistenceRule table.
TrackUsage	<i>Type:</i> boolean If this field is <code>True</code> , the linked file evidence should be considered when calculating whether the application title is being used. If <code>False</code> , the file is not tracked for usage calculations.
IsLocal	<i>Type:</i> boolean If this field is <code>False</code> , the link has come from the ARL. If it is <code>True</code> , then the link has been created by an operator.
IsShared	<i>Type:</i> boolean

SoftwareTitleHierarchy Table

SoftwareTitleHierarchy records a hierarchy of applications. This table records relationships between Oracle database and component applications, between suites and their members, and between generic titles and more specific ones that will replace them.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 460: Database columns for SoftwareTitleHierarchy table

Database Column	Details
ParentSoftwareTitleID	<i>Type:</i> integer. Key The parent application. Foreign key to the SoftwareTitle table.
ChildSoftwareTitleID	<i>Type:</i> integer. Key The child application. Foreign key to the SoftwareTitle table.
IsLicensable	<i>Type:</i> boolean. Nullable This field is used for Oracle option titles. Set this field to True to indicate that the child application needs to be separately licensed. If this field is False, the child application does not need to be separately licensed when the parent application is present and licensed.
IsMandatory	<i>Type:</i> boolean. Nullable This field is used on component applications of software suites. When the value is True, the child application must be installed for the suite to be recognized as installed. Otherwise, the application may or may not be installed for the suite to be recognized.
RemovalOfChild	<i>Type:</i> boolean. Nullable This field is used to allow removal of titles when higher quality titles (with more specified evidence) are also found installed. When the value is True, the child application should be removed if evidence is found that both it and its parent title are installed. Otherwise, the child application is left in place.
IsLocal	<i>Type:</i> boolean If this field is False, the link has come from the ARL. If it is True, then the link has been created by an operator.

Database Column	Details
IsMandatoryDefault	<i>Type:</i> boolean. Nullable This field is used on component applications of software suites. This indicates the Default value of the Mandatory field and can be used to determine if this has been overridden by the user, in the case of an application with non-local membership to the suite (that is, the ARL specifies that the app belongs to the suite).
IsShared	<i>Type:</i> boolean

SoftwareTitleHierarchyEx Table

The SoftwareTitleHierarchyEx table contains additional information on the suite by FlexNet Manager Suite.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 461: Database columns for SoftwareTitleHierarchyEx table

Database Column	Details
ParentSoftwareTitleID	Type: integer. Key The parent application. Foreign key to the SoftwareTitle table.
ChildSoftwareTitleID	Type: integer. Key The child application. Foreign key to the SoftwareTitle table.
IsMandatory	Type: boolean. Nullable This field is used on component applications of software suites. When the value is True, the child application must be installed for the suite to be recognized as installed. Otherwise, the application may or may not be installed for the suite to be recognized.

SoftwareTitleInstallerEvidence Table

SoftwareTitleInstallerEvidence links software (application) titles to installer evidence.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 462: Database columns for SoftwareTitleInstallerEvidence table

Database Column	Details
SoftwareTitleID	<i>Type:</i> integer. Key The software title to which the installer evidence is related. Foreign key to the SoftwareTitle table.
InstallerEvidenceID	<i>Type:</i> integer. Key The installer evidence related to the software title. Foreign key to the InstallerEvidence table.
IsLocal	<i>Type:</i> boolean If this field is <i>False</i> , the link has come from the ARL. If it is <i>True</i> , then the link has been created by an operator.
IsShared	<i>Type:</i> boolean

SoftwareTitleLicense Table

The SoftwareTitleLicense table links software (application) titles to licenses.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 463: Database columns for SoftwareTitleLicense table

Database Column	Details
SoftwareTitleID	Type: integer. Key The application. Foreign key to the SoftwareTitle table.
SoftwareLicenseID	Type: integer. Key The license covering this application. Foreign key to the SoftwareLicense table.
CompliancePriority	Type: integer. Nullable Installations of this application will consume the linked licenses in this table in order of priority. When NULL, the default priority stored in SoftwareLicenseType table will be used.
LicenseKeyValue	Type: text (max 400 characters). Nullable The license (installation) key value to be used when this license covers an installation of this application.
SoftwareTitleLicense ReasonID	Type: integer The reason that this application has been added to this license. Foreign key to the SoftwareTitleLicenseReason table.
CreationUser	Type: text (max 128 characters). Nullable The operator who created the record.
CreationDate	Type: datetime The date the record was created.

SoftwareTitleLicenseProposal Table

The SoftwareTitleLicenseProposal table is used to store a summary of application changes to a particular software license. The changes have been inferred from changes to the license definition used to create the software license.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 464: Database columns for SoftwareTitleLicenseProposal table

Database Column	Details
SoftwareTitleLicense ProposalID	Type: integer. Key. Generated ID Primary key for the SoftwareTitleLicenseProposal table.
SoftwareTitleID	Type: integer. Key Foreign key to the SoftwareTitle table.
SoftwareTitleProductID	Type: integer. Key. Nullable Foreign key to the SoftwareTitleProduct table.
OldPrimarySoftwareTitleID	Type: integer. Nullable The existing primary application of the license. This can be null if there is no primary application.
Supplementary	Type: boolean Whether this product will be added to this license as supplementary (counted for consumption) or not.
SoftwareLicenseID	Type: integer. Key Foreign key to the SoftwareLicense table.
SoftwareLicense DefinitionID	Type: integer Foreign key to the SoftwareLicenseDefinition table.
LicenseDefinitionVersion	Type: integer The version of the license definition that has been used for these proposed changes.
SoftwareTitleLicense ProposalActionID	Type: integer. Key The proposed action for the software title on the software license.
SoftwareLicense ProposalStatusID	Type: integer The state of this software license change proposal.

Database Column	Details
Conflicted	<i>Type:</i> boolean Whether this license title change proposal conflicts with another for the same license.
CreationUser	<i>Type:</i> text (max 128 characters). Nullable The operator who created the record.
CreationDate	<i>Type:</i> datetime The date the record was created.
UpdatedUser	<i>Type:</i> text (max 128 characters). Nullable The operator who updated the record.
UpdatedDate	<i>Type:</i> datetime. Nullable The date the record was updated.

SoftwareTitleLicenseProposalAction Table

SoftwareTitleLicenseProposalAction is a static table listing all of the actions that can be proposed for a software title on a software license.

Table 465: Database columns for SoftwareTitleLicenseProposalAction table

Database Column	Details
SoftwareTitleLicenseProposalActionID	<i>Type:</i> integer. Key. Generated ID
ResourceName	<i>Type:</i> text (max 256 characters). Key The unique name of the localizable resource string representing the SoftwareTitleLicenseProposalAction record. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 256 characters) The text to display if the state resource string has no translation.

SoftwareTitleLicenseReason Table

SoftwareTitleLicenseReason is a static table listing valid reasons why a software title was added to a license.

Table 466: Database columns for SoftwareTitleLicenseReason table

Database Column	Details
SoftwareTitleLicenseReasonID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each SoftwareTitleLicenseReason. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = Manual• 2 = Current• 3 = Edition Downgrade• 4 = Version Downgrade• 5 = Version Upgrade.
ReasonResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing the reason a license was linked to a title. Foreign key to the ComplianceResourceString table.</p>
ReasonDefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the reason resource string has no translation.</p>

SoftwareTitleOracle Table

The SoftwareTitleOracle table stores attributes of an application installation that are relevant to Oracle applications only. These characteristics are important for Oracle licensing.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 467: Database columns for SoftwareTitleOracle table

Database Column	Details
SoftwareTitleID	Type: integer. Key The Oracle application. Foreign key to the SoftwareTitle table.
MaximumSockets	Type: integer. Nullable The maximum number of sockets allowed on a computer where the application is installed.
NUPProcessorMultiplier	Type: integer. Nullable The multiplier value to use when determining the minimum Named User Plus licenses for the application.
OverrideSoftwareTitleTypeID	Type: integer. Nullable If this is not null, then the application was initially created as non-Oracle, but the operator wants to license it as an Oracle title. Foreign key to the SoftwareTitleType table.
IsShared	Type: boolean

SoftwareTitleProduct Table

The “product”, unique for a given publisher, is the common name of a set of applications, independent of version or edition (for example, “Acrobat”).


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 468: Database columns for SoftwareTitleProduct table

Database Column	Details
SoftwareTitleProductID	Type: integer. Key. Generated ID The unique identifier for a product.
SoftwareTitlePublisherID	Type: integer. Key. Nullable The publisher of this product. Foreign key to the SoftwareTitlePublisher table.
ProductName	Type: text (max 200 characters). Key The application’s product name.
IsLocal	Type: boolean If this field is False, the product has come from the ARL. If it is True, then the product has been created by an operator.
IsShared	Type: boolean

SoftwareTitleProperty Table

SoftwareTitleProperty defines extra custom properties for all applications.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 469: Database columns for SoftwareTitleProperty table

Database Column	Details
SoftwareTitlePropertyID	Type: integer. Key. Generated ID The unique identifier for a software title property.
PropertyName	Type: text (max 256 characters). Key The name of the property.
CustomPropertyDisplayXMLID	Type: integer. Nullable Foreign key to a record in the CustomPropertyDisplayXML table, describing how to show the property on a property dialog.

SoftwareTitlePropertyValue Table

For each application, SoftwareTitlePropertyValue stores the values for the custom properties defined in SoftwareTitleProperty.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 470: Database columns for SoftwareTitlePropertyValue table

Database Column	Details
SoftwareTitleProperty ValueID	Type: integer. Key. Generated ID A unique identifier for a property value.
SoftwareTitleID	Type: integer. Key The title for which the property is being stored. Foreign key to the SoftwareTitle table.
SoftwareTitlePropertyID	Type: integer. Key The property whose value is being stored. Foreign key to the SoftwareTitleProperty table.
PropertyValue	Type: text (max 4000 characters) The property value.
CreationUser	Type: text (max 128 characters). Nullable The operator who created the record.
CreationDate	Type: datetime The date the record was created.
UpdatedUser	Type: text (max 128 characters). Nullable The operator who last updated the record.
UpdatedDate	Type: datetime. Nullable The date the record was last updated.

SoftwareTitlePublisher Table

Publishers of software applications (for example, “Microsoft”). Note that only application records take the publisher name from this table. License and contract records take the publisher name from the Vendor table.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 471: Database columns for SoftwareTitlePublisher table

Database Column	Details
SoftwareTitlePublisherID	<i>Type:</i> integer. Key. Generated ID The unique identifier for a publisher.
PublisherName	<i>Type:</i> text (max 200 characters). Key The publisher name.
IsLocal	<i>Type:</i> boolean If this field is <i>False</i> , the publisher has come from the ARL. If it is <i>True</i> , then the publisher has been created by an operator.
EOSLUrl	<i>Type:</i> text (max 2083 characters). Nullable The publisher’s end of support life URL.
IsShared	<i>Type:</i> boolean

SoftwareTitleRegistryEvidence Table

Reserved for future use.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 472: Database columns for SoftwareTitleRegistryEvidence table

Database Column	Details
SoftwareTitleID	Type: integer. Key The software title to which the registry evidence is related. Foreign key to the SoftwareTitle table.
RegistryEvidenceID	Type: integer. Key The registry evidence related to the software title. Foreign key to the RegistryEvidence table.
IsShared	Type: boolean

SoftwareTitleSuite Table

For software that has been classed as a suite (because it has other applications linking to it as component applications), SoftwareTitleSuite identifies how many of its member applications must be present for the installation to count as a suite installation, using “application evidence” for suite recognition.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 473: Database columns for SoftwareTitleSuite table

Database Column	Details
SoftwareTitleID	Type: integer. Key The suite. Foreign key to the SoftwareTitle table.
MinNumberApps	Type: integer The minimum number of member applications of the software suite that must be installed.
MinNumberAppsDefault	Type: integer. Nullable The original, default value of MinNumberApps before it was changed.
IsShared	Type: boolean

SoftwareTitleSuiteEx Table

The SoftwareTitleSuiteEx table contains additional information on the suite by FlexNet Manager Suite.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 474: Database columns for SoftwareTitleSuiteEx table

Database Column	Details
SoftwareTitleID	Type: integer. Key A unique identifier for a software record.
MinNumberApps	Type: integer. Nullable The minimum number of member applications of the software suite that must be installed.

SoftwareTitleType Table

SoftwareTitleType is a static table listing possible types of software (application) titles. This is used particularly to identify types that need special processing. It is quite distinct from license types.

Table 475: Database columns for SoftwareTitleType table

Database Column	Details
SoftwareTitleTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for a SoftwareTitleType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = General • 2 = Oracle Database • 3 = Oracle Option • 4 = Oracle Application • 5 = Oracle EBS Server • 6 = Oracle EBS.
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing a document type. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the type resource string has no translation.</p>
InstanceTypeID	<p><i>Type:</i> integer</p> <p>The type of instance that can be created for this application. Foreign key to the InstanceType table.</p>

SoftwareTitleVersion Table

A list of application versions, which must be unique for a given product. Examples include “6.4”, “XP”, “Vista” and “2003”.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 476: Database columns for SoftwareTitleVersion table

Database Column	Details
SoftwareTitleVersionID	Type: integer. Key. Generated ID The unique identifier for a version.
SoftwareTitleProductID	Type: integer. Key The version’s product. Foreign key to the SoftwareTitleProduct table.
VersionName	Type: text (max 50 characters). Key The text for this application version.
VersionWeight	Type: decimal Version weight (for ordering, so we know which versions are upgrades/ downgrades of other versions).
IsLocal	Type: boolean If this field is False, the version has come from the ARL. If it is True, then the version has been created by an operator.
IsShared	Type: boolean

SoftwareTitleVersionServicePack Table


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 477: Database columns for SoftwareTitleVersionServicePack table

Database Column	Details
SoftwareTitleVersionID	Type: integer. Key The application version. Foreign key to the SoftwareTitleVersion table.
ServicePackID	Type: integer. Key The service pack. Foreign key to the ServicePack table.

SoftwareTitleWMIEvidence Table

SoftwareTitleWMIEvidence links software titles to WMI evidence.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 478: Database columns for SoftwareTitleWMIEvidence table

Database Column	Details
SoftwareTitleID	Type: integer. Key The software title to which the WMI evidence is related. Foreign key to the SoftwareTitle table.
WMIEvidenceID	Type: integer. Key The WMI evidence related to the software title. Foreign key to the WMIEvidence table.
IsLocal	Type: boolean If this field is False, the link has come from the ARL. If it is True, then the link has been created by an operator.
IsShared	Type: boolean

SoftwareUserLicensePointsConsumedData Table

SoftwareUserLicensePointsConsumed records how many software license entitlements have been consumed for a given license by a given end-user.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 479: Database columns for SoftwareUserLicensePointsConsumedData table

Database Column	Details
ComplianceUserID	<i>Type:</i> integer. Key The end-user. Foreign key to the ComplianceUserSnapshot table.
SoftwareLicenseID	<i>Type:</i> integer. Key The license. Foreign key to the SoftwareLicenseSnapshot table.
LicensesConsumed	<i>Type:</i> integer The number of points (or entitlements) consumed for the license by the end-user.
CalculatedConsumption	<i>Type:</i> integer The calculated consumption value for this license assignment before exemptions or overrides are considered.
LicensesUsed	<i>Type:</i> integer How many of the points consumed are for installations that are actually being used.
LicenseMeasurementID	<i>Type:</i> integer. Key The license measurement ID. Foreign key to the LicenseMeasurement table.

SoftwareUserLicensePointsConsumedSuggested Table

SoftwareUserLicensePointsConsumedSuggested records how many software license entitlements would be consumed by an end-user for an optimized (suggested) license. Currently used to track optimized license usage suggested by FlexNet Manager for SAP.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 480: Database columns for SoftwareUserLicensePointsConsumedSuggested table

Database Column	Details
ComplianceUserID	Type: integer. Key The end-user. Foreign key to the ComplianceUser table.
SuggestedSoftwareLicenseID	Type: integer. Key The suggested or optimized license. Foreign key to the SoftwareLicense table.
LicensesConsumed	Type: integer The number of points (or entitlements) consumed for the license by the end-user.
LicensesUsed	Type: integer How many of the points consumed are for installations that are actually being used.
LicenseMeasurementID	Type: integer. Key The associated SAP license measurement snapshot. Foreign key to the LicenseMeasurement table.
LicensesCalculated	Type: integer The number of points (or entitlements) calculated for the license by the end-user.

SoftwareUserLicensePointsConsumedSuggestedHistory Table

SoftwareUserLicensePointsConsumedSuggestedHistory table records the history of suggested (optimised) license consumption.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 481: Database columns for SoftwareUserLicensePointsConsumedSuggestedHistory table

Database Column	Details
ComplianceUserID	Type: integer. Key The end-user. Foreign key to the ComplianceUser table.
SuggestedSoftwareLicenseID	Type: integer. Key The suggested or optimized license. Foreign key to the SoftwareLicense table.
LicensesConsumed	Type: integer The number of points (or entitlements) consumed for the license by the end-user.
LicensesUsed	Type: integer How many of the points consumed are for installations that are actually being used.
LicenseMeasurementID	Type: integer. Key The associated SAP license measurement snapshot. Foreign key to the LicenseMeasurement table.
LicensesCalculated	Type: integer The number of points (or entitlements) calculated for the license by the end-user.

SoftwareUserLicensePointsHistory Table

SoftwareUserLicensePointsHistory records history of license consumption by end-users.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 482: Database columns for SoftwareUserLicensePointsHistory table

Database Column	Details
ComplianceUserID	Type: integer. Key The end-user. Foreign key to the ComplianceUser table.
SoftwareLicenseID	Type: integer. Key The license. Foreign key to the SoftwareLicense table.
LicensesConsumed	Type: integer The number of points (or entitlements) consumed for the license by an end-user.
LicensesUsed	Type: integer How many of the points consumed are for installations that are actually being used.
LicenseMeasurementID	Type: integer. Key The associated SAP license measurement snapshot. Foreign key to the LicenseMeasurement table.
LicensesCalculated	Type: integer The number of points (or entitlements) calculated for the license by the end-user.

Tag Table

Reserved for future development.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 483: Database columns for Tag table

Database Column	Details
TagID	Type: integer. Key. Generated ID The unique ID for this tag.
Name	Type: text (max 128 characters). Key The name of this tag.
Description	Type: text Description of this tag and its purpose.

TargetOperatingSystemType Table

TargetOperatingSystemType; is a static table listing all types of OSes that can be targeted by licensing.

Table 484: Database columns for TargetOperatingSystemType table

Database Column	Details
TargetOperatingSystemTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each TargetOperatingSystemType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = All• 2 = Windows Server operating systems• 3 = Windows desktop operating systems• 4 = Non Windows Server operating systems
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing an Operating System family. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the type resource string has no translation.</p>

VDI Table

VDI is the list of VDI devices


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 485: Database columns for VDI table

Database Column	Details
VDIID	Type: integer. Key. Generated ID A unique identifier for a VDI device.
ComputerName	Type: text (max 256 characters). Key The computer name of the VDI.
ComplianceDomainID	Type: integer. Key. Nullable The domain the VDI is a member of. Foreign key to the ComplianceDomain table.
VDIGroupID	Type: integer. Key The VDI group the VDI device belongs to. Foreign key to the VDIGroup table.
VDITemplateID	Type: integer. Key The master VM template of the VDI. Foreign key to the VDITemplate table.
RetiredDate	Type: datetime. Key. Nullable The date the VDI device was deleted.
ApplicationDeliveryOnly	Type: boolean. Key Determines whether the VDI device is used only to server applications.

VDIEndPointAccess Table

VDIEndPointAccess is the list of endpoint devices that have accessed VDI devices


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 486: Database columns for VDIEndPointAccess table

Database Column	Details
VDIEndPointAccessID	Type: integer. Key. Generated ID A unique identifier for an endpoint device accessing a VDI.
ComplianceComputerID	Type: integer. Key. Nullable A unique identifier for the endpoint. Foreign key to the ComplianceComputer table.
ComplianceUserID	Type: integer. Key. Nullable A unique identifier for the endpoint user. Foreign key to the ComplianceUser table.
VDIID	Type: integer. Key A unique identifier for the VDI. Foreign key to the VDI table.
LogonTime	Type: datetime. Nullable The date the user logged on to the VDI.

VDIGroup Table

VDIGroup stores the list of available VDI groups in a VDI environment.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 487: Database columns for VDIGroup table

Database Column	Details
VDIGroupID	Type: integer. Key. Generated ID A unique identifier for a VDI Group record.
GroupName	Type: text (max 128 characters). Key The VDI Group name
VDISiteID	Type: integer. Key The VDI site ID
VDIGroupUUID	Type: unique identifier. Key. Nullable The UUID of the VDI group

VDISite Table

VDISite stores the list of available VDI sites.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 488: Database columns for VDISite table

Database Column	Details
VDISiteID	Type: integer. Key. Generated ID A unique identifier for a VDI site record.
SiteName	Type: text (max 256 characters). Key The VDI Group name
AccessModeID	Type: integer. Key The access mode of the VDI site. Foreign key to the AccessMode table.

VDITemplate Table

VDITemplate stores the list of available VDI groups in a VDI environment.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 489: Database columns for VDI Template table

Database Column	Details
VDITemplateID	Type: integer. Key. Generated ID A unique identifier for a VDI Group record.
TemplateName	Type: text (max 256 characters). Key The VDI template name.
VDISiteID	Type: integer. Key. Nullable The VDI template's site ID
ComplianceComputerID	Type: integer. Key. Nullable The VDI template's ComplianceComputerID

VDIUser Table

VDIUser is the list of users that have access to VDI groups


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 490: Database columns for VDIUser table

Database Column	Details
VDIUserID	Type: integer. Key. Generated ID A unique identifier for a VDI User.
VDIGroupID	Type: integer. Key A unique identifier for the VDI Group. Foreign key to the VDIGroup table.
ComplianceUserID	Type: integer. Key. Nullable A unique identifier for the user with access to a VDI Group. Foreign key to the ComplianceUser table.

WMIEvidence Table

WMIEvidence lists WMI evidence that is used to identify that a particular item of software (defined in the SoftwareTitle table) has been installed on a computer.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 491: Database columns for WMIEvidence table

Database Column	Details
WMIEvidenceID	Type: integer. Key. Generated ID A unique identifier for a WMI evidence record.
ClassName	Type: text (max 50 characters). Key The WMI class name of the WMI evidence.
PropertyName	Type: text (max 50 characters). Key The WMI property name of the WMI evidence.
PropertyValue	Type: text (max 256 characters). Key The value of the WMI evidence property.
Ignored	Type: boolean Set this field to True if this WMI evidence is ignored for application recognition.
IsShared	Type: boolean

WMIEvidenceMatchCount Table

WMIEvidenceMatchCount tracks the number of times that each WMI evidence (rule) has been detected as installed and recorded in the data source. A separate count is kept for each WMI evidence rule, and for each data source.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 492: Database columns for WMIEvidenceMatchCount table

Database Column	Details
WMIEvidenceMatchCountID	Type: integer. Key. Generated ID A synthetic unique identifier is required, since ComplianceConnectionID, being nullable, cannot be included in the primary key.
WMIEvidenceID	Type: integer. Key WMI evidence rule being matched. Foreign key to the WMIEvidence table.
ComplianceConnectionID	Type: integer. Key. Nullable Data source where the match is occurring. Foreign key to the ComplianceConnection table.
MatchedCount	Type: integer The number of installed WMI evidence records in this data source matching this WMI evidence rule.
InstallCount	Type: integer The number of physical application installations recognized in this data source using this WMI evidence rule.

Compliance.Logic.Structure Tables

The complete set of database tables documented here includes:

- ComplianceDomain table (see [ComplianceDomain Table](#))
- GroupEx table (see [GroupEx Table](#))
- GroupExPathCultureType table (see [GroupExPathCultureType Table](#))
- GroupType table (see [GroupType Table](#))
- MemberEx table (see [MemberEx Table](#))
- RoleRight table (see [RoleRight Table](#))

ComplianceDomain Table

Stores a list of domain names imported FlexNet Manager Suite.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 493: Database columns for ComplianceDomain table

Database Column	Details
ComplianceDomainID	Type: integer. Key. Generated ID A unique identifier for a domain.
QualifiedName	Type: text (max 100 characters) The fully qualified name of the domain.
FlatName	Type: text (max 32 characters) The flat name of the domain.

GroupEx Table

The GroupEx table stores information about enterprise groups and roles.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 494: Database columns for GroupEx table

Database Column	Details
GroupID	Type: integer. Key. Generated ID A unique identifier for a group.
GroupTypeID	Type: integer. Key Identifies the group type. Foreign key to the GroupType table.
BusinessView	Type: boolean. Key Set this to True if the group is a business view (that is, is a group heading like Roles or Categories).
Path	Type: text (max 500 characters) Complete path of the group.
NextChild	Type: integer The ID number for the next child to be created under this group. Internal use only: do not edit.
GroupExID	Type: text (max 128 characters). Key Unique string identifier for this extension record.
BusinessPhoneNumber	Type: text (max 30 characters). Nullable The business phone number of the group.
FaxPhoneNumber	Type: text (max 30 characters). Nullable The fax number of the group.
Address_Street	Type: text (max 200 characters). Nullable The street address of the group.
Address_City	Type: text (max 200 characters). Nullable The city of the group.
Address_State	Type: text (max 200 characters). Nullable The state of the group.

Database Column	Details
Address_ZIP	<i>Type:</i> text (max 20 characters). Nullable The ZIP or postal code of the group.
Address_Country	<i>Type:</i> text (max 100 characters). Nullable The country of the group.
Email	<i>Type:</i> text (max 200 characters). Nullable The email address of the group.
Comments	<i>Type:</i> text. Nullable Comments about the group.
IsStockLocation	<i>Type:</i> boolean For locations only. If this field is set to True, the location is considered to be a stock or storage location.
ContactID	<i>Type:</i> integer. Nullable A contact person for this group. This field is no longer in use in FlexNet Manager Suite
ManagerID	<i>Type:</i> integer. Nullable A manager for this group. This field is no longer in use in FlexNet Manager Suite
GroupCN	<i>Type:</i> text (max 256 characters). Nullable The common name for the group.
NameResourceName	<i>Type:</i> text (max 256 characters). Nullable The unique name of the localizable resource string representing an enterprise group name (GroupCN). Foreign key to the ComplianceResourceString table.
DescriptionResourceName	<i>Type:</i> text (max 256 characters). Nullable The unique name of the localizable resource string representing an enterprise group description (Comments). Foreign key to the ComplianceResourceString table.
ParentGroupExID	<i>Type:</i> text (max 128 characters). Key. Nullable Unique string identifier for the parent record.
TreeLevel	<i>Type:</i> integer. Nullable The level of this group in the hierarchy.
TreePath	<i>Type:</i> text (max 4000 characters). Key. Nullable A generated path that can be used to sort groups in tree order.
IsShared	<i>Type:</i> boolean

GroupExPathCultureType Table

The GroupExPathCultureType table stores complete enterprise group paths per culture type for each enterprise group.

Table 495: Database columns for GroupExPathCultureType table

Database Column	Details
GroupID	<i>Type:</i> integer. Key The ID of the group the translated path belongs to.
CultureType	<i>Type:</i> text (max 12 characters). Key A unique identifier for a culture type.
Path	<i>Type:</i> text (max 500 characters) The translated group path for the specific culture type.
TreePath	<i>Type:</i> text (max 4000 characters) A generated path that can be used to sort groups in tree order.

GroupType Table

The collection of types of enterprise groups, such as locations, departments, and cost centers.

Table 496: Database columns for GroupType table

Database Column	Details
GroupTypeID	<i>Type:</i> integer. Key. Generated ID A unique identifier for each GroupType. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• 1 = Location• 2 = Departments• 3 = Cost Center• 4 = Category• 5 = Role.
Description	<i>Type:</i> text (max 255 characters). Key A description of the type of enterprise group.
ResourceName	<i>Type:</i> text (max 256 characters). Key. Nullable The unique name of the localizable resource string representing a group type. Foreign key to the ComplianceResourceString table.

MemberEx Table

The MemberEx table stores the membership lists for every enterprise group or role.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 497: Database columns for MemberEx table

Database Column	Details
GroupID	Type: integer. Key The GroupEx to which the member belongs.
TargetTypeID	Type: integer. Key The TargetType. Possible values are: <ul style="list-style-type: none">• 3 = Enterprise Group• 9 = Asset• 10 = Contract• 11 = Purchase Order• 12 = Software License• 13 = Software Title• 14 = Computer• 15 = User• 16 = Operator• 17 = SAP system landscapes• 18 = SAP systems• 19 = SAP rule sets
TargetID	Type: integer. Key The Asset, Contract, etc. identifier, depending on TargetType.

RoleRight Table

Each action by FlexNet Manager Suite requires the role to have one or more RoleRights to perform an ActionClass over a given Resource.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 498: Database columns for RoleRight table

Database Column	Details
GroupID	Type: integer. Key The role to whom the right is granted or denied.
ResourceID	Type: integer. Key The Resource to which the RoleRight applies.
ActionClassID	Type: integer. Key The action class which applies (read or modify).
Denied	Type: boolean When TRUE (1), indicates that the specified right is denied.
ScopeGroupID	Type: integer. Key. Nullable The enterprise group to which the right for this role applies, if applicable.

Compliance.Logic.Users Tables

The complete set of database tables documented here includes:

- ComplianceUser table (see [ComplianceUser Table](#))
- ComplianceUserConnection table (see [ComplianceUserConnection Table](#))
- ComplianceUserInventorySourceType table (see [ComplianceUserInventorySourceType Table](#))
- ComplianceUserStatus table (see [ComplianceUserStatus Table](#))
- EmploymentStatus table (see [EmploymentStatus Table](#))
- UserSuffix table (see [UserSuffix Table](#))
- UserTitle table (see [UserTitle Table](#))

ComplianceUser Table

ComplianceUser stores information about end-users in the enterprise, including contact details, login details and inventory source details (if applicable). End-users in ComplianceUser will not be able to log in to FlexNet Manager Suite unless they have a corresponding record in the ComplianceOperator table.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 499: Database columns for ComplianceUser table

Database Column	Details
ComplianceUserID	Type: integer. Key. Generated ID A unique identifier for the end-user.
UserName	Type: text (max 512 characters). Nullable The end-user's full name. When creating a new end-user manually, defaults to a concatenation of title, first name, middle name, last name and suffix.
SAMAccountName	Type: text (max 64 characters). Key. Nullable The login name (SAM account name) of the end-user.
ComplianceDomainID	Type: integer. Key. Nullable Domain that the end-user belongs to. Foreign key to the ComplianceDomain table.
LocationID	Type: text (max 128 characters). Key. Nullable Any enterprise location associated with this end-user. Foreign key to the GroupEx table.
BusinessUnitID	Type: text (max 128 characters). Key. Nullable Any corporate unit in the enterprise associated with this end-user. Foreign key to the GroupEx table.
CostCenterID	Type: text (max 128 characters). Key. Nullable Any cost center in the enterprise associated with this end-user. Foreign key to the GroupEx table.
CategoryID	Type: text (max 128 characters). Key. Nullable No longer in use, but retained for legacy systems. Any enterprise category associated with this end-user. Foreign key to the GroupEx table.

Database Column	Details
EmployeeNumber	<i>Type:</i> text (max 128 characters). Key. Nullable The employee number of the end-user (as defined in an organization's own HR system).
UserTitleID	<i>Type:</i> integer. Nullable The title of the end-user. Foreign key to the UserTitle table.
FirstName	<i>Type:</i> text (max 128 characters). Nullable The first name of the end-user.
MiddleName	<i>Type:</i> text (max 128 characters). Nullable The middle name(s) of the end-user.
LastName	<i>Type:</i> text (max 128 characters). Nullable The last name (surname) of the end-user.
UserSuffixID	<i>Type:</i> integer. Nullable The suffix to the name of the end-user. Foreign key to the UserSuffix table.
JobTitle	<i>Type:</i> text (max 128 characters). Nullable The job title of the end-user.
BusinessPhoneNumber	<i>Type:</i> text (max 30 characters). Nullable The work phone number of the end-user.
MobilePhoneNumber	<i>Type:</i> text (max 30 characters). Nullable The mobile phone number of the end-user.
FaxPhoneNumber	<i>Type:</i> text (max 30 characters). Nullable The fax number of the end-user.
Address_Street	<i>Type:</i> text (max 200 characters). Nullable The street address of the end-user.
Address_City	<i>Type:</i> text (max 200 characters). Nullable The city or suburb name of the end-user.
Address_State	<i>Type:</i> text (max 200 characters). Nullable The state or province of the end-user.
Address_ZIP	<i>Type:</i> text (max 20 characters). Nullable The ZIP or postal code of the end-user.
Address_Country	<i>Type:</i> text (max 100 characters). Nullable The country of the end-user.

Database Column	Details
Email	<i>Type:</i> text (max 200 characters). Key. Nullable The email address of the end-user.
AlternateEmail	<i>Type:</i> text (max 200 characters). Nullable The alternate email address of the end-user.
Messenger	<i>Type:</i> text (max 200 characters). Nullable The instant messenger address of the end-user.
ManagerID	<i>Type:</i> integer. Key. Nullable The manager of the end-user. Foreign key to another end-user in the ComplianceUser table.
CurrencyID	<i>Type:</i> integer. Nullable No longer in use - default currency is now stored in the OperatorTenantSetting table.
UserStatusID	<i>Type:</i> integer The end-user's status. Foreign key to the ComplianceUserStatus table.
EmploymentStatusID	<i>Type:</i> integer. Nullable The end-user's employment status. Foreign key to the EmploymentStatus table.
IsIncluded	<i>Type:</i> boolean If False, the end-user's login name is in the list of excluded accounts, and this end-user will not consume licenses or be recorded as the last-logged-on or calculated end-user of a computer. This end-user will also not appear in many lists of end-users.
CreationUser	<i>Type:</i> text (max 128 characters). Nullable The operator who created the record.
CreationDate	<i>Type:</i> datetime The date the record was created.
UpdatedUser	<i>Type:</i> text (max 128 characters). Nullable The operator who last updated the record.
UpdatedDate	<i>Type:</i> datetime. Nullable The date the record was last updated.
ComplianceUser InventorySourceTypeID	<i>Type:</i> integer Whether this end-user has ever been reported in inventory, or has been manually created and maintained. Foreign key to the ComplianceUserInventorySourceType table.

Database Column	Details
InventoryAgent	<i>Type:</i> text (max 64 characters). Nullable If this end-user is reported in inventory, the name of the person or tool that performed the last inventory.
GeneratedFromEmail	<i>Type:</i> boolean If True, the <code>ComplianceUser</code> record was generated using the email address provided by a source connection.

ComplianceUserConnection Table

ComplianceUserConnection stores a link between end-users in ComplianceUser which have been reported in inventory, and external IDs which can be used to identify them in their inventory sources. End-users reported in multiple inventory sources will appear multiple times in this table.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 500: Database columns for ComplianceUserConnection table

Database Column	Details
ComplianceUserID	Type: integer. Key A unique identifier for the end-user. Foreign key to the ComplianceUser table.
ComplianceConnectionID	Type: integer. Key The inventory source where the end-user was reported. Foreign key to the ComplianceConnection table.
ExternalID	Type: big integer. Key A (hopefully unique) identifier for the end-user in the external inventory source.

ComplianceUserInventorySourceType Table

ComplianceUserInventorySourceType is a static table used to define possible end-user inventory source values (that is, whether the end-user was created manually or reported by the compliance importer).

Table 501: Database columns for ComplianceUserInventorySourceType table

Database Column	Details
ComplianceUser	<i>Type:</i> integer. Key. Generated ID
InventorySourceTypeID	<p>A unique identifier for each ComplianceUserInventorySourceType. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = Automatic (end-user was recently updated during an inventory import) • 2 = Manual (end-user was created manually by an operator, using FlexNet Manager Suite, and has never been updated by the compliance importer).
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing an inventory source. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the inventory source resource string has no translation.</p>

ComplianceUserStatus Table

ComplianceUserStatus is a static table listing status values for end-user.

Table 502: Database columns for ComplianceUserStatus table

Database Column	Details
ComplianceUserStatusID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each ComplianceUserStatus. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = Active • 2 = Inactive • 3 = Retired • 4 = On leave • 5 = Pending (perhaps for an employee just starting with the company).
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing an end-user status. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the status resource string has no translation.</p>
IsUserActive	<p><i>Type:</i> boolean. Key</p> <p>If this field is set to <code>False</code>, any end-user with this status will not consume licenses or be recorded as the last-logged-on or calculated end-user of a computer. This end-user will also not appear in many lists of end-users.</p>

EmploymentStatus Table

EmploymentStatus is a static table listing possible employment statuses values for end-users.

Table 503: Database columns for EmploymentStatus table

Database Column	Details
EmploymentStatusID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each EmploymentStatus. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = Employee• 2 = Consultant• 3 = Temporary• 4 = Part time• 5 = Casual.
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing an employment status. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the employment status resource string has no translation.</p>

UserSuffix Table

UserSuffix is a static table listing possible name suffixes for end-users.

Table 504: Database columns for UserSuffix table

Database Column	Details
UserSuffixID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each UserSuffix. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = Jr.• 2 = Sr.• 3 = I• 4 = II• 5 = III.
ResourceString	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing an end-user name suffix. Foreign key to the ComplianceResourceString table.</p>
DefaultString	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the suffix resource string has no translation.</p>

UserTitle Table

UserTitle is a static table listing the possible titles of end-users.

Table 505: Database columns for UserTitle table

Database Column	Details
UserTitleID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each UserTitle. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = Mr. • 2 = Miss • 3 = Mrs. • 4 = Ms. • 5 = Dr. • 6 = Prof.
ResourceString	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The unique name of the localizable resource string representing an end-user title. Foreign key to the ComplianceResourceString table.</p>
DefaultString	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the title resource string has no translation.</p>

Compliance.SAP Tables

The complete set of database tables documented here includes:

- SAPActivityCheckMultipleLogons table (see [SAPActivityCheckMultipleLogons Table](#))
- SAPActivityCheckSummary table (see [SAPActivityCheckSummary Table](#))
- SAPActivityCheckWorkTime table (see [SAPActivityCheckWorkTime Table](#))
- SAPCompositeRole table (see [SAPCompositeRole Table](#))
- SAPConnectivityDirectionType table (see [SAPConnectivityDirectionType Table](#))
- SAPConnectivityType table (see [SAPConnectivityType Table](#))
- SAPConsolidatedUser table (see [SAPConsolidatedUser Table](#))
- SAPConsolidatedUserDuplicate table (see [SAPConsolidatedUserDuplicate Table](#))
- SAPConsumption table (see [SAPConsumption Table](#))
- SAPContentEngine table (see [SAPContentEngine Table](#))
- SAPContentEngineRule table (see [SAPContentEngineRule Table](#))
- SAPDuplicateUserRecommendation table (see [SAPDuplicateUserRecommendation Table](#))
- SAPEngine table (see [SAPEngine Table](#))
- SAPEngineConsumptionSummary table (see [SAPEngineConsumptionSummary Table](#))
- SAPEngineMetric table (see [SAPEngineMetric Table](#))
- SAPEngineMetricName table (see [SAPEngineMetricName Table](#))
- SAPEngineName table (see [SAPEngineName Table](#))
- SAPEnginePeriodType table (see [SAPEnginePeriodType Table](#))
- SAPEngineSystemConsumption table (see [SAPEngineSystemConsumption Table](#))
- SAPImportedInventoryFileDigest table (see [SAPImportedInventoryFileDigest Table](#))
- SAPLicenseRatio table (see [SAPLicenseRatio Table](#))
- SAPLicenseRecommendation table (see [SAPLicenseRecommendation Table](#))
- SAPLicenseType table (see [SAPLicenseType Table](#))
- SAPLicenseTypeHierarchy table (see [SAPLicenseTypeHierarchy Table](#))
- SAPLicenseTypeName table (see [SAPLicenseTypeName Table](#))
- SAPModule table (see [SAPModule Table](#))
- SAPMultipleLogon table (see [SAPMultipleLogon Table](#))

- SAPObject table (see [SAPObject Table](#))
- SAPObjectType table (see [SAPObjectType Table](#))
- SAPRFCCConnection table (see [SAPRFCCConnection Table](#))
- SAPRFCCConnectionSummary table (see [SAPRFCCConnectionSummary Table](#))
- SAPRecommendationAdjustmentReason table (see [SAPRecommendationAdjustmentReason Table](#))
- SAPRecommendationProcessedStatus table (see [SAPRecommendationProcessedStatus Table](#))
- SAPRecommendationSet table (see [SAPRecommendationSet Table](#))
- SAPRecommendationSetStatus table (see [SAPRecommendationSetStatus Table](#))
- SAPRecommendationSetSummary table (see [SAPRecommendationSetSummary Table](#))
- SAPRole table (see [SAPRole Table](#))
- SAPRoleConsumption table (see [SAPRoleConsumption Table](#))
- SAPRoleTransactionCode table (see [SAPRoleTransactionCode Table](#))
- SAPRule table (see [SAPRule Table](#))
- SAPRuleAlgorithm table (see [SAPRuleAlgorithm Table](#))
- SAPRuleCategory table (see [SAPRuleCategory Table](#))
- SAPRuleMapping table (see [SAPRuleMapping Table](#))
- SAPRuleSet table (see [SAPRuleSet Table](#))
- SAPRuleSetMapping table (see [SAPRuleSetMapping Table](#))
- SAPRuleType table (see [SAPRuleType Table](#))
- SAPSecurityUser table (see [SAPSecurityUser Table](#))
- SAPSystem table (see [SAPSystem Table](#))
- SAPSystemActivityCheckSummary table (see [SAPSystemActivityCheckSummary Table](#))
- SAPSystemEngineMetric table (see [SAPSystemEngineMetric Table](#))
- SAPSystemEnvironment table (see [SAPSystemEnvironment Table](#))
- SAPSystemGroup table (see [SAPSystemGroup Table](#))
- SAPSystemLandscape table (see [SAPSystemLandscape Table](#))
- SAPSystemLandscapeEngine table (see [SAPSystemLandscapeEngine Table](#))
- SAPSystemLandscapeEngineMapping table (see [SAPSystemLandscapeEngineMapping Table](#))
- SAPSystemLandscapeLicenseType table (see [SAPSystemLandscapeLicenseType Table](#))
- SAPSystemLandscapeLicenseTypeHierarchy table (see [SAPSystemLandscapeLicenseTypeHierarchy Table](#))

- SAPSystemLandscapeLicenseTypeImport table (see [SAPSystemLandscapeLicenseTypeImport Table](#))
- SAPSystemLandscapeStatus table (see [SAPSystemLandscapeStatus Table](#))
- SAPSystemModule table (see [SAPSystemModule Table](#))
- SAPSystemObject table (see [SAPSystemObject Table](#))
- SAPSystemPriceList table (see [SAPSystemPriceList Table](#))
- SAPSystemPriceListName table (see [SAPSystemPriceListName Table](#))
- SAPSystemRFCCConnectionSummary table (see [SAPSystemRFCCConnectionSummary Table](#))
- SAPSystemRoleType table (see [SAPSystemRoleType Table](#))
- SAPSystemType table (see [SAPSystemType Table](#))
- SAPTransactionProfile table (see [SAPTransactionProfile Table](#))
- SAPTransactionProfileObject table (see [SAPTransactionProfileObject Table](#))
- SAPUser table (see [SAPUser Table](#))
- SAPUserRole table (see [SAPUserRole Table](#))
- SAPUserType table (see [SAPUserType Table](#))

SAPActivityCheckMultipleLogons Table

This table stores SAP activity check data related to work time.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 506: Database columns for SAPActivityCheckMultipleLogons table

Database Column	Details
SAPActivityCheckMultipleLogonsID	Type: integer. Key. Generated ID A unique identifier for the SAP activity check multiple login data.
SAPActivityCheckMultipleLogonsUID	Type: text (max 32 characters). Key The SAP unique identifier for the SAP activity check multiple login data.
SAPUserID	Type: integer. Key Foreign key to the SAP user.
SAPSystemLandscapeID	Type: integer. Key Foreign key to the system landscape that the SAP activity check multiple login data belongs to.
MeasurementDate	Type: datetime The date that the SAP activity check multiple login data was measured.
MeasurementPeriodStartDate	Type: datetime The start date that the SAP activity check multiple login data was measured from.
MeasurementPeriodEndDate	Type: datetime The end date that the SAP activity check multiple login data was measured to.
NumberOfMultipleLogons	Type: integer The number of logons the user account has made from different systems at the same time during the measurement period.
MultipleLogonsPeakDate	Type: datetime The date where the number of logons the user account has made from different systems at the same time during the measurement period reached its peak value.

SAPActivityCheckSummary Table

This table stores SAP activity check summary data.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 507: Database columns for SAPActivityCheckSummary table

Database Column	Details
SAPActivityCheckSummaryID	Type: integer. Key. Generated ID A unique identifier for the SAP activity check summary.
SAPUserID	Type: integer. Key Foreign key to the SAP user.
SAPSystemLandscapeID	Type: integer. Key Foreign key to the system landscape that the SAP activity check work time data belongs to.
HasExceededBreakDuration	Type: boolean Indicates whether or not the user has exceeded the minimum required break duration.
HasMultipleLogons	Type: boolean Indicates whether or not the user has multiple logons.
IsHidden	Type: boolean Is this record marked as hidden in the UI.

SAPActivityCheckWorkTime Table

This table stores SAP activity check data related to work time.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 508: Database columns for SAPActivityCheckWorkTime table

Database Column	Details
SAPActivityCheckWorkTimeID	Type: integer. Key. Generated ID A unique identifier for the SAP activity check work time data.
SAPActivityCheckWorkTimeUID	Type: text (max 32 characters). Key The SAP unique identifier for the SAP activity check work time data.
SAPUserID	Type: integer. Key Foreign key to the SAP user.
SAPSystemLandscapeID	Type: integer. Key Foreign key to the system landscape that the SAP activity check work time data belongs to.
MeasurementDate	Type: datetime The date that the SAP activity check work time data was measured.
MeasurementPeriodStartDate	Type: datetime The start date that the SAP activity check work time data was measured from.
MeasurementPeriodEndDate	Type: datetime The end date that the SAP activity check work time data was measured to.
BreakDurationSetting	Type: integer The minimum number of seconds that a user must not be running any transactions in a 24 hour period.
TableName	Type: text (max 256 characters). Key The name of the SAP table that was accessed during the minimum required break period.
BreakDurationResult	Type: integer The number of days that the user has not meet the minimum break duration setting during the measurement period.

SAPCompositeRole Table

This table stores SAP composite roles.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 509: Database columns for SAPCompositeRole table

Database Column	Details
SAPCompositeRoleID	Type: integer. Key. Generated ID A unique identifier for SAP composite role.
CompositeRoleID	Type: integer. Key Foreign key to SAP role which contain one or more single roles.
SingleRoleID	Type: integer. Key Foreign key to SAP role that is a member if the composite role.

SAPConnectivityDirectionType Table

This table stores SAP connectivity direction type.

Table 510: Database columns for SAPConnectivityDirectionType table

Database Column	Details
SAPConnectivityDirectionTypeID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the SAP connectivity direction type.
TypeName	<i>Type:</i> text (max 64 characters). Key A unique lookup for each SAPConnectivityDirectionType. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• Out• In• InOut
ResourceName	<i>Type:</i> text (max 256 characters). Nullable A localizable resource string representing a SAP connectivity type. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the SAP connectivity type resource string has no translation.

SAPConnectivityType Table

This table stores SAP connectivity type.

Table 511: Database columns for SAPConnectivityType table

Database Column	Details
SAPConnectivityTypeID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the SAP connectivity type.
TypeName	<i>Type:</i> text (max 64 characters). Key A unique lookup for each SAPConnectivityType. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• Interactive• Batch
ResourceName	<i>Type:</i> text (max 256 characters). Nullable A localizable resource string representing a SAP connectivity type. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the SAP connectivity type resource string has no translation.

SAPConsolidatedUser Table

This table stores the data specific to an SAP consolidated user.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 512: Database columns for SAPConsolidatedUser table

Database Column	Details
SAPConsolidatedUserID	Type: integer. Key. Generated ID A unique identifier for the SAP consolidated user.
UserUID	Type: text (max 128 characters). Key A globally unique identifier for the SAP license recommendation.
SAPRecommendationSetID	Type: integer. Key Foreign key to the SAP recommendation set that the duplicate user recommendation belongs to.
SAPUserID	Type: integer. Key Foreign key to the SAP user that the duplicate user recommendation belongs to.
UserName	Type: text The user name of the user that the duplicate user recommendation belongs to.
DuplicateGroupNum	Type: integer The unique identifier showing which users are duplicates of one another.
LicenseType	Type: text (max 2 characters). Nullable The license code originally assigned to the user.
IsConsolidatedBySAP	Type: boolean Whether or not this user is consolidated by SAP.
OptimalLicenseType	Type: text (max 2 characters). Nullable The license code recommended the user be assigned ignoring license ratios and rebalancing.

SAPConsolidatedUserDuplicate Table

This table stores the data specific to an SAP consolidated user duplicate.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 513: Database columns for SAPConsolidatedUserDuplicate table

Database Column	Details
SAPConsolidatedUserDuplicateID	Type: integer. Key. Generated ID A unique identifier for the SAP consolidated duplicate user.
SAPRecommendationSetID	Type: integer. Key Foreign key to the SAP recommendation set that the duplicate user belongs to.
SAPConsolidatedUserID	Type: integer. Key Foreign key to the SAP consolidated user linked to a SAP user.
SAPUserID	Type: integer. Key Foreign key to the SAP user that the duplicate user belongs to.
IsConsolidatedBySAP	Type: boolean. Key Whether or not this user is consolidated by SAP.

SAPConsumption Table

This table stores the data related to the definition of SAP consumption data.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 514: Database columns for SAPConsumption table

Database Column	Details
SAPConsumptionID	<i>Type:</i> integer. Key. Generated ID The unique identifier for the SAP consumption.
SAPUserID	<i>Type:</i> integer. Key Foreign key to the SAP user that the consumption belongs to.
TimePeriodStartDate	<i>Type:</i> datetime. Key The date and time of the consumption
AccountObject	<i>Type:</i> text (max 40 characters). Key The account object
AccountObjectDetails	<i>Type:</i> text (max 40 characters). Key The account object details
EntryType	<i>Type:</i> text (max 1 characters). Key The consumption entry type
TaskType	<i>Type:</i> text (max 2 characters). Key The consumption task type
CPUTime	<i>Type:</i> decimal. Key. Nullable CPU usage in seconds
MemoryUsed	<i>Type:</i> big integer. Nullable Memory used
PrivateMemoryUsed	<i>Type:</i> big integer. Nullable Private memory used
AccessCount	<i>Type:</i> integer. Nullable Number of times the object has been used/accessed.

SAPContentEngine Table

This table stores an engine from downloadable content.

Table 515: Database columns for SAPContentEngine table

Database Column	Details
SAPContentEngineID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the SAP content engine table.
EngineContentUID	<i>Type:</i> text (max 128 characters). Key A global unique identifier for the engine.
EngineName	<i>Type:</i> text (max 128 characters) Name of engine.
EngineDescription	<i>Type:</i> text. Nullable Description of engine.
Comments	<i>Type:</i> text. Nullable Comments from factory.
ApplicationID	<i>Type:</i> integer. Nullable SAP internal application ID
ConsumptionUnit	<i>Type:</i> text. Nullable Unit description to describe the consumption amount.
CreationDate	<i>Type:</i> datetime The data and time the engine was created.
UpdatedDate	<i>Type:</i> datetime The date and time the engine was last updated.

SAPContentEngineRule Table

This table stores an engine rule from downloadable content.

Table 516: Database columns for SAPContentEngineRule table

Database Column	Details
SAPContentEngineRuleID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the SAP content engine rule table.
EngineContentUID	<i>Type:</i> text (max 128 characters) A global unique identifier for the engine.
RuleContentUID	<i>Type:</i> text (max 128 characters). Key A global unique identifier for the engine rule.
RuleName	<i>Type:</i> text (max 128 characters) Name of engine rule.
RuleDefinition	<i>Type:</i> text. Nullable Rule definition for calculating consumption of an engine.
IsDefault	<i>Type:</i> boolean Is this formula the default for created packages.
CreationDate	<i>Type:</i> datetime The data and time the engine rule was created.
UpdatedDate	<i>Type:</i> datetime The date and time the engine rule was last updated.

SAPDuplicateUserRecommendation Table

This table stores the data specific to an SAP duplicate user recommendation.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 517: Database columns for SAPDuplicateUserRecommendation table

Database Column	Details
SAPDuplicateUserRecommendationID	Type: integer. Key. Generated ID A unique identifier for the SAP duplicate user recommendation.
RecommendationUID	Type: text (max 128 characters). Key A globally unique identifier for the SAP license recommendation.
SAPRecommendationSetID	Type: integer. Key Foreign key to the SAP recommendation set that the duplicate user recommendation belongs to.
DuplicateGroupNum	Type: integer The unique identifier showing which users are duplicates of one another.
SAPUserID	Type: integer. Key. Nullable The unique identifier of the user that the duplicate user recommendation belongs to.
UserName	Type: text The user name of the user that the duplicate user recommendation belongs to.
SystemID	Type: text The ID of the system that the duplicate user recommendation belongs to.
ClientID	Type: text The ID of the client that the duplicate user recommendation belongs to.
IsConsolidatedBySAP	Type: boolean Whether or not this duplicate is consolidated by SAP.
SAPRuleID	Type: integer. Nullable The unique identifier of the rule used to produce the duplicate user recommendation.

Database Column	Details
RuleSetName	<i>Type:</i> text. Nullable The name of the rule set used to produce the duplicate user recommendation.
RuleName	<i>Type:</i> text. Nullable The name of the rule used to produce the duplicate user recommendation.
RuleSequenceNumber	<i>Type:</i> integer. Nullable The sequence number of the rule used to produce the duplicate user recommendation.
RuleMessage	<i>Type:</i> text. Nullable The message produced given by the rule used to produce the duplicate user recommendation.
SAPRecommendation ProcessedStatusID	<i>Type:</i> integer Foreign key to the SAP recommendation processed status of the duplicate user recommendation.
RuleMessageResourceName	<i>Type:</i> text (max 256 characters). Nullable The resource name of the message produced given by the rule used to produce the duplicate user recommendation.
RuleMessageParameters	<i>Type:</i> text (max 256 characters). Nullable The parameters used by the message produced given by the rule used to produce the duplicate user recommendation.

SAPEngine Table

This table stores the application engines used in SAP.

Table 518: Database columns for SAPEngine table

Database Column	Details
SAPEngineID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the SAP engine table.
ApplicationID	<i>Type:</i> integer. Key The unique identifier given to the application engine by SAP.
SAPEnginePeriodTypeID	<i>Type:</i> integer A unique identifier for the SAP engine period type.

SAPEngineConsumptionSummary Table

This table stores the total consumption of SAP package consumption recommendation.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 519: Database columns for SAPEngineConsumptionSummary table

Database Column	Details
SAPEngineConsumptionSummaryID	Type: integer. Key. Generated ID A unique identifier for the SAP engine consumption.
LandscapeUID	Type: text (max 128 characters) A global unique identifier for the system landscape the summary belongs to.
RecommendationSetUID	Type: text (max 128 characters) A global unique identifier for the SAP recommendation set the summary belongs to.
SAPRecommendationSetStatusID	Type: integer The status of the recommendation set.
SAPSystemLandscapeEngineID	Type: integer. Key. Nullable A unique identifier for the SAP system landscape engine table.
EngineUID	Type: text (max 128 characters) A global unique identifier for the SAP engine in a system landscape.
EngineName	Type: text (max 128 characters) Name of engine.
Consumed	Type: decimal. Nullable The number of consumed units for the package (null = indeterminate)
ConsumptionUnit	Type: text. Nullable Unit description to describe the consumption amount.
ReasonMessage	Type: text. Nullable And optional message detailing the reason for the consumed result.
EntitlementsPurchased	Type: integer Total number of purchased license entitlements.
EngineUnitPrice	Type: currency. Nullable The unit price of a license entitlement.

Database Column	Details
EngineUnitPriceRateID	<i>Type:</i> integer. Nullable The unit price rate of a license entitlement.
CalculationDate	<i>Type:</i> datetime The date of the license postion calculation.
SystemMeasurementDate	<i>Type:</i> datetime The date the system measurement calculation was performed.

SAPEngineMetric Table

This table stores the application engine metrics used in SAP.

Table 520: Database columns for SAPEngineMetric table

Database Column	Details
SAPEngineMetricID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the SAP engine metric table.
MetricID	<i>Type:</i> integer. Key The unique identifier given to the application engine metric by SAP.

SAPEngineMetricName Table

This table stores the name of applications engine metrics in different languages.

Table 521: Database columns for SAPEngineMetricName table

Database Column	Details
SAPEngineMetricNameID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the SAP engine metric name table.
SAPEngineMetricID	<i>Type:</i> integer. Key The unique identifier of an SAP engine metric.
EngineMetricName	<i>Type:</i> text (max 128 characters). Key. Nullable The name of the application engine metric.
Language	<i>Type:</i> text (max 4 characters). Key A unique code to identify the language.

SAPEngineName Table

This table stores the name of applications engines in different languages.

Table 522: Database columns for SAPEngineName table

Database Column	Details
SAPEngineNameID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the SAP engine name table.
SAPEngineID	<i>Type:</i> integer. Key The unique identifier of an SAP engine.
EngineName	<i>Type:</i> text (max 128 characters). Key. Nullable The name of the application engine.
Language	<i>Type:</i> text (max 4 characters). Key A unique code to identify the language.

SAPEnginePeriodType Table

This table stores the types of SAP applications engine measurement periods.

Table 523: Database columns for SAPEnginePeriodType table

Database Column	Details
SAPEnginePeriodTypeID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the SAP engine period type table.
PeriodTypeCode	<i>Type:</i> text (max 1 characters). Key A unique lookup for each SAPEnginePeriodType. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• Y = Last year• C = Last calendar year• T = Year to date• M = This month• Q = This quarter• 6 = Last six months• U = Undefined
ResourceName	<i>Type:</i> text (max 256 characters) A localizable resource string representing a SAP system type. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the system type resource string has no translation.

SAPEngineSystemConsumption Table

This table stores the per-system consumption of SAP package consumption recommendation.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 524: Database columns for SAPEngineSystemConsumption table

Database Column	Details
SAPEngineSystem ConsumptionID	Type: integer. Key. Generated ID A unique identifier for the SAP engine consumption.
SAPRecommendationSetID	Type: integer. Key Foreign key to the SAP recommendation set that the license recommendation belongs to.
SAPSystemLandscape EngineID	Type: integer. Key. Nullable A unique identifier for the SAP system landscape engine table.
EngineUID	Type: text (max 128 characters) A global unique identifier for the SAP engine in a system landscape.
EngineName	Type: text (max 128 characters) Name of engine.
SAPSystemID	Type: integer. Key. Nullable The unique identifier of the system that the consumed count belongs to.
SystemID	Type: text The ID of the system that the license recommendation belongs to.
ClientID	Type: text The ID of the client that the license recommendation belongs to.
Consumed	Type: decimal. Nullable The number of consumed units for the package (null = indeterminate)
ReasonMessage	Type: text. Nullable And optional message detailing the reason for the consumed result.
SystemMeasurementDate	Type: datetime. Nullable The date the system measurement calculation was performed.

SAPImportedInventoryFileDigest Table

This table stores digests of imported SAP inventory files.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 525: Database columns for SAPImportedInventoryFileDigest table

Database Column	Details
SAPImportedInventoryFileDigestID	Type: integer. Key. Generated ID A unique identifier for the SAP impoted inventory file digest.
LandscapeUID	Type: text (max 128 characters). Key A global unique identifier for the system landscape.
SystemID	Type: text (max 64 characters). Key The System ID that is used to identify the SAP system.
ClientID	Type: text (max 32 characters). Key The Client ID that is to be used when connecting to the SAP system.
SystemNumber	Type: text (max 32 characters). Key. Nullable The SAP system number. This value will be used by the RFC connection.
MD5Hash	Type: text (max 64 characters). Key MD5 hash of imported SAP inventory file content.
CreationDate	Type: datetime The data and time the digest record was created.

SAPLicenseRatio Table

This table stores SAP license ratios used for recommending optimizations for SAP.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 526: Database columns for SAPLicenseRatio table

Database Column	Details
SAPLicenseRatioID	Type: integer. Key. Generated ID A unique identifier for the SAP license ratio.
LeftLicenseType	Type: text (max 2 characters) The type of license assigned to the left side of the license ratio.
LeftValue	Type: integer The value belonging to the left side of the license ratio.
RightLicenseType	Type: text (max 2 characters) The type of license assigned to the right side of the license ratio.
RightValue	Type: integer The value belonging to the right side of the license ratio.
SAPSystemLandscapeID	Type: integer. Key Foreign key to the system landscape that the license ratio belongs to.
IsActive	Type: boolean Whether or not this license ratio is used to automatically optimize SAP license assignments.
CreationUser	Type: text (max 256 characters) The user who created the license ratio.
CreationDate	Type: datetime The data and time the license ratio was created.
UpdatedUser	Type: text (max 256 characters) The last user who update the license ratio.
UpdatedDate	Type: datetime The date and time the license ratio was last updated.

SAPLicenseRecommendation Table

This table stores the data specific to an SAP license recommendation.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 527: Database columns for SAPLicenseRecommendation table

Database Column	Details
SAPLicenseRecommendationID	Type: integer. Key. Generated ID A unique identifier for the SAP license recommendation.
RecommendationUID	Type: text (max 128 characters). Key A globally unique identifier for the SAP license recommendation.
SAPRecommendationSetID	Type: integer. Key Foreign key to the SAP recommendation set that the license recommendation belongs to.
SAPUserID	Type: integer. Key. Nullable The unique identifier of the user that the license recommendation belongs to.
UserName	Type: text The user name of the user that the license recommendation belongs to.
SystemID	Type: text The ID of the system that the license recommendation belongs to.
ClientID	Type: text The ID of the client that the license recommendation belongs to.
OriginalLicenseType	Type: text (max 2 characters). Nullable The license code originally assigned to the user.
RecommendedLicenseType	Type: text (max 2 characters). Nullable The license code recommended the user be assigned.
SAPRuleID	Type: integer. Nullable The unique identifier of the rule used to produce the license recommendation.
RuleSetName	Type: text. Nullable The name of the rule set used to produce the license recommendation.

Database Column	Details
RuleName	<i>Type:</i> text. Nullable The name of the rule used to produce the license recommendation.
RuleSequenceNumber	<i>Type:</i> integer. Nullable The sequence number of the rule used to produce the license recommendation.
RuleMessage	<i>Type:</i> text. Nullable The message produced given by the rule used to produce the license recommendation.
SAPRecommendation ProcessedStatusID	<i>Type:</i> integer Foreign key to the SAP recommendation processed status of the license recommendation.
OptimalLicenseType	<i>Type:</i> text (max 2 characters). Nullable The license code recommended the user be assigned ignoring license ratios and rebalancing.
SAPRecommendation AdjustmentReasonID	<i>Type:</i> integer. Nullable The unique identifier of the reason why the license recommendation differs from optimal.
RuleMessageResourceName	<i>Type:</i> text (max 256 characters). Nullable The resource name of the message produced given by the rule used to produce the license recommendation.
RuleMessageParameters	<i>Type:</i> text (max 256 characters). Nullable The parameters used by the message produced given by the rule used to produce the license recommendation.

SAPLicenseType Table

This table stores the SAP license type on SAP systems.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 528: Database columns for SAPLicenseType table

Database Column	Details
SAPLicenseTypeID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the SAP license type.
SAPSystemID	<i>Type:</i> integer. Key Foreign key to the system that the SAP license type belongs to.
Identifier	<i>Type:</i> text (max 2 characters). Key SAP license type identifier
SAPSpecialVersionID	<i>Type:</i> integer. Key. Nullable SAP special version ID
Active	<i>Type:</i> boolean Indicates whether the SAP license type is active or not active.
SpecialVersionAssignment	<i>Type:</i> boolean. Nullable Indicates whether the SAP license type is affected by special version.
SSCR_Allow	<i>Type:</i> boolean. Nullable
IsDeleted	<i>Type:</i> boolean Indicated whether the SAP license type has been deleted or not.

SAPLicenseTypeHierarchy Table

This table stores SAP license type hierarchy.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 529: Database columns for SAPLicenseTypeHierarchy table

Database Column	Details
SAPLicenseTypeHierarchyID	Type: integer. Key. Generated ID The unique identifier for the SAP license type hierarchy.
SAPLicenseTypeID	Type: integer. Key Parent license type. Foreign key to the SAP license type.
ChildSAPLicenseTypeID	Type: integer. Key Child license type. Foreign key to SAP license type.

SAPLicenseTypeName Table

This table stores SAP license types in various languages.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 530: Database columns for SAPLicenseTypeName table

Database Column	Details
SAPLicenseTypeNameID	Type: integer. Key. Generated ID Unique identifier for SAP license type name.
SAPLicenseTypeID	Type: integer. Key Foreign key to the SAP license type.
Language	Type: text (max 4 characters) The two letter language code.
ShortName	Type: text (max 128 characters). Nullable SAP license type short name.
LongName	Type: text (max 256 characters). Nullable SAP license type long name

SAPModule Table

This table stores the modules used in SAP.

Table 531: Database columns for SAPModule table

Database Column	Details
SAPModuleID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the SAP module table.
ModuleName	<i>Type:</i> text (max 64 characters). Key The name of the module.
SubModuleName	<i>Type:</i> text (max 64 characters). Key. Nullable The name of the sub module.
ObjectName	<i>Type:</i> text (max 40 characters). Key. Nullable The name of the object linked to the SAP system module.

SAPMultipleLogon Table

This table stores logon metrics for SAP users.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 532: Database columns for SAPMultipleLogon table

Database Column	Details
SAPMultipleLogonID	Type: integer. Key. Generated ID A unique identifier for the user’s logon metrics
SAPUserID	Type: integer. Key Foreign key to the SAP user.
Year	Type: text (max 4 characters) The year of the logon metrics
NumberOfMultipleLogon	Type: integer. Nullable Number of multiple concurrent logon
MaxMultipleLogon	Type: integer. Nullable Maximum number of concurrent logon

SAPObject Table

This table stores the SAP object

Table 533: Database columns for SAPObject table

Database Column	Details
SAPObjectID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the SAP object.
ObjectName	<i>Type:</i> text (max 40 characters). Key Name of the object
SAPObjectTypeID	<i>Type:</i> integer. Key Foreign key to the SAP object type that identifies the object type.

SAPObjectType Table

This tables stores SAP object types

Table 534: Database columns for SAPObjectType table

Database Column	Details
SAPObjectTypeID	<i>Type:</i> integer. Key. Generated ID <ul style="list-style-type: none">• 1 = Transaction• 2 = Report• 3 = Job• 4 = NonSAP
TypeName	<i>Type:</i> text (max 64 characters). Key A unique name for the SAP object type.
ResourceName	<i>Type:</i> text (max 256 characters). Nullable A localizable resource string representing a SAP object type. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the object type resource string has no translation.

SAPRFCConnection Table

This table stores RFC connections made to the SAP system.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 535: Database columns for SAPRFCConnection table

Database Column	Details
SAPRFCConnectionID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the SAP RFC consumption.
SAPUserID	<i>Type:</i> integer. Key SAP user performing the RFC connection. Foreign key to the SAPUser table
TimePeriodStartDate	<i>Type:</i> datetime. Key The date and time of the RFC connection
RemoteSystem	<i>Type:</i> text (max 128 characters). Key Remote system name connecting to the SAP system.
ProgramName	<i>Type:</i> text (max 40 characters). Key Program Name associated to the function name.
FunctionName	<i>Type:</i> text (max 40 characters). Key The function executed by the RFC calls
TaskType	<i>Type:</i> text (max 2 characters). Key. Nullable Task type.
RFCDestination	<i>Type:</i> text (max 128 characters). Key The RFC destination string value.
TotalExecutionCount	<i>Type:</i> integer The number of times the function is executed.
TotalExecutionTime	<i>Type:</i> decimal Total execution time.
TotalCallTime	<i>Type:</i> decimal Total call time.
TotalDataSent	<i>Type:</i> big integer Total data sent by the RFC calls.

Database Column	Details
TotalDataReceived	Type: big integer Total data received b the RFC calls.

SAPRFCConnectionSummary Table

This table stores the remote RFC consumption summary. It only includes Non-SAP remote system


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 536: Database columns for SAPRFCConnectionSummary table

Database Column	Details
SAPRFCConnectionSummaryID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the remote SAP RFC connection summary.
RemoteSystem	<i>Type:</i> text (max 128 characters). Key Remote system making the RFC calls.
NumberOfSAPSystems	<i>Type:</i> integer Number of SAP systems the Remote System is connecting to.
NumberOfDialogUsers	<i>Type:</i> integer Number of Dialog SAP users making the RFC call to the SAP system.
NumberOfNonDialogUsers	<i>Type:</i> integer Number of Service SAP users making the RFC call to the SAP system.
NumberOfExecutedPrograms	<i>Type:</i> integer The number of executed programs
NumberOfExecutedFunctions	<i>Type:</i> integer The number of executed functions
TotalExecutionCount	<i>Type:</i> integer The total excution count of all functions.
TotalExecutionTime	<i>Type:</i> decimal Total execution time.
TotalCallTime	<i>Type:</i> decimal Total call time.
TotalDataSent	<i>Type:</i> big integer Total data sent by the RFC calls.
TotalDataReceived	<i>Type:</i> big integer Total data received b the RFC calls.

Database Column	Details
IsHidden	<i>Type:</i> boolean Is this record marked as hidden in the UI.

SAPRecommendationAdjustmentReason Table

This table stores SAP Recommendation adjustment reasons.

Table 537: Database columns for SAPRecommendationAdjustmentReason table

Database Column	Details
SAPRecommendation AdjustmentReasonID	<i>Type:</i> integer. Key. Generated ID A unique identifier for each SAPRecommendationAdjustmentReason. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• 1 = License ratio enforced• 2 = Excess purchase(s) of covering license type applied.
ResourceName	<i>Type:</i> text (max 256 characters). Key A localizable resource string representing a SAP recommendation adjustment reason. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the adjustment reason resource string has no translation.

SAPRecommendationProcessedStatus Table

This table stores SAP Recommendation Processed status.

Table 538: Database columns for SAPRecommendationProcessedStatus table

Database Column	Details
SAPRecommendation ProcessedStatusID	<i>Type:</i> integer. Key. Generated ID A unique identifier for each SAPRecommendationProcessedStatus. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• 1 = Pending• 2 = Accepted• 3 = Rejected
ResourceName	<i>Type:</i> text (max 256 characters). Key A localizable resource string representing a SAP recommendation processed status. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the status resource string has no translation.

SAPRecommendationSet Table

This table stores data specific to the definition of a recommendation set.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 539: Database columns for SAPRecommendationSet table

Database Column	Details
SAPRecommendationSetID	Type: integer. Key. Generated ID A unique identifier for the SAP recommendation set.
RecommendationSetUID	Type: text (max 128 characters). Key A global unique identifier for the SAP recommendation set.
RecommendationSetName	Type: text (max 128 characters) Name of recommendation set.
RecommendationSet Description	Type: text. Nullable Description of recommendation set.
LandscapeUID	Type: text (max 128 characters) A global unique identifier for the system landscape the recommendation set belongs to.
SAPRecommendationSet StatusID	Type: integer. Key The status of the recommendation set.
CalculationDate	Type: datetime. Nullable The date of the license postion calculation.
CreationUser	Type: text (max 256 characters) The user who created the recommendation set.
CreationDate	Type: datetime The data and time the recommendation set was created.
UpdatedUser	Type: text (max 256 characters) The last user who update the recommendation set.
UpdatedDate	Type: datetime The date and time the recommendation set was last updated.
ReviewedUser	Type: text (max 256 characters). Nullable The user who reviewed the recommendation set.

Database Column	Details
ReviewedDate	<i>Type:</i> datetime. Nullable The date and time the recommendation set was reviewed.
ReleasedUser	<i>Type:</i> text (max 256 characters). Nullable The user who released the recommendation set.
ReleasedDate	<i>Type:</i> datetime. Nullable The date and time the recommendation set was released.
Uploaded	<i>Type:</i> boolean Indicates whether the recommendation set was oploaded by FNM-SAP
UploadedDate	<i>Type:</i> datetime. Nullable The date the recommendation set was oploaded by FNM-SAP

SAPRecommendationSetStatus Table

This table stores SAP Recommendation Set status.

Table 540: Database columns for SAPRecommendationSetStatus table

Database Column	Details
SAPRecommendationSet StatusID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>A unique identifier for each SAPRecommendationSetStatus. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none"> • 1 = In Review • 2 = Archived • 3 = Released • 4 = New License Position • 5 = Rejected • 6 = Simulation. • 7 = Creating
ResourceName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>A localizable resource string representing a SAP recommendation set status. Foreign key to the ComplianceResourceString table.</p>
DefaultValue	<p><i>Type:</i> text (max 100 characters)</p> <p>The text to display if the status resource string has no translation.</p>

SAPRecommendationSetSummary Table

This table stores a history of SAP license positions.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 541: Database columns for SAPRecommendationSetSummary table

Database Column	Details
SAPRecommendationSet SummaryID	Type: integer. Key. Generated ID A unique identifier for the SAP license recommendation summary.
LandscapeUID	Type: text (max 128 characters). Key A global unique identifier for the system landscape the summary belongs to.
RecommendationSetUID	Type: text (max 128 characters). Key A global unique identifier for the SAP recommendation set the summary belongs to.
SAPRecommendationSet StatusID	Type: integer The status of the recommendation set.
LicenseType	Type: text (max 2 characters). Key. Nullable The license code to which the position applies.
EntitlementsPurchased	Type: integer Total number of purchased license entitlements.
EntitlementsOriginal	Type: integer Total number of consumed license entitlements.
EntitlementsRecommended	Type: integer Total number of recommended license entitlements.
LicenseTypeUnitPrice	Type: currency. Nullable The unit price of a license entitlement.
LicenseTypeUnitPrice RateID	Type: integer. Nullable The unit price rate of a license entitlement.
CalculationDate	Type: datetime The date of the license position calculation.

Database Column	Details
EntitlementsOptimal	<i>Type:</i> integer Total number of recommended license entitlements without license ratio constraints.

SAPRole Table

This table stores SAP roles


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 542: Database columns for SAPRole table

Database Column	Details
SAPRoleID	Type: integer. Key. Generated ID A unique identifier for the SAP role.
SAPSystemID	Type: integer. Key Foreign key to the system that the role belongs to.
RoleName	Type: text (max 30 characters) The name of the role.
NumberOfTransactionCodes	Type: integer. Nullable Total number of transaction codes allowed to be executed by this role.
LicenseType	Type: text (max 2 characters). Nullable License type associated to this role

SAPRoleConsumption Table

This table stores SAP roles and its link to SAP consumption.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 543: Database columns for SAPRoleConsumption table

Database Column	Details
SAPRoleConsumptionID	Type: integer. Key. Generated ID A unique identifier for for SAP role consumption.
SAPUserID	Type: integer. Key Foreign key to the SAP user that the role consumption belongs to.
CompositeRoleID	Type: integer. Key. Nullable Foreign key to SAP role.
SingleRoleID	Type: integer. Key Foreign key to SAP role.
SingleRoleTransaction CodeID	Type: integer. Key Foreign key to SAP transaction code.
SAPConsumptionID	Type: integer. Key Foreign key to SAP consumption.

SAPRoleTransactionCode Table

This table stores list of roles and its transaction codes.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 544: Database columns for SAPRoleTransactionCode table

Database Column	Details
SAPRoleTransactionCodeID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the roles and its transaction codes.
SAPRoleID	<i>Type:</i> integer. Key Foreign to the SAP Roles where transaction codes belong to.
TCodeLow	<i>Type:</i> text (max 80 characters). Key. Nullable Lower range of the transaction code.
TCodeHigh	<i>Type:</i> text (max 40 characters). Nullable Upper range of the transaction code.

SAPRule Table

This table stores SAP rules used for recommending optimizations for SAP.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 545: Database columns for SAPRule table

Database Column	Details
SAPRuleID	Type: integer. Key. Generated ID A unique identifier for the SAP rule.
RuleName	Type: text (max 128 characters) Name of the rule.
SAPRuleTypeID	Type: integer. Key Foreign key to the rule type of the SAP rule.
SAPRuleSetID	Type: integer. Key Foreign key to the rule set that the SAP rule belongs to.
RuleDefinition	Type: text The rule definition XML used to build the rule statement used by the SAP rules engine.
SequenceNumber	Type: integer The sequence number used to designate the order of the rules within the rule set.
SAPRuleCategoryID	Type: integer. Key Foreign key to the rule category of the SAP rule.
IsActive	Type: boolean Whether or not this rule is active for execution.
UseRuleSetMapping	Type: boolean Whether or not to use mapping from the SAP rule set
CreationUser	Type: text (max 256 characters) The user who created the system landscape.
CreationDate	Type: datetime The data and time the system landscape was created.

Database Column	Details
UpdatedUser	<i>Type:</i> text (max 256 characters) The last user who update the system landscape.
UpdatedDate	<i>Type:</i> datetime The date and time the system landscape was last updated.

SAPRuleAlgorithm Table

This table stores the available SAP rule algorithms used by SAP rules.

Table 546: Database columns for SAPRuleAlgorithm table

Database Column	Details
SAPRuleAlgorithmID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the SAP rule algorithm.
AlgorithmName	<i>Type:</i> text (max 100 characters). Key A unique name for the SAP category.
SAPRuleCategoryID	<i>Type:</i> integer. Key Foreign key to the rule category of the SAP rule algorithm.
TitleResourceName	<i>Type:</i> text (max 256 characters). Nullable A localizable resource string representing a SAP rule algorithm. Foreign key to the ComplianceResourceString table.
TitleDefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the rule type resource string has no translation.
AlgorithmType	<i>Type:</i> text Type associated with this algorithm
AlgorithmData	<i>Type:</i> text. Nullable Data associated with this algorithm, such as a custom SQL query to run.

SAPRuleCategory Table

This table stores the different rule categories used in recommending optimizations for SAP.

Table 547: Database columns for SAPRuleCategory table

Database Column	Details
SAPRuleCategoryID	Type: integer. Key. Generated ID A unique identifier for the SAP rule category.
CategoryName	Type: text (max 100 characters). Key A unique name for the SAP category.

SAPRuleMapping Table

This table stores mapping between SAP rule to either System Landscapes, System Groups or SAP systems.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 548: Database columns for SAPRuleMapping table

Database Column	Details
SAPRuleMappingID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the SAP rule set mapping.
SAPRuleID	<i>Type:</i> integer. Key Foreign key to SAP Rule ID
SAPSystemLandscapeID	<i>Type:</i> integer. Key. Nullable Foreign key to System Landscape ID
SAPSystemGroupID	<i>Type:</i> integer. Key. Nullable Foreign key to System Group ID.
SAPSystemID	<i>Type:</i> integer. Key. Nullable Foreign key to the SAP system.
CreationUser	<i>Type:</i> text (max 256 characters) The user who created the system landscape.
CreationDate	<i>Type:</i> datetime The data and time the system landscape was created.
UpdatedUser	<i>Type:</i> text (max 256 characters) The last user who update the system landscape.
UpdatedDate	<i>Type:</i> datetime The date and time the system landscape was last updated.

SAPRuleSet Table

This table stores SAP rule sets used for recommending optimizations for SAP.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 549: Database columns for SAPRuleSet table

Database Column	Details
SAPRuleSetID	Type: integer. Key. Generated ID A unique identifier for the SAP rule set.
RuleSetName	Type: text (max 128 characters) Name of rule set.
RuleSetDescription	Type: text. Nullable Description of rule set.
SAPSystemLandscapeID	Type: integer. Key Foreign key to the system landscape that the SAP rule set belongs to.
IsActive	Type: boolean Whether or not this rule set is used to automatically optimize SAP license assignments.
SequenceNumber	Type: integer The sequence number used to designate the order of the rule sets within the landscape.
SAPRuleCategoryID	Type: integer. Key Foreign key to the rule category of the SAP rule set.
NumberOfConsumptionMonth	Type: integer
ConsumptionMonthEndDate	Type: datetime. Nullable End date of consumption period used for recommending optimizations. If null,
CreationUser	Type: text (max 256 characters) The user who created the system landscape.
CreationDate	Type: datetime The data and time the system landscape was created.

Database Column	Details
UpdatedUser	<i>Type:</i> text (max 256 characters) The last user who update the system landscape.
UpdatedDate	<i>Type:</i> datetime The date and time the system landscape was last updated.
SecurityTypeID	<i>Type:</i> integer Security type for this object. Foreign key to the SecurityType table.

SAPRuleSetMapping Table

This table stores mapping between SAP rule sets to either System Landscapes, System Groups or SAP systems.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 550: Database columns for SAPRuleSetMapping table

Database Column	Details
SAPRuleSetMappingID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the SAP rule set mapping.
SAPRuleSetID	<i>Type:</i> integer. Key Foreign key to SAP Rule Set ID
SAPSystemLandscapeID	<i>Type:</i> integer. Key. Nullable Foreign key to System Landscape ID
SAPSystemGroupID	<i>Type:</i> integer. Key. Nullable Foreign key to System Group ID.
SAPSystemID	<i>Type:</i> integer. Key. Nullable Foreign key to the SAP system.
CreationUser	<i>Type:</i> text (max 256 characters) The user who created the system landscape.
CreationDate	<i>Type:</i> datetime The data and time the system landscape was created.
UpdatedUser	<i>Type:</i> text (max 256 characters) The last user who update the system landscape.
UpdatedDate	<i>Type:</i> datetime The date and time the system landscape was last updated.

SAPRuleType Table

This table stores the available SAP rule types used for recommending optimizations for SAP.

Table 551: Database columns for SAPRuleType table

Database Column	Details
SAPRuleTypeID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the SAP rule type.
TypeName	<i>Type:</i> text (max 100 characters). Key A unique name for the SAP rule type.
SAPRuleCategoryID	<i>Type:</i> integer. Key Foreign key to the rule category of the SAP rule.
TitleResourceName	<i>Type:</i> text (max 256 characters). Nullable A localizable resource string representing a SAP rule type. Foreign key to the ComplianceResourceString table.
TitleDefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the rule type resource string has no translation.
RuleTemplate	<i>Type:</i> text The template used to build a rule for the SAP rules engine.
DefaultRuleDefinition	<i>Type:</i> text. Nullable Default rule definition for newly created SAP rule

SAPSecurityUser Table

This table stores the operators allowed to access SAP objects.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 552: Database columns for SAPSecurityUser table

Database Column	Details
SAPSecurityUserID	Type: integer. Key. Generated ID A unique identifier for the SAP security user table.
TargetTypeID	Type: integer. Key Target type of object with restricted access.
SAPSystemLandscapeID	Type: integer. Key. Nullable The unique identifier of a SAP system landscape.
SAPSystemID	Type: integer. Key. Nullable The unique identifier of a SAP system.
SAPRuleSetID	Type: integer. Key. Nullable The unique identifier of a SAP rule set.
ResourceID	Type: integer The unique identifier of a security resource.
ActionClassID	Type: integer The unique identifier of a security action class.
ComplianceOperatorID	Type: integer. Key The unique identifier of an operator.

SAPSystem Table

This table stores the data specific to the definition of SAP systems.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 553: Database columns for SAPSystem table

Database Column	Details
SAPSystemID	Type: integer. Key. Generated ID A unique identifier for the SAP system.
SystemName	Type: text (max 128 characters) The name of the SAP system.
SystemDescription	Type: text. Nullable A more detailed description of the SAP system.
SAPSystemLandscapeID	Type: integer. Key Foreign key to the system landscape that the SAP system belongs to.
SAPSystemGroupID	Type: integer. Key. Nullable Foreign key to the system group that the SAP system belongs to.
SAPSystemEnvironmentID	Type: integer. Key. Nullable The type of environment for the SAP system.
SystemID	Type: text (max 64 characters) The System ID that is used to identify the SAP system.
ClientID	Type: text (max 32 characters) The Client ID that is to be used when connecting to the SAP system.
ServerName	Type: text (max 256 characters). Nullable The DNS name of the SAP system. This value will be used by the RFC connection. This field can also store the SAP System's IP address.
SystemNumber	Type: text (max 32 characters). Nullable The SAP system number. This value will be used by the RFC connection.
Username	Type: text (max 256 characters). Nullable The user name that is to be used when connecting to the SAP system.
Password	Type: binary. Nullable The password that is to be used when connecting to the SAP system.

Database Column	Details
IsOfflineSystem	Type: boolean Indicates whether an SAP system is offline.
IsPortalSystem	Type: boolean Indicates whether the system is a portal system.
SystemStatus	Type: text (max 128 characters). Nullable The status of the SAP system.
UsersControlledByCUA	Type: boolean Identifies whether the uses on the SAP system are controlled by a CUA.
ModelView	Type: text (max 128 characters). Nullable Further clarification required.
CUACentralSystem	Type: boolean The status of the SAP system.
CUACentralSystemID	Type: text (max 128 characters). Nullable The System ID of the CUA system that this SAP system is controlled by.
FNMSAPRelease	Type: text (max 128 characters). Nullable The version of FNM for SAP installed on the SAP system.
LAWVersion	Type: text (max 128 characters). Nullable The version of the License Assignment Workbench module installed on the SAP system.
SAPRelease	Type: text (max 128 characters). Nullable The version of SAP installed on the SAP system.
SAPPatchRelease	Type: text (max 128 characters). Nullable The SAP patch version
STPIRelease	Type: text (max 128 characters). Nullable The ST-PI version
DBSystem	Type: text (max 128 characters). Nullable The database system running on the SAP system.
HardwareKey	Type: text (max 128 characters). Nullable The hardware key of the SAP system.
InstallationNumber	Type: text (max 128 characters). Nullable The SAP system installation number

Database Column	Details
LastChangedOn	Type: datetime. Nullable The date and time the SAP system data was last refreshed.
SupportPackage	Type: text (max 128 characters). Nullable The support package of the SAP system.
HRSystem	Type: text (max 128 characters). Nullable The SAP system which contains the HR data.
SystemType	Type: text (max 128 characters). Nullable Indicates whether the SAP system is an ABAP or JAVA based system.
DefaultLicenseType	Type: text (max 2 characters). Nullable Default license type for the SAP system.
ContactFirstName	Type: text (max 128 characters). Nullable First name of the contact for this system.
ContactLastName	Type: text (max 128 characters). Nullable Last name of the contact for this system.
ContactBusinessPhone Number	Type: text (max 30 characters). Nullable Business phone number of the contact for this system.
ContactMobilePhoneNumber	Type: text (max 30 characters). Nullable Mobile phone number of the contact for this system.
ContactEmail	Type: text (max 200 characters). Nullable Email address of the contact for this system.
Location	Type: text (max 128 characters). Nullable Location of this system.
InventoryDate	Type: datetime. Nullable The date and time the SAP system data was collected by SAP Reader.
CreationUser	Type: text (max 256 characters) The user who created the system landscape.
CreationDate	Type: datetime The data and time the system landscape was created.
UpdatedUser	Type: text (max 256 characters) The last user who update the system landscape.
UpdatedDate	Type: datetime The date and time the system landscape was last updated.

Database Column	Details
SecurityTypeID	<i>Type:</i> integer. Key Security type for this object. Foreign key to the SecurityType table.
AccessToModuleData	<i>Type:</i> boolean Indicates whether the system has access to module data.
SAPSystemTypeID	<i>Type:</i> integer The type of system for the system. Foreign key to the SAPSystemType table.
SAPConnectivityTypeID	<i>Type:</i> integer. Nullable The type of connectivity for the SAP system. Foreign key to the SAPConnectivityType table.
SAPConnectivityDirectionTypeID	<i>Type:</i> integer. Nullable The type of SAP connectivity direction for the SAP system. Foreign key to the SAPConnectivityDirectionType table.
BeaconUID	<i>Type:</i> unique identifier. Key. Nullable The inventory beacon where this connection is defined.
SAPSystemRoleTypeID	<i>Type:</i> integer. Nullable The type of SAP SystemRole for the SAP system. Foreign key to SAPSystemRoleType Table
MasterSAPSystemID	<i>Type:</i> integer. Nullable A unique identifier for the Master SAP system.

SAPSystemActivityCheckSummary Table

This table stores the link between SAP System and SAP Activity Check Summary data.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 554: Database columns for SAPSystemActivityCheckSummary table

Database Column	Details
SAPSystemActivityCheckSummaryID	Type: integer. Key. Generated ID A unique identifier.
SAPSystemID	Type: integer. Key The Non-SAP system foreign key.
SAPActivityCheckSummaryID	Type: integer. Key The SAP Activity Check Summary data foreign key.

SAPSystemEngineMetric Table

This table stores the value of applications engine metrics per system.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 555: Database columns for SAPSystemEngineMetric table

Database Column	Details
SAPSystemEngineMetricID	Type: integer. Key. Generated ID A unique identifier for the SAP system engine metric name table.
SAPEngineID	Type: integer. Key The unique identifier of an SAP engine.
SAPEngineMetricID	Type: integer. Key The unique identifier of an SAP engine metric.
SAPSystemID	Type: integer. Key The unique identifier of a SAP system.
SAPEnginePeriodTypeID	Type: integer. Key A unique identifier for the SAP engine period type.
MetricValue	Type: decimal The value of the application engine metric.
PeriodStartDate	Type: datetime. Key. Nullable The start date of the SAP application engine metric calculation period.
PeriodEndDate	Type: datetime. Key. Nullable The end date of the SAP application engine metric calculation period.
CalculationDate	Type: datetime. Key. Nullable The date the SAP application engine metric calculation was performed.

SAPSystemEnvironment Table

This table stores SAP System Environment.

Table 556: Database columns for SAPSystemEnvironment table

Database Column	Details
SAPSystemEnvironmentID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the SAP System Environment.
EnvironmentCode	<i>Type:</i> text (max 1 characters). Key A unique lookup for each SAPSystemEnvironment. Possible values and the corresponding default strings are: <ul style="list-style-type: none"> • P = Production • T = Test • C = Customizing • D = Demo • E = Training/Education • S = SAP reference
ResourceName	<i>Type:</i> text (max 256 characters) A localizable resource string representing a SAP system environment name. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the SAP system environment resource string has no translation.

SAPSystemGroup Table

This table stores the data specific to the definition of SAP system groups.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 557: Database columns for SAPSystemGroup table

Database Column	Details
SAPSystemGroupID	Type: integer. Key. Generated ID A unique identifier for the SAP system group.
GroupName	Type: text (max 128 characters). Key The name of the SAP system group.
GroupDescription	Type: text. Nullable A more detailed description of the SAP system group.
SAPSystemLandscapeID	Type: integer. Key Foreign key to the system landscape that the SAP system group belongs to.
ParentSAPSystemGroupID	Type: integer. Key. Nullable Foreign key to the SAP system group that is its parent. This field will be null if the SAP system group is itself a top level SAP system group.
CreationUser	Type: text (max 256 characters) The user who created the system landscape.
CreationDate	Type: datetime The data and time the system landscape was created.
UpdatedUser	Type: text (max 256 characters) The last user who update the system landscape.
UpdatedDate	Type: datetime The date and time the system landscape was last updated.

SAPSystemLandscape Table

This table stores the data specific to the definition of system landscapes.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 558: Database columns for SAPSystemLandscape table

Database Column	Details
SAPSystemLandscapeID	Type: integer. Key. Generated ID A unique identifier for the system landscape.
LandscapeUID	Type: text (max 128 characters). Key A global unique identifier for the system landscape.
LandscapeName	Type: text (max 128 characters) A unique identifier for the system landscape.
LandscapeDescription	Type: text. Nullable A more detailed description of the SAP system group.
SAPSystemLandscape StatusID	Type: integer Identifies whether this system landscape is actively being used in the license optimization process.
LocationID	Type: text (max 128 characters). Key. Nullable Any enterprise location associated with this landscape. Foreign key to the GroupEx table.
BusinessUnitID	Type: text (max 128 characters). Key. Nullable Any corporate unit in the enterprise associated with this landscape. Foreign key to the GroupEx table.
CostCenterID	Type: text (max 128 characters). Key. Nullable Any cost center in the enterprise associated with this landscape. Foreign key to the GroupEx table.
CategoryID	Type: text (max 128 characters). Key. Nullable Any enterprise category associated with this landscape. Foreign key to the GroupEx table.
CreationUser	Type: text (max 256 characters) The user who created the system landscape.

Database Column	Details
CreationDate	<i>Type:</i> datetime The data and time the system landscape was created.
UpdatedUser	<i>Type:</i> text (max 256 characters) The last user who update the system landscape.
UpdatedDate	<i>Type:</i> datetime The date and time the system landscape was last updated.
SecurityTypeID	<i>Type:</i> integer Security type for this object. Foreign key to the SecurityType table.
CanRebalanceLicenseTypes	<i>Type:</i> boolean Indicates whether license types can be rebalanced to use excess purchases of higher license types.

SAPSystemLandscapeEngine Table

This table stores an engine in the system landscape.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 559: Database columns for SAPSystemLandscapeEngine table

Database Column	Details
SAPSystemLandscapeEngineID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the SAP system landscape engine table.
SAPSystemLandscapeID	<i>Type:</i> integer. Key Foreign key to the system landscape that the SAP engine belongs to.
EngineUID	<i>Type:</i> text (max 128 characters). Key A global unique identifier for the SAP engine in a system landscape.
EngineName	<i>Type:</i> text (max 128 characters) Name of engine.
EngineDescription	<i>Type:</i> text. Nullable Description of engine.
ApplicationID	<i>Type:</i> integer. Nullable SAP internal application ID
IsActive	<i>Type:</i> boolean Whether or not the engine is active for inclusion in license position.
NumberPurchased	<i>Type:</i> integer. Nullable
UnitPrice	<i>Type:</i> currency. Nullable
UnitPriceRateID	<i>Type:</i> integer. Nullable
SAPContentEngineID	<i>Type:</i> integer. Key. Nullable A unique identifier for the SAP content engine table.
SAPContentEngineRuleID	<i>Type:</i> integer. Key. Nullable A unique identifier for the SAP content engine rule table.
CustomRuleDefinition	<i>Type:</i> text. Nullable Custom rule definition for calculating consumption of an engine.

Database Column	Details
CustomTotalConsumption	<i>Type:</i> integer. Nullable Self-declared total consumption.
UseCustomTotalConsumption	<i>Type:</i> boolean Use CustomTotalConsumption
ConsumptionUnit	<i>Type:</i> text. Nullable Unit description to describe the consumption amount.
CreationUser	<i>Type:</i> text (max 256 characters) The user who created the system landscape.
CreationDate	<i>Type:</i> datetime The data and time the system landscape was created.
UpdatedUser	<i>Type:</i> text (max 256 characters) The last user who update the system landscape.
UpdatedDate	<i>Type:</i> datetime The date and time the system landscape was last updated.

SAPSystemLandscapeEngineMapping Table

This table stores mapping between SAP system landscape engines to either System Landscapes, System Groups or SAP systems.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 560: Database columns for SAPSystemLandscapeEngineMapping table

Database Column	Details
SAPSystemLandscapeEngineMappingID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the SAP system landscape engine mapping.
SAPSystemLandscapeEngineID	<i>Type:</i> integer. Key Foreign key to SAPSystemLandscapeEngine ID
SAPSystemLandscapeID	<i>Type:</i> integer. Key. Nullable Foreign key to System Landscape ID
SAPSystemGroupID	<i>Type:</i> integer. Key. Nullable Foreign key to System Group ID.
SAPSystemID	<i>Type:</i> integer. Key. Nullable Foreign key to the SAP system.
CreationUser	<i>Type:</i> text (max 256 characters) The user who created the system landscape.
CreationDate	<i>Type:</i> datetime The data and time the system landscape was created.
UpdatedUser	<i>Type:</i> text (max 256 characters) The last user who update the system landscape.
UpdatedDate	<i>Type:</i> datetime The date and time the system landscape was last updated.

SAPSystemLandscapeLicenseType Table

This table stores SAP license types belonging to SAP system landscapes.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 561: Database columns for SAPSystemLandscapeLicenseType table

Database Column	Details
SAPSystemLandscapeLicenseTypeID	Type: integer. Key. Generated ID A unique identifier for SAP system landscape license type.
SAPSystemLandscapeID	Type: integer. Key Foreign key to SAP system landscape.
Identifier	Type: text (max 2 characters). Key The SAP license type identifier.
ShortName	Type: text (max 128 characters). Nullable The SAP license type short name.
LongName	Type: text (max 256 characters). Nullable The SAP license type long name.
Active	Type: boolean Indicate whether the SAP license is active or not.
NumberPurchased	Type: integer. Nullable Number purchased.
UnitPrice	Type: currency. Nullable Unit price of a SAP license type.
UnitPriceRateID	Type: integer. Nullable The unit price rate of a SAP license type.
CreationUser	Type: text (max 128 characters). Nullable The user who created the SAP license type.
CreationDate	Type: datetime The data and time the SAP license type was created.
UpdatedUser	Type: text (max 128 characters). Nullable The last user who update the SAP license type.

Database Column	Details
UpdatedDate	<i>Type:</i> datetime The date and time the SAP license type was last updated.
AllowLicenseBalancing	<i>Type:</i> boolean Indicates whether license types can be rebalanced to use excess purchases of higher license types.

SAPSystemLandscapeLicenseTypeHierarchy Table

This table stores the SAP license hierarchy for a SAP system landscape.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 562: Database columns for SAPSystemLandscapeLicenseTypeHierarchy table

Database Column	Details
SAPSystemLandscape LicenseTypeHierarchyID	Type: integer. Key. Generated ID A unique identifier for the license type hierarchy
SAPSystemLandscape LicenseTypeID	Type: integer. Key A parent system landscape license type. Foreign key to SAP system landscape license type.
ChildSAPSystem LandscapeLicenseTypeID	Type: integer. Key A child system landscape license type. Foreign key to SAP system landscape license type.

SAPSystemLandscapeLicenseTypeImport Table

This table stores the imported SAP license type.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 563: Database columns for SAPSystemLandscapeLicenseTypeImport table

Database Column	Details
SAPSystemLandscapeLicenseTypeImportID	Type: integer. Key. Generated ID A unique identifier for the imported SAP license type.
SAPSystemLandscapeID	Type: integer. Key Foreign key to SAP system landscape.
SAPSystemID	Type: integer. Key Foreign key to SAP system
SystemName	Type: text (max 128 characters). Nullable The SAP system name.
ImportUser	Type: text (max 128 characters). Nullable The user who imported the SAP license type
ImportDate	Type: datetime The data and time the SAP license type was imported

SAPSystemLandscapeStatus Table

This table stores SAP System Landscape status.

Table 564: Database columns for SAPSystemLandscapeStatus table

Database Column	Details
SAPSystemLandscape StatusID	<i>Type:</i> integer. Key. Generated ID A unique identifier for each SAPSystemLandscapeStatus. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• 1 = Inactive• 2 = Active• 3 = Archived• 4 = Simulation
ResourceName	<i>Type:</i> text (max 256 characters). Key A localizable resource string representing a SAP System Landscape status. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the status resource string has no translation.

SAPSystemModule Table

This table stores the modules used in SAP and the system they are used on.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 565: Database columns for SAPSystemModule table

Database Column	Details
SAPSystemModuleID	Type: integer. Key. Generated ID A unique identifier for the SAP system module table.
SAPSystemID	Type: integer. Key The unique identifier of a SAP system.
SAPModuleID	Type: integer. Key The unique identifier of a SAP module.

SAPSystemObject Table

This table stores objects belonging to SAP systems


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 566: Database columns for SAPSystemObject table

Database Column	Details
SAPSystemObjectID	Type: integer. Generated ID A unique identifier for the SAP system object
SAPSystemID	Type: integer. Key Foreign key to the SAP system that the object belongs to.
SAPObjectID	Type: integer. Key Foreign key to the SAP object.

SAPSystemPriceList Table

This table stores the SAP system price list.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 567: Database columns for SAPSystemPriceList table

Database Column	Details
SAPSystemPriceListID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the SAP system price list.
SAPSystemID	<i>Type:</i> integer. Key Foreign key to the system that the price list belongs to.
PriceListID	<i>Type:</i> text (max 2 characters). Key SAP Price List ID
DefaultLicenseType	<i>Type:</i> text (max 2 characters). Nullable LicenseType associated to this price list
IsActive	<i>Type:</i> boolean Indicates whether the price list is active or not active.
Surcharge	<i>Type:</i> boolean Indicates whether the price list affected by surcharge.

SAPSystemPriceListName Table

This table stores the SAP system price name in multiple languages.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 568: Database columns for SAPSystemPriceListName table

Database Column	Details
SAPSystemPriceListNameID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the SAP system price list name.
SAPSystemPriceListID	<i>Type:</i> integer. Key Foreign key to the SAP price list.
Language	<i>Type:</i> text (max 4 characters) A unique code to identify the language.
PriceListName	<i>Type:</i> text (max 128 characters). Nullable The name of the SAP price list.

SAPSystemRFCConnectionSummary Table

This table stores the link between SAP System and RFC Consumption.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 569: Database columns for SAPSystemRFCConnectionSummary table

Database Column	Details
SAPSystemRFCConnectionSummaryID	Type: integer. Key. Generated ID A unique identifier.
SAPSystemID	Type: integer. Key The Non-SAP system
SAPRFCConnectionSummaryID	Type: integer. Key The RFC consumption.

SAPSystemRoleType Table

This table stores SAP System Role Type.

Table 570: Database columns for SAPSystemRoleType table

Database Column	Details
SAPSystemRoleTypeID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the SAP System Role type.
TypeName	<i>Type:</i> text (max 64 characters). Key A unique lookup for each SAPSystemRoleType. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• AdminModule• IndependentSAPSystem• DependentSAPSystem
ResourceName	<i>Type:</i> text (max 256 characters). Nullable A localizable resource string representing a SAP System Role type. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the SAP System Role type resource string has no translation.

SAPSystemType Table

This table stores SAP system type.

Table 571: Database columns for SAPSystemType table

Database Column	Details
SAPSystemTypeID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the SAP system type.
TypeName	<i>Type:</i> text (max 64 characters). Key A unique lookup for each SAPSystemType. Possible values and the corresponding default strings are: <ul style="list-style-type: none">• SAP• NonSAP
ResourceName	<i>Type:</i> text (max 256 characters). Nullable A localizable resource string representing a SAP system type. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the SAP system type resource string has no translation.

SAPTransactionProfile Table

This table stores SAP transaction profiles.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 572: Database columns for SAPTransactionProfile table

Database Column	Details
SAPTransactionProfileID	Type: integer. Key. Generated ID A unique identifier for the SAP transaction profile.
SAPSystemLandscapeID	Type: integer. Key Foreign key to SAP system landscapes the SAP transaction profile belongs to.
TransactionProfileName	Type: text (max 128 characters) Name of the SAP transaction profile
Description	Type: text. Nullable Description of the SAP transaction profile
CreationUser	Type: text (max 128 characters). Nullable The user who created the SAP transaction profile.
CreationDate	Type: datetime The data and time the SAP transaction profile was created.
UpdatedUser	Type: text (max 128 characters). Nullable The last user who update the SAP transaction profile.
UpdatedDate	Type: datetime The date and time the SAP transaction profile was last updated.

SAPTransactionProfileObject Table

This table stores the linking between SAP transaction profile and SAP object.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 573: Database columns for SAPTransactionProfileObject table

Database Column	Details
SAPTransactionProfile ObjectID	Type: integer. Key. Generated ID A unique identifier for the SAP transaction profile object
SAPTransactionProfileID	Type: integer. Key Foreign key to a SAP transaction profile.
ObjectName	Type: text (max 128 characters) The SAP object name
Description	Type: text. Nullable The SAP object description
IsTransaction	Type: boolean Indicates whether the object is of type Transaction
IsReport	Type: boolean Indicates whether the object is of type Report
IsJob	Type: boolean Indicates whether the object is of type Job
IsExcludedFromProfile	Type: boolean Indicates whether the object is marked as excluded from this profile.
CreationUser	Type: text (max 128 characters). Nullable The user who created the profile and object link.
CreationDate	Type: datetime The data and time the profile and object link was created.
UpdatedUser	Type: text (max 128 characters). Nullable The last user who update the profile and object link.
UpdatedDate	Type: datetime The date and time the profile and object link was last updated.

Database Column	Details
IsNonSAP	<i>Type:</i> boolean Indicates whether the object is of type Non-SAP

SAPUser Table

This table stores the data specific to the definition of SAP users.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 574: Database columns for SAPUser table

Database Column	Details
SAPUserID	<i>Type:</i> integer. Key. Generated ID A unique identifier for the SAP user.
SAPSystemID	<i>Type:</i> integer. Key Foreign key to the system that the user belongs to.
UserName	<i>Type:</i> text (max 256 characters). Key The SAP user's username.
FirstName	<i>Type:</i> text (max 40 characters). Nullable The SAP user's first name.
LastName	<i>Type:</i> text (max 40 characters). Nullable The SAP user's last name.
ValidFrom	<i>Type:</i> datetime. Nullable The date that the SAP user is valid from on the SAP system.
ValidTo	<i>Type:</i> datetime. Nullable The date that the SAP user is valid to on the SAP system.
UserType	<i>Type:</i> text (max 1 characters). Nullable The type of user the SAP user is.
LicenseType	<i>Type:</i> text (max 2 characters). Nullable The type of license assigned to the SAP user.
UserGroup	<i>Type:</i> text (max 12 characters). Nullable The user group the SAP user belongs to.
LastLogonDate	<i>Type:</i> datetime. Nullable The date when the SAP user last logged on to the SAP system.
IsDeveloper	<i>Type:</i> boolean Indicates whether the SAP user is a developer or not.

Database Column	Details
UserCreationDate	<i>Type:</i> datetime. Nullable The date the SAP user was created.
EmailAddress	<i>Type:</i> text (max 128 characters). Nullable The SAP user's email address.
TelephoneNumber	<i>Type:</i> text (max 30 characters). Nullable The SAP user's telephone number.
TelephoneExtension	<i>Type:</i> text (max 10 characters). Nullable The SAP user's telephone extension.
AccountID	<i>Type:</i> text (max 12 characters). Nullable The SAP user's account ID.
CostCenter	<i>Type:</i> text (max 8 characters). Nullable The cost center the SAP user belongs to.
CompanyName1	<i>Type:</i> text (max 40 characters). Nullable The name of the company the SAP user belongs to.
CompanyName2	<i>Type:</i> text (max 40 characters). Nullable The name of a second company the SAP user belongs to.
Department	<i>Type:</i> text (max 40 characters). Nullable The department the SAP user belongs to.
UserFunction	<i>Type:</i> text (max 40 characters). Nullable
UserLockStatus	<i>Type:</i> integer. Nullable User lock status.
SpecialVersionAssignment	<i>Type:</i> text (max 2 characters). Nullable
CountrySurcharge	<i>Type:</i> text (max 4 characters). Nullable
RepresentativeFromDate	<i>Type:</i> datetime. Nullable
RepresentativeToDate	<i>Type:</i> datetime. Nullable
IsDeleted	<i>Type:</i> boolean Indicated whether the SAP user has been deleted or not.
ChargeableUserClient	<i>Type:</i> text (max 32 characters). Nullable
ChargeableUserSysID	<i>Type:</i> text (max 32 characters). Nullable
ChargeableUserName	<i>Type:</i> text (max 12 characters). Nullable

Database Column	Details
RemoteServerUserName	Type: text (max 64 characters). Nullable Remote server user name

SAPUserRole Table

This table stores SAP users and its SAP role memberships


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 575: Database columns for SAPUserRole table

Database Column	Details
SAPUserRoleID	Type: integer. Key. Generated ID A unique identifier for SAP user role.
SAPUserID	Type: integer. Key Foreign key to the SAP user that the role belongs to.
SAPRoleID	Type: integer. Key Foreign key to SAP role.
ValidFrom	Type: datetime. Nullable The date that the SAP role is valid from.
ValidTo	Type: datetime. Nullable The date that the SAP role is valid to.

SAPUserType Table

This table stores SAP User type.

Table 576: Database columns for SAPUserType table

Database Column	Details
SAPUserTypeID	<i>Type:</i> integer. Key. Generated ID
UserCode	<i>Type:</i> text (max 1 characters). Key A unique lookup for each SAPUserType. Possible values and the corresponding default strings are: <ul style="list-style-type: none"> • A = Dialog • B = System • C = Communication Data • D = BDC • L = Reference • S = Service
ResourceName	<i>Type:</i> text (max 256 characters) A localizable resource string representing a SAP user type. Foreign key to the ComplianceResourceString table.
DefaultValue	<i>Type:</i> text (max 100 characters) The text to display if the system type resource string has no translation.

ManageSoft Tables

The complete set of database tables documented here includes:

- DatabaseConfiguration table (see [DatabaseConfiguration Table](#))

DatabaseConfiguration Table

The DatabaseConfiguration table contains configuration properties for the FlexNet Manager Suite database tables, which are used for ongoing maintenance of the database.

Table 577: Database columns for DatabaseConfiguration table

Database Column	Details
Property	<i>Type:</i> text (max 32 characters). Key The name of the property.
Value	<i>Type:</i> text (max 256 characters) The value of the property.
Created	<i>Type:</i> datetime The date and time the property was created.
LastUpdate	<i>Type:</i> datetime The date and time the property was last updated.

ReferenceData Tables

The complete set of database tables documented here includes:

- Country table (see [Country Table](#))
- Language table (see [Language Table](#))
- Locale table (see [Locale Table](#))

Country Table

Stores country information, including their ISO country code and English names.

Table 578: Database columns for Country table

Database Column	Details
CountryCode	Type: text (max 2 characters). Key The two letter country code.
Name	Type: text (max 128 characters). Key The english name of the country.

Language Table

Stores language information, including their English names, and various forms of language id.

Table 579: Database columns for Language table

Database Column	Details
LangCode3	<i>Type:</i> text (max 3 characters). Key The three letter language code.
LangCode2	<i>Type:</i> text (max 2 characters). Nullable The two letter language code.
EnglishName	<i>Type:</i> text (max 128 characters). Key The english name of the language.
LocalName	<i>Type:</i> text (max 128 characters). Nullable The name of the language, written in the local language.
MSLanguageID	<i>Type:</i> integer. Nullable The Microsoft language id, as specified in winnt.h in the Platform SDK.

Locale Table

Stores locale information, which consists of country and language combinations. Use the `LocaleCode` column as the foreign key into this table.

Table 580: Database columns for Locale table

Database Column	Details
<code>LocaleCode</code>	<i>Type:</i> text (max 6 characters). Key A combination of the language code and country code, separated by a hyphen. If there is no country code, then there will be no hyphen added. This column MUST have the correct value when inserted, based on the values of the language and country codes.
<code>LangCode3</code>	<i>Type:</i> text (max 3 characters). Key The three letter language code.
<code>CountryCode</code>	<i>Type:</i> text (max 2 characters). Key. Nullable The two letter country code.
<code>LocaleName</code>	<i>Type:</i> text (max 128 characters) The name of the locale. For example, "English (United States)".
<code>MSLocaleID</code>	<i>Type:</i> integer. Nullable The Microsoft identifier for the locale. For example, 1033 for English (United States).

Rights Tables

The complete set of database tables documented here includes:

- ActionClass table (see [ActionClass Table](#))
- PartitionType table (see [PartitionType Table](#))
- Resource table (see [Resource Table](#))

ActionClass Table

The types of action on a Resource for which rights may be granted or denied.

Table 581: Database columns for ActionClass table

Database Column	Details
ActionClassID	<i>Type:</i> integer. Key. Generated ID Auto-generated identity number.
ActionClassName	<i>Type:</i> text (max 16 characters). Key The name of the ActionClass.

PartitionType Table

Some secured Resources may be partitioned. Partitions are used to grant rights to one part of a Resource excluding other parts, for example limiting rights so that the operator can access only certain distribution servers, organizational units, or areas in the software library. There are three types of partitioning, defined by entries in this table.

Table 582: Database columns for PartitionType table

Database Column	Details
PartitionTypeID	Type: integer. Key. Generated ID Auto-generated identity number.
PartitionTypeName	Type: text (max 32 characters). Key Name of the PartitionType.

Resource Table

Access rights are granted to the Resources defined in this table.

Table 583: Database columns for Resource table

Database Column	Details
ResourceID	<i>Type:</i> integer. Key. Generated ID Auto-generated identity number.
ResourceName	<i>Type:</i> text (max 16 characters). Key Name of the Resource.
PartitionTypeID	<i>Type:</i> integer. Nullable If not NULL, the type of partitioning used with this Resource.

Targeting Tables

The complete set of database tables documented here includes:

- TargetType table (see [TargetType Table](#))

TargetType Table

The TargetType table contains a row for each type of object that can be targeted in FlexNet Manager Suite.

Table 584: Database columns for TargetType table

Database Column	Details
TargetTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>The ID for the target type:</p> <ul style="list-style-type: none"> Computers Users Group DistributionLocation DistributionServer Organization Assets Contracts Purchase orders Software licenses Software titles Compliance computers Compliance users Operators SAP system landscapes SAP systems SAP rule sets Discovered devices Beacon Vendor Device Rule Inventory connection FNMP Server Fast Import OLE DB Connection ORACLE Connection

Database Column	Details
	<ul style="list-style-type: none">• XML• Intermediate File• ADSI Connection• Web Service• SQL Connection• Software Title Evidence• FNMEA Agent• Installed Software• Baseline Import
TargetTypeName	Type: text (max 256 characters). Key The name of the target type.

Tenants Tables

The complete set of database tables documented here includes:

- FlexeraLicense table (see [FlexeraLicense Table](#))
- Tenant table (see [Tenant Table](#))

FlexeraLicense Table

The FlexeraLicense table contains the encoded contents of the Flexera Software licenses required for the tenants in the system. This table is also used by the system in the single-tenant setup where there is only one tenant.

Table 585: Database columns for FlexeraLicense table

Database Column	Details
TenantUID	Type: text (max 40 characters). Key The unique identifier of a tenant. A reference to the Tenant to which this license is attached.
License	Type: text The encoded contents of the Flexera Software license attached to a particular Tenant.
LicenseChecksum	Type: integer. Key The check sum of the license.
LicenseDetails	Type: XML. Nullable XML definition of the license details

Tenant Table

The Tenant table contains the details of each tenant in multitenant FlexNet Manager Suite database tables.

Table 586: Database columns for Tenant table

Database Column	Details
TenantID	<i>Type:</i> integer. Key. Generated ID The tenant ID in a multi-tenant database.
TenantUID	<i>Type:</i> text (max 40 characters). Key The unique identifier of a tenant. This identifier is used to identify the tenant in environments where tenant information is stored on multiple databases.
TenantName	<i>Type:</i> text (max 256 characters). Key The name of the tenant.
Comments	<i>Type:</i> text. Nullable Operator comments about this tenant record.
CreationUser	<i>Type:</i> text (max 128 characters). Nullable The operator who created the tenant record.
CreationDate	<i>Type:</i> datetime The date the tenant record was created.
UpdatedUser	<i>Type:</i> text (max 128 characters). Nullable The name of the operator who last updated the tenant record.
UpdatedDate	<i>Type:</i> datetime. Nullable The date the tenant record was last updated.

2

Compliance Reader Database Schema

This chapter describes the schema for the staging tables used by the importer (`ComplianceReader.exe`) in the process of importing data into the main FlexNet Manager Suite. Imports through these tables may come from many sources, including (but not limited to) the inventory data collected by the FlexNet inventory agent and rationalized in the inventory database (see [Inventory Database Schema](#)).

For each data source, data in these tables is over-written as each import.

Information Structure

The following information is provided about database tables. Items appear only when relevant to the database column, and are suppressed where they do not apply. Two of these items (shown bold) are columns in the following pages, and the remainder are displayed within the **Details**.

Item	Comment
Database Column	The name of the column in the SQL table.
<i>Type</i>	The data type of the contents of the database column.
Size	For types that have a maximum capacity, the upper limit is provided in parentheses.
Key	The word "Key" appears when a column is a unique key field within the table. It is possible for several database columns to be part of the key, so that this indicator may appear for several columns in a table.
Generated ID	This indicates that a numeric ID is assigned by the database.
Nullable	If this indicator is present, the database column permits nulls.
Computed	This indicator appears for columns that are automatically computed by the database.
Default	If a column has a default value declared in the schema, this is specified at the end of the first set of details for the column.
Details	Describes the data stored in the database column, including many of the indicators described above.

Compliance.InventoryReader.Logic Tables

The complete set of database tables documented here includes:

- ExpiredImportedComputer table (see [ExpiredImportedComputer Table](#))
- ImportedARSLicense table (see [ImportedARSLicense Table](#))
- ImportedAccessingDevice table (see [ImportedAccessingDevice Table](#))
- ImportedAccessingUser table (see [ImportedAccessingUser Table](#))
- ImportedActiveDirectoryComputer table (see [ImportedActiveDirectoryComputer Table](#))
- ImportedActiveDirectoryDomain table (see [ImportedActiveDirectoryDomain Table](#))
- ImportedActiveDirectoryExternalMember table (see [ImportedActiveDirectoryExternalMember Table](#))
- ImportedActiveDirectoryGroup table (see [ImportedActiveDirectoryGroup Table](#))
- ImportedActiveDirectoryMember table (see [ImportedActiveDirectoryMember Table](#))
- ImportedActiveDirectoryUser table (see [ImportedActiveDirectoryUser Table](#))
- ImportedActiveSyncDevice table (see [ImportedActiveSyncDevice Table](#))
- ImportedAttributeMapping table (see [ImportedAttributeMapping Table](#))
- ImportedClientAccessEvidence table (see [ImportedClientAccessEvidence Table](#))
- ImportedClientAccessEvidenceMapping table (see [ImportedClientAccessEvidenceMapping Table](#))
- ImportedClientAccessedAccessEvidence table (see [ImportedClientAccessedAccessEvidence Table](#))
- ImportedClientAccessedAccessOccurrence table (see [ImportedClientAccessedAccessOccurrence Table](#))
- ImportedCluster table (see [ImportedCluster Table](#))
- ImportedClusterGroup table (see [ImportedClusterGroup Table](#))
- ImportedClusterGroupMember table (see [ImportedClusterGroupMember Table](#))
- ImportedClusterHostAffinityRule table (see [ImportedClusterHostAffinityRule Table](#))
- ImportedClusterNode table (see [ImportedClusterNode Table](#))
- ImportedComputer table (see [ImportedComputer Table](#))
- ImportedComputerCustomProperty table (see [ImportedComputerCustomProperty Table](#))
- ImportedComputerScriptResult table (see [ImportedComputerScriptResult Table](#))
- ImportedCustomPropertyName table (see [ImportedCustomPropertyName Table](#))
- ImportedDomain table (see [ImportedDomain Table](#))
- ImportedEvidenceAttribute table (see [ImportedEvidenceAttribute Table](#))

- ImportedFNMEAFeature table (see [ImportedFNMEAFeature Table](#))
- ImportedFNMEAProduct table (see [ImportedFNMEAProduct Table](#))
- ImportedFNMEAUsageStatus table (see [ImportedFNMEAUsageStatus Table](#))
- ImportedFileEvidence table (see [ImportedFileEvidence Table](#))
- ImportedFileEvidenceMapping table (see [ImportedFileEvidenceMapping Table](#))
- ImportedGuidMapping table (see [ImportedGuidMapping Table](#))
- ImportedILMTPVUCounts table (see [ImportedILMTPVUCounts Table](#))
- ImportedILMTPVUCreatedLicenses table (see [ImportedILMTPVUCreatedLicenses Table](#))
- ImportedILMTVMMMapping table (see [ImportedILMTVMMMapping Table](#))
- ImportedInstalledFileEvidence table (see [ImportedInstalledFileEvidence Table](#))
- ImportedInstalledFileEvidenceUsage table (see [ImportedInstalledFileEvidenceUsage Table](#))
- ImportedInstalledInstallerEvidence table (see [ImportedInstalledInstallerEvidence Table](#))
- ImportedInstalledInstallerEvidenceAttribute table (see [ImportedInstalledInstallerEvidenceAttribute Table](#))
- ImportedInstalledInstallerEvidenceUsage table (see [ImportedInstalledInstallerEvidenceUsage Table](#))
- ImportedInstalledWMIEvidence table (see [ImportedInstalledWMIEvidence Table](#))
- ImportedInstallerEvidence table (see [ImportedInstallerEvidence Table](#))
- ImportedInstallerEvidenceMapping table (see [ImportedInstallerEvidenceMapping Table](#))
- ImportedInstallerEvidenceRepackageMapping table (see [ImportedInstallerEvidenceRepackageMapping Table](#))
- ImportedInstance table (see [ImportedInstance Table](#))
- ImportedInstanceUser table (see [ImportedInstanceUser Table](#))
- ImportedMissingComputer table (see [ImportedMissingComputer Table](#))
- ImportedMissingLicenseUser table (see [ImportedMissingLicenseUser Table](#))
- ImportedMissingUser table (see [ImportedMissingUser Table](#))
- ImportedProductCodeEvidenceMapping table (see [ImportedProductCodeEvidenceMapping Table](#))
- ImportedRelatedInstalledInstallerEvidence table (see [ImportedRelatedInstalledInstallerEvidence Table](#))
- ImportedRemoteApplication table (see [ImportedRemoteApplication Table](#))
- ImportedRemoteApplicationAccess table (see [ImportedRemoteApplicationAccess Table](#))
- ImportedRemoteApplicationInstallerData table (see [ImportedRemoteApplicationInstallerData Table](#))
- ImportedRemoteApplicationServer table (see [ImportedRemoteApplicationServer Table](#))
- ImportedRemoteServerFileEvidenceMapping table (see [ImportedRemoteServerFileEvidenceMapping Table](#))

- ImportedRemoteUsage table (see [ImportedRemoteUsage Table](#))
- ImportedRemoteUserToApplicationAccess table (see [ImportedRemoteUserToApplicationAccess Table](#))
- ImportedSite table (see [ImportedSite Table](#))
- ImportedSiteSubnet table (see [ImportedSiteSubnet Table](#))
- ImportedSoftwareLicense table (see [ImportedSoftwareLicense Table](#))
- ImportedSoftwareLicenseAllocation table (see [ImportedSoftwareLicenseAllocation Table](#))
- ImportedStringMapping table (see [ImportedStringMapping Table](#))
- ImportedStringMappingLatin1CS table (see [ImportedStringMappingLatin1CS Table](#))
- ImportedUser table (see [ImportedUser Table](#))
- ImportedVDI table (see [ImportedVDI Table](#))
- ImportedVDIEndPointAccess table (see [ImportedVDIEndPointAccess Table](#))
- ImportedVDITemplate table (see [ImportedVDITemplate Table](#))
- ImportedVDIUser table (see [ImportedVDIUser Table](#))
- ImportedVMHostDatastore table (see [ImportedVMHostDatastore Table](#))
- ImportedVMHostManagedBySoftware table (see [ImportedVMHostManagedBySoftware Table](#))
- ImportedVMHostProperty table (see [ImportedVMHostProperty Table](#))
- ImportedVMPool table (see [ImportedVMPool Table](#))
- ImportedVirtualMachine table (see [ImportedVirtualMachine Table](#))
- ImportedWMIEvidence table (see [ImportedWMIEvidence Table](#))
- ImportedWMIEvidenceRuleMapping table (see [ImportedWMIEvidenceRuleMapping Table](#))
- ImporterValueMapping table (see [ImporterValueMapping Table](#))
- InstalledApplications table (see [InstalledApplications Table](#))
- RelatedInstalledApplications table (see [RelatedInstalledApplications Table](#))

ExpiredImportedComputer Table

The ExpiredImportedComputer table holds all of the computers which have been retrieved from the source connections and are expired.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 587: Database columns for ExpiredImportedComputer table

Database Column	Details
ComplianceConnectionID	<i>Type:</i> integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
ExternalID	<i>Type:</i> big integer. Key. Nullable The identifier used in the source connection for the computer.
ComputerName	<i>Type:</i> text (max 256 characters). Nullable The name of the computer. In Windows, this is the NetBIOS name of the local computer, as returned by GetComputerName(). For UNIX, it is the host name of the machine, as returned by gethostname(2).
Domain	<i>Type:</i> text (max 100 characters). Nullable The domain of the computer.
OperatingSystem	<i>Type:</i> text (max 128 characters). Nullable The operating system of the computer.
ServicePack	<i>Type:</i> text (max 128 characters). Nullable The service pack installed for the operating system.
NumberOfProcessors	<i>Type:</i> integer. Nullable The number of processors in the computer.
ProcessorType	<i>Type:</i> text (max 256 characters). Nullable The type of processor in the computer.
MaxClockSpeed	<i>Type:</i> integer. Nullable The maximum clock speed of the fastest processor in the computer.
NumberOfCores	<i>Type:</i> integer. Nullable The number of cores in the computer.

Database Column	Details
TotalMemory	<p><i>Type:</i> big integer. Nullable</p> <p>The total RAM in the computer, in bytes.</p>
ChassisType	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>The type of case of the computer. The value must be a (case insensitive) exact match for one of the values shown. Note that some license types use this information to optimize the licensing position, particularly with desktop and laptop computers.</p>
NumberOfHardDrives	<p><i>Type:</i> integer. Nullable</p> <p>The number of hard drives in the computer.</p>
TotalDiskSpace	<p><i>Type:</i> big integer. Nullable</p> <p>The total size of all hard drives in the computer.</p>
NumberOfNetworkCards	<p><i>Type:</i> integer. Nullable</p> <p>The number of network cards in the computer.</p>
NumberOfDisplayAdapters	<p><i>Type:</i> integer. Nullable</p> <p>The number of graphics cards in the computer.</p>
IPAddress	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>The IP address of the computer.</p>
MACAddress	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>The MAC address of the computer.</p>

Database Column	Details
Manufacturer	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>The manufacturer of the computer hardware. Some examples include:</p> <ul style="list-style-type: none"> • On Windows, the SMBios manufacturer (the WMI Manufacturer property of the 'Win32_ComputerSystem' class). • On Linux, 'Manufacturer' in the 'System Information' section resulting from the 'dmidecode' command. Sample command: 'dmidecode -s system-manufacturer' • On Solaris x86, as for Linux, with failovers first to 'sysinfo SI_HW_PROVIDER' and then to 'ModelNo'. • On Solaris SPARC, the 'sysinfo SI_HW_PROVIDER'. Typically this value is 'Sun_Microsystems' or, more recently, 'Oracle Corporation'. Failover to the 'ModelNo'. • On HP-UX, the string literal 'HP'. • On AIX, the 'modelname' system attribute preceding the comma character. For example, if the 'modelname' system attribute is 'IBM,8202-E4B', then use 'IBM'. This value is typically 'IBM'.
ModelNo	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>The model number of the computer.</p>

Database Column	Details
SerialNo	<p><i>Type:</i> text (max 100 characters). Nullable</p> <p>The hardware serial number of the computer. The goal of this value is to be tied to the physical hardware, partition or virtual machine and to be as unique as possible across all computers in the organization. This is due to its use in tracking computers, particularly after an operating system rebuild. This value is also used to socialize computer inventory from different inventory sources, and is used to map virtual machine guest operating system inventory to the VM host on which the virtual machine is running. Example sources:</p> <ul style="list-style-type: none"> • On Windows, the SMBios serial number. The WMI 'SerialNumber' property of the 'Win32_BIOS' class. Can fail over to the 'SerialNumber' property of the 'Win32_SystemEnclosure' class which is typically the same value. • On Linux, the SMBios serial number read using the command 'dmidecode -s system-serial-number'. Specifically, the 'System Information' section and the 'Serial Number' in that section is used. • On Solaris 10 8/07 or later, for a non-global zone, the UUID value from the /etc/zones/index file. For a global zone, the same as Solaris 10 releases earlier than 8/07. • For Solaris 10 releases earlier than 8/07, the hexadecimal version of 'SI_HW_SERIAL' with an appended hyphen character followed by the Zone's name. For example, '838bfc7b-global' or '838bfc7b-myzone'. • For Solaris 8 and 9, The hexadecimal version of 'SI_HW_SERIAL'. • For Mac OS X, the serial number of the machine as printed on the packaging and found in "About this Mac" from the desktop. • For HP-UX, the 'confstr _CS_PARTITION_IDENT' partition identifier if it is an nPar or vPar, or '_CS_MACHINE_IDENT' if not; with a failover to the machine serial number, and a final failover to the 'uname' machine identification number. • For AIX, the 'id_to_partition' system attribute, starting from the third character (strips a '0X' from the start). For example, if the 'id_to_partition' system attribute is '0X0473409002F7B201' then use '0473409002F7B201'.
HostID	<p><i>Type:</i> text (max 100 characters). Nullable</p> <p>An identifier for the host of the computer (when the computer is a virtual machine).</p>
LastLoggedOnUser	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>The DOMAIN/SAMAccountName of the user last logged onto the computer.</p>

Database Column	Details
InventoryDate	<p><i>Type:</i> datetime. Nullable</p> <p>The date the computer last had inventory reported.</p>
HardwareInventoryDate	<p><i>Type:</i> datetime. Nullable</p> <p>The date (and optionally time) when the hardware was last inventoried. For automated/scheduled data uploads through an inventory beacon, make sure that inventory dates are kept current, as they are used to report out-of-date inventory sources. For a one-time upload to the central application server, leave inventory dates empty (null). At each import from the saved file, the import date is used as the inventory date, which prevents the inventory becoming stale.</p>
ServicesInventoryDate	<p><i>Type:</i> datetime. Nullable</p> <p>The date when services (for example, Oracle) were last scanned on this computer. For automated/scheduled data uploads through an inventory beacon, make sure that inventory dates are kept current, as they are used to report out-of-date inventory sources. For a one-time upload to the central application server, leave inventory dates empty (null). At each import from the saved file, the import date is used as the inventory date, which prevents the inventory becoming stale.</p>
InventoryAgent	<p><i>Type:</i> text (max 128 characters)</p> <p>The name of the person or tool that performed the last inventory.</p>
ComplianceComputerID	<p><i>Type:</i> integer. Nullable</p> <p>Identifier of the computer in the ComplianceComputer table that this imported computer links to. This is populated by the import process and does not need to be provided by the source connections.</p>
ComplianceDomainID	<p><i>Type:</i> integer. Nullable</p> <p>Identifier of the domain in the ComplianceDomain table that this computer belongs to. This is populated by the import process and does not need to be provided by the source connections.</p>
IncompleteRecord	<p><i>Type:</i> boolean. Nullable</p> <p>Used to identify records which do not have all information specified. Primarily used for ManageSoft source connections where the domain name was not reliably reported.</p>
NumberOfSockets	<p><i>Type:</i> integer. Nullable</p> <p>The number of sockets in the computer.</p>
PartialNumberOfProcessors	<p><i>Type:</i> decimal. Nullable</p> <p>The fractional processor count available to this computer.</p>

Database Column	Details
UntrustedSerialNo	<p><i>Type:</i> boolean</p> <p>Use when this computer is known to have a serial number from a data source that should not be trusted.</p>
FullDetailsFromExternalID	<p><i>Type:</i> big integer. Nullable</p> <p>If this computer is marked as incomplete, and some of its properties are updated from another computer, record the external ID if the full computer.</p>
FullDetailsFromComplianceConnectionID	<p><i>Type:</i> integer. Nullable</p> <p>If this computer is marked as incomplete, and some of its properties are updated from another computer, record the connection ID if the full computer.</p>
ComplianceComputerTypeID	<p><i>Type:</i> integer. Nullable</p> <p>If you know that the computer is a virtual machine or VM host, record that data here. If you are unsure, leave this cell empty (NULL): this allows the system to infer the computer type (for example, a computer with VMs linked to it is inferred to be a VM host). If data comes from multiple inventory sources, leaving this value as null also allows the value to be inserted from another source. So, unless there is a very good reason, do not just specify 'Computer', but allow the inference rules to help.</p>
ILMTAgentID	<p><i>Type:</i> big integer. Nullable</p> <p>Store the unique ID used by the ILMT agent on this device, if the inventory source is aware of this value.</p>
HostIdentifyingNumber	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>Virtual hosts may have an identifier that is unique only across that hardware model. It is less unique than the true hardware serial number, for example.</p>
HostType	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>The type of the physical host computer. This value is similar to the model number, but it is always for the physical server that an execution context may be running on. Therefore, this will generally be a known value for standalone machines and partitions, but it will not be known for virtual machines. This value is used for matching computers. Examples:</p> <ul style="list-style-type: none"> • 'i86pc' • 'Sun-Fire-T1000' • 'rx7620' • '785' (for a 9000/785/C3700) • '8202' (for an IBM,8202-E4B).

Database Column	Details
NumberOfLogicalProcessors	<i>Type:</i> integer. Nullable The number of logical processors in the computer.
IsRemoteACLDevice	<i>Type:</i> boolean Used to determine if the current record is a remote ACL based device.
IsDuplicate	<i>Type:</i> boolean Used to identify that imported computer is a duplicate of another, whereby a new computer will not created.
LegacySerialNo	<i>Type:</i> text (max 100 characters). Nullable A previous serial number of this computer that can also be used for matching.
UUID	<i>Type:</i> unique identifier. Nullable The BIOS UUID of the computer.
IMEI	<i>Type:</i> text (max 256 characters). Nullable IMEI (International Mobile Equipment Identity) is a 15- or 17-digit code that uniquely identifies mobile phone sets. Leave blank (null) for other device types.
PhoneNumber	<i>Type:</i> text (max 128 characters). Nullable The phone number of the device. Used for mobile devices.
EmailAddress	<i>Type:</i> text (max 256 characters). Nullable The email address associated with the device. Typically used for mobile devices.
CalculatedUser	<i>Type:</i> text (max 128 characters). Nullable The domain/SAMAccountName of the calculated user. Some inventory systems calculate the user who owns a computer. For example, it might be the user who, over the last ten logins, logged in most often.
LastSuccessfulInventoryDate	<i>Type:</i> datetime. Nullable For incremental imports, this represents the inventory date of the computer in the source at the time this record was last successfully imported. If the import procedure has failed, this may be different to the inventory date. At the end of a successful incremental import, this value is updated to match the inventory date. If no value is present in this field, either there has not been a successful import of this computer or the reader for this record is not using an incremental update model.
MDScheduleGeneratedDate	<i>Type:</i> datetime. Nullable The last time the managed device schedule was regenerated.

Database Column	Details
MDScheduleContainsPVUScan	<i>Type:</i> boolean. Nullable Does this managed device include an event in its current schedule for running extra IBM PVU hardware scans.
FirmwareSerialNumber	<i>Type:</i> text (max 100 characters). Nullable Serial number in the system firmware such as BIOS, EEPROM etc.
MachineID	<i>Type:</i> text (max 100 characters). Nullable For AIX, it is the System ID. For HP-UX, it is the Machine/Software ID. It is unset for other platforms.
IgnoredDueToLicense	<i>Type:</i> boolean True if this machine is not imported into compliance computer table due to license limitation

ImportedARSLicense Table

The ImportedARSLicense table stores Action Request System BMC licenses.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 588: Database columns for ImportedARSLicense table

Database Column	Details
ComplianceConnectionID	<i>Type:</i> integer. Key. Nullable The identifier of a data source connection in the ComplianceConnection table.
ComputerID	<i>Type:</i> big integer. Key The identifier used in the source connection to represent the computer.
SoftwareLicenseID	<i>Type:</i> integer. Nullable The identifier for the license in the SoftwareLicense table.
ARSLicenseID	<i>Type:</i> integer The identifier for the imported ARS license.
ComplianceComputerID	<i>Type:</i> integer. Nullable The identifier for the compliance computer in the ComplianceComputer table.
LicenseType	<i>Type:</i> text (max 128 characters). Key The ARS license name.
ECMLicenseName	<i>Type:</i> text (max 256 characters) The name of the license in the FlexNet Manager Suite.
LicenseKey	<i>Type:</i> text (max 32 characters). Key. Nullable The imported license key.
LicenseSubType	<i>Type:</i> text (max 16 characters). Key The license subtype (FlexNet Manager Suite license version).
IssueDate	<i>Type:</i> datetime. Key The identifier for the issue date.
ExpiryDate	<i>Type:</i> datetime. Key. Nullable The identifier for the expiry date.

Database Column	Details
SiteName	<i>Type:</i> text (max 64 characters) The identifier for the site name.
HostID	<i>Type:</i> text (max 64 characters) An identifier for the ARS host in the source connection (not used in FlexNet Manager Suite).
LicenseNum	<i>Type:</i> integer The purchase count for the ARS license.
TokenList	<i>Type:</i> text (max 128 characters). Nullable The ARS token list (not used in FlexNet Manager Suite).
Comment	<i>Type:</i> text. Nullable Extra information about the ARS license.
Deleted	<i>Type:</i> integer Set this flag if an ARS license is to be deleted.

ImportedAccessingDevice Table

The ImportedAccessingDevice table holds a record client access device information.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 589: Database columns for ImportedAccessingDevice table

Database Column	Details
ComplianceConnectionID	<i>Type:</i> integer. Key The identifier for a data source connection in the ComplianceConnection table.
ExternalAccessingDeviceID	<i>Type:</i> big integer. Key The identifier used to identify the device in source connection
AccessingDeviceID	<i>Type:</i> integer. Key. Nullable Matching accessing device ID. Foreign key to the AccessingDevice table.
IPAddress	<i>Type:</i> text (max 256 characters). Key. Nullable IP Address of the client accessing device.
ComputerName	<i>Type:</i> text (max 256 characters). Key. Nullable Computer name of the client accessing device.
SerialNo	<i>Type:</i> text (max 100 characters). Nullable Serial no of the client accessing device.
Domain	<i>Type:</i> text (max 100 characters). Key. Nullable Domain name of the client accessing device.

ImportedAccessingUser Table

The ImportedAccessingUser table holds a record of the user access infomation.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 590: Database columns for ImportedAccessingUser table

Database Column	Details
ComplianceConnectionID	Type: integer. Key The identifier for a data source connection in the ComplianceConnection table.
ExternalAccessingUserID	Type: big integer. Key The accessing user id. This is part of the key.
AccessingUserID	Type: integer. Key. Nullable The matchihng AccessingUser ID. Foreign key to the AccessingUser table.
UserName	Type: text (max 256 characters). Key User name of the accessing user.
DomainName	Type: text (max 100 characters). Key. Nullable Domain name of the accessing user.
SAMAccountName	Type: text (max 64 characters). Nullable SAM account name of the accessing user.

ImportedActiveDirectoryComputer Table

The ImportedActiveDirectoryComputer table stores the incoming active directory data for computers.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 591: Database columns for ImportedActiveDirectoryComputer table

Database Column	Details
ComplianceConnectionID	<i>Type:</i> integer. Key The identifier of a data source connection in the ComplianceConnection table.
GUID	<i>Type:</i> unique identifier. Key The GUID of the computer.
ComputerName	<i>Type:</i> text (max 64 characters) The name of the computer. In Windows, this is the NetBIOS name of the local computer, as returned by <code>GetComputerName()</code> . For UNIX, it is the host name of the machine, as returned by <code>gethostname(2)</code> .
DomainName	<i>Type:</i> text (max 100 characters) The domain name for the computer.
SID	<i>Type:</i> text (max 256 characters). Nullable The SID of the computer.

ImportedActiveDirectoryDomain Table

The ImportedActiveDirectoryDomain table stores the incoming active directory domains for a connection source.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 592: Database columns for ImportedActiveDirectoryDomain table

Database Column	Details
ComplianceConnectionID	Type: integer. Key The identifier of a data source connection in the ComplianceConnection table.
DomainFQDN	Type: text (max 100 characters). Key The fully qualified name domain name of the AD domain
FlatName	Type: text (max 32 characters) The AD domain flat name
LastADImportTime	Type: datetime The last time the AD data was imported

ImportedActiveDirectoryExternalMember Table

The ImportedActiveDirectoryExternalMember table stores the incoming active directory data for external AD member objects.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 593: Database columns for ImportedActiveDirectoryExternalMember table

Database Column	Details
ComplianceConnectionID	Type: integer. Key The identifier of a data source connection in the ComplianceConnection table.
ParentGroupGUID	Type: unique identifier. Key The parent AD group GUID.
SID	Type: text (max 256 characters). Key The SID of the member object.

ImportedActiveDirectoryGroup Table

The ImportedActiveDirectoryGroup table stores the incoming active directory data for a connection source.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 594: Database columns for ImportedActiveDirectoryGroup table

Database Column	Details
ComplianceConnectionID	Type: integer. Key The identifier of a data source connection in the ComplianceConnection table.
GUID	Type: unique identifier. Key The GUID of the AD group.
SID	Type: text (max 256 characters). Nullable The SID of the AD group.
Name	Type: text (max 128 characters). Nullable The AD group name
DomainName	Type: text (max 100 characters) The domain name for the user.

ImportedActiveDirectoryMember Table

The ImportedActiveDirectoryMember table stores the incoming active directory data for AD member objects.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 595: Database columns for ImportedActiveDirectoryMember table

Database Column	Details
ComplianceConnectionID	Type: integer. Key The identifier of a data source connection in the ComplianceConnection table.
GUID	Type: unique identifier. Key The GUID of the member object.
ParentGroupGUID	Type: unique identifier. Key The parent AD group GUID.

ImportedActiveDirectoryUser Table

The ImportedActiveDirectoryUser table stores the incoming active directory data for users.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 596: Database columns for ImportedActiveDirectoryUser table

Database Column	Details
ComplianceConnectionID	Type: integer. Key The identifier of a data source connection in the ComplianceConnection table.
GUID	Type: unique identifier. Key The GUID of the user.
SAMAccountName	Type: text (max 20 characters) The user name.
DomainName	Type: text (max 100 characters) The domain name for the user.
Sid	Type: text (max 256 characters). Nullable The Sid for the user.

ImportedActiveSyncDevice Table

The ImportedActiveSyncDevice table stores details of ActiveSync partnerships. A partnership is a user/device pair, so there may be multiple rows for one device.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 597: Database columns for ImportedActiveSyncDevice table

Database Column	Details
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
ExternalID	Type: integer. Key. Generated ID The identifier used in the source connection for the computer.
ActiveSyncID	Type: text (max 512 characters). Key. Nullable The EASIdentity presented by the source, a combination of the AD user and the unique device ID.
Domain	Type: text (max 100 characters). Nullable The domain of the device. This may be a flat name or FQDN.
DeviceID	Type: text (max 100 characters). Nullable The unique device identifier.
DeviceOS	Type: text (max 100 characters). Nullable The device operating system.
DeviceModel	Type: text (max 100 characters). Nullable The device model.
DeviceType	Type: text (max 50 characters). Nullable The device type.
DeviceUserAgent	Type: text (max 100 characters). Nullable The device user agent; an ActiveSync client-specific value that may identify the device type.
UserDisplayName	Type: text (max 256 characters). Nullable The AD user display name.

Database Column	Details
IMEI	<p>Type: text (max 256 characters). Nullable</p> <p>IMEI (International Mobile Equipment Identity) is a 15- or 17-digit code that uniquely identifies mobile phone sets. Leave blank (null) for other device types.</p>
PhoneNumber	<p>Type: text (max 128 characters). Nullable</p> <p>The phone number of the device. Used for mobile devices.</p>
EmailAddress	<p>Type: text (max 256 characters). Nullable</p> <p>The user's primary email address.</p>
ExchangeServer	<p>Type: text (max 256 characters). Nullable</p> <p>The source exchange server for this information.</p>
WhenCreatedUTC	<p>Type: datetime. Nullable</p> <p>The date/time this partnership was created, in UTC.</p>
LastSyncAttemptTime	<p>Type: datetime. Nullable</p> <p>The last attempted sync time for this partnership, in UTC.</p>
LastSuccessSync	<p>Type: datetime. Nullable</p> <p>The last successful sync time for this partnership, in UTC.</p>

ImportedAttributeMapping Table

The ImportedAttributeMapping table is used by the importer to link imported instance attributes with attributes in the Attribute table.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 598: Database columns for ImportedAttributeMapping table

Database Column	Details
AttributeID	Type: integer. Nullable The identifier for the instance attribute in the Attribute table.
ExternalAttributeID	Type: integer. Key. Nullable The identifier used in the source connection for the imported instance attribute.
ComplianceConnectionID	Type: integer. Key. Nullable The identifier of a data source connection in the ComplianceConnection table.

ImportedClientAccessEvidence Table

The ImportedClientAccessEvidence table holds all of the client access evidence which has been retrieved from the source connections.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 599: Database columns for ImportedClientAccessEvidence table

Database Column	Details
ComplianceConnectionID	Type: integer. Key The identifier for a data source connection in the ComplianceConnection table.
ExternalAccessEvidenceID	Type: big integer. Key The identifier of the client access evidence.
ProductName	Type: text (max 256 characters). Key. Nullable The name of the product being accessed by user or computer. This may include version and edition too.
Version	Type: text (max 72 characters). Key. Nullable The version of the installed product.
Edition	Type: text (max 50 characters). Nullable The edition of the installed product.
UALRoleName	Type: text (max 256 characters). Nullable The UAL role name of the product being accessed by user or computer. This is used when retrieve data using UAL.
UALRoleGUID	Type: unique identifier. Nullable The UAL role GUID of the product being accessed by user or computer. This is used when retrieve data using UAL

ImportedClientAccessEvidenceMapping Table

The ImportedClientAccessEvidenceMapping is the mapping table for imported access evidence and access evidence


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 600: Database columns for ImportedClientAccessEvidenceMapping table

Database Column	Details
ComplianceConnectionID	Type: integer. Key The identifier for a data source connection in the ComplianceConnection table.
ExternalAccessEvidenceID	Type: big integer. Key External Access evidend id. Foreign key to ImportedClientAccessedAccessEvidence table.
AccessEvidenceID	Type: integer. Key Access evidend id. Foreign key to AccessEvidence table.

ImportedClientAccessedAccessEvidence Table

The ImportedClientAccessedAccessEvidence table holds a record of the installer evidence that has been installed on a computer from the source connections.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 601: Database columns for ImportedClientAccessedAccessEvidence table

Database Column	Details
ImportedClientAccessedAccessEvidenceID	Type: big integer. Key The identifier used in the source connection for the installer evidence.
ComplianceConnectionID	Type: integer. Key The identifier for a data source connection in the ComplianceConnection table.
ExternalAccessEvidenceID	Type: big integer. Key Access evidence id .Foreign key to the ImportedClientAccessEvidence table.
ExternalAccessingDeviceID	Type: big integer. Key. Nullable Accessing computer id .Foreign key to the ImportedAccessingDevice table
ExternalAccessingUserID	Type: big integer. Key. Nullable Accessing userid. Foreign key to the ImportedAccessingUser table
ExternalServerComputerID	Type: big integer. Key. Nullable Server computer id .Foreign key to the ImportedComputer table.
ClientAccessSource	Type: text (max 100 characters). Key Referencing to the client access source type.

ImportedClientAccessedAccessOccurrence Table

The ImportedClientAccessedAccessOccurrence table holds the access information of device or user


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 602: Database columns for ImportedClientAccessedAccessOccurrence table

Database Column	Details
ComplianceConnectionID	Type: integer. Key The identifier for a data source connection in the ComplianceConnection table.
ImportedClientAccessedAccessEvidenceID	Type: big integer. Key Access evidence id .Foreign key to the ImportedClientAccessedAccessEvidence table..
AccessCount	Type: integer Number of access frequency for given date
InventoryDate	Type: datetime. Key Date on which inventory occurrence was recorded.
LicenseDate	Type: datetime. Key Date which will be used for licensing purpose.
AccessDate	Type: datetime. Nullable The access date.

ImportedCluster Table

The ImportedCluster table holds all of the clusters which have been retrieved from the source connections.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 603: Database columns for ImportedCluster table

Database Column	Details
ExternalID	Type: big integer. Key. Nullable The unique identifier for this imported cluster.
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
ClusterID	Type: integer. Nullable The unique identifier for this imported cluster. Note that this maps to the 'ExternalID' column in the 'ImportedCluster' table, and not to the 'ClusterID' column.
ExternalName	Type: text (max 256 characters). Nullable The identifier of the cluster in the external cluster management system.
Name	Type: text (max 256 characters) The user-visible name of the cluster.
Namespace	Type: text (max 256 characters). Nullable The name of the domain/datacenter containing the cluster.
ClusterTypeID	Type: integer The type of cluster.
InventoryDate	Type: datetime. Nullable The date the cluster last had inventory reported.
InventoryAgent	Type: text (max 64 characters). Nullable The name of the person or tool that performed the last inventory.
DRS	Type: boolean. Nullable Whether Distributed Resource Scheduler (DRS) is enabled
DPM	Type: boolean. Nullable Whether Distributed Power Management (DPM) is enabled

ImportedClusterGroup Table

The ImportedClusterGroup table holds all of the group objects defined on clusters which have been retrieved from the source connections.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 604: Database columns for ImportedClusterGroup table

Database Column	Details
ExternalID	Type: big integer. Key. Nullable The unique identifier for this imported cluster group.
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
ClusterID	Type: integer. Nullable The assigned identifier for this cluster group.
ClusterExternalID	Type: big integer. Key The unique identifier for the imported cluster.
Name	Type: text (max 256 characters) The name of the cluster group.
ClusterTypeID	Type: integer Foreign key to the ClusterType table.

ImportedClusterGroupMember Table

The ImportedClusterGroupMember table holds all of the group memberships defined on clusters which have been retrieved from the source connections.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 605: Database columns for ImportedClusterGroupMember table

Database Column	Details
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
ClusterGroupExternalID	Type: big integer. Key The unique identifier for the imported cluster group.
ComputerExternalID	Type: big integer. Key. Nullable The identifier used in the source connection for the external computer which is a member of the group.
VCObjectID	Type: text (max 256 characters). Key. Nullable The identifier of the virtual machine in Virtual Center.

ImportedClusterHostAffinityRule Table

The ImportedClusterHostAffinityRule table holds all of the host affinity rules for a cluster which have been retrieved from the source connections.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 606: Database columns for ImportedClusterHostAffinityRule table

Database Column	Details
ComplianceConnectionID	<i>Type:</i> integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
ClusterExternalID	<i>Type:</i> big integer. Key The unique identifier for the imported cluster.
Name	<i>Type:</i> text (max 256 characters). Key The name of the cluster group.
ClusterHostGroup ExternalID	<i>Type:</i> big integer. Key The unique identifier for the imported cluster host group.
ClusterVMGroupExternalID	<i>Type:</i> big integer. Key The unique identifier for the imported cluster VM group.
ClusterHostAffinity RuleTypeID	<i>Type:</i> integer A unique identifier indicating a type of Cluster Host Affinity Rule.

ImportedClusterNode Table

The ImportedClusterNode table holds all of the cluster nodes which have been retrieved from the source connections.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 607: Database columns for ImportedClusterNode table

Database Column	Details
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
ClusterExternalID	Type: big integer. Key The unique identifier for the imported cluster.
ComputerExternalID	Type: big integer. Key. Nullable The identifier used in the source connection for the external computer which is a member of the cluster.
ClusterNodeTypeID	Type: integer Foreign key to the ClusterNodeType table.

ImportedComputer Table

The ImportedComputer table holds all of the computers which have been retrieved from the source connections.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 608: Database columns for ImportedComputer table

Database Column	Details
ComplianceConnectionID	<i>Type:</i> integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
ExternalID	<i>Type:</i> big integer. Key. Nullable The identifier used in the source connection for the computer.
ComputerName	<i>Type:</i> text (max 256 characters). Key. Nullable The name of the computer. In Windows, this is the NetBIOS name of the local computer, as returned by GetComputerName(). For UNIX, it is the host name of the machine, as returned by gethostname(2).
Domain	<i>Type:</i> text (max 100 characters). Key. Nullable The domain of the computer.
OperatingSystem	<i>Type:</i> text (max 128 characters). Nullable The operating system of the computer.
ServicePack	<i>Type:</i> text (max 128 characters). Nullable The service pack installed for the operating system.
NumberOfProcessors	<i>Type:</i> integer. Nullable The number of processors in the computer.
ProcessorType	<i>Type:</i> text (max 256 characters). Nullable The type of processor in the computer.
MaxClockSpeed	<i>Type:</i> integer. Nullable The maximum clock speed of the fastest processor in the computer.
NumberOfCores	<i>Type:</i> integer. Nullable The number of cores in the computer.

Database Column	Details
TotalMemory	<p><i>Type:</i> big integer. Nullable</p> <p>The total RAM in the computer, in bytes.</p>
ChassisType	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>The type of case of the computer. The value must be a (case insensitive) exact match for one of the values shown. Note that some license types use this information to optimize the licensing position, particularly with desktop and laptop computers.</p>
NumberOfHardDrives	<p><i>Type:</i> integer. Nullable</p> <p>The number of hard drives in the computer.</p>
TotalDiskSpace	<p><i>Type:</i> big integer. Nullable</p> <p>The total size of all hard drives in the computer.</p>
NumberOfNetworkCards	<p><i>Type:</i> integer. Nullable</p> <p>The number of network cards in the computer.</p>
NumberOfDisplayAdapters	<p><i>Type:</i> integer. Nullable</p> <p>The number of graphics cards in the computer.</p>
IPAddress	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>The IP address of the computer.</p>
MACAddress	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>The MAC address of the computer.</p>

Database Column	Details
Manufacturer	<p><i>Type:</i> text (max 128 characters). Key. Nullable</p> <p>The manufacturer of the computer hardware. Some examples include:</p> <ul style="list-style-type: none"> On Windows, the SMBios manufacturer (the WMI Manufacturer property of the 'Win32_ComputerSystem' class). On Linux, 'Manufacturer' in the 'System Information' section resulting from the 'dmidecode' command. Sample command: 'dmidecode -s system-manufacturer' On Solaris x86, as for Linux, with failovers first to 'sysinfo SI_HW_PROVIDER' and then to 'ModelNo'. On Solaris SPARC, the 'sysinfo SI_HW_PROVIDER'. Typically this value is 'Sun_Microsystems' or, more recently, 'Oracle Corporation'. Failover to the 'ModelNo'. On HP-UX, the string literal 'HP'. On AIX, the 'modelname' system attribute preceding the comma character. For example, if the 'modelname' system attribute is 'IBM,8202-E4B', then use 'IBM'. This value is typically 'IBM'.
ModelNo	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>The model of the computer hardware or the virtual machine. This value is defined for the context of the current execution environment, rather than the physical server that may be hosting a virtual machine or partition. Examples:</p> <ul style="list-style-type: none"> On Windows, the SMBios product name. The WMI Model property of the Win32_ComputerSystem class. On Linux, the SMBios product name read using the command 'dmidecode -s system-product-name'. Specifically, the 'System Information' section and the 'Product Name' in that section is used. On Solaris x86, as for Linux, with failover to the 'sysinfo SI_PLATFORM', stripping 'SUNW', and replacing hyphen characters with space characters. On Solaris SPARC, the 'openprom' "banner-name" value read from '/dev/openprom'. Failover to the 'sysinfo SI_PLATFORM', stripping 'SUNW', and replacing hyphen characters with space characters. On HP-UX, the 'confstr_CS_MACHINE_MODEL'. On AIX, the 'modelname' system attribute following the comma character. For example, if the 'modelname' system attribute is 'IBM,8202-E4B', then use '8202-E4B'.

Database Column	Details
SerialNo	<p><i>Type:</i> text (max 100 characters). Nullable</p> <p>The hardware serial number of the computer. The goal of this value is to be tied to the physical hardware, partition or virtual machine and to be as unique as possible across all computers in the organization. This is due to its use in tracking computers, particularly after an operating system rebuild. This value is also used to socialize computer inventory from different inventory sources, and is used to map virtual machine guest operating system inventory to the VM host on which the virtual machine is running. Example sources:</p> <ul style="list-style-type: none"> • On Windows, the SMBios serial number. The WMI 'SerialNumber' property of the 'Win32_BIOS' class. Can fail over to the 'SerialNumber' property of the 'Win32_SystemEnclosure' class which is typically the same value. • On Linux, the SMBios serial number read using the command 'dmidecode -s system-serial-number'. Specifically, the 'System Information' section and the 'Serial Number' in that section is used. • On Solaris 10 8/07 or later, for a non-global zone, the UUID value from the /etc/zones/index file. For a global zone, the same as Solaris 10 releases earlier than 8/07. • For Solaris 10 releases earlier than 8/07, the hexadecimal version of 'SI_HW_SERIAL' with an appended hyphen character followed by the Zone's name. For example, '838bfc7b-global' or '838bfc7b-myzone'. • For Solaris 8 and 9, The hexadecimal version of 'SI_HW_SERIAL'. • For Mac OS X, the serial number of the machine as printed on the packaging and found in "About this Mac" from the desktop. • For HP-UX, the 'confstr _CS_PARTITION_IDENT' partition identifier if it is an nPar or vPar, or '_CS_MACHINE_IDENT' if not; with a failover to the machine serial number, and a final failover to the 'uname' machine identification number. • For AIX, the 'id_to_partition' system attribute, starting from the third character (strips a '0X' from the start). For example, if the 'id_to_partition' system attribute is '0X0473409002F7B201' then use '0473409002F7B201'.

Database Column	Details
HostID	<p><i>Type:</i> text (max 100 characters). Nullable</p> <p>An identifier for the host of the computer (when inventorying a machine partition such as Solaris Zone, AIX IPar, HP-UX nPar/vPar). Examples:</p> <ul style="list-style-type: none"> • For a Zone on Solaris, the hexadecimal version of SI_HW_SERIAL. • For nPar/vPar on HP-UX, the 'confstr_CS_MACHINE_IDENT' unique machine identifier. • For IPar on AIX, the 'modelName' system attribute following the comma character. For example, if the 'modelName' system attribute is 'IBM,8202-E4B', then use '8202-E4B'.
LastLoggedOnUser	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>The DOMAIN/SAMAccountName of the user last logged onto the computer.</p>
InventoryDate	<p><i>Type:</i> datetime. Nullable</p> <p>The date the computer last had inventory reported.</p>
HardwareInventoryDate	<p><i>Type:</i> datetime. Nullable</p> <p>The date (and optionally time) when the hardware was last inventoried. For automated/scheduled data uploads through an inventory beacon, make sure that inventory dates are kept current, as they are used to report out-of-date inventory sources. For a one-time upload to the central application server, leave inventory dates empty (null). At each import from the saved file, the import date is used as the inventory date, which prevents the inventory becoming stale. Notice that this value is not available in the web interface.</p>
ServicesInventoryDate	<p><i>Type:</i> datetime. Nullable</p> <p>The date when services (for example, Oracle) were last scanned on this computer. For automated/scheduled data uploads through an inventory beacon, make sure that inventory dates are kept current, as they are used to report out-of-date inventory sources. For a one-time upload to the central application server, leave inventory dates empty (null). At each import from the saved file, the import date is used as the inventory date, which prevents the inventory becoming stale.</p>
InventoryAgent	<p><i>Type:</i> text (max 128 characters)</p> <p>The name of the person or tool that performed the last inventory. For imported spreadsheets, you may wish to include the name of the person preparing the data, in case there is subsequent follow-up required.</p>

Database Column	Details
ComplianceComputerID	<p><i>Type:</i> integer. Key. Nullable</p> <p>Identifier of the computer in the ComplianceComputer table that this imported computer links to. This is populated by the import process and does not need to be provided by the source connections.</p>
ComplianceDomainID	<p><i>Type:</i> integer. Key. Nullable</p> <p>Identifier of the domain in the ComplianceDomain table that this computer belongs to. This is populated by the import process and does not need to be provided by the source connections.</p>
IncompleteRecord	<p><i>Type:</i> boolean. Nullable</p> <p>Used to identify records which do not have all information specified. Primarily used for ManageSoft source connections where the domain name was not reliably reported.</p>
NumberOfSockets	<p><i>Type:</i> integer. Nullable</p> <p>The number of sockets in the computer.</p>
PartialNumberOfProcessors	<p><i>Type:</i> decimal. Nullable</p> <p>The fractional processor count available to this computer.</p>
UntrustedSerialNo	<p><i>Type:</i> boolean</p> <p>Is this computer known to have a serial number from a data source that should not be trusted.</p>
FullDetailsFromExternalID	<p><i>Type:</i> big integer. Nullable</p> <p>If this computer is marked as incomplete, and some of its properties are updated from another computer, record the external ID if the full computer.</p>
FullDetailsFrom ComplianceConnectionID	<p><i>Type:</i> integer. Nullable</p> <p>If this computer is marked as incomplete, and some of its properties are updated from another computer, record the connection ID if the full computer.</p>
ComplianceComputerTypeID	<p><i>Type:</i> integer. Nullable</p> <p>If you know that the computer is a virtual machine or VM host, record that data here. If you are unsure, leave this cell empty (NULL): this allows the system to infer the computer type (for example, a computer with VMs linked to it is inferred to be a VM host). If data comes from multiple inventory sources, leaving this value as null also allows the value to be inserted from another source. So, unless there is a very good reason, do not just specify 'Computer', but allow the inference rules to help.</p>

Database Column	Details
ILMTAgentID	<p><i>Type:</i> big integer. Key. Nullable</p> <p>The unique ID used by the IBM License Metric Tool (ILMT) inventory agent on this device, if the inventory source is aware of this value. This can be used to track a computer over time and can be used to socialize different inventory sources. Currently the ILMT and ManageSoft inventory adapters report this value. To find these values:</p> <ul style="list-style-type: none"> On Windows: The standalone and agent based ILMT configuration files are '\$(WindowsFolder)/itlm/tlmstandalone.ini' and '\$(WindowsFolder)/itlm/tlmagent.ini' respectively. Read the 'agentid' property from these files using a case-insensitive match against the property name. On UNIX: The standalone and agent based ILMT configuration files are '/etc/tlmstandalone.ini' and '/etc/tlmagent.ini' respectively. Read the 'agentid' property from these files using a case-insensitive match against the property name.
HostIdentifyingNumber	<p><i>Type:</i> text (max 128 characters). Key. Nullable</p> <p>Virtual hosts may have an identifier that is unique only across that hardware model. It is less unique than the true hardware serial number, for example.</p>
HostType	<p><i>Type:</i> text (max 128 characters). Key. Nullable</p> <p>The type of the physical host computer. This value is similar to the model number, but it is always for the physical server that an execution context may be running on. Therefore, this will generally be a known value for standalone machines and partitions, but it will not be known for virtual machines. This value is used for matching computers. Examples:</p> <ul style="list-style-type: none"> 'i86pc' 'Sun-Fire-T1000' 'rx7620' '785' (for a 9000/785/C3700) '8202' (for an IBM,8202-E4B).
NumberOfLogicalProcessors	<p><i>Type:</i> integer. Nullable</p> <p>The number of logical processors in the computer.</p>
IsRemoteACLDevice	<p><i>Type:</i> boolean. Key</p> <p>Used to determine if the current record is a remote ACL based device.</p>
IsDuplicate	<p><i>Type:</i> boolean</p> <p>Used to identify that imported computer is a duplicate of another, whereby a new computer will not be created.</p>

Database Column	Details
LegacySerialNo	<p><i>Type:</i> text (max 100 characters). Nullable</p> <p>A previous serial number of this computer that can also be used for matching.</p>
UUID	<p><i>Type:</i> unique identifier. Key. Nullable</p> <p>The BIOS UUID of the computer.</p>
IMEI	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>IMEI (International Mobile Equipment Identity) is a 15- or 17-digit code that uniquely identifies mobile phone sets. Leave blank (null) for other device types.</p>
PhoneNumber	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>The phone number of the device. Used for mobile devices.</p>
EmailAddress	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>The email address associated with the device. Typically used for mobile devices.</p>
CalculatedUser	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>The domain/SAMAccountName of the calculated user. Some inventory systems calculate the user who owns a computer. For example, it might be the user who, over the last ten logins, logged in most often.</p>
LastSuccessfulInventoryDate	<p><i>Type:</i> datetime. Nullable</p> <p>For incremental imports, this represents the inventory date of the computer in the source at the time this record was last successfully imported. If the import procedure has failed, this may be different to the inventory date. At the end of a successful incremental import, this value is updated to match the inventory date. If no value is present in this field, either there has not been a successful import of this computer or the reader for this record is not using an incremental update model.</p>
MDScheduleGeneratedDate	<p><i>Type:</i> datetime. Nullable</p> <p>The last time the managed device schedule was regenerated.</p>
MDScheduleContainsPVUScan	<p><i>Type:</i> boolean. Nullable</p> <p>Does this managed device include an event in its current schedule for running extra IBM PVU hardware scans.</p>
FirmwareSerialNumber	<p><i>Type:</i> text (max 100 characters). Nullable</p> <p>Serial number in the system firmware such as BIOS, EEPROM etc.</p>
MachineID	<p><i>Type:</i> text (max 100 characters). Nullable</p> <p>For AIX, it is the System ID. For HP-UX, it is the Machine/Software ID. It is unset for other platforms.</p>

Database Column	Details
IgnoredDueToLicense	<i>Type:</i> boolean True if this machine is not imported into compliance computer table due to license limitation

ImportedComputerCustomProperty Table

The ImportedComputerCustomProperty table is used by the importer to import custom properties for computers.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 609: Database columns for ImportedComputerCustomProperty table

Database Column	Details
ComplianceConnectionID	Type: integer. Key The identifier of a data source connection in the ComplianceConnection table.
ExternalID	Type: big integer. Key The identifier, in the source connection, of the computer that this property belongs to.
PropertyNameID	Type: integer. Key The identifier for custom property in the ImportedCustomPropertyName table.
PropertyValue	Type: text (max 256 characters) The value of the custom property.

ImportedComputerScriptResult Table

The ImportedComputerScriptResult table holds all of the script results which have been retrieved from the source connections.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 610: Database columns for ImportedComputerScriptResult table

Database Column	Details
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
ExternalComputerID	Type: big integer. Key. Nullable The identifier used in the source connection for the computer.
RecognitionRule	Type: text (max 256 characters). Key. Nullable The recognition rule.
Revision	Type: integer. Nullable The revision number of the recognition rule.
InventoryDate	Type: datetime. Nullable The date the recognition rule ran.
Result	Type: text. Nullable The result of the recognition rule script.

ImportedCustomPropertyName Table

The ImportedCustomPropertyName table is used by the importer to store the names of custom properties.

Table 611: Database columns for ImportedCustomPropertyName table

Database Column	Details
PropertyNameID	Type: integer. Key. Generated ID A unique identifier for custom property.
PropertyName	Type: text (max 256 characters). Key The name of the custom property.

ImportedDomain Table

The ImportedDomain table holds all of the domains which have been retrieved from the source connections.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 612: Database columns for ImportedDomain table

Database Column	Details
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
ComplianceDomainID	Type: integer. Nullable Identifier of the domain in the ComplianceDomain table that this imported domain links to. This is populated as part of the import process and does not need to be provided by the source connections.
QualifiedName	Type: text (max 200 characters). Key. Nullable The fully qualified name of the domain.
FlatName	Type: text (max 200 characters). Key. Nullable The flat name of the domain.

ImportedEvidenceAttribute Table

The ImportedEvidenceAttribute table holds all of the instance attributes from the source connections.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 613: Database columns for ImportedEvidenceAttribute table

Database Column	Details
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
AttributeID	Type: integer. Key. Nullable The identifier used in the source connection for the instance attribute.
AttributeName	Type: text (max 256 characters). Key. Nullable The name of the instance attribute.

ImportedFNMEAFeature Table

The ImportedFNMEAFeature table is used by the importer to import FlexNet Manager for Engineering Applications features.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 614: Database columns for ImportedFNMEAFeature table

Database Column	Details
ComplianceConnectionID	<i>Type:</i> integer The identifier of a data source connection in the ComplianceConnection table.
ExternalID	<i>Type:</i> integer. Key. Generated ID The identifier of the feature from the external data source.
Name	<i>Type:</i> text (max 256 characters) The name for this feature.
Version	<i>Type:</i> text (max 32 characters). Nullable The version of this feature.
Publisher	<i>Type:</i> text (max 256 characters) The publisher of the feature.
VendorDaemon	<i>Type:</i> text (max 256 characters) The vendor daemon of the feature.
ConsumedQuantity	<i>Type:</i> integer The count of the feature installs.
OutOfComplianceQuantity	<i>Type:</i> integer The count of out-of-compliance feature installs, as calculated by FlexNet Manager for Engineering Applications.
ComplianceStatus	<i>Type:</i> text (max 32 characters) The compliance status of this feature, as calculated by FlexNet Manager for Engineering Applications.

Database Column	Details
FNMEAFeatureID	<p>Type: integer. Nullable</p> <p>The identifier of the FlexNet Manager for Engineering Applications feature in the FNMEAFeature table that this imported FlexNet Manager for Engineering Applications feature links to. This is populated by the import process and does not need to be provided by the source connections.</p>

ImportedFNMEAPProduct Table

The ImportedFNMEAPProduct table is used by the importer to import FlexNet Manager for Engineering Applications products.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 615: Database columns for ImportedFNMEAPProduct table

Database Column	Details
ComplianceConnectionID	<i>Type:</i> integer. Key The identifier of a data source connection in the ComplianceConnection table.
ExternalID	<i>Type:</i> text (max 256 characters). Key The identifier of the product from the external data source. This is the product number in FlexNet Manager for Engineering Applications.
FeatureID	<i>Type:</i> integer. Key The identifier (from the external data source) of the feature this product is associated with.
Name	<i>Type:</i> text (max 256 characters) The name for this product.
Version	<i>Type:</i> text (max 32 characters). Key The version of this product.
VendorDaemon	<i>Type:</i> text (max 256 characters). Key The vendor daemon of the products feature.
Publisher	<i>Type:</i> text (max 256 characters) The publisher of the product.
PurchasedQuantity	<i>Type:</i> integer The count of the products purchased.
OutOfComplianceQuantity	<i>Type:</i> integer The count of out-of-compliance product installs, as calculated by FlexNet Manager for Engineering Applications.
ComplianceStatus	<i>Type:</i> text (max 32 characters) The compliance status of this feature, as calculated by FlexNet Manager for Engineering Applications.

Database Column	Details
FeatureQuantity	<i>Type:</i> integer The count of the features available per product purchased.
SoftwareLicenseID	<i>Type:</i> integer. Nullable The identifier of the software license in the SoftwareLicense table that this imported FlexNet Manager for Engineering Applications product links to. This is populated by the import process and does not need to be provided by the source connections.

ImportedFNMEAUsageStatus Table

The ImportedFNMEAUsageStatus table is used by the importer to import FlexNet Manager for Engineering Applications status values.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 616: Database columns for ImportedFNMEAUsageStatus table

Database Column	Details
ComplianceConnectionID	Type: integer. Key The identifier of a data source connection in the ComplianceConnection table.
ProductNumber	Type: text (max 256 characters). Key The identifier of the product from the external data source. This is the product number in FlexNet Manager for Engineering Applications.
Version	Type: text (max 32 characters). Key The version of the product.
Publisher	Type: text (max 256 characters). Key The publisher of the product.
Month	Type: integer The month of the usage for this product.
Year	Type: integer The year of the usage of this product.
HWMUsage	Type: integer The high water mark usage of this product.

ImportedFileEvidence Table

The ImportedFileEvidence table holds all of the file evidence which has been retrieved from the source connections.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 617: Database columns for ImportedFileEvidence table

Database Column	Details
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
ExternalFileID	Type: big integer. Key. Nullable The identifier used in the source connection for the file evidence.
FileName	Type: text (max 256 characters). Key. Nullable The name of the file used as evidence of software installation.
FileVersion	Type: text (max 100 characters). Nullable The version number of the file used as evidence of software installation.
ProductVersion	Type: text (max 200 characters). Nullable The product version number in the file header.
ProductName	Type: text (max 200 characters). Nullable The product name in the file header.
FilePath	Type: text (max 400 characters). Nullable The path of the file used as evidence of software installation.
Company	Type: text (max 100 characters). Key. Nullable The company in the file header.
Description	Type: text (max 200 characters) The description in the file header.
FileSize	Type: integer. Nullable The size of the file.
Language	Type: text (max 200 characters). Nullable The language in the file header.

Database Column	Details
AccessModeID	Type: integer. Key. Nullable The access mode ID of the file evidence.

ImportedFileEvidenceMapping Table

The ImportedFileEvidenceMapping table is used by the importer to link imported file evidence with evidence in the FileEvidence table.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 618: Database columns for ImportedFileEvidenceMapping table

Database Column	Details
FileEvidenceID	Type: integer. Key. Nullable The identifier for the file evidence in the NewFileEvidence table.
ExternalFileID	Type: big integer. Key. Nullable The identifier used in the source connection for the imported file evidence.
ComplianceConnectionID	Type: integer. Key. Nullable The identifier of a data source connection in the ComplianceConnection table.

ImportedGuidMapping Table

The ImportedGuidMapping table is used by the importer to keep a history of entities that have been imported from a data source that uses GUID IDs rather than integer IDs.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 619: Database columns for ImportedGuidMapping table

Database Column	Details
ComplianceConnectionID	Type: integer. Key The identifier of a data source connection in the ComplianceConnection table.
Category	Type: text (max 100 characters). Key The importer category applicable for this ID space.
OriginalID	Type: unique identifier. Key The ID of this entity in the source database.
MappedID	Type: big integer. Generated ID A unique integer value we can use as an 'external ID' safely in the ImportedComputer table.

ImportedILMTPVUCounts Table

This table allows the summarised PVU sub capacity numbers to be imported from ILMT. These numbers are calculated by ILMT for a particular date range as PVU “reports”.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 620: Database columns for ImportedILMTPVUCounts table

Database Column	Details
ExternalNodeID	Type: big integer. Key The external ID of the server to which these points apply.
ExternalVMID	Type: big integer. Key. Nullable The external ID of the virtual machine associated with the node (server).
ComplianceConnectionID	Type: integer. Key The current connection ID for this data source.
TitleName	Type: text (max 512 characters). Key The name of the title these points apply to.
Publisher	Type: text (max 254 characters). Key The name of the publisher of the title these points apply to.
SubCapacityCores	Type: integer The number of sub-capacity licensable cores for the license on the computer.
FullCapacityCores	Type: integer The number of full-capacity licensable cores for the license on the computer.
SubCapacityPVU	Type: integer The number of sub-capacity PVU counts consumed for the license on the computer.
FullCapacityPVU	Type: integer The number of full-capacity PVU counts consumed for the license on the computer.
PeakSubCapacityPVU	Type: integer The peak number of sub-capacity PVU counts consumed for the license on the computer.

Database Column	Details
PeakFullCapacityPVU	<i>Type:</i> integer The peak number of full-capacity PVU counts consumed for the license on the computer.

ImportedILMTPVUCreatedLicenses Table

This table stores a history of IBM PVU licenses that have been created by the ILMT adapter.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 621: Database columns for ImportedILMTPVUCreatedLicenses table

Database Column	Details
SoftwareLicenseID	Type: integer The ID of the created license.
TitleName	Type: text (max 512 characters) The name of the title that triggered the creation of the license.
Publisher	Type: text (max 254 characters) The name of the publisher of the title that triggered the creation of the license.

ImportedILMTVMMapping Table

The ImportedILMTVMMapping table is used by the importer to keep a history of all Virtual Machine IDs (adm.VM records) that have been imported from ILMT data sources.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 622: Database columns for ImportedILMTVMMapping table

Database Column	Details
ComplianceConnectionID	Type: integer. Key The identifier of a data source connection in the ComplianceConnection table.
OriginalID	Type: big integer. Key The agent ID of this agent in the ILMT database.
MappedID	Type: integer. Generated ID A unique integer value we can use as an 'external ID' safely in the ImportedComputer table.

ImportedInstalledFileEvidence Table

The ImportedInstalledFileEvidence table holds a record of the file evidence that has been installed on a computer from the source connections.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 623: Database columns for ImportedInstalledFileEvidence table

Database Column	Details
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
ExternalID	Type: big integer. Key. Nullable The identifier used in the source connection for the computer that the file evidence is installed on.
ExternalFileID	Type: big integer. Key. Nullable The identifier used in the source connection for the file evidence.
ExternalFilePathID	Type: big integer. Key. Nullable The identifier used in the source connection for the path of the file evidence.

ImportedInstalledFileEvidenceUsage Table

The ImportedInstalledFileEvidenceUsage table holds a record of end-users that are using file evidence from the source connection.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 624: Database columns for ImportedInstalledFileEvidenceUsage table

Database Column	Details
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
StartDate	Type: text (max 10 characters). Nullable The start date of the file evidence usage tracking period.
ExternalID	Type: big integer. Key. Nullable The identifier used in the source connection for the computer that the file evidence is installed on.
ExternalUserID	Type: big integer. Key. Nullable The identifier used in the source connection for the end-user that has used the file evidence.
ExternalFileID	Type: big integer. Key. Nullable The identifier used in the source connection for the file evidence.
ActiveTimeInSeconds	Type: big integer. Nullable The number of seconds that the file evidence was in use during the usage tracking period.
NumberOfSessions	Type: big integer. Nullable The number of sessions that the file evidence was in use during the usage tracking period.
LastUsedDate	Type: text (max 10 characters). Nullable The last used date of the file evidence.

ImportedInstalledInstallerEvidence Table

The ImportedInstalledInstallerEvidence table holds a record of the installer evidence that has been installed on a computer from the source connections.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 625: Database columns for ImportedInstalledInstallerEvidence table

Database Column	Details
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
ExternalInstallerEvidenceID	Type: big integer. Key. Nullable The identifier used in the source connection for the installer evidence.
ExternalComputerID	Type: big integer. Key. Nullable The identifier used in the source connection for the computer that the installer evidence is installed on.
ExternalInstanceID	Type: big integer. Key. Nullable The identifier used in the source connection for the instance that the installer evidence is associated with.
InstallDate	Type: text (max 10 characters). Nullable The install date of the installer evidence.
DiscoveryDate	Type: text (max 10 characters). Nullable The date that the installer evidence was first seen.

ImportedInstalledInstallerEvidenceAttribute Table

The ImportedInstalledInstallerEvidenceAttribute table holds a record of the values of the instance attributes for each installer evidence which is reported to be installed on a computer.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 626: Database columns for ImportedInstalledInstallerEvidenceAttribute table

Database Column	Details
ComplianceConnectionID	<i>Type:</i> integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
ExternalInstallerEvidenceID	<i>Type:</i> big integer. Key. Nullable The identifier used in the source connection for the installer evidence.
ExternalComputerID	<i>Type:</i> big integer. Key. Nullable The identifier used in the source connection for the computer that the installer evidence is installed on.
ExternalInstanceID	<i>Type:</i> big integer. Key. Nullable The identifier used in the source connection for the instance that the installer evidence is associated with.
AttributeID	<i>Type:</i> integer. Key The identifier used in the source connection for the instance attribute.
Value	<i>Type:</i> text The value of the instance attribute for the installed installer evidence.

ImportedInstalledInstallerEvidenceUsage Table

The ImportedInstalledInstallerEvidenceUsage table holds a record of installed evidence being used from the source connections.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 627: Database columns for ImportedInstalledInstallerEvidenceUsage table

Database Column	Details
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
StartDate	Type: text (max 10 characters). Nullable The start date of the installer evidence usage tracking period.
ExternalID	Type: big integer. Key. Nullable The identifier used in the source connection for the computer that the installer evidence is installed on.
ExternalInstallerID	Type: big integer. Key. Nullable The identifier used in the source connection for the installer evidence.
ExternalInstanceID	Type: big integer. Key. Nullable The identifier used in the source connection for the instance that the installer evidence is associated with.
NumberOfSessions	Type: big integer. Nullable The number of sessions that the installer evidence was in use during the usage tracking period.
LastUsedDate	Type: text (max 10 characters). Nullable The last used date of the installed installer evidence.
ExternalUserID	Type: big integer. Key. Nullable The identifier used in the source connection for the user that the installer evidence was used on.

ImportedInstalledWMIEvidence Table

The ImportedInstalledWMIEvidence table holds a record of the WMI evidence that has been installed on a computer from the source connections.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 628: Database columns for ImportedInstalledWMIEvidence table

Database Column	Details
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
ExternalComputerID	Type: big integer. Key. Nullable The identifier used in the source connection for the computer that the WMI evidence is installed on.
ExternalEvidenceID	Type: big integer. Key. Nullable The identifier used in the source connection for the WMI evidence.
InstanceName	Type: text (max 256 characters). Key. Nullable The name of the WMI class instance used in the source connection for the WMI evidence

ImportedInstallerEvidence Table

The ImportedInstallerEvidence table holds all of the installer evidence which has been retrieved from the source connections.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 629: Database columns for ImportedInstallerEvidence table

Database Column	Details
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
ExternalInstallerID	Type: big integer. Key. Nullable The identifier used in the source connection for the installer evidence.
DisplayName	Type: text (max 256 characters). Key. Nullable The display name of the software as reported by the installer evidence.
Version	Type: text (max 72 characters). Key. Nullable The version of the software as reported by the installer evidence.
Publisher	Type: text (max 200 characters). Key. Nullable The publisher of the software as reported by the installer evidence.
Evidence	Type: text (max 32 characters). Nullable Identifier for the type of installer evidence.
ProductCode	Type: text (max 55 characters). Nullable The product code of the evidence. This is usually the MSI product code.
AccessModeID	Type: integer. Key. Nullable The access mode ID of the file evidence.

ImportedInstallerEvidenceMapping Table

The ImportedInstallerEvidenceMapping table is used by the importer to link imported installer evidence with evidence in the InstallerEvidence table.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 630: Database columns for ImportedInstallerEvidenceMapping table

Database Column	Details
InstallerEvidenceID	Type: integer. Key. Nullable The identifier for the installer evidence in the InstallerEvidence table.
ExternalInstallerID	Type: big integer. Key. Nullable The identifier used in the source connection for the imported installer evidence.
ComplianceConnectionID	Type: integer. Key. Nullable The identifier of a data source connection in the ComplianceConnection table.

ImportedInstallerEvidenceRepackageMapping Table

The ImportedInstallerEvidenceRepackageMapping table is used by the importer to map the original and current installer evidence of repackaged softwares as reported by the ISO tag evidence.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 631: Database columns for ImportedInstallerEvidenceRepackageMapping table

Database Column	Details
ComplianceConnectionID	Type: integer. Key. Nullable The identifier of a data source connection in the ComplianceConnection table.
OrigDisplayName	Type: text (max 256 characters). Key. Nullable The original display name of the repackaged software as reported by the ISO tag evidence.
OrigVersion	Type: text (max 72 characters). Key. Nullable The original version of the repackaged software as reported by the ISO tag evidence.
OrigPublisher	Type: text (max 200 characters). Key. Nullable The original publisher of the repackaged software as reported by the ISO tag evidence.
CurrentDisplayName	Type: text (max 256 characters). Key. Nullable The current display name of the repackaged software as reported by the ISO tag evidence.
CurrentVersion	Type: text (max 72 characters). Key. Nullable The current version of the repackaged software as reported by the ISO tag evidence.
CurrentPublisher	Type: text (max 200 characters). Key. Nullable The current publisher of the repackaged software as reported by the ISO tag evidence.

ImportedInstance Table

The ImportedInstance table holds all of the instances which have been retrieved from the source connections.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 632: Database columns for ImportedInstance table

Database Column	Details
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
InstanceID	Type: big integer. Key. Nullable The identifier used in the source connection for the instance.
InstanceName	Type: text (max 256 characters). Nullable The name of the instance.
ParentInstanceID	Type: big integer. Key. Nullable The identifier used in the source connection for the parent instance.
ExternalComputerID	Type: big integer. Key. Nullable The identifier used in the source connection for the computer.
AuditEvidence	Type: binary. Nullable Oracle LMS CVS files in zip archive.
AuditEvidenceDate	Type: datetime. Nullable Oracle LMS CSV files collection date.

ImportedInstanceUser Table

The ImportedInstanceUser table holds all of the end-users of an instance which have been retrieved from the source connections.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 633: Database columns for ImportedInstanceUser table

Database Column	Details
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
ExternalID	Type: big integer. Key The identifier used in the source connection for the instance end-user.
ComputerID	Type: big integer. Key The identifier used in the source connection for the computer.
InstanceID	Type: big integer. Key The identifier used in the source connection for the instance.
AccountStatus	Type: text (max 256 characters). Nullable The current status of the end-user account.
CreationDate	Type: datetime. Nullable The date and time when the end-user was created.
LastLogonDate	Type: datetime. Nullable The date and time when the end-user last logged on to the computer.
DefaultTablespace	Type: text (max 256 characters). Nullable The default tablespace for an Oracle end-user.
TempTablespace	Type: text (max 256 characters). Nullable The temporary tablespace for an Oracle end-user.
ApplicationID	Type: text (max 400 characters). Key. Nullable The Oracle EBS application ID the user has access to.

ImportedMissingComputer Table

The ImportedMissingComputer table holds all of the computers which no longer have inventory records in the source connections.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 634: Database columns for ImportedMissingComputer table

Database Column	Details
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
ExternalID	Type: big integer. Key. Nullable The identifier used in the source connection for the computer.
ComplianceComputerID	Type: integer. Key. Nullable Identifier of the computer in the ComplianceComputer table that this imported computer links to.

ImportedMissingLicenseUser Table

The ImportedMissingLicenseUser table holds all of the external end-users which no longer have inventory records in the source connections.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 635: Database columns for ImportedMissingLicenseUser table

Database Column	Details
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
ExternalID	Type: big integer. Key. Nullable The identifier used in the source connection for the external end-user.
LicenseUserID	Type: integer. Key. Nullable The identifier for the external end-user in the LicenseUser table.

ImportedMissingUser Table

The ImportedMissingUser table holds all of the end-users which no longer have inventory records in the source connections.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 636: Database columns for ImportedMissingUser table

Database Column	Details
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
ExternalID	Type: big integer. Key. Nullable The identifier used in the source connection for the end-user.
ComplianceUserID	Type: integer. Key. Nullable The identifier for the end-user in the ComplianceUser table.

ImportedProductCodeEvidenceMapping Table

The ImportedProductCodeEvidenceMapping table is used by the importer to link imported product code evidence with evidence in the InstallerEvidence table.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 637: Database columns for ImportedProductCodeEvidenceMapping table

Database Column	Details
InstallerEvidenceID	Type: integer. Key. Nullable The identifier for the installer evidence in the InstallerEvidence table.
ExternalInstallerID	Type: big integer. Key. Nullable The identifier used in the source connection for the imported installer evidence.
ComplianceConnectionID	Type: integer. Key. Nullable The identifier of a data source connection in the ComplianceConnection table.

ImportedRelatedInstalledInstallerEvidence Table

The ImportedRelatedInstalledInstallerEvidence table holds parent-child relationship between installer evidence.

 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 638: Database columns for ImportedRelatedInstalledInstallerEvidence table

Database Column	Details
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
ParentExternal InstallerEvidenceID	Type: big integer. Key. Nullable The identifier used in the source connection for the installer evidence.
ParentExternalComputerID	Type: big integer. Key. Nullable The identifier used in the source connection for the computer that the installer evidence is installed on.
ChildExternalInstaller EvidenceID	Type: big integer. Key. Nullable The identifier used in the source connection for the installer evidence.
ChildExternalComputerID	Type: big integer. Key. Nullable The identifier used in the source connection for the computer that the installer evidence is installed on.
IsCharged	Type: boolean. Key. Nullable The identifier used in the source connection to determine the pricing relation between parent and child installer evidence (specifies if it is charged = 1 or free = 0).
ConfidenceLevel	Type: integer. Nullable Confidence level for each bundled installer evidence (as a percentage).

ImportedRemoteApplication Table

This ImportedRemoteApplication table stores all the published applications from Citrix XenApp/App-V Management Server.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 639: Database columns for ImportedRemoteApplication table

Database Column	Details
FarmName	Type: text (max 256 characters). Nullable The farm from which the application belongs to.
AppID	Type: text (max 256 characters). Key. Nullable The unique identifier for XenApp applications.
AppName	Type: text (max 256 characters). Nullable The application name available in XenApp.
AppFileName	Type: text (max 256 characters). Key. Nullable The application executable name.
AppFileVersion	Type: text (max 256 characters). Key. Nullable The application executable version.
AppFilePublisher	Type: text (max 256 characters). Key. Nullable The application publisher.
AppFileDescription	Type: text (max 256 characters). Key. Nullable The application description.
IsStreamingProfile	Type: boolean. Nullable Whether the application is a streaming profile.
AccessModeID	Type: integer. Key The access mode of the virtual application.

ImportedRemoteApplicationAccess Table

This ImportedRemoteApplicationAccess table stores all users/groups with sid who have access to what virtual applications.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 640: Database columns for ImportedRemoteApplicationAccess table

Database Column	Details
FarmName	Type: text (max 256 characters). Nullable The farm from which the virtual application belongs to.
AppID	Type: text (max 256 characters). Nullable The unique identifier for virtual applications.
Sid	Type: text (max 256 characters). Nullable The sid that has access to the application.
AccessModeID	Type: integer The access mode of the virtual application.

ImportedRemoteApplicationInstallerData Table

This ImportedRemoteApplicationInstallerData table stores all the MSI information in a streamed profile.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 641: Database columns for ImportedRemoteApplicationInstallerData table

Database Column	Details
FarmName	Type: text (max 256 characters). Nullable The farm from which the application belongs to.
AppID	Type: text (max 256 characters). Key. Nullable The unique identifier for virtual applications.
DisplayName	Type: text (max 256 characters). Key. Nullable The application name.
Publisher	Type: text (max 200 characters). Key. Nullable The application publisher name.
Version	Type: text (max 72 characters). Key. Nullable The application version.
ProductCode	Type: text (max 55 characters). Nullable The product code of the evidence. This is usually the MSI product code.
AccessModeID	Type: integer. Key The access mode of the virtual application.

ImportedRemoteApplicationServer Table

This ImportedRemoteApplicationServer table stores the servers from which applications are published from.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 642: Database columns for ImportedRemoteApplicationServer table

Database Column	Details
FarmName	Type: text (max 256 characters). Nullable The farm from which the server belongs to.
AppID	Type: text (max 256 characters). Key. Nullable The unique identifier for XenApp applications.
ServerName	Type: text (max 256 characters). Key. Nullable The XenApp server the application is available under.
ServerDomainName	Type: text (max 256 characters). Key. Nullable The XenApp server domain name.
VDIGroupUUID	Type: unique identifier. Nullable The desktop group UUID from which the application is published
AccessModeID	Type: integer. Key The access mode of the virtual application.

ImportedRemoteServerFileEvidenceMapping Table

The ImportedRemoteServerFileEvidenceMapping table stores the mapping between file evidence on servers to software titles


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 643: Database columns for ImportedRemoteServerFileEvidenceMapping table

Database Column	Details
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
ExternalServerID	Type: big integer. Key. Nullable The External Server ID for the remote server.
ExternalFileID	Type: big integer. Key. Nullable The identifier used in the source connection for the file evidence.
SoftwareTitleID	Type: integer. Nullable The software title ID corresponding to the piece of file evidence.

ImportedRemoteUsage Table

This ImportedRemoteUsage table stores the remote usage for applications in remote hosting environments


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 644: Database columns for ImportedRemoteUsage table

Database Column	Details
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
ExternalServerID	Type: big integer. Key. Nullable The External Server ID for the remote server.
ExternalClientID	Type: big integer. Nullable The External client ID for the remote client machine.
ExternalFileID	Type: big integer. Key. Nullable The identifier used in the source connection for the file evidence.
ExternalInstallerEvidenceID	Type: big integer. Nullable The identifier used in the source connection for the installer evidence.
ExternalUserID	Type: big integer. Nullable The identifier used in the source connection for the end-user that has used the file evidence.
StartDate	Type: text (max 10 characters). Nullable The start date of the remote usage tracking period.
ActiveTimeInSeconds	Type: big integer. Nullable The number of seconds that the file evidence was in use during the usage tracking period.
NumberOfSessions	Type: big integer. Nullable The number of sessions that the file evidence was in use during the usage tracking period.
AccessModeID	Type: integer. Nullable The access mode ID for the remote usage.

ImportedRemoteUserToApplicationAccess Table

The ImportedRemoteUserToApplicationAccess table stores the applications that remote users have access to


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 645: Database columns for ImportedRemoteUserToApplicationAccess table

Database Column	Details
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
ExternalServerID	Type: big integer. Key. Nullable The External Server ID for the remote server.
VDIGroupUUID	Type: unique identifier. Nullable The desktop group UUID from which the application is published
ExternalFileID	Type: big integer. Key. Nullable The identifier used in the source connection for the file evidence.
ExternalInstallerEvidenceID	Type: big integer. Key. Nullable The identifier used in the source connection for the installer evidence.
ExternalUserID	Type: big integer. Key. Nullable The identifier used in the source connection for the end-user that has used the file evidence.
AccessModeID	Type: integer. Key. Nullable The access mode ID for the remote application access.
LastUsedDate	Type: datetime. Key. Nullable The last time the remote application was used by the user.

ImportedSite Table

The ImportedSubnet contains sites imported from Microsoft Active Directory


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 646: Database columns for ImportedSite table

Database Column	Details
ComplianceConnectionID	Type: integer. Key The identifier for a data source connection in the ComplianceConnection table.
Name	Type: text (max 256 characters). Key The site's name.
AutoPopulated	Type: boolean Is the site auto populated at source?
Enabled	Type: boolean Is the site enabled?

ImportedSiteSubnet Table

The ImportedSiteSubnet contains sites and subnets imported from Microsoft Active Directory


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 647: Database columns for ImportedSiteSubnet table

Database Column	Details
ComplianceConnectionID	Type: integer. Key The identifier for a data source connection in the ComplianceConnection table.
SiteName	Type: text (max 256 characters). Key The site's name.
IPSubnet	Type: text (max 64 characters). Key The IP subnet.
IPSubnetBits	Type: tiny integer. Key The IP subnet mask in CIDR notation.
AutoPopulated	Type: boolean Is the subnet auto populated at source?
Enabled	Type: boolean Is the subnet enabled?

ImportedSoftwareLicense Table

The ImportedSoftwareLicense table holds all of the licenses which have been retrieved from the source connections.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 648: Database columns for ImportedSoftwareLicense table

Database Column	Details
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
ExternalLicenseID	Type: big integer. Key. Nullable The identifier used in the source connection for the license.
LicenseName	Type: text (max 256 characters). Nullable The name of the license.
SoftwareLicenseTypeID	Type: integer. Nullable The license type ID of the license.
EntitlementCount	Type: integer. Nullable The number of entitlements for the license.
IsSubscription	Type: boolean Indicates whether or not the license is a subscription license.
ExpiryDate	Type: datetime. Nullable The expiry date of a subscription license.
PartNo	Type: text (max 100 characters). Nullable The publisher's part number for this license.
SoftwareLicenseID	Type: integer. Nullable Identifier of the license in the SoftwareLicense table that this imported license links to. This is populated by the import process and does not need to be provided by the source connections.

ImportedSoftwareLicenseAllocation Table

The ImportedSoftwareLicenseAllocation table holds the links between licenses and end-users which have been retrieved from the source connections.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 649: Database columns for ImportedSoftwareLicenseAllocation table

Database Column	Details
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
ExternalLicenseID	Type: big integer. Key. Nullable The identifier used in the source connection for the license.
ExternalUserID	Type: big integer. Key. Nullable The identifier used in the source connection for the license.

ImportedStringMapping Table

The ImportedStringMapping table is used by the importer to keep a history of entities that have been imported from a data source that uses string IDs rather than integer IDs.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 650: Database columns for ImportedStringMapping table

Database Column	Details
ComplianceConnectionID	<i>Type:</i> integer. Key The identifier of a data source connection in the ComplianceConnection table.
Category	<i>Type:</i> text (max 100 characters). Key The importer category applicable for this ID space.
OriginalID	<i>Type:</i> text (max 400 characters). Key The ID of this entity in the source database.
MappedID	<i>Type:</i> big integer. Generated ID A unique integer value we can use as an 'external ID' safely in the ImportedComputer table.

ImportedStringMappingLatin1CS Table

The ImportedStringMappingLatin1CS table is used by the importer to keep a history of entities that have been imported from a data source that uses case sensitive string IDs rather than integer IDs.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 651: Database columns for ImportedStringMappingLatin1CS table

Database Column	Details
ComplianceConnectionID	Type: integer. Key The identifier of a data source connection in the ComplianceConnection table.
Category	Type: text (max 100 characters). Key The importer category applicable for this ID space.
OriginalID	Type: text (max 400 characters). Key The ID of this entity in the source database.
MappedID	Type: big integer. Generated ID A unique integer value we can use as an 'external ID' safely in the ImportedComputer table.

ImportedUser Table

The ImportedUser table holds all of the end-users which have been retrieved from the source connections.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 652: Database columns for ImportedUser table

Database Column	Details
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
ExternalID	Type: big integer. Key. Nullable The identifier used in the source connection for the end-user.
UserName	Type: text (max 64 characters). Nullable The account name of the end-user.
Domain	Type: text (max 100 characters). Key. Nullable The domain of the end-user.
SAMAccountName	Type: text (max 64 characters). Key. Nullable The SAM account name of the end-user.
InventoryAgent	Type: text (max 64 characters). Nullable The name of the person or tool that performed the last inventory. For imported spreadsheets, you may wish to include the name of the person preparing the data, in case there is subsequent follow-up required.
FirstName	Type: text (max 128 characters). Nullable The first name of the end-user.
LastName	Type: text (max 128 characters). Nullable The last name or surname of the end-user.
Email	Type: text (max 200 characters). Nullable The email address of the end-user.
EmployeeNumber	Type: text (max 128 characters). Nullable The employee number of the end-user.

Database Column	Details
CostCenter	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>The cost center of the end-user, as reported in SAP. Does not necessarily map to a cost centre in the GroupEx table.</p>
ComplianceUserID	<p><i>Type:</i> integer. Nullable</p> <p>Identifier of the end-user in the ComplianceUser table that this imported user links to. This is populated by the import process and does not need to be provided by the source connections.</p>
ComplianceDomainID	<p><i>Type:</i> integer. Nullable</p> <p>Identifier of the domain in the ComplianceDomain table that this end-user belongs to. This is populated by the import process and does not need to be provided by the source connections.</p>
IsBlacklisted	<p><i>Type:</i> boolean. Key</p> <p>This is populated by the import process and does not need to be provided by the source connections. The field is set to True if the end-user matches a record from the UserNameBlacklist table, meaning the account should not be included in compliance calculations.</p>
MapUsingEmailAddress	<p><i>Type:</i> boolean</p> <p>Indicates whether or not the user's email address should be used to try and map it to an existing ComplianceUser record.</p>

ImportedVDI Table

The ImportedVDIUser table stores the list of VDI devices, their master VM template and the VDI group the VDI device resides under.

 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 653: Database columns for ImportedVDI table

Database Column	Details
ComplianceConnectionID	<i>Type:</i> integer The identifier of a data source connection in the ComplianceConnection table.
ExternalDeviceID	<i>Type:</i> big integer. Nullable The identifier used in the source connection for the VDI device.
ComputerName	<i>Type:</i> text (max 64 characters). Nullable The computer name of the VDI.
Domain	<i>Type:</i> text (max 100 characters). Nullable The domain name of the VDI device.
VDIGroupName	<i>Type:</i> text (max 100 characters). Key. Nullable The VDI group the VDI device belongs to.
TemplateName	<i>Type:</i> text (max 100 characters). Key. Nullable The VDI template the VDI is cloned from.
SiteName	<i>Type:</i> text (max 256 characters). Key. Nullable The site name of the VDI.
BrokerType	<i>Type:</i> text (max 64 characters). Key. Nullable The broker type of the VDI device.
IsPersistent	<i>Type:</i> boolean. Key. Nullable Determine whether the VDI device is a persistent VDI device.
VDIGroupUUID	<i>Type:</i> unique identifier. Nullable The group UUID the VDI device belongs to.
ApplicationDeliveryOnly	<i>Type:</i> boolean. Nullable Determines whether the VDI device is used only to server applications.

ImportedVDIEndPointAccess Table

The ImportedVDIEndPointAccess table stores the list of users on end-points that have accessed VDI devices.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 654: Database columns for ImportedVDIEndPointAccess table

Database Column	Details
ComplianceConnectionID	Type: integer. Nullable The identifier of a data source connection in the ComplianceConnection table.
ExternalDeviceID	Type: big integer. Nullable The identifier used in the source connection for the device.
ExternalUserID	Type: big integer. Nullable The identifier used in the source connection for the user.
VDIDeviceName	Type: text (max 64 characters). Nullable The computer name of the VDI device.
VDIDeviceDomain	Type: text (max 100 characters). Nullable The domain name of the VDI device.
VDITemplateName	Type: text (max 256 characters). Nullable The VDI template the VDI device was cloned from.
LogonTime	Type: datetime. Key. Nullable The logon time of the VDI device by the user.
BrokerType	Type: text (max 64 characters). Nullable The broker type of the VDI device.

ImportedVDITemplate Table

The ImportedVDITemplate table stores the list of VDI templates.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 655: Database columns for ImportedVDITemplate table

Database Column	Details
ComplianceConnectionID	Type: integer The identifier of a data source connection in the ComplianceConnection table.
TemplateName	Type: text (max 64 characters). Key. Nullable The template name of the VDI template.
SiteName	Type: text (max 256 characters). Key. Nullable The site name of the VDI.
BrokerType	Type: text (max 64 characters). Key. Nullable The broker type of the VDI template.
VDITemplateExternalID	Type: big integer. Nullable The ExternalID of the VDI template in the ImportedComputer table.

ImportedVDIUser Table

The ImportedVDIUser table stores the list of users that have been granted access to VDI groups.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 656: Database columns for ImportedVDIUser table

Database Column	Details
ComplianceConnectionID	Type: integer. Key The identifier of a data source connection in the ComplianceConnection table.
ExternalUserID	Type: big integer. Key. Nullable The identifier used in the source connection for the end-user that has access to the VDI.
VDIGroupName	Type: text (max 100 characters). Nullable The VDI group the end-user has access to.
SiteName	Type: text (max 256 characters). Nullable The site name of the VDI.
BrokerType	Type: text (max 64 characters). Nullable The broker type of the VDI for the end user.

ImportedVMHostDatastore Table

The ImportedVMHostDatastore table holds all of the datastore objects available to virtual machines hosts.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 657: Database columns for ImportedVMHostDatastore table

Database Column	Details
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
ExternalComputerID	Type: big integer. Key. Nullable The identifier used in the source connection for the virtual machine’s host computer ID.
Datastore	Type: text (max 64 characters). Nullable The datastore availaboe on the VM host.

ImportedVMHostManagedBySoftware Table

The ImportedVMHostManagedBySoftware table contains relationships between installer evidence of management software and VM hosts it manages.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 658: Database columns for ImportedVMHostManagedBySoftware table

Database Column	Details
ComplianceConnectionID	Type: integer. Key The identifier for a data source connection in the ComplianceConnection table.
ExternalInstallerID	Type: big integer. Key The identifier used in the source connection for an installer evidence of management software.
ExternalComputerID	Type: big integer. Key The identifier used in the source connection for the computer that the management software installer evidence is installed on.
RelationType	Type: text (max 100 characters). Key Identifier for the type of relation, to be matched against ImporterString column of RelationType table.
ExternalVMHostID	Type: big integer. Key The identifier used in the source connection for the VM host computer that is managed by a management software.

ImportedVMHostProperty Table

The ImportedVMHostProperty table holds additional properties for virtual machines hosts which have been retrieved from the source connections.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 659: Database columns for ImportedVMHostProperty table

Database Column	Details
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
ExternalComputerID	Type: big integer. Key. Nullable The identifier used in the source connection for the virtual machine's host computer ID.
VMTypeID	Type: big integer. Nullable The VMHost technology type. Foreign key to the VMType table.
HypervisorVersion	Type: text (max 32 characters). Nullable The hypervisor version of the VM host.
HyperThreadingEnabled	Type: boolean. Nullable Set this to True if this VM host has hyper threading enabled.
PowerState	Type: text (max 32 characters). Nullable The power state of the VM host.
ManagingSoftwareVersion	Type: text (max 32 characters). Nullable The version of the managing software for the VM host.
ConnectionState	Type: text (max 32 characters). Nullable The connection state of the VM host to the managing software environment.

ImportedVMPool Table

The ImportedVMPool table holds all of the virtual machine pools which have been retrieved from the source connections and the number of processors and cores that are assigned to each pool.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 660: Database columns for ImportedVMPool table

Database Column	Details
PoolName	Type: text (max 100 characters). Key. Nullable The name of the pool.
VCObjectID	Type: text (max 256 characters). Nullable The identifier of the virtual machine folder in Virtual Center.
ParentName	Type: text (max 100 characters). Nullable The name of the parent pool. This is the PoolName property for the parent pool.
PoolFriendlyName	Type: text (max 256 characters). Nullable The friendly name of the pool.
HostComputerID	Type: big integer. Key. Nullable The identifier used in the source connection for the computer which is hosting the pool.
ObjectType	Type: text (max 256 characters). Key. Nullable The type of pool.
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
ParentObjectType	Type: text (max 256 characters). Nullable The type of pool of the parent.
NumberOfProcessors	Type: decimal. Nullable The number of processors available to this pool.
NumberOfCores	Type: decimal. Nullable The number of cores available to this pool.

ImportedVirtualMachine Table

The ImportedVirtualMachine table holds all of the virtual machines which have been retrieved from the source connections.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 661: Database columns for ImportedVirtualMachine table

Database Column	Details
HostComputerID	Type: big integer. Key. Nullable The identifier used in the source connection for the virtual machine's host computer.
VirtualMachineType	Type: text (max 100 characters). Nullable The type of virtual machine.
VMName	Type: text (max 256 characters). Nullable The name of the virtual machine.
VCObjectID	Type: text (max 256 characters). Nullable The identifier of the virtual machine in Virtual Center.
FriendlyName	Type: text (max 256 characters). Nullable The friendly name of the virtual machine.
ComputerName	Type: text (max 256 characters). Nullable The computer name of the virtual machine.
UUID	Type: text (max 256 characters). Key. Nullable The UUID of the virtual machine.
TotalMemory	Type: big integer. Nullable The total RAM in the computer, in bytes.
PoolName	Type: text (max 100 characters). Nullable The name of the pool that the virtual machine belongs to.
CPUUsage	Type: integer. Nullable The maximum CPU usage of the virtual machine (MHz).
MemoryUsage	Type: big integer. Nullable The maximum memory usage of the virtual machine (bytes).

Database Column	Details
VMEnabledStateID	<p><i>Type:</i> integer. Nullable</p> <p>The state of the machine (powered on, off, etc).</p>
ModelNo	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>The model number of the virtual machine.</p>
Manufacturer	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>The manufacturer of the computer hardware. Some examples include:</p> <ul style="list-style-type: none"> • On Windows, the SMBios manufacturer (the WMI Manufacturer property of the 'Win32_ComputerSystem' class). • On Linux, 'Manufacturer' in the 'System Information' section resulting from the 'dmidecode' command. Sample command: 'dmidecode -s system-manufacturer' • On Solaris x86, as for Linux, with failovers first to 'sysinfo SI_HW_PROVIDER' and then to 'ModelNo'. • On Solaris SPARC, the 'sysinfo SI_HW_PROVIDER'. Typically this value is 'Sun_Microsystems' or, more recently, 'Oracle Corporation'. Failover to the 'ModelNo'. • On HP-UX, the string literal 'HP'. • On AIX, the 'modelname' system attribute preceding the comma character. For example, if the 'modelname' system attribute is 'IBM,8202-E4B', then use 'IBM'. This value is typically 'IBM'.
NumberOfProcessors	<p><i>Type:</i> integer. Nullable</p> <p>The number of processors in the virtual machine.</p>
ProcessorType	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>The type of processor in the virtual machine.</p>
NumberOfHardDrives	<p><i>Type:</i> integer. Nullable</p> <p>The number of hard drives in the virtual machine.</p>
NumberOfNetworkCards	<p><i>Type:</i> integer. Nullable</p> <p>The number of network cards in the virtual machine.</p>
InventoryAgent	<p><i>Type:</i> text (max 64 characters). Nullable</p> <p>The name of the person or tool that performed the last inventory.</p>
ComplianceConnectionID	<p><i>Type:</i> integer. Key. Nullable</p> <p>The identifier for a data source connection in the ComplianceConnection table.</p>

Database Column	Details
VMLocation	<i>Type:</i> text (max 256 characters). Nullable Location of the virtual machine on the file system.
GuestFullName	<i>Type:</i> text (max 256 characters). Nullable Configured operating system for the guest.
VMComputerID	<i>Type:</i> big integer. Key. Nullable The identifier used in the source connection for the virtual machine's computer.
PoolType	<i>Type:</i> text (max 100 characters). Nullable The type of the pool that the virtual machine belongs to.
AffinityEnabled	<i>Type:</i> boolean Set this to True if this VM is unable to move to different host computers.
CPUAffinity	<i>Type:</i> text (max 256 characters). Nullable Contains the CPU Affinity value for virtual machine(Host Logical Processors)
CoreAffinity	<i>Type:</i> text (max 256 characters). Nullable Contains the Core Affinity value for virtual machine
PartitionID	<i>Type:</i> text (max 100 characters). Nullable Partition ID generated and used by the managing virtualization platform
PartitionNumber	<i>Type:</i> integer. Nullable Number of this partition
FullComputerName	<i>Type:</i> text (max 256 characters). Nullable The virtual machine full computer name as determined by the VM guest managing tool.
IPAddress	<i>Type:</i> text (max 256 characters). Nullable IP Address of the virtual machine as determined by the VM guest managing tool.

ImportedWMIEvidence Table

The ImportedWMIEvidence table holds all of the WMI evidence which has been retrieved from the source connections.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 662: Database columns for ImportedWMIEvidence table

Database Column	Details
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
ClassName	Type: text (max 50 characters). Key. Nullable The WMI class name of the WMI evidence.
PropertyName	Type: text (max 50 characters). Key. Nullable The WMI property name of the WMI evidence.
PropertyValue	Type: text (max 256 characters). Key. Nullable The value of the property of the WMI evidence.
ExternalEvidenceID	Type: big integer. Key. Nullable The identifier used in the source connection for the WMI evidence.

ImportedWMIEvidenceRuleMapping Table

The ImportedWMIEvidenceRuleMapping table is used by the importer to link imported WMI evidence with evidence in the WMIEvidence table.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 663: Database columns for ImportedWMIEvidenceRuleMapping table

Database Column	Details
EvidenceRuleID	Type: integer. Nullable The identifier for the WMI evidence in the WMIEvidence table.
ExternalEvidenceID	Type: big integer. Key. Nullable The identifier used in the source connection for the imported WMI evidence.
ComplianceConnectionID	Type: integer. Key. Nullable The identifier of a data source connection in the ComplianceConnection table.

ImporterValueMapping Table

The ImporterValueMapping table stores mapping pairs for use by importer tasks. It serves as a basic lookup translation table that is not connection-specific.

Table 664: Database columns for ImporterValueMapping table

Database Column	Details
ImporterValueMappingID	Type: integer. Key. Generated ID Unique auto-incrementing identifier.
Category	Type: text (max 100 characters). Key The importer section applicable for this key, uses dotted notation: e.g. "MobileDevice.Apple.Model".
FromValue	Type: text (max 256 characters). Key The value to translate.
ToValue	Type: text (max 256 characters). Nullable The required destination value for the Category/FromValue pair.

InstalledApplications Table

The InstalledApplications table is populated by the import process to track which software has been installed.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 665: Database columns for InstalledApplications table

Database Column	Details
ComplianceComputerID	<i>Type:</i> integer. Key The identifier for the computer in the ComplianceComputer table that the software is installed on.
SoftwareTitleID	<i>Type:</i> integer. Key The identifier for the software in the SoftwareTitle table that is installed.
InstanceName	<i>Type:</i> text (max 256 characters). Nullable The name of the instance that the software installation is associated with.
InstallerEvidence	<i>Type:</i> boolean This field is True if the installation is reported due to installer evidence.
FileEvidence	<i>Type:</i> boolean This field is True if the installation is reported due to file evidence.
WMIEvidence	<i>Type:</i> boolean This field is True if the installation is reported due to WMI evidence.
AccessModeID	<i>Type:</i> integer The access mode for which the installed application has been accessed. Foreign key to the AccessMode table.
IsACL	<i>Type:</i> boolean Determines whether the access mode record came from ACL data.

RelatedInstalledApplications Table

The RelatedInstalledApplications table is populated by the import process to track which relationship between applications.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 666: Database columns for RelatedInstalledApplications table

Database Column	Details
ParentComplianceComputerID	<i>Type:</i> integer. Key The parent identifier for the computer in the ComplianceComputer table that the software is installed on.
ParentSoftwareTitleID	<i>Type:</i> integer. Key The parent identifier for the software in the SoftwareTitle table that is installed.
ParentAccessModeID	<i>Type:</i> integer. Key The access mode for which the installed application has been accessed. Foreign key to the AccessMode table.
ChildComplianceComputerID	<i>Type:</i> integer. Key The child identifier for the computer in the ComplianceComputer table that the software is installed on.
ChildSoftwareTitleID	<i>Type:</i> integer. Key The child identifier for the software in the SoftwareTitle table that is installed.
ChildAccessModeID	<i>Type:</i> integer. Key The access mode for which the installed application has been accessed. Foreign key to the AccessMode table.
IsCharged	<i>Type:</i> boolean. Key The identifier used in the source connection to determine the pricing relation between parent and child installer evidence (specifies if it is charged or free).
ConfidenceLevel	<i>Type:</i> integer. Nullable Confidence level for each bundled installer evidence (as a percentage).

Compliance.InventoryWriter.Matching Tables

The complete set of database tables documented here includes:

- ComplianceComputerMatchResult table (see [ComplianceComputerMatchResult Table](#))
- ImportedComputerMatchResult table (see [ImportedComputerMatchResult Table](#))
- ImportedSoftwareBundleInstallerEvidence table (see [ImportedSoftwareBundleInstallerEvidence Table](#))
- ImportedVirtualMachineMatchResult table (see [ImportedVirtualMachineMatchResult Table](#))
- VirtualMachineMatchResult table (see [VirtualMachineMatchResult Table](#))

ComplianceComputerMatchResult Table

The ComplianceComputerMatchResult table stores the results of performing matching between ImportedComputers and ComplianceComputers.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 667: Database columns for ComplianceComputerMatchResult table

Database Column	Details
ComplianceConnectionID	Type: integer. Key The identifier for a data source connection in the ComplianceConnection table that supplied the ImportedComputer.
ExternalID	Type: big integer. Key The identifier used in the source connection for the ImportedComputer.
ComplianceComputerID	Type: integer. Key Identifier of the computer in the ComplianceComputer table that this ImportedComputer links to.
MatchingRule	Type: text (max 128 characters) The matching rule which determined the match between this ImportedComputer and ComplianceComputer.

ImportedComputerMatchResult Table

The ImportedComputerMatchResult table stores the results of performing matching between ImportedComputers.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 668: Database columns for ImportedComputerMatchResult table

Database Column	Details
PrimaryCompliance ConnectionID	Type: integer. Key The identifier for a data source connection in the ComplianceConnection table that supplied the primary ImportedComputer.
PrimaryExternalID	Type: big integer. Key The identifier used in the source connection for the primary ImportedComputer.
MatchedCompliance ConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table that supplied the matched ImportedComputer.
MatchedExternalID	Type: big integer. Key. Nullable The identifier used in the source connection for the matched ImportedComputer.
MatchingRule	Type: text (max 128 characters) The matching rule which determined the match between these ImportedComputers.

ImportedSoftwareBundleInstallerEvidence Table

The ImportedSoftwareBundleInstallerEvidence table holds software bundle to installer evidence information retrieved from the source connections.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 669: Database columns for ImportedSoftwareBundleInstallerEvidence table

Database Column	Details
ComplianceConnectionID	Type: integer. Key. Nullable The identifier for a data source connection in the ComplianceConnection table.
BundleName	Type: text (max 256 characters). Key. Nullable Bundle name
BundlePublisher	Type: text (max 64 characters). Key. Nullable Bundle’s publisher
EvidenceDisplayName	Type: text (max 256 characters). Key. Nullable The version of the software as reported by the installer evidence.
EvidenceVersion	Type: text (max 72 characters). Key. Nullable Identifier for the type of installer evidence.
EvidencePublisher	Type: text (max 200 characters). Key. Nullable The publisher of the software as reported by the installer evidence.
Supplementary	Type: boolean Whether this installer evidence on this bundle is supplementary (counted for consumption) or not.
MeasuredForCompliance	Type: boolean Whether this installer evidence on this bundle is measured for compliance breaches.
ProductRatio	Type: integer If this installer evidence is supplementary on the bundle, the number of entitlements consumed related to the entitlements consumed for the parent product.

Database Column	Details
ParentProductRatio	<p><i>Type:</i> integer</p> <p>If this installer evidence is supplementary on the bundle, the number of entitlements consumed related to the entitlements consumed for the supplementary product.</p>
DowngradeEnabled	<p><i>Type:</i> boolean</p> <p>If this field is <code>True</code>, this bundle can cover previous releases, or lower editions, of applications linked to this license. If this field is <code>False</code> (the default), there is no downgrade right conferred by this license.</p>
DowngradeToVersion	<p><i>Type:</i> boolean</p> <p>If this field is <code>True</code>, the bundle covers previous releases (with the same edition) of the primary application. If this field is <code>False</code> (the default), earlier versions of the primary application are not covered by downgrade rights.</p>
DowngradeToVersionID	<p><i>Type:</i> integer. Nullable</p> <p>If the previous field is <code>True</code> and the value of this field is <code>NULL</code>, downgrade rights cover all earlier releases (with the same edition) of the primary application. If not <code>NULL</code>, downgrade rights cover all versions of the primary application down to and including this version. Foreign key to the <code>SoftwareTitleVersion</code> table.</p>
DowngradeToEdition	<p><i>Type:</i> boolean</p> <p>If this field is <code>True</code>, the license covers lower editions (with the same version) of the primary application. If this field is <code>False</code> (the default), lower editions of the primary application are not covered by downgrade rights.</p>
DowngradeToEditionID	<p><i>Type:</i> integer. Nullable</p> <p>If the previous field is <code>True</code> and the value of this field is <code>NULL</code>, downgrade rights cover all lower editions (with the same version) of the primary application. If not <code>NULL</code>, downgrade rights cover all editions of the primary application down to and including this edition. Foreign key to the <code>SoftwareTitleEdition</code> table.</p>
UpgradeEnabled	<p><i>Type:</i> boolean</p> <p>If this field is <code>True</code>, the license can cover future releases (with the same edition) of the primary application. If this bit is <code>False</code> (the default), there is no upgrade right conferred by this license.</p>
UpgradeToVersion	<p><i>Type:</i> boolean</p> <p>If this field is <code>True</code>, the license covers later releases (with the same edition) of the primary application. If this field is <code>False</code> (the default), later versions of the primary application are not covered by upgrade rights.</p>

Database Column	Details
UpgradeToVersionID	<p><i>Type:</i> integer. Nullable</p> <p>If the previous field is True and the value of this field is NULL, upgrade rights cover all later version (with the same edition) of the primary application. If not NULL, upgrade rights cover all versions of the primary application up to and including this version. Foreign key to the SoftwareTitleEdition table.</p>
UpgradeUntil	<p><i>Type:</i> boolean</p> <p>If this bit is 1, the upgrade right covers future releases of applications that get linked to this license, provided that the release date of each version is before (or on) a specified date. If this bit is zero (the default), the upgrade right is not date limited.</p>
UpgradeUntilDate	<p><i>Type:</i> datetime. Nullable</p> <p>If this field is set, only applications released before this date are covered by upgrade rights.</p>

ImportedVirtualMachineMatchResult Table

The ImportedVirtualMachineMatchResult table stores the results of performing matching between ImportedVirtualMachines.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 670: Database columns for ImportedVirtualMachineMatchResult table

Database Column	Details
PrimaryCompliance ConnectionID	<i>Type:</i> integer. Key The identifier for a data source connection in the ComplianceConnection table that supplied the primary ImportedVirtualMachine.
PrimaryVMComputerID	<i>Type:</i> big integer. Key The identifier used in the source connection for the primary ImportedVirtualMachine.
PrimaryHostComputerID	<i>Type:</i> big integer. Key The identifier used in the source connection for the primary host ImportedVirtualMachine.
MatchedCompliance ConnectionID	<i>Type:</i> integer. Key The identifier for a data source connection in the ComplianceConnection table that supplied the matched ImportedVirtualMachine.
MatchedVMComputerID	<i>Type:</i> big integer. Key The identifier used in the source connection for the matched ImportedVirtualMachine.
MatchedHostComputerID	<i>Type:</i> big integer. Key The identifier used in the source connection for the matched host ImportedVirtualMachine.
MatchingRule	<i>Type:</i> text (max 128 characters) The matching rule which determined the match between these ImportedVirtualMachines.
NeedsCreation	<i>Type:</i> boolean Whether this ImportedVirtualMachine is awaiting creation as a VirtualMachine or not.

VirtualMachineMatchResult Table

The VirtualMachineMatchResult table stores the results of performing matching between ImportedVirtualMachines and VirtualMachines.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 671: Database columns for VirtualMachineMatchResult table

Database Column	Details
ComplianceConnectionID	Type: integer. Key The identifier for a data source connection in the ComplianceConnection table that supplied the ImportedVirtualMachine.
VMComputerID	Type: big integer. Key The identifier used in the source connection for the ImportedVirtualMachine.
HostComputerID	Type: big integer. Key The identifier used in the source connection for the host of the ImportedVirtualMachine.
VirtualMachineID	Type: integer. Key Identifier of the virtual machine in the VirtualMachine table that this ImportedVirtualMachine links to.
MatchingRule	Type: text (max 128 characters) The matching rule which determined the match between these VirtualMachines.

3

Inventory Database Schema

This chapter describes the schema for the FlexNet Manager Suite database that collects inventory uploaded by the FlexNet inventory agent, either when installed on 'adopted' devices, or when executing a remote, zero-touch inventory.

This inventory data undergoes some rationalization within this schema. The import of the resulting clean inventory data from this database to the compliance database is the work of the Compliance Reader, making use of another intermediate schema (see [Compliance Reader Database Schema](#)).

Information Structure

The following information is provided about database tables. Items appear only when relevant to the database column, and are suppressed where they do not apply. Two of these items (shown bold) are columns in the following pages, and the remainder are displayed within the **Details**.

Item	Comment
Database Column	The name of the column in the SQL table.
<i>Type</i>	The data type of the contents of the database column.
Size	For types that have a maximum capacity, the upper limit is provided in parentheses.
Key	The word "Key" appears when a column is a unique key field within the table. It is possible for several database columns to be part of the key, so that this indicator may appear for several columns in a table.
Generated ID	This indicates that a numeric ID is assigned by the database.
Nullable	If this indicator is present, the database column permits nulls.
Computed	This indicator appears for columns that are automatically computed by the database.
Default	If a column has a default value declared in the schema, this is specified at the end of the first set of details for the column.
Details	Describes the data stored in the database column, including many of the indicators described above.

AD Tables

The complete set of database tables documented here includes:

- ADComputer table (see [ADComputer Table](#))
- ADEternalMember table (see [ADEternalMember Table](#))
- ADSDOU table (see [ADSDOU Table](#))
- ADUser table (see [ADUser Table](#))

ADComputer Table

The ADComputer table is populated with data from Active Directory in preparation for an Active Directory reconciliation.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 672: Database columns for ADComputer table

Database Column	Details
DomainID	Type: integer. Key OrganizationID of the domain in which the computer resides.
ComputerCN	Type: text (max 64 characters). Key The computer's common name.
ComputerOURDN	Type: text (max 384 characters). Key The relative distinguished name of the organizational unit or container holding this computer.
GUID	Type: binary (max 16 bytes). Key The objectGUID of the Active Directory object that represents this computer, if known.
SID	Type: text (max 256 characters). Nullable The computer's SID.

ADExternalMember Table

The ADExternalMember table stores cross domain Active Directory objects.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 673: Database columns for ADExternalMember table

Database Column	Details
GroupID	Type: integer. Key The GroupID the external member belongs to.
ExternalMemberSID	Type: text (max 256 characters). Key The external member SID.

ADSDOU Table

The ADSDOU table is populated with domain, and organizational unit data from Active Directory in preparation for an Active Directory reconciliation.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 674: Database columns for ADSDOU table

Database Column	Details
DomainID	Type: integer. Key The domain in which this object resides.
RDN	Type: text (max 400 characters). Key The relative distinguished name of this object.
GUID	Type: binary (max 16 bytes). Key The ObjectGUID of this Active Directory object.
BlockInheritance	Type: boolean True (1) if package allocations should not be inherited from parent OUs or Domain, unless no-override is set for the Allocation (in the policy group membership mode).

ADUser Table

The ADUser table contains is populated with data from Active Directory in preparation for an Active Directory reconciliation. It is a temporary table.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 675: Database columns for ADUser table

Database Column	Details
DomainID	Type: integer. Key The domain in which this user resides.
UserCN	Type: text (max 64 characters). Key The user's common name.
UserOURDN	Type: text (max 384 characters). Key The relative distinguished name of the organizational unit or container holding this user.
GUID	Type: binary (max 16 bytes). Key. Nullable The Active Directory GUID of this user.
SAMAccountName	Type: text (max 20 characters). Nullable The user's logon name used to support clients and servers from versions of Windows prior to Windows 2000.
Sid	Type: text (max 512 characters). Nullable User's Sid

Allocation Tables

The complete set of database tables documented here includes:

- AllocationDetails table (see [AllocationDetails Table](#))
- InstallationPostponement table (see [InstallationPostponement Table](#))
- PackageAllocation table (see [PackageAllocation Table](#))
- PackageApplies table (see [PackageApplies Table](#))
- Policy table (see [Policy Table](#))
- PolicyApplies table (see [PolicyApplies Table](#))

AllocationDetails Table

The AllocationDetails table contains various details that, when taken together, describe the rules under which a particular software policy (allocation) should be applied. One row is created in this table for each distinct set of values, and these collected details may apply to many packages and to many users or computers.

Table 676: Database columns for AllocationDetails table

Database Column	Details
AllocationDetailsID	<i>Type:</i> integer. Key. Generated ID Auto-generated unique identifier
Action	<i>Type:</i> text (max 16 characters). Key. Nullable An action that indicates whether the package is mandatory or optional for the user or computer. Possible values are: <ul style="list-style-type: none"> install (for mandatory installations) choose (for optional installations) alwaysupdate (for installations that are optional, but with updates to existing installations of the same package being mandatory).
EffectiveFrom	<i>Type:</i> datetime. Key. Nullable Date and time at which the policy becomes effective. Prior to this date and time, the package will not be installed.
EffectiveFromIsLocal	<i>Type:</i> boolean. Key. Nullable Indicates whether the date and time in the EffectiveFrom field is local time on the managed device, or UTC time. The possible values are zero for UTC time and one for local time.
EffectiveUntil	<i>Type:</i> datetime. Key. Nullable Date and time at which the policy ceases to be effective. After this date and time, the package will not be installed. The time zone used is the same as for EffectiveFrom.
Wake	<i>Type:</i> boolean. Key. Nullable Indicates whether FlexNet Manager Suite should use the Wake on LAN feature to wake a managed device when the package is to be installed. For more information on this feature, see the documentation.
PostponeNoLaterThan	<i>Type:</i> datetime. Key. Nullable Latest absolute time until which an end-user may postpone installation of this package. Only mandatory package installations can be postponed (that is, packages for which Action is either install or alwaysupdate).

Database Column	Details
PostponeNoLaterThanIsLocal	<p><i>Type:</i> boolean. Key</p> <p>Indicates whether PostponeNoLaterThan should be interpreted as a local time on each managed device (1), or as a UTC time (0). The value of this field should be ignored if PostponeNoLaterThan is NULL.</p>
PostponePeriod	<p><i>Type:</i> integer. Key. Nullable</p> <p>Number of seconds for which package installations may be postponed by an end-user after this policy first applies. Only mandatory package installations can be postponed (that is, packages for which Action is either install or alwaysupdate).</p>
PostponeLatest	<p><i>Type:</i> boolean. Key</p> <p>Indicates whether package installation may be postponed to the latest (1) or earliest (0) date indicated by the PostponeNoLaterThan and PostponePeriod fields if both of those fields are set. The value of this field should be ignored if either PostponeNoLaterThan or PostponePeriod are NULL.</p>
PostponeOKForLowBandwidth	<p><i>Type:</i> boolean. Key</p> <p>Indicates whether a valid reason for postponing installation of this package is because the managed device is connected to a distribution location via a "slow" network connection (as determined by the NetworkHighSpeed preference on the managed device).</p>
PostponeOKForAnyReason	<p><i>Type:</i> boolean. Key</p> <p>Indicates whether installation of this package can be postponed for any reason at the discretion of the end-user on the managed device on which this package is to be installed.</p>
Exclusive	<p><i>Type:</i> boolean. Key</p> <p>Whether (1) or not (0, default) to uninstall the package when it is removed from policy. This value is retrieved from Active Directory.</p>
Removable	<p><i>Type:</i> boolean. Key</p> <p>Whether (1) or not (0, default) this mandatory package can be removed by the user once it has initially been installed. This value is retrieved from Active Directory.</p>

InstallationPostponement Table

The `InstallationPostponement` table stores the resultant set of policy (RSOP) for all users and computers. It represents what packages each user and computer should have installed, whereas `Installation` represents what they actually have installed.

Table 677: Database columns for `InstallationPostponement` table

Database Column	Details
<code>TargetTypeID</code>	<p><i>Type:</i> integer. Key</p> <p>The target type of the package. Possible values are:</p> <ul style="list-style-type: none"> • 1 (computer policy) • 2 (user policy) <p>This is a foreign key into the <code>TargetType</code> table.</p>
<code>TargetID</code>	<p><i>Type:</i> integer. Key</p> <p>The user or computer targeted by the package. This is a foreign key into the <code>User</code> or <code>Computer</code> table.</p>
<code>PackagePathID</code>	<p><i>Type:</i> integer. Key</p> <p>The package applied by the <code>Policy</code>.</p>
<code>PolicyGUID</code>	<p><i>Type:</i> binary (max 16 bytes). Key</p> <p>The GUID of the group policy in Active Directory that records whether the package is targeted to the user or computer.</p>
<code>AllocationDetailsID</code>	<p><i>Type:</i> integer. Key</p> <p>The details indicating how and when this package should be installed. This is a foreign key into the <code>AllocationDetails</code> table.</p>

Database Column	Details
PostponePeriodStart	<p><i>Type:</i> datetime. Nullable</p> <p>UTC time at which any postponement period for this policy started. The postponement period for installation of this package (that is, the period during which end-users may postpone installation of this package) will end at this time plus any period specified by PostponePeriod. After the postponement period ends, the installation agent will attempt to force the package to be installed. This field is NULL until and unless an installation event log is received from the managed device indicating that the installation of the package has in fact been postponed. If PostponePeriod is NULL, the value of PostponePeriodStart represents the time at which the installation of this package was first postponed.</p> <p>An example SQL query to determine the expected (UTC) time at which the postponement period for this package will expire can be written as shown below. Note that this query will convert any local time PostponeNoLaterThan value to UTC using the timezone configured on the SQL Server.</p> <pre> SELECT *, CASE WHEN PostponePeriod IS NULL OR PostponePeriodStart IS NULL OR (PostponeLatest = 1 AND PostponePeriodEndUTC <= PostponeNoLaterThanUTC) OR (PostponeLatest = 0 AND PostponePeriodEndUTC >= PostponeNoLaterThanUTC) THEN PostponeNoLaterThanUTC ELSE PostponePeriodEndUTC END AS PostponeLatestUTC FROM (SELECT *, CASE PostponeNoLaterThanIsLocal WHEN 1 THEN DATEADD(s, DATEDIFF(s, GETDATE(), GETUTCDATE()), PostponeNoLaterThan) ELSE PostponeNoLaterThan END AS PostponeNoLaterThanUTC , DATEADD(s, PostponePeriod, PostponePeriodStart) AS PostponePeriodEndUTC FROM Targetedpackage) tp </pre>

PackageAllocation Table

A PackageAllocation row exists for every PackagePath which has been approved to a Policy.

Table 678: Database columns for PackageAllocation table

Database Column	Details
PolicyGUID	<i>Type:</i> binary (max 16 bytes). Key The Policy to which the PackagePath has been approved. This is a foreign key into the Policy table.
PackagePathID	<i>Type:</i> integer. Key The PackagePath which has been approved. This is a foreign key into the PackagePath table.
AccessGroupID	<i>Type:</i> integer. Key. Nullable The Group to which the package applies. This group will have a NULL GroupCN it's an Access Control List (ACL) group. This is a foreign key into the Group table.
TargetTypeID	<i>Type:</i> integer. Key The target type of the package. Possible values are: <ul style="list-style-type: none"> • 1 = computer policy • 2 = user policy. This is a foreign key into the TargetType table.
Precedence	<i>Type:</i> integer The order of application of this package within this policy. The default value is 0.
AllocationDetailsID	<i>Type:</i> integer. Key The details indicating how and when this package should be installed. This is a foreign key into the AllocationDetails table.

PackageApplies Table

The PackageApplies table stores the resultant set of policy (RSOP) for all users and computers. It represents what packages each user and computer should have installed, whereas Installation represents what they actually have installed.

Table 679: Database columns for PackageApplies table

Database Column	Details
TargetTypeID	<p><i>Type:</i> integer. Key</p> <p>The target type of the package. Possible values are:</p> <ul style="list-style-type: none"> • 1 (computer policy) • 2 (user policy) <p>This is a foreign key into the TargetType table.</p>
TargetOID	<p><i>Type:</i> integer. Key</p> <p>The organizational unit of the user or computer targeted by the package. This is a foreign key into the Organization table. This column is included in the table for clustering purposes. The value of TargetOID could be determined by looking up the User or Computer table.</p>
TargetID	<p><i>Type:</i> integer. Key</p> <p>The user or computer targeted by the package. This is a foreign key into the User or Computer table.</p>
PackagePathID	<p><i>Type:</i> integer. Key</p> <p>The package applied by the Policy.</p>
PolicyGUID	<p><i>Type:</i> binary (max 16 bytes). Key</p> <p>The GUID of the group policy in Active Directory that records whether the package is targeted to the user or computer.</p>
AllocationDetailsID	<p><i>Type:</i> integer. Key</p> <p>The details indicating how and when this package should be installed. This is a foreign key into the AllocationDetails table.</p>
Precedence	<p><i>Type:</i> integer</p> <p>The order of application of this policy for this target device, defaults to 0.</p>
PolicyVersion	<p><i>Type:</i> integer</p> <p>Policy version number from the underlying directory service.</p>

Policy Table

The Policy table correlates the GUID of an Active Directory policy with its display name. This is used in reporting and in .npl files.

Table 680: Database columns for Policy table

Database Column	Details
GUID	<i>Type:</i> binary (max 16 bytes). Key The GUID of the policy in Active Directory.
DomainID	<i>Type:</i> integer. Key. Nullable Organization id of the domain in which the policy resides.
DisplayName	<i>Type:</i> text (max 512 characters). Key. Nullable The display name for the policy, for use in .npl files.
AccessGroupID	<i>Type:</i> integer. Key. Nullable The Access Control List for the policy, represented as an anonymous Group.
EnabledForUsers	<i>Type:</i> boolean This policy has been enabled for software management for users.
EnabledForComputers	<i>Type:</i> boolean This policy has been enabled for software management for computers.

PolicyApplies Table

The PolicyApplies table stores the identities of the principals to whom each policy applies, whether or not any packages or schedules apply.

Table 681: Database columns for PolicyApplies table

Database Column	Details
DomainID	Type: integer. Key Organizational id of the domain in which the policy resides.
TargetOUID	Type: integer. Key The OUID of the user or computer to whom the policy applies. Foreign key (unchecked) into the Organization table.
TargetTypeID	Type: integer. Key The target type of the package. Possible values are 1 (computer policy), 2 (user policy). This is a foreign key into the TargetType table.
TargetID	Type: integer. Key The user or computer to whom the policy applies. Foreign key (unchecked) into the User or Computer table.
GUID	Type: binary (max 16 bytes). Key The GUID of the policy in Active Directory.

ClientAccess Tables

The complete set of database tables documented here includes:

- ClientAccessDetail table (see [ClientAccessDetail Table](#))
- ClientAccessOccurrence table (see [ClientAccessOccurrence Table](#))
- ClientAccessingDevice table (see [ClientAccessingDevice Table](#))
- ClientAccessingUser table (see [ClientAccessingUser Table](#))
- UALSoftwareDetail table (see [UALSoftwareDetail Table](#))

ClientAccessDetail Table

Records the entries for the client accesses obtained from the User access logging.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 682: Database columns for ClientAccessDetail table

Database Column	Details
ClientAccessDetailID	Type: big integer. Key. Generated ID Auto-generated identity number.
ClientAccessingDeviceID	Type: integer. Key. Nullable The client access device related record. This is a foreign key into the ClientAccessingDevice table.
ClientAccessingUserID	Type: integer. Key. Nullable The client access user related record. This is a foreign key into the ClientAccessingUser table.
ServerComputerID	Type: integer. Key The record of the server from which the inventory is obtained. This is a foreign key into the Computer table.
UALSoftwareDetailID	Type: integer. Key The client access software related record. This is a foreign key into the UALSoftwareDetail table.

ClientAccessOccurrence Table

Records the entries for the software access occurrence in the User access logging.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 683: Database columns for ClientAccessOccurrence table

Database Column	Details
ClientAccessDetailID	Type: big integer. Key Client access related record. This is a foreign key into the ClientAccessingDetails table.
AccessDate	Type: datetime. Nullable Date and time at which access was made to server.
InventoryDate	Type: datetime. Key Date and time at which this inventory occurrence was recorded.
LicenseDate	Type: datetime. Key Date used for licensing purposes.
AccessCount	Type: integer Number of times access was made to server.

ClientAccessingDevice Table

Records the entries for the client accessing devices obtained from the User access logging.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 684: Database columns for ClientAccessingDevice table

Database Column	Details
ClientAccessingDeviceID	Type: integer. Key. Generated ID Auto-generated identity number.
IPAddress	Type: text (max 256 characters). Key. Nullable IP Address of the client accessing device.
ComputerName	Type: text (max 256 characters). Key. Nullable Computer name of the client accessing device.

ClientAccessingUser Table

Records the entries for the client accessing users obtained from the User access logging.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 685: Database columns for ClientAccessingUser table

Database Column	Details
ClientAccessingUserID	Type: integer. Key. Generated ID Auto-generated identity number.
UserName	Type: text (max 256 characters). Key User name of the accessing user.
DomainName	Type: text (max 100 characters). Key. Nullable Domain name of the accessing user.

UALSoftwareDetail Table

Records the entries for the softwares registered in the User access logging.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 686: Database columns for UALSoftwareDetail table

Database Column	Details
UALSoftwareDetailID	Type: integer. Key. Generated ID Auto-generated identity number.
ProductName	Type: text (max 256 characters). Key The name of the instalaltion product. This may include version and edition too.
RoleName	Type: text (max 256 characters). Key. Nullable The URL role name. This is used when retrieve data using UAL.
RoleGUID	Type: unique identifier. Key. Nullable The URL role GUID. This is used when retrieve data using UAL
ClientAccessSource	Type: text (max 100 characters). Key Referencing to the client access source type.

DirectoryObjects Tables

The complete set of database tables documented here includes:

- Computer table (see [Computer Table](#))
- OperatingSystem table (see [OperatingSystem Table](#))
- User table (see [User Table](#))

Computer Table

The Computer table contains all computers that have ever reported information or have been targeted by policy in a FlexNet Manager Suite environment.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 687: Database columns for Computer table

Database Column	Details
ComputerID	Type: integer. Key. Generated ID The ID for the computer. This is automatically generated by SQL Server.
ComputerOUID	Type: integer. Key The organizational unit of the computer in Active Directory. In an SMS organization, this is set to the OUID of the unknown OU.
ComputerCN	Type: text (max 64 characters). Key The computer's common name. In an Active Directory environment this is the common name attribute of the computer's distinguished name. This is the same as the SAM account name.
OperatingSystemID	Type: integer. Nullable The operating system of the computer, if known. This allows efficient determination of the operating system breakdown of computers in an organization.
GUID	Type: binary (max 16 bytes). Key. Nullable The objectGUID of the Active Directory object that represents this computer, if known.

OperatingSystem Table

This table stores the information about different types of OS available on the network devices

Table 688: Database columns for OperatingSystem table

Database Column	Details
OperatingSystemID	<i>Type:</i> integer. Key. Generated ID Auto-generated identity number
OperatingSystemName	<i>Type:</i> text (max 128 characters). Key Name of operating system
Category	<i>Type:</i> integer. Nullable Reference to operating system category

User Table

The User table contains all of the users that have ever reported information in a FlexNet Manager Suite environment. A row has been added to cater for installations that occur from computer policy. This row has a UserID set to 1 and a UserCN of SYSTEM, and belongs to Organization 1, which is the universal Domain.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 689: Database columns for User table

Database Column	Details
UserID	Type: integer. Key. Generated ID The ID for the user. This is automatically generated by SQL Server.
UserOUID	Type: integer. Key The organizational unit of the user in Active Directory. This is a foreign key into the Organization table. In an SMS environment, this is always set to the unknown OU.
UserCN	Type: text (max 64 characters). Key The user’s common name. In an Active Directory environment this is the common name attribute of the user’s distinguished name.
GUID	Type: binary (max 16 bytes). Key. Nullable The objectGUID of the Active Directory object that represents this user, if known.
SAMAccountName	Type: text (max 20 characters). Key. Nullable The SAM account name used to uniquely identify this user in event logs and user inventories.

Directory Tables

The complete set of database tables documented here includes:

- Domain table (see [Domain Table](#))
- DomainConfiguration table (see [DomainConfiguration Table](#))
- Group table (see [Group Table](#))
- Member table (see [Member Table](#))
- Organization table (see [Organization Table](#))
- TransitiveMember table (see [TransitiveMember Table](#))

Domain Table

The Domain table, in combination with the Organization table, contains data about all of the domains, and organizational units that have ever had users or computers report information in a FlexNet Manager Suite environment.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 690: Database columns for Domain table

Database Column	Details
OrganizationID	Type: integer. Key Organizational ID. This is a foreign key into the Organization table.
DN	Type: text (max 100 characters). Key. Nullable Fully qualified distinguished name.
DomainType	Type: text (max 4 characters). Key. Nullable The type of directory service running, for example AD, NT 4.
FlatName	Type: text (max 32 characters). Nullable The NT 4 domain name.
PreferredDomainController	Type: text (max 32 characters). Nullable Preferred domain controller to query.
PreferredDomain ControllerOnly	Type: boolean Whether (0) or not to fail over to alternate server if the preferred domain controller is not contactable.
ADReconcile	Type: boolean Whether (1) or not (0) to reconcile the FlexNet Manager Suite database with Active Directory.
ADLoadLatency	Type: integer If reconciling Active Directory with the FlexNet Manager Suite database, the length of time in minutes before the Active Directory data is refreshed in the FlexNet Manager Suite database. The default value is 60 minutes. A value of 0 means load the Active Directory data into the FlexNet Manager Suite database at each reconciliation. Set this to a high value to minimize network traffic for domains for delayed reconciliation is acceptable.
MergePolicies	Type: boolean Whether (1) or not (0) to generate merged policies.

Database Column	Details
LastADReconcile	<p><i>Type:</i> datetime. Nullable</p> <p>The date and time of the last reconciliation of the FlexNet Manager Suite database with Active Directory.</p>
LastADReconcileStatus	<p><i>Type:</i> boolean</p> <p>This field is currently unused.</p>
LastADLoad	<p><i>Type:</i> datetime. Nullable</p> <p>The date and time of the last Active Directory load. A value of NULL indicates that Active Directory data should be loaded at the next reconcile operation.</p>
LastPolicyMerge	<p><i>Type:</i> datetime. Nullable</p> <p>The date and time of the last generation of merged policy.</p>
LastPolicyMergeStatus	<p><i>Type:</i> boolean</p> <p>This field is currently unused.</p>
DNReverse	<p><i>Type:</i> text (max 100 characters). Key. Nullable</p> <p>Fully qualified distinguished name, in reverse order (to improve sub-domain search performance).</p>

DomainConfiguration Table

The DomainConfiguration table contains configuration properties for the Domain table

Table 691: Database columns for DomainConfiguration table

Database Column	Details
DomainID	<i>Type:</i> integer. Key OrganizationID of the domain in which the entry resides.
Property	<i>Type:</i> text (max 32 characters). Key The name of the property.
Value	<i>Type:</i> text (max 256 characters). Nullable The value of the property.
DateValue	<i>Type:</i> datetime. Nullable The date and time value of the property.
LastUpdate	<i>Type:</i> datetime The date and time the property was last updated.

Group Table

Each Group identifies either a named group or an unnamed Access Control List (ACL). Each Group is associated with rows in the Member table.

Table 692: Database columns for Group table

Database Column	Details
GroupID	<i>Type:</i> integer. Key. Generated ID The ID for the group, automatically generated by SQL Server.
GUID	<i>Type:</i> binary (max 16 bytes). Key The Globally Unique Identifier for the group. In the case where this Group represents an Access Control List for a Policy or a PackageAllocation, the GUID is that of this object.
GroupCN	<i>Type:</i> text (max 128 characters). Key. Nullable The Common Name for the group. In the case where this Group represents an Access Control List for a Policy or a PackageAllocation, the GroupCN is NULL.
GroupOUID	<i>Type:</i> integer. Key A reference to the Organization to which the group belongs.
GroupType	<i>Type:</i> integer. Nullable The bitmask of flags defining the type of this Group.
SID	<i>Type:</i> text (max 256 characters). Nullable The security identifier of this Group.

Member Table

The Member table stores the membership lists for every group. Each Member details a User, Computer, Group, or Organization (only Policy ACL groups), and whether the specified item is excluded (only ACL groups), included (the default) or included mandatorily (cannot be excluded - used only for Organizations in Policy ACLs).

Table 693: Database columns for Member table

Database Column	Details
GroupID	<i>Type:</i> integer. Key The Group of which this is a Member.
TargetTypeID	<i>Type:</i> integer. Key The TargetType. Possible values are: <ul style="list-style-type: none">• 1 = Computer• 2 = User• 3 = Group• 8 = OrgUnit• 16 = Operator
TargetID	<i>Type:</i> integer. Key The ComputerID, UserID, GroupID or OrganizationID.
MemberMode	<i>Type:</i> integer The MemberMode is 0 for Exclude (regardless of any other memberships, the principals of this Target are excluded from this group), 1 for Include, and 2 for Always - NoOverride.

Organization Table

The `Organization` table contains data about organizational units used in a FlexNet Manager Suite environment.

 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 694: Database columns for `Organization` table

Database Column	Details
<code>OrganizationID</code>	<p>Type: integer. Key. Generated ID</p> <p>The ID for the organizational unit. (1 is used for “unknown OU” in the universal domain). This is automatically generated by SQL Server.</p>
<code>RDN</code>	<p>Type: text (max 400 characters). Key. Nullable</p> <p>The relative distinguished name of this organizational unit.</p>
<code>GUID</code>	<p>Type: binary (max 16 bytes). Key. Nullable</p> <p>The objectGUID of the Active Directory object that represents this organizational unit, if known.</p>
<code>DomainID</code>	<p>Type: integer. Key. Nullable</p> <p>OrganizationID of the domain in which the entry resides. For a domain, must be set to reference self.</p>
<code>RDNReverse</code>	<p>Type: text (max 400 characters). Key. Nullable</p> <p>The relative distinguished name of the computer, reversed for superior performance on sub-organization searching.</p>
<code>IsUnknown</code>	<p>Type: integer</p> <p>True (1) if the organizational unit cannot be resolved through Active Directory (for example, the unknown OU, which has a NULL RDN), false (0) otherwise (if the OU has a non-empty RDN).</p>
<code>IsDomain</code>	<p>Type: integer</p> <p>True (1) if the organizational unit is a domain (has an empty - not NULL - RDN), false (0) otherwise.</p>
<code>BlockInheritance</code>	<p>Type: boolean</p> <p>True (1) if package allocations should not be inherited from the parent Organization, unless <code>NoOverride</code> is set for the Policy. <code>NoOverride</code> is set using <code>MemberMode=2</code> (Always) on the Organization member in the Policy ACL group.</p>

TransitiveMember Table

The TransitiveMember table stores data similar to the Member table, but is populated only when needed, such as to assist in evaluating the rights of a particular user. The difference is that for each user, it contains the full list of groups in which they are members either directly or indirectly through membership in other groups.

Table 695: Database columns for TransitiveMember table

Database Column	Details
GroupID	Type: integer. Key The Group of which this is a Member.
TargetTypeID	Type: integer. Key The TargetType. Possible values are: <ul style="list-style-type: none">• 1 = Computer• 2 = User• 3 = Group• 8 = OrgUnit
TargetID	Type: integer. Key The ComputerID, UserID, GroupID or OrganizationID.
MemberMode	Type: integer The MemberMode is 0 for Exclude (regardless of any other memberships, the principals of this Target are excluded from this group), 1 for Include, and 2 for Always - NoOverride.

Distribution Tables

The complete set of database tables documented here includes:

- DistributedPackage table (see [DistributedPackage Table](#))
- DistributionGroup table (see [DistributionGroup Table](#))
- DistributionGroupMember table (see [DistributionGroupMember Table](#))
- DistributionServer table (see [DistributionServer Table](#))
- DistributionServerStatus table (see [DistributionServerStatus Table](#))
- DistributionServerType table (see [DistributionServerType Table](#))

DistributedPackage Table

The DistributedPackage table stores the status (both of current and pending distributions) of package distributions to distribution servers and distribution locations.

Table 696: Database columns for DistributedPackage table

Database Column	Details
DistributedPackageID	<i>Type:</i> integer. Key. Generated ID Auto-generated identity number
ServerUID	<i>Type:</i> binary (max 16 bytes). Key The distribution server or distribution location related to the status record. This is a foreign key into the DistributionServer table.
RequestedVersionID	<i>Type:</i> integer. Key. Nullable The id for the Requested PackageVersion.
RequestState	<i>Type:</i> text (max 16 characters). Nullable The state of a package that is pending distribution. The possible values are: <ul style="list-style-type: none"> empty (literal string) pending removing If the RequestState field contains a value other than the literal string empty, the RequestState overrides the ConfirmedState of the package.
RequestDate	<i>Type:</i> datetime. Nullable The date and time at which the package distribution began. Only used for distributions currently in progress.
ConfirmedVersionID	<i>Type:</i> integer. Key. Nullable The id for the Existing PackageVersion
ConfirmedState	<i>Type:</i> text (max 16 characters). Nullable The state of the package currently on the distribution server or distribution location. The possible values are: <ul style="list-style-type: none"> available unavailable If the RequestState field contains a value other than the literal string empty, then the RequestState overrides the ConfirmedState of the package.

Database Column	Details
ConfirmedDate	<i>Type:</i> datetime. Nullable The date and time that the current distribution status of a package was recorded.
ConfirmedReason	<i>Type:</i> text. Nullable The reason that package distribution failed. This is only specified in the case of a failure.

DistributionGroup Table

All defined distribution groups are stored in the DistributionGroup table.

Table 697: Database columns for DistributionGroup table

Database Column	Details
GroupUID	<i>Type:</i> binary (max 16 bytes). Key A unique identifier for this distribution group.
GroupName	<i>Type:</i> text (max 128 characters). Key The descriptive name assigned to this distribution group.

DistributionGroupMember Table

Any distribution servers and distribution locations assigned to distribution groups are stored in the DistributionGroupMember table.

Table 698: Database columns for DistributionGroupMember table

Database Column	Details
GroupUID	<i>Type:</i> binary (max 16 bytes). Key A unique identifier for this distribution group. This UID is a foreign key to the GroupUID in the DistributionGroup table.
MemberID	<i>Type:</i> binary (max 16 bytes). Key A unique identifier for the distribution server or distribution location that is a member of this group. This UID is a foreign key to the ServerUID in the DistributionServer table.
MemberType	<i>Type:</i> integer An identifier for the type of this distribution group member. This identifier is a foreign key to the TargetTypeID in the DistributionServerType table.

DistributionServer Table

The `DistributionServer` table stores all of the distribution servers and distribution locations in the FlexNet Manager Suite distribution hierarchy.

Table 699: Database columns for `DistributionServer` table

Database Column	Details
ServerUID	<i>Type:</i> binary (max 16 bytes). Key A unique identifier for the distribution server or distribution location. The core distribution server has a value of all zeroes.
DNSName	<i>Type:</i> text (max 128 characters). Nullable DNS name of the server
ServerType	<i>Type:</i> small integer The server type. The possible values are: <ul style="list-style-type: none"> • 0 for distribution location • 1 for distribution server
ServerName	<i>Type:</i> text (max 64 characters) The name of the distribution server or distribution location.
PrimaryParentUID	<i>Type:</i> binary (max 16 bytes). Key. Nullable The parent of the distribution server or distribution location. For the core distribution server, the <code>PrimaryParentUID</code> is NULL.
ConfigState	<i>Type:</i> text (max 20 characters). Nullable The state of configuration of the distribution server. This is only set for distribution servers (<code>ServerType</code> is 1). This can be one of the following values: <ul style="list-style-type: none"> • configure • failed • pending • NULL
LastConfigStart	<i>Type:</i> datetime. Nullable The date and time of the last configuration message sent to the distribution server. This is only set for distribution servers (<code>ServerType</code> is 1).

Database Column	Details
LastConfigJobId	<i>Type:</i> text (max 40 characters). Nullable The job identifier for the last configuration message sent to the distribution server. This is only set for distribution servers (ServerType is 1).
ConfigFailReason	<i>Type:</i> text. Nullable The reason for a configuration failure for the distribution server.
PolicyQuarantined	<i>Type:</i> boolean Boolean value indicating whether this distribution location is quarantined from receiving policy distributions.
TenantID	<i>Type:</i> small integer The Tenant ID this Distribution Server has been assigned to.

DistributionServerStatus Table

The `DistributionServerStatus` table stores status information for the distribution servers in the FlexNet Manager Suite distribution hierarchy.

Table 700: Database columns for `DistributionServerStatus` table

Database Column	Details
ServerUID	<i>Type:</i> binary (max 16 bytes). Key The distribution server related to the status record. This is a foreign key into the <code>DistributionServer</code> table.
ReportedDate	<i>Type:</i> datetime The date and time at which the distribution server last reported status information for this parameter.
Type	<i>Type:</i> text (max 32 characters). Key The type of the status parameter reported. Currently supported types are 'job' for jobs on the distribution server and 'logs' for log files awaiting upload from the distribution server.
Name	<i>Type:</i> text (max 64 characters). Key The name of the status parameter reported. This is an internal name for the parameter and is not intended for display.
Count	<i>Type:</i> integer The count of items for this status parameter currently awaiting processing by this distribution server.
DelayedCount	<i>Type:</i> integer The count of items for this status parameter that are older than a configurable time period that are currently awaiting processing by this distribution server. This will not necessarily have meaning for each status parameter.

DistributionServerType Table

The available distribution server types are defined in the DistributionServerType table.

Table 701: Database columns for DistributionServerType table

Database Column	Details
DistributionServerTypeID	<i>Type:</i> integer. Key An identifier for this distribution server type.
DistributionServerType Name	<i>Type:</i> text (max 256 characters). Key The descriptive name assigned to this distribution server type.

IM_Right Tables

The complete set of database tables documented here includes:

- Right table (see [Right Table](#))

Right Table

Each action by FlexNet Manager Suite requires one or more Rights to perform an ActionClass over a given Resource.

Table 702: Database columns for Right table

Database Column	Details
RightID	<i>Type:</i> integer. Key. Generated ID Auto-generated identity number.
GroupID	<i>Type:</i> integer. Key The group to whom the Right is granted or denied (deny always takes precedence!).
ResourceID	<i>Type:</i> integer. Key The Resource to which the Right applies.
ActionClassID	<i>Type:</i> integer. Key The action class which applies (read or modify).
Denied	<i>Type:</i> boolean When TRUE (1), indicates that the specified right is denied.
Value	<i>Type:</i> integer. Key. Nullable The integer id of an item which depends on the PartitionType of the associated resource. In FlexNet Manager Suite 7.5, only Organization partitioning (PartitionTypeID = 1) is used, so the Value field contains an OrganizationID. The Right applies to this organization and all child organizations, unless denied by another Right.

Installation Tables

The complete set of database tables documented here includes:

- Installation table (see [Installation Table](#))
- InstallationHistory table (see [InstallationHistory Table](#))
- Reason table (see [Reason Table](#))

Installation Table

The `Installation` table contains the latest installation status of each package for each user and computer. Success or failure of installations is recorded. When a package is uninstalled, its installation status record is removed from the table. When an installation is successful, the successful installation status record replaces any earlier failure status records. Once an installation is successful, the `Installation` table retains the successful installation status record even if there are subsequent failed installation attempts. If there have been any subsequent failed installations, the latest of these failure records is also be retained. For example, if an installation fails, and then succeeds on a subsequent attempt, only the successful status is recorded. If an installation succeeds, but a later installation attempt fails, then both the success and failure status records are stored. All other installations are added to the `InstallationHistory` table as new status information is generated.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 703: Database columns for `Installation` table

Database Column	Details
<code>ComputerID</code>	<p><i>Type:</i> integer. Key</p> <p>The computer that the installation event occurred on. This is a foreign key into the <code>Computer</code> table.</p>
<code>UserID</code>	<p><i>Type:</i> integer. Key</p> <p>The user associated with the installation event. This is a foreign key into the <code>User</code> table. If the <code>UserID</code> is 1 (system user), then the installation event occurred as part of computer policy. Otherwise, the installation event occurred as part of user policy.</p>
<code>PackageVersionID</code>	<p><i>Type:</i> integer. Key</p> <p>Package version that was installed</p>
<code>OrganizationID</code>	<p><i>Type:</i> integer. Key</p> <p>The organizational unit of the user or computer associated with the installation event. This is a foreign key into the <code>Organization</code> table. This column is included in the table for clustering purposes. The value of <code>OUID</code> could be determined by looking up the <code>User</code> or <code>Computer</code> table. If the <code>UserID</code> is 1 (system user), <code>OUID</code> represents the organizational unit of the computer that the installation event occurred on. Otherwise, it represents the organizational unit of the user associated with the installation event.</p>
<code>Action</code>	<p><i>Type:</i> text (max 10 characters)</p> <p>The action performed on the package. This is currently set to "install". In future, "upgrade", "update" and "selfheal" may be added.</p>

Database Column	Details
Reported	<i>Type:</i> datetime. Nullable The date and time that the installation event occurred.
Received	<i>Type:</i> datetime. Nullable The date and time that the installation status event was received into the database.
FailReasonID	<i>Type:</i> integer. Nullable A reference to the reason for the installation failure. If the installation succeeded then this value is NULL.
Result	<i>Type:</i> text (max 16 characters). Nullable The result of the package installation. Possible values are success or failure.

InstallationHistory Table

The action performed on the package, normally “install” or “uninstall”. In the event that installation event logs were lost, entries may be reconstructed here from data in inventory (cache tracking). Such entries may be less reliable (in particular the recorded date will be the date of the inventory) and will have one of the following Action values:

- “inv insert”
- “inv delete”
- “inv update”



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 704: Database columns for InstallationHistory table

Database Column	Details
ComputerID	Type: integer. Key The computer that the installation event occurred on. This is a foreign key into the Computer table.
UserID	Type: integer. Key The user associated with the installation event. This is a foreign key into the User table. If the UserID is 1 then the installation event occurred as part of computer policy. Otherwise, the installation event occurred as part of user policy.
PackageVersionID	Type: integer. Key The id for the PackageVersion installed
Reported	Type: datetime. Key The date and time that the installation event occurred.
Action	Type: text (max 10 characters) The action performed on the package. This value can be either, install or uninstall.
Received	Type: datetime. Nullable The date and time that the installation status event was received into the database.
FailReasonID	Type: integer. Nullable A reference to the reason for the installation failure. If the installation succeeded then this value is NULL.

Database Column	Details
Result	Type: text (max 16 characters). Nullable The result of the package installation. Possible values are either success or failure.

Reason Table

Stores extended text uploaded from logs to describe operational failures.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 705: Database columns for Reason table

Database Column	Details
ReasonID	<i>Type:</i> integer. Key. Generated ID The ID for the Reason. This is automatically generated by SQL Server.
ReasonHash	<i>Type:</i> integer. Key The checksum of the ReasonText, calculated by SQL Server.
ReasonText	<i>Type:</i> text The Reason text.

Inventory Tables

The complete set of database tables documented here includes:

- HardwareClass table (see [HardwareClass Table](#))
- HardwareObject table (see [HardwareObject Table](#))
- HardwareProperty table (see [HardwareProperty Table](#))
- HardwareValue table (see [HardwareValue Table](#))
- InventoryReport table (see [InventoryReport Table](#))
- ServiceComponent table (see [ServiceComponent Table](#))
- ServiceProvider table (see [ServiceProvider Table](#))
- ServiceProviderApplicationOracle table (see [ServiceProviderApplicationOracle Table](#))
- ServiceProviderApplicationUsagePerMonth table (see [ServiceProviderApplicationUsagePerMonth Table](#))
- ServiceProviderApplicationUsageType table (see [ServiceProviderApplicationUsageType Table](#))
- ServiceProviderApplicationUserOracle table (see [ServiceProviderApplicationUserOracle Table](#))
- ServiceProviderComponent table (see [ServiceProviderComponent Table](#))
- ServiceProviderComponentProperty table (see [ServiceProviderComponentProperty Table](#))
- ServiceProviderComponentValue table (see [ServiceProviderComponentValue Table](#))
- ServiceProviderName table (see [ServiceProviderName Table](#))
- ServiceProviderProperty table (see [ServiceProviderProperty Table](#))
- ServiceProviderType table (see [ServiceProviderType Table](#))
- ServiceProviderValue table (see [ServiceProviderValue Table](#))
- ServiceUser table (see [ServiceUser Table](#))
- ServiceUserOracle table (see [ServiceUserOracle Table](#))
- SoftwareDetails table (see [SoftwareDetails Table](#))
- SoftwareFile table (see [SoftwareFile Table](#))
- SoftwareFileName table (see [SoftwareFileName Table](#))
- SoftwareFilePath table (see [SoftwareFilePath Table](#))
- SoftwareFileProperty table (see [SoftwareFileProperty Table](#))
- SoftwareIsoTagEntity table (see [SoftwareIsoTagEntity Table](#))
- SoftwareIsoTagFile table (see [SoftwareIsoTagFile Table](#))

- SoftwareIsoTagSoftwareVersion table (see [SoftwareIsoTagSoftwareVersion Table](#))
- SoftwareIsoTagUnique table (see [SoftwareIsoTagUnique Table](#))
- SoftwareOccurrence table (see [SoftwareOccurrence Table](#))
- SoftwareOccurrenceSoftwareIsoTagFile table (see [SoftwareOccurrenceSoftwareIsoTagFile Table](#))
- SoftwareProperty table (see [SoftwareProperty Table](#))
- SoftwareValue table (see [SoftwareValue Table](#))
- SoftwareVersion table (see [SoftwareVersion Table](#))
- VirtualDesktopAccess table (see [VirtualDesktopAccess Table](#))
- VirtualDesktopApplicationUsage table (see [VirtualDesktopApplicationUsage Table](#))
- VirtualDesktopGroupAccess table (see [VirtualDesktopGroupAccess Table](#))
- VirtualDesktopGroupAccessScan table (see [VirtualDesktopGroupAccessScan Table](#))

HardwareClass Table

HardwareClass contains a record for every class of hardware object found during hardware inventories, including mainly the WMI classes

Table 706: Database columns for HardwareClass table

Database Column	Details
HardwareClassID	Type: integer. Key. Generated ID Auto-generated identity number
Class	Type: text (max 256 characters). Key Hardware Class name
SuperClassID	Type: integer. Key. Nullable Reference to superclass, if any (and known)

HardwareObject Table

The HardwareObject table entries describe a specific configuration item (usually a piece of physical hardware) associated with a computer. The information is represented in the database as Windows Management Instrumentation (WMI) classes.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 707: Database columns for HardwareObject table

Database Column	Details
HardwareObjectID	<i>Type:</i> integer. Key. Generated ID Auto-generated identity number
ComputerID	<i>Type:</i> integer. Key The computer on which the hardware was found. It is a foreign key into the Computer table.
HardwareName	<i>Type:</i> text (max 256 characters). Key The hardware name as reported by the system.
Occurrence	<i>Type:</i> integer. Key The distinguishing identifier for the hardware. For example, if a computer has more than one memory card with the same Class and HardwareName, each memory card is assigned an Occurrence value (0, 1, 2...).
HardwareClassID	<i>Type:</i> integer. Key The id for the HardwareClass of the object.

HardwareProperty Table

The HardwareProperty table provides property names and values for each hardware object. The information is represented in the database as Windows Management Instrumentation (WMI) properties.

Table 708: Database columns for HardwareProperty table

Database Column	Details
HardwarePropertyID	Type: integer. Key. Generated ID Auto-generated identity number
Property	Type: text (max 256 characters). Key The hardware property. A single hardware object can have many properties.

HardwareValue Table

The value of a specified HardwareProperty of the specified HardwareObject.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 709: Database columns for HardwareValue table

Database Column	Details
HardwareObjectID	Type: integer. Key Object.
HardwarePropertyID	Type: integer. Key Property.
Value	Type: text (max 256 characters). Nullable Property value.

InventoryReport Table

The InventoryReport table contains a record of every user and computer that has reported hardware or software inventory. It details the date and time when the hardware or software tracking was performed.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 710: Database columns for InventoryReport table

Database Column	Details
ComputerID	Type: integer. Key The computer that the inventory was tracked on. This is a foreign key into the Computer table.
UserID	Type: integer. Key The user for whom inventory was tracked. For computer inventory, the UserID is 1 (system user). This is a foreign key into the User table.
SWDate	Type: datetime. Nullable The time software was tracked, or is NULL if no tracking is recorded.
HWDate	Type: datetime. Nullable The time hardware was tracked, or is NULL if no tracking is recorded.
FilesDate	Type: datetime. Nullable The time files were tracked, or is NULL if no tracking is recorded.
ServicesDate	Type: datetime. Nullable The time Oracle services were tracked, or is NULL if no tracking is recorded.
VMwareServicesDate	Type: datetime. Nullable The time VMware services were tracked, or is NULL if no tracking is recorded.
SequenceNumber	Type: integer. Nullable Used when generating a differential inventory.
OVMMDate	Type: datetime. Nullable The time Oracle VM manager was interrogated, or is NULL if no interrogation is recorded.
AccessDate	Type: datetime. Nullable Access time information was tracked, or is NULL if no tracking is recorded.

ServiceComponent Table

A software component installed to implement a `ServiceProvider`.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 711: Database columns for `ServiceComponent` table

Database Column	Details
<code>ServiceComponentID</code>	<i>Type:</i> integer. Key. Generated ID Unique ID for the service component.
<code>Name</code>	<i>Type:</i> text (max 128 characters). Key The name of the service component.
<code>Version</code>	<i>Type:</i> text (max 32 characters). Key The version of the service component.
<code>Publisher</code>	<i>Type:</i> text (max 128 characters). Key The publisher of the service component.
<code>Edition</code>	<i>Type:</i> text (max 128 characters). Key The edition of the service component.

ServiceProvider Table

The inventoried providers of services.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 712: Database columns for ServiceProvider table

Database Column	Details
ServiceProviderID	Type: integer. Key. Generated ID Unique ID for the service provider.
ComputerID	Type: integer. Key The Computer this service provider is hosted by.
ParentServiceProviderID	Type: integer. Nullable The ServiceProvider this provider is parented by.
ServiceProviderTypeID	Type: integer. Key The ServiceProviderType of the service provider.
ServiceProviderNameID	Type: integer. Key The ServiceProviderName of the service provider.
LastInventoryDate	Type: datetime The date and time that the service provider was last inventoried.
LastInventoryResult	Type: integer. Nullable The error code returned when the service provider was last inventoried.
LastInventoryError	Type: text (max 256 characters). Nullable The error message returned when the service provider was last inventoried.
CreationDate	Type: datetime. Nullable The date and time that the service provider was created.
AuditEvidence	Type: binary. Nullable The Oracle LMS audit evidence in zip archive.

ServiceProviderApplicationOracle Table

An Oracle application.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 713: Database columns for ServiceProviderApplicationOracle table

Database Column	Details
ServiceProviderApplicationOracleID	Type: integer. Key. Generated ID Unique ID for the Oracle application.
ServiceProviderID	Type: integer. Key Unique ID for the service provider.
Name	Type: text (max 240 characters). Key The application name.
Users	Type: integer The number of users.
ApplicationID	Type: integer. Key The ID of the application as assigned by Oracle.

ServiceProviderApplicationUsagePerMonth Table

A count of oracle application usage items per month.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 714: Database columns for ServiceProviderApplicationUsagePerMonth table

Database Column	Details
ServiceProviderApplicationUsagePerMonthID	Type: integer. Key. Generated ID Unique ID for the Oracle per month summary count.
ServiceProviderID	Type: integer. Key Unique ID for the service provider.
ServiceProviderApplicationUsageTypeID	Type: integer. Key The ServiceProviderApplicationUsageType of the service provider application usage.
YearMonth	Type: datetime. Key The year and month of the count.
ItemsUsed	Type: integer The number of items used.

ServiceProviderApplicationUsageType Table

The types of inventoried ServiceProviderApplicationUsagePerMonth items.

Table 715: Database columns for ServiceProviderApplicationUsageType table

Database Column	Details
ServiceProvider	Type: integer. Key. Generated ID
ApplicationUsageTypeID	Unique ID for the service provider application usage item type.
Type	Type: text (max 128 characters). Key The type of a service provider application usage item.

ServiceProviderApplicationUserOracle Table

An Oracle applications User.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 716: Database columns for ServiceProviderApplicationUserOracle table

Database Column	Details
ServiceProvider ApplicationUserOracleID	Type: integer. Key. Generated ID Unique ID for the Oracle application user.
ServiceProvider ApplicationOracleID	Type: integer. Key The application this user is associated with.
UserID	Type: integer. Key The application users user ID.
UserName	Type: text (max 100 characters) The application users user name.
Description	Type: text (max 240 characters). Nullable The application users description.
EMail	Type: text (max 240 characters). Nullable The application users email address.

ServiceProviderComponent Table

A software component installed to implement a `ServiceProvider`.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 717: Database columns for `ServiceProviderComponent` table

Database Column	Details
<code>ServiceProviderID</code>	<i>Type:</i> integer. Key The <code>ServiceProvider</code> this component is associated with.
<code>ServiceComponentID</code>	<i>Type:</i> integer. Key The <code>ServiceComponent</code> this provider is associated with.

ServiceProviderComponentProperty Table

The ServiceProviderComponentProperty table provides property names and values for each service component on a provider.

Table 718: Database columns for ServiceProviderComponentProperty table

Database Column	Details
ServiceProvider	Type: integer. Key. Generated ID
ComponentPropertyID	Auto-generated identity number
Property	Type: text (max 256 characters). Key The service component property. A single service component on a provider can have many properties.

ServiceProviderComponentValue Table

The value of a specified ServiceProviderComponentProperty of the specified ServiceProviderComponent.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 719: Database columns for ServiceProviderComponentValue table

Database Column	Details
ServiceProviderID	Type: integer. Key Service provider.
ServiceComponentID	Type: integer. Key Service component.
ServiceProvider ComponentPropertyID	Type: integer. Key Property.
Value	Type: text (max 256 characters). Nullable Property value.

ServiceProviderName Table

The names of inventoried ServiceProviders.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 720: Database columns for ServiceProviderName table

Database Column	Details
ServiceProviderNameID	Type: integer. Key. Generated ID Unique ID for the service provider name.
Name	Type: text (max 128 characters). Key The name of a service provider.

ServiceProviderProperty Table

The ServiceProviderProperty table provides property names and values for each service provider.

Table 721: Database columns for ServiceProviderProperty table

Database Column	Details
ServiceProviderPropertyID	<i>Type:</i> integer. Key. Generated ID Auto-generated identity number
Property	<i>Type:</i> text (max 256 characters). Key The service provider property. A single service provider can have many properties.

ServiceProviderType Table

The types of inventoried ServiceProviders.

Table 722: Database columns for ServiceProviderType table

Database Column	Details
ServiceProviderTypeID	Type: integer. Key. Generated ID Unique ID for the service provider type.
Type	Type: text (max 128 characters). Key The type of a service provider.

ServiceProviderValue Table

The value of a specified ServiceProviderProperty of the specified ServiceProvider.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 723: Database columns for ServiceProviderValue table

Database Column	Details
ServiceProviderID	Type: integer. Key Service provider.
ServiceProviderPropertyID	Type: integer. Key Property.
Value	Type: text (max 256 characters). Nullable Property value.

ServiceUser Table

A user that uses a ServiceProvider.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 724: Database columns for ServiceUser table

Database Column	Details
ServiceUserID	Type: integer. Key. Generated ID Unique ID for the service user.
ServiceProviderID	Type: integer. Key The ServiceProvider this user is associated with.
Name	Type: text (max 128 characters). Key The name of the service user.
Description	Type: text (max 256 characters). Nullable A textual description of the service user.
AccountStatus	Type: text (max 256 characters). Nullable Current status of user account.
CreationDate	Type: datetime. Nullable Date and time when user was created.
LastLogonDate	Type: datetime. Nullable Date and time when user last logged on.

ServiceUserOracle Table

A specific kind of ServiceUser, specifically an Oracle user.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 725: Database columns for ServiceUserOracle table

Database Column	Details
ServiceUserOracleID	<i>Type:</i> integer. Key. Generated ID Unique ID for the Oracle service user.
ServiceUserID	<i>Type:</i> integer. Key The service user this user is associated with.
DefaultTablespace	<i>Type:</i> text (max 256 characters). Nullable The default tablespace for the user.
TempTablespace	<i>Type:</i> text (max 256 characters). Nullable The temporary tablespace for the user.

SoftwareDetails Table

The SoftwareDetails table contains a record of detailed data for each SoftwareOccurrence found.

Table 726: Database columns for SoftwareDetails table

Database Column	Details
SoftwareDetailsID	<i>Type:</i> integer. Key. Generated ID The id for the software details. This is automatically generated by SQL Server.
RawSoftwareName	<i>Type:</i> text (max 128 characters). Key The name of the software defined by the vendor, unprocessed by FlexNet Manager Suite.
RawVersion	<i>Type:</i> text (max 32 characters). Key The version of the software defined by the vendor, unprocessed by FlexNet Manager Suite.
Publisher	<i>Type:</i> text (max 256 characters). Key The publisher of the software defined by the vendor.
ProductID	<i>Type:</i> text (max 256 characters). Key The MSI product ID of the software defined by the vendor.

SoftwareFile Table

The SoftwareFile table contains a record for each file associated with an application on each computer. File tracking is not enabled by default. For more information on configuring which files to track, see the section about the Inventory Agent.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 727: Database columns for SoftwareFile table

Database Column	Details
SoftwareFileID	<i>Type:</i> integer. Key. Generated ID The id for the software file. This is automatically generated by SQL Server.
ComputerID	<i>Type:</i> integer. Key The computer on which the file was tracked. This is a foreign key into the Computer table.
SoftwareID	<i>Type:</i> integer. Key. Nullable The software containing the file that was tracked. This is a foreign key into the SoftwareVersion table.
SoftwareIsoTagFileID	<i>Type:</i> integer. Key. Nullable The software ID tag content of the file. This is a foreign key into the SoftwareIsoTagFile table.
Version	<i>Type:</i> text (max 32 characters). Nullable The version of the software file defined by the vendor.
MD5	<i>Type:</i> text (max 32 characters) The file's MD5 digest.
Size	<i>Type:</i> integer The file's size in bytes.
DateTime	<i>Type:</i> datetime. Nullable The last date and time the file was modified on the computer.
FileVersion	<i>Type:</i> text (max 256 characters). Nullable The file version of the software file defined by the vendor.
FileDescription	<i>Type:</i> text (max 256 characters). Nullable The file description of the software file defined by the vendor.

Database Column	Details
Language	<i>Type:</i> text (max 256 characters). Nullable The language of the software file defined by the vendor.
CompanyName	<i>Type:</i> text (max 256 characters). Nullable The company name of the software file defined by the vendor.
SoftwareFilePathID	<i>Type:</i> integer. Key. Nullable The full path to the file that was tracked, minus the filename. This is a foreign key into the SoftwareFilePath table.
SoftwareFileNameID	<i>Type:</i> integer. Key. Nullable The name of the file that was tracked, minus the path. This is a foreign key into the SoftwareFileName table.

SoftwareFileName Table

The SoftwareFileName table contains a record for each unique file name for files captured in inventory.

Table 728: Database columns for SoftwareFileName table

Database Column	Details
SoftwareFileNameID	<i>Type:</i> integer. Key. Generated ID The id for the software file name. This is automatically generated by SQL Server.
Name	<i>Type:</i> text (max 400 characters). Key The name of a file captured in inventory, minus the path.
CreationDate	<i>Type:</i> datetime. Key The creation date of the SoftwareFileName which will be used to cleanup the older unused records.

SoftwareFilePath Table

The SoftwareFilePath table contains a record for each unique file path for files captured in inventory.

Table 729: Database columns for SoftwareFilePath table

Database Column	Details
SoftwareFilePathID	<i>Type:</i> integer. Key. Generated ID The id for the software file path. This is automatically generated by SQL Server.
Path	<i>Type:</i> text (max 400 characters). Key The full path to a file captured in inventory, minus the filename.
CreationDate	<i>Type:</i> datetime. Key The creation date of the SoftwareFilePath which will be used to cleanup the older unused records.

SoftwareFileProperty Table

The SoftwareFileProperty table provides property names and values for each software file object.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 730: Database columns for SoftwareFileProperty table

Database Column	Details
SoftwareFileID	Type: integer. Key The SoftwareFile that this property belongs to
Name	Type: text (max 256 characters). Key The software file property name.
Value	Type: text (max 256 characters) The software file property value.

SoftwareIsoTagEntity Table

The SoftwareIsoTagEntity table provides property names and values for each unique entities on software ID tags.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 731: Database columns for SoftwareIsoTagEntity table

Database Column	Details
SoftwareIsoTagEntityID	Type: integer. Key. Generated ID The SoftwareIsoTagEntity table unique ID for each records.
RegID	Type: text (max 200 characters). Key The unique registration ID value of an entity in an software ID tag.
Name	Type: text (max 200 characters). Key The entity name value in a software ID tag.

SoftwareIsoTagFile Table

The SoftwareIsoTagFile table provides property names and values for each Software ID Tag in a normalized manner.

 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 732: Database columns for SoftwareIsoTagFile table

Database Column	Details
SoftwareIsoTagFileID	<i>Type:</i> integer. Key. Generated ID The SoftwareIsoTagFile that this property belongs to
MD5	<i>Type:</i> text (max 32 characters). Key The MD5 property value of software ID tag file.
TagContent	<i>Type:</i> text The actual content of the software id tag file.
EntitlementRequired Indicator	<i>Type:</i> boolean. Nullable The entitlement required indicator value of the software ID tag.
SoftwareIsoTagSoftware VersionID	<i>Type:</i> integer. Key. Nullable The product version and name identifier for this software. This is a foreign key into the SoftwareIsoTagSoftwareVersion table.
SoftwareCreatorEntityID	<i>Type:</i> integer. Key. Nullable The software creator related data for software ID tag. This is a foreign key into the SoftwareIsoTagEntity table.
SoftwareLicensorEntityID	<i>Type:</i> integer. Key. Nullable The software licensor related data for software ID tag. This is a foreign key into the SoftwareIsoTagEntity table.
TagCreatorEntityID	<i>Type:</i> integer. Key. Nullable The tag creator related data for software ID tag. This is a foreign key into the SoftwareIsoTagEntity table.
OriginalArpGuid	<i>Type:</i> text (max 200 characters). Nullable The original GUID of add-remove programs values of a repackaged software.

Database Column	Details
OriginalArpPublisher	<i>Type:</i> text (max 200 characters). Nullable The original publisher of add-remove programs values of a repackaged software.
OriginalArpDisplayName	<i>Type:</i> text (max 200 characters). Nullable The original display name of add-remove programs values of a repackaged software.
OriginalArpDisplayVersion	<i>Type:</i> text (max 200 characters). Nullable The original display version of add-remove programs values of a repackaged software.
CurrentArpGuid	<i>Type:</i> text (max 200 characters). Nullable The current GUID of add-remove programs values of a repackaged software.
CurrentArpPublisher	<i>Type:</i> text (max 200 characters). Nullable The current publisher of add-remove programs values of a repackaged software.
CurrentArpDisplayName	<i>Type:</i> text (max 200 characters). Nullable The current display name of add-remove programs values of a repackaged software.
CurrentArpDisplayVersion	<i>Type:</i> text (max 200 characters). Nullable The current display version of add-remove programs values of a repackaged software.
AdminStudioAppCatalogID	<i>Type:</i> text (max 200 characters). Nullable Application catalog ID of a repackaged application in AdminStudio.
IsValidSchema	<i>Type:</i> boolean. Nullable Whether the software id tag has valid schema.
IsValidSignature	<i>Type:</i> boolean. Nullable Whether the software id tag has valid digital signature.
ActivationStatus	<i>Type:</i> text (max 50 characters). Nullable The activation status value of software ID tag.
ChannelType	<i>Type:</i> text (max 200 characters). Nullable The channel type value of software ID tag.
SerialNumber	<i>Type:</i> text (max 200 characters). Nullable The serial number value of software ID tag.

Database Column	Details
ParseErrorMessage	<i>Type:</i> text (max 1000 characters). Nullable The message of the error occurred while reading the software iso tag file.

SoftwareIsoTagSoftwareVersion Table

The SoftwareIsoTagSoftwareVersion table provides property names and values for each software ID tag unique product related data.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 733: Database columns for SoftwareIsoTagSoftwareVersion table

Database Column	Details
SoftwareIsoTagSoftwareVersionID	Type: integer. Key. Generated ID The SoftwareIsoTagSoftwareVersion table unique ID for each records.
TagCreatorEntityID	Type: integer. Key The tag creator related data for software ID tag. This is a foreign key into the SoftwareIsoTagEntity table.
TagSoftwareUniqueID	Type: integer. Key. Nullable The software unique ID related data for software ID tag. This is a foreign key into the SoftwareIsoTagUnique table.
ProductTitle	Type: text (max 200 characters). Key The product title value for software ID tag.
ProductVersionName	Type: text (max 200 characters). Key The product version name value for software ID tag.
ProductVersionMajor	Type: integer. Key The major version value of software ID tag.
ProductVersionMinor	Type: integer. Key The minor version value of software ID tag.
ProductVersionBuild	Type: integer. Key The build version value of software ID tag.
ProductVersionReview	Type: integer. Key The review version value of software ID tag.

SoftwareIsoTagUnique Table

The SoftwareIsoTagUnique table provides property names and values for each unique id on software ID tags.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 734: Database columns for SoftwareIsoTagUnique table

Database Column	Details
SoftwareIsoTagUniqueID	Type: integer. Key. Generated ID The SoftwareIsoTagUniqueID table unique ID for each records.
UniqueID	Type: text (max 200 characters). Key The unique ID value of a software ID tag.

SoftwareOccurrence Table

The SoftwareOccurrence table contains the list (by computer and user) of applications that are installed. The applications may not have been installed through FlexNet Manager Suite. The information is obtained from managed devices from:

- FlexNet Manager Suite packages cache
- Add/Remove Programs registry entries
- Microsoft Installer
- ProductVersion resource strings in program files, if files are tracked


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 735: Database columns for SoftwareOccurrence table

Database Column	Details
SoftwareOccurrenceID	Type: integer. Key. Generated ID The id for the software occurrence. This is automatically generated by SQL Server.
ComputerID	Type: integer. Key The computer on which the software was tracked. For user inventory, this is the computer that the user was logged on to at the time of the Generate Inventory event. This is a foreign key into the Computer table.
UserID	Type: integer. Key User for whom the SoftwareVersion was installed. This is a foreign key to the User table.
SoftwareID	Type: integer. Key The software that has been tracked. This is a foreign key to the SoftwareVersion table.
SoftwareDetailsID	Type: integer. Key The details that have been tracked. This is a foreign key to the SoftwareDetails table.

Database Column	Details
Evidence	<p><i>Type:</i> text (max 32 characters). Nullable</p> <p>An indication of how the software was determined to be on the managed device. The valid entries are:</p> <ul style="list-style-type: none"> • msi • managesoft • uninstall • exehdr (for file tracking only) • dllhdr (for file tracking only)
PackagePathID	<p><i>Type:</i> integer. Key. Nullable</p> <p>FlexNet Manager Suite PackageFullName if known (not always!).</p>
PolicyGUID	<p><i>Type:</i> binary (max 16 bytes). Nullable</p> <p>FlexNet Manager Suite Policy GUID if known.</p>
InstallationDate	<p><i>Type:</i> datetime. Nullable</p> <p>The date and time that the software was installed.</p>

SoftwareOccurrenceSoftwareIsoTagFile Table

The SoftwareOccurrenceSoftwareIsoTagFile table is link table joining records in SoftwareOccurrence and SoftwareIsoTagFile tables.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 736: Database columns for SoftwareOccurrenceSoftwareIsoTagFile table

Database Column	Details
SoftwareOccurrence	Type: integer. Key. Generated ID
SoftwareIsoTagFileID	The SoftwareOccurrenceSoftwareIsoTagFile table unique ID for each records.
SoftwareOccurrenceID	Type: integer. Key This is a foreign key into the SoftwareOccurrence table.
SoftwareIsoTagFileID	Type: integer. Key This is a foreign key into the SoftwareIsoTagFile table.

SoftwareProperty Table

The SoftwareProperty table contains a record for each unique property name captured in inventory.

Table 737: Database columns for SoftwareProperty table

Database Column	Details
SoftwarePropertyID	<i>Type:</i> integer. Key. Generated ID The id for the software property. This is automatically generated by SQL Server.
Property	<i>Type:</i> text (max 256 characters). Key The software property. A single software object can have many properties.

SoftwareValue Table

The value of a specified SoftwareProperty of the specified SoftwareOccurrence.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 738: Database columns for SoftwareValue table

Database Column	Details
SoftwareOccurrenceID	Type: integer. Key Object.
SoftwarePropertyID	Type: integer. Key Property.
Value	Type: text (max 256 characters). Nullable Property value.

SoftwareVersion Table

The SoftwareVersion table contains a record for each software name/version combination returned through inventory. The software names and versions are gathered from places such as Add/Remove Programs on managed devices. They do not represent package names and versions from the software library, although correlation is likely.

Table 739: Database columns for SoftwareVersion table

Database Column	Details
SoftwareID	<i>Type:</i> integer. Key. Generated ID The id for the software version. This is automatically generated by SQL Server.
SoftwareName	<i>Type:</i> text (max 128 characters). Key The name of the software defined by the vendor.
Version	<i>Type:</i> text (max 32 characters). Key The version of the software defined by the vendor.
CreationDate	<i>Type:</i> datetime. Key The creation date of the SoftwareVersion which will be used to cleanup the older unused records.

VirtualDesktopAccess Table

A VDI device a User has accessed on an end-point.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 740: Database columns for VirtualDesktopAccess table

Database Column	Details
ComputerID	Type: integer. Key The end-point ComputerID. This is a foreign key into the Computer table.
UserID	Type: integer. Key The ID for the user accessing the VDI device. This is a foreign key into the User table.
MachineName	Type: text (max 64 characters). Key Computer name of the VDI device.
MachineDomain	Type: text (max 256 characters). Key. Nullable Fully qualified domain of the VDI device.
VDITemplateName	Type: text (max 256 characters). Key The template from which the VDI device was cloned.
Type	Type: text (max 64 characters). Key The type of VDI.
LogonTime	Type: datetime. Key The time the user logged on to the VDI device.
VirtualDesktopAccessID	Type: integer. Key. Generated ID The ID of the user session to the VDI device.

VirtualDesktopApplicationUsage Table

A virtualized application is used from VDI.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 741: Database columns for VirtualDesktopApplicationUsage table

Database Column	Details
VirtualDesktopApplicationUsageID	Type: integer. Key. Generated ID The ID of the application usage record.
VirtualDesktopAccessID	Type: integer. Key The ID of the corresponding VDI access record. This is a foreign key into the VirtualDesktopAccess table.
Name	Type: text (max 64 characters). Key The display name of the virtual application.
Version	Type: text (max 16 characters). Key The version of the virtual application.
PackageGUID	Type: unique identifier. Key The GUID of the package that the virtual application is associated with.
LastLaunchOnSystem	Type: datetime The last date and time that the virtual application was launched.
AccessMode	Type: text (max 100 characters). Key The access mode for the application.

VirtualDesktopGroupAccess Table

A user with access to a particular VDI Group for a given site.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 742: Database columns for VirtualDesktopGroupAccess table

Database Column	Details
VDISiteName	Type: text (max 256 characters). Key the VDI Site.
VDIGroupName	Type: text (max 256 characters). Key The name of the VDI Group.
Sid	Type: text (max 512 characters). Key. Nullable The Sid of the user.
VDIBrokerType	Type: text (max 64 characters). Key The type of VDI infrastructure.

VirtualDesktopGroupAccessScan Table

The last scan time of the VDI to retrieve ACL information


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 743: Database columns for VirtualDesktopGroupAccessScan table

Database Column	Details
VDIBrokerType	Type: text (max 64 characters). Key The type of VDI.
VDISiteName	Type: text (max 256 characters). Key The VDI Site.
ScanTime	Type: datetime The VDI Site.

Licensing Tables

The complete set of database tables documented here includes:

- LicenseAllocation table (see [LicenseAllocation Table](#))
- LicenseModel table (see [LicenseModel Table](#))
- LicensePurchase table (see [LicensePurchase Table](#))
- ProductContainsSoftware table (see [ProductContainsSoftware Table](#))
- SoftwareProduct table (see [SoftwareProduct Table](#))
- SoftwarePublisher table (see [SoftwarePublisher Table](#))
- SoftwareReseller table (see [SoftwareReseller Table](#))

LicenseAllocation Table

The `LicenseAllocation` table specifies the allocation of licenses for each organizational unit. The same licensable product definition (from `SoftwareProduct`) may have license allocations for more than one organizational unit.

Table 744: Database columns for `LicenseAllocation` table

Database Column	Details
<code>AllocationID</code>	<i>Type:</i> integer. Key. Generated ID Unique identifier for the license allocation record. This is automatically generated by SQL Server.
<code>SoftwareProductID</code>	<i>Type:</i> integer. Key The license that maps to an application. This is a foreign key into the <code>SoftwareProduct</code> table.
<code>OrganizationID</code>	<i>Type:</i> integer. Key Id of the organizational unit to which the software is allocated.
<code>UnitsAllocated</code>	<i>Type:</i> integer. Nullable The number of units allocated for the application.
<code>Expiry</code>	<i>Type:</i> datetime. Nullable The date and time that the license allocation expires.

LicenseModel Table

The LicenseModel table defines the license models available (for example, Site license). Each licensable product (listed in SoftwareProduct) is assigned a license model. A license model may apply to multiple licensable products.

Table 745: Database columns for LicenseModel table

Database Column	Details
ModelID	Type: integer. Key. Generated ID The unique identifier for a license model.
Name	Type: text (max 256 characters). Key The name of the license model.

LicensePurchase Table

LicensePurchase records details of purchases of licenses for a specified SoftwareProduct.

Table 746: Database columns for LicensePurchase table

Database Column	Details
SoftwareProductID	<i>Type:</i> integer. Key The SoftwareProduct purchased.
ResellerID	<i>Type:</i> integer. Key The Reseller from which the software product was purchased.
OrganizationID	<i>Type:</i> integer. Key The organizational unit that owns the license for the product.
Purchased	<i>Type:</i> datetime. Key When the purchase was made.
Expires	<i>Type:</i> datetime. Nullable When the license expires.
Price	<i>Type:</i> integer. Nullable The price paid for the license.
Quantity	<i>Type:</i> integer Number of units licensed.
OrderNumber	<i>Type:</i> text (max 32 characters). Key Cross-reference to customer's purchase order number.

ProductContainsSoftware Table

The ProductContainsSoftware table lists the applications returned by inventory (in the SoftwareVersion table) that are covered by licensable products (listed in SoftwareProduct). A license can map to multiple applications: if any of these applications is installed, a license is required.

Table 747: Database columns for ProductContainsSoftware table

Database Column	Details
SoftwareProductID	<i>Type:</i> integer. Key The license that maps to an application. This is a foreign key into the SoftwareProduct table.
SoftwareVersionID	<i>Type:</i> integer. Key The application maps to the license. This is a foreign key into the SoftwareVersion table.

SoftwareProduct Table

The SoftwareProduct table contains all of the licensable products (license definitions) for an organization. It represents all of the license agreements available for monitoring.

Table 748: Database columns for SoftwareProduct table

Database Column	Details
SoftwareProductID	<i>Type:</i> integer. Key. Generated ID This is a unique identifier for the software product.
ProductName	<i>Type:</i> text (max 256 characters). Key The name of the license. This normally corresponds to the name of the software product as defined by the vendor.
ModelID	<i>Type:</i> integer. Key Reference to the Licensing model for FlexNet Manager Suite
TrackedByID	<i>Type:</i> integer In what units are Licences counted?
PublisherID	<i>Type:</i> integer. Key Reference to publisher
Agreement	<i>Type:</i> text (max 256 characters) A URL to the license agreement for the product.[Comments]
Comments	<i>Type:</i> text. Nullable Additional comments

SoftwarePublisher Table

The SoftwarePublisher table lists application publishers (for example, Microsoft). Each licensable product (listed in SoftwareProduct) is assigned a publisher. A publisher may be assigned to multiple licensable products.

Table 749: Database columns for SoftwarePublisher table

Database Column	Details
PublisherID	Type: integer. Key. Generated ID The unique identifier for a publisher.
Name	Type: text (max 256 characters). Key The name of the publisher.
SupportURL	Type: text (max 256 characters) The support URL.
SupportPhone	Type: text (max 256 characters) The support phone number.
ContactName	Type: text (max 256 characters) The name of the contact.
Comments	Type: text (max 512 characters) An arbitrary comment about the publisher.

SoftwareReseller Table

The `SoftwareReseller` table lists application resellers (usually the organization listed on the purchase order for the product). Each licensable product (listed in `SoftwareProduct`) is assigned an application reseller. A reseller may be assigned to multiple licensable products.

Table 750: Database columns for `SoftwareReseller` table

Database Column	Details
<code>ResellerID</code>	<i>Type:</i> integer. Key. Generated ID Auto-generated identifier of Reseller
<code>Name</code>	<i>Type:</i> text (max 256 characters). Key The name of the reseller.
<code>ContactName</code>	<i>Type:</i> text (max 256 characters) The name of the sales contact.
<code>ContactPhone</code>	<i>Type:</i> text (max 256 characters) The contact phone number.
<code>Comments</code>	<i>Type:</i> text (max 512 characters) An arbitrary comment about the reseller.

ManageSoft Tables

The complete set of database tables documented here includes:

- DatabaseConfiguration table (see [DatabaseConfiguration Table](#))

DatabaseConfiguration Table

The DatabaseConfiguration table contains configuration properties for the FlexNet Manager Suite database tables, which are used for ongoing maintenance of the database.

Table 751: Database columns for DatabaseConfiguration table

Database Column	Details
Property	<i>Type:</i> text (max 32 characters). Key The name of the property.
Value	<i>Type:</i> text (max 256 characters) The value of the property.
Created	<i>Type:</i> datetime The date and time the property was created.
LastUpdate	<i>Type:</i> datetime The date and time the property was last updated.

Networking Tables

The complete set of database tables documented here includes:

- NetworkLocation table (see [NetworkLocation Table](#))
- Subnet table (see [Subnet Table](#))

NetworkLocation Table

The Location table contains data about Locations


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 752: Database columns for NetworkLocation table

Database Column	Details
NetworkLocationID	Type: integer. Key. Generated ID The ID for the Location
Name	Type: text (max 256 characters). Key The name of the Location
DN	Type: text (max 1024 characters). Key. Nullable The Distinguished name of the Location
AutoPopulated	Type: boolean Specifies whether the row was populated automatically(1) or manually(0).
Enabled	Type: boolean Specifies whether the row will be used when mapping domains and devices to Locations
DomainID	Type: integer. Key DomainID of the domain in which the NetworkLocation resides

Subnet Table

The Subnet table contains data about subnets in a location.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 753: Database columns for Subnet table

Database Column	Details
SubnetID	Type: integer. Key. Generated ID The ID for the Subnet
IPSubnet	Type: text (max 64 characters). Key The IPSubnet of the Subnet
IPSubnetMask	Type: text (max 64 characters). Key The IPSubnetMask of the Subnet
NetworkLocationID	Type: integer. Key NetworkLocationID of the NetworkLocation in which the Subnet resides
AutoPopulated	Type: boolean Specifies whether the row was populated automatically(1) or manually(0).
Enabled	Type: boolean Specifies whether the row will be used when mapping domains and devices to Locations

Packaging Tables

The complete set of database tables documented here includes:

- Architecture table (see [Architecture Table](#))
- FileNameMap table (see [FileNameMap Table](#))
- Media table (see [Media Table](#))
- MediaContainsPackagePath table (see [MediaContainsPackagePath Table](#))
- MediaContainsPackageVersion table (see [MediaContainsPackageVersion Table](#))
- MediaType table (see [MediaType Table](#))
- PackageFamily table (see [PackageFamily Table](#))
- PackagePath table (see [PackagePath Table](#))
- PackagePathType table (see [PackagePathType Table](#))
- PackageProvides table (see [PackageProvides Table](#))
- PackageRequires table (see [PackageRequires Table](#))
- PackageState table (see [PackageState Table](#))
- PackageVersion table (see [PackageVersion Table](#))
- PackageVersionArchitecture table (see [PackageVersionArchitecture Table](#))
- PackageVersionEnvironment table (see [PackageVersionEnvironment Table](#))
- PackageVersionInState table (see [PackageVersionInState Table](#))
- PackageVersionLocale table (see [PackageVersionLocale Table](#))

Architecture Table

Architecture identifies a target CPU (ABI), used to identify on what type of computer a package may be installed.

Table 754: Database columns for Architecture table

Database Column	Details
ArchitectureID	Type: integer. Key. Generated ID Auto-generated identity number
ArchitectureName	Type: text (max 64 characters). Key Name of the computer architecture

FileNameMap Table

Stores mappings from a file on disk to a filename that will be used on the managed device. Currently used by the HPUNIX wizards to rename files that have non-Windows conforming names.

Table 755: Database columns for FileNameMap table

Database Column	Details
MediaID	<i>Type:</i> integer. Key The Media that the SourceFile exists on.
SourceFile	<i>Type:</i> text (max 256 characters). Key The file to be renamed.
DestFile	<i>Type:</i> text (max 256 characters) The final file name.
IsFile	<i>Type:</i> boolean Boolean field that specifies whether the row refers to a file or a directory.

Media Table

Packages are stored on Media identified in this table.

Table 756: Database columns for Media table

Database Column	Details
MediaID	<i>Type:</i> integer. Key. Generated ID Auto-generated identity number, 1 = local administration server.
Title	<i>Type:</i> text (max 128 characters). Key Name of media (empty for local administration server).
MediaTypeID	<i>Type:</i> integer. Key What type of media?
Location	<i>Type:</i> text (max 256 characters). Nullable Where on the media?

MediaContainsPackagePath Table

This table identifies which Media contains which PackagePath. A record exists here at least for every PackagePath currently in the local administration server.

Table 757: Database columns for MediaContainsPackagePath table

Database Column	Details
MediaID	<i>Type:</i> integer. Key What Media contains the package?
PackagePathID	<i>Type:</i> integer. Key What PackagePath?

MediaContainsPackageVersion Table

This table identifies which Media contains which PackageVersion. A record exists here at least for every PackageVersion currently in the local administration server.

Table 758: Database columns for MediaContainsPackageVersion table

Database Column	Details
MediaID	Type: integer. Key What Media contains the package?
PackageVersionID	Type: integer. Key What PackageVersion?

MediaType Table

Packages are stored on Media of various types. This table contains a record for each type.

Table 759: Database columns for MediaType table

Database Column	Details
MediaTypeID	<i>Type:</i> integer. Key. Generated ID Auto-generated identity number, 1 = Warehouse (administration server).
Description	<i>Type:</i> text (max 128 characters). Key Media type name (for example: Warehouse, Filesystem, CD).

PackageFamily Table

PackageFamily is a short name used by the client to decide where a package to be downloaded to and whether it's an upgrade or downgrade of a previous package. Only one package version of a family may be installed in a given context.

Table 760: Database columns for PackageFamily table

Database Column	Details
PackageFamilyID	Type: integer. Key. Generated ID Auto-generated identity number
PackageName	Type: text (max 64 characters). Key Package family name

PackagePath Table

Package Path identifies a filesystem path where the package will be stored in the software library and in transit. As such, the administration server and each distribution server may only contain a single package version having a given Path

Table 761: Database columns for PackagePath table

Database Column	Details
PackagePathID	<i>Type:</i> integer. Key. Generated ID Auto-generated identity number
PackageFullName	<i>Type:</i> text (max 256 characters). Key. Nullable Package Path string
ParentPathID	<i>Type:</i> integer. Key. Nullable When a package is a variant of a parent package, this contains a reference to the parent package's path.
PackagePathTypeID	<i>Type:</i> integer The type of PackagePath that this row represents.

PackagePathType Table

This table contains the list of different types of packages, which also corresponds to the main areas in the Software Library.

Table 762: Database columns for PackagePathType table

Database Column	Details
PackagePathTypeID	Type: integer. Key. Generated ID Auto-generated identity number
Description	Type: text (max 128 characters). Key This describes the type of the package

PackageProvides Table

PackageProvides is used when a package can satisfy a virtual dependency, like “web-browser”.

Table 763: Database columns for PackageProvides table

Database Column	Details
PackageProvidesID	<i>Type:</i> integer. Key. Generated ID Auto-generated identity number
PackageVersionID	<i>Type:</i> integer. Key The package which provides the interface
PackageFamilyID	<i>Type:</i> integer. Key The (virtual) package which is provided
Version	<i>Type:</i> text (max 32 characters). Key. Nullable The version provided, if necessary

PackageRequires Table

PackageRequires is used when a package requires another package or some other configuration, like a piece of hardware for example.

Table 764: Database columns for PackageRequires table

Database Column	Details
PackageVersionID	<i>Type:</i> integer. Key The PackageVersion which has the requirement.
RequiredType	<i>Type:</i> text (max 8 characters). Key Requirement type: for example, software, hardware.
RequiredObject	<i>Type:</i> text (max 64 characters). Key Required object: for example, PackageFamily name.
Strength	<i>Type:</i> integer. Nullable Strength of the requirement.
Property	<i>Type:</i> text (max 64 characters). Nullable The required property of the object (for example, package version).
Value	<i>Type:</i> text (max 64 characters). Nullable The value of the required property.
Match	<i>Type:</i> integer. Key How to match the required value.

PackageState Table

This table contains the package states that may be assigned to a package in the software library. The default set of states are based on ITIL release management processes.

Table 765: Database columns for PackageState table

Database Column	Details
PackageStateID	<i>Type:</i> integer. Key. Generated ID Auto-generated identity number
Name	<i>Type:</i> text (max 64 characters). Key Package State Name
CanAddToPolicy	<i>Type:</i> boolean Whether a package in this state can be added to policy

PackageVersion Table

The PackageVersion table contains information about all of the packages in the software library. It is primarily used to map between Installation and PackageApplies for the purpose of comparing what users and computers should have versus what they actually have installed. This table only stores the details of one version of each package. This will change in future releases.

Table 766: Database columns for PackageVersion table

Database Column	Details
PackageVersionID	<i>Type:</i> integer. Key. Generated ID Auto-generated identity number
PackagePathID	<i>Type:</i> integer. Key Reference to Path (Full name) of Package
Version	<i>Type:</i> text (max 32 characters). Key The version number of the package. The Installation table also has PackageName and Version columns. This value can be used to find the corresponding PackageFullName so that Installation can be mapped to PackageApplies.
Update	<i>Type:</i> text (max 64 characters). Key The current update (or patch) number of the package
PackageFamilyID	<i>Type:</i> integer. Key A managed device may only have one PackageVersion in a family.
Title	<i>Type:</i> text (max 64 characters). Nullable The friendly name for the package.
MD5	<i>Type:</i> text (max 40 characters). Nullable The MD5 digest of the project file (.ndp) for the package. This is updated in the database when the package is packed or distributed.
Size	<i>Type:</i> integer. Nullable If set, contains the size in bytes of the distributable form of the package
Category	<i>Type:</i> text (max 128 characters). Nullable A category or class used to group packages

PackageVersionArchitecture Table

PackageVersionArchitecture specifies all the architectures that a particular package version applies to.

Table 767: Database columns for PackageVersionArchitecture table

Database Column	Details
PackageVersionID	Type: integer. Key Foreign key into the PackageVersion table.
ArchitectureID	Type: integer. Key Foreign key into the Architecture table.

PackageVersionEnvironment Table

PackageVersionEnvironment specifies all the environments (operating systems) that a particular package version applies to.

Table 768: Database columns for PackageVersionEnvironment table

Database Column	Details
PackageVersionID	Type: integer. Key Foreign key into the PackageVersion table.
Environment	Type: text (max 128 characters). Key Name of the environment that is used in the package. This refers to the environments used in the Packer.

PackageVersionInState Table

This table contains a history of changes made to the state of a package. Note that the username is recorded as a nvarchar rather than a foreign key to the user table so that if a user is deleted, there is still a record of the changes that were made.

Table 769: Database columns for PackageVersionInState table

Database Column	Details
PackageVersionID	<i>Type:</i> integer. Key The package that has been changed
PackageStateID	<i>Type:</i> integer. Key The state that was set
UserName	<i>Type:</i> text (max 64 characters). Key The user that made the state change
Changed	<i>Type:</i> datetime. Key The date/time that the change was made
Comments	<i>Type:</i> text (max 256 characters) A user defined set of comments relating to the state change

PackageVersionLocale Table

PackageVersionLocale specifies all the locales (language and country combinations) that a particular package version applies to.

Table 770: Database columns for PackageVersionLocale table

Database Column	Details
PackageVersionID	Type: integer. Key Foreign key into the PackageVersion table.
LocaleCode	Type: text (max 6 characters). Key Foreign key into the Locale table.

ReferenceData Tables

The complete set of database tables documented here includes:

- Country table (see [Country Table](#))
- Language table (see [Language Table](#))
- Locale table (see [Locale Table](#))

Country Table

Stores country information, including their ISO country code and English names.

Table 771: Database columns for Country table

Database Column	Details
CountryCode	Type: text (max 2 characters). Key The two letter country code.
Name	Type: text (max 128 characters). Key The english name of the country.

Language Table

Stores language information, including their English names, and various forms of language id.

Table 772: Database columns for Language table

Database Column	Details
LangCode3	<i>Type:</i> text (max 3 characters). Key The three letter language code.
LangCode2	<i>Type:</i> text (max 2 characters). Nullable The two letter language code.
EnglishName	<i>Type:</i> text (max 128 characters). Key The english name of the language.
LocalName	<i>Type:</i> text (max 128 characters). Nullable The name of the language, written in the local language.
MSLanguageID	<i>Type:</i> integer. Nullable The Microsoft language id, as specified in winnt.h in the Platform SDK.

Locale Table

Stores locale information, which consists of country and language combinations. Use the LocaleCode column as the foreign key into this table.

Table 773: Database columns for Locale table

Database Column	Details
LocaleCode	<i>Type:</i> text (max 6 characters). Key A combination of the language code and country code, separated by a hyphen. If there is no country code, then there will be no hyphen added. This column MUST have the correct value when inserted, based on the values of the language and country codes.
LangCode3	<i>Type:</i> text (max 3 characters). Key The three letter language code.
CountryCode	<i>Type:</i> text (max 2 characters). Key. Nullable The two letter country code.
LocaleName	<i>Type:</i> text (max 128 characters) The name of the locale. For example, "English (United States)".
MSLocaleID	<i>Type:</i> integer. Nullable The Microsoft identifier for the locale. For example, 1033 for English (United States).

Rights Tables

The complete set of database tables documented here includes:

- ActionClass table (see [ActionClass Table](#))
- PartitionType table (see [PartitionType Table](#))
- Resource table (see [Resource Table](#))

ActionClass Table

The types of action on a Resource for which rights may be granted or denied.

Table 774: Database columns for ActionClass table

Database Column	Details
ActionClassID	<i>Type:</i> integer. Key. Generated ID Auto-generated identity number.
ActionClassName	<i>Type:</i> text (max 16 characters). Key The name of the ActionClass.

PartitionType Table

Some secured Resources may be partitioned. Partitions are used to grant rights to one part of a Resource excluding other parts, for example limiting rights so that the operator can access only certain distribution servers, organizational units, or areas in the software library. There are three types of partitioning, defined by entries in this table.

Table 775: Database columns for PartitionType table

Database Column	Details
PartitionTypeID	Type: integer. Key. Generated ID Auto-generated identity number.
PartitionTypeName	Type: text (max 32 characters). Key Name of the PartitionType.

Resource Table

Access rights are granted to the Resources defined in this table.

Table 776: Database columns for Resource table

Database Column	Details
ResourceID	<i>Type:</i> integer. Key. Generated ID Auto-generated identity number.
ResourceName	<i>Type:</i> text (max 16 characters). Key Name of the Resource.
PartitionTypeID	<i>Type:</i> integer. Nullable If not NULL, the type of partitioning used with this Resource.

ScriptResult Tables

The complete set of database tables documented here includes:

- ComputerScriptResult table (see [ComputerScriptResult Table](#))

ComputerScriptResult Table

This table are used to store recognition rules and their results


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 777: Database columns for ComputerScriptResult table

Database Column	Details
ComputerID	Type: integer. Key The computer that the installation event occurred on. This is a foreign key into the Computer table.
RecognitionRule	Type: text (max 256 characters). Key The recognition rule.
Revision	Type: integer. Nullable The revision number of the recognition rule.
InventoryDate	Type: datetime The date the recognition rule ran.
Result	Type: text. Nullable The result of the recognition rule script.

Status Tables

The complete set of database tables documented here includes:

- AMTEventLog table (see [AMTEventLog Table](#))

AMTEventLog Table

Records the entries in the AMT event log for a NetworkDevice.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 778: Database columns for AMTEventLog table

Database Column	Details
AMTEventLogID	Type: integer. Key. Generated ID Auto-generated identity number.
DeviceID	Type: integer. Key. Nullable NetworkDevice identity number.
Reported	Type: datetime Date and time the event log entry was reported at.
PETDeviceAddress	Type: small integer The device address from the PET message format.
PETEventSensorType	Type: small integer The event sensor type from the PET message format.
PETEventType	Type: small integer The event type from the PET message format.
PETEventOffset	Type: small integer The event offset from the PET message format.
PETEventSourceType	Type: small integer The event source type from the PET message format.
PETEventSeverity	Type: small integer The event severity from the PET message format.
PETSensorNumber	Type: small integer The sensor number from the PET message format.
PETEntity	Type: small integer The entity from the PET message format.
PETEntityInstance	Type: small integer The entity instance address from the PET message format.

Database Column	Details
PETEventData	<i>Type:</i> text (max 32 characters) The event data from the PET message format.

Targeting Tables

The complete set of database tables documented here includes:

- TargetType table (see [TargetType Table](#))

TargetType Table

The TargetType table contains a row for each type of object that can be targeted in FlexNet Manager Suite.

Table 779: Database columns for TargetType table

Database Column	Details
TargetTypeID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>The ID for the target type:</p> <ul style="list-style-type: none"> • Computers • Users • Group • DistributionLocation • DistributionServer • Organization • Assets • Contracts • Purchase orders • Software licenses • Software titles • Compliance computers • Compliance users • Operators • SAP system landscapes • SAP systems • SAP rule sets • Discovered devices • Beacon • Vendor • Device • Rule • Inventory connection • FNMP Server • Fast Import • OLE DB Connection • ORACLE Connection

Database Column	Details
	<ul style="list-style-type: none">• XML• Intermediate File• ADSI Connection• Web Service• SQL Connection• Software Title Evidence• FNMEA Agent• Installed Software• Baseline Import
TargetTypeName	Type: text (max 256 characters). Key The name of the target type.

Tenants Tables

The complete set of database tables documented here includes:

- FlexeraLicense table (see [FlexeraLicense Table](#))
- Tenant table (see [Tenant Table](#))

FlexeraLicense Table

The FlexeraLicense table contains the encoded contents of the Flexera Software licenses required for the tenants in the system. This table is also used by the system in the single-tenant setup where there is only one tenant.

Table 780: Database columns for FlexeraLicense table

Database Column	Details
TenantUID	Type: text (max 40 characters). Key The unique identifier of a tenant. A reference to the Tenant to which this license is attached.
License	Type: text The encoded contents of the Flexera Software license attached to a particular Tenant.
LicenseChecksum	Type: integer. Key The check sum of the license.
LicenseDetails	Type: XML. Nullable XML definition of the license details

Tenant Table

The Tenant table contains the details of each tenant in multitenant FlexNet Manager Suite database tables.

Table 781: Database columns for Tenant table

Database Column	Details
TenantID	<i>Type:</i> integer. Key. Generated ID The tenant ID in a multi-tenant database.
TenantUID	<i>Type:</i> text (max 40 characters). Key The unique identifier of a tenant. This identifier is used to identify the tenant in environments where tenant information is stored on multiple databases.
TenantName	<i>Type:</i> text (max 256 characters). Key The name of the tenant.
Comments	<i>Type:</i> text. Nullable Operator comments about this tenant record.
CreationUser	<i>Type:</i> text (max 128 characters). Nullable The operator who created the tenant record.
CreationDate	<i>Type:</i> datetime The date the tenant record was created.
UpdatedUser	<i>Type:</i> text (max 128 characters). Nullable The name of the operator who last updated the tenant record.
UpdatedDate	<i>Type:</i> datetime. Nullable The date the tenant record was last updated.

Usage Tables

The complete set of database tables documented here includes:

- ComputerUsage table (see [ComputerUsage Table](#))
- SoftwareFileUsage table (see [SoftwareFileUsage Table](#))
- SoftwareUsagePerWeek table (see [SoftwareUsagePerWeek Table](#))

ComputerUsage Table

Each time usage information is received, the ComputerUsage table is updated with the current day's time-stamp.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 782: Database columns for ComputerUsage table

Database Column	Details
ComputerID	<i>Type:</i> integer. Key The id of the computer this information applies to. This id is a foreign key to the Computer table. It forms part of the unique index that identifies each row of data.
UserID	<i>Type:</i> integer. Key The id of the user context in which the application was detected. This is a foreign key to the User table. It forms part of the unique index that identifies each row of data.
LastReported	<i>Type:</i> datetime. Nullable The date that the user last reported usage information from the specified computer.

SoftwareFileUsage Table

This table contains information about each file relevant to reporting software usage information on each computer.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 783: Database columns for SoftwareFileUsage table

Database Column	Details
SoftwareFileUsageID	Type: integer. Key. Generated ID Auto-generated identity number
ComputerID	Type: integer. Key The id of the computer this information applies to. This id is a foreign key to the Computer table. It forms part of the unique index that identifies each row of data.
UserID	Type: integer. Key The id of the user context in which the application was detected. This is a foreign key to the User table. It forms part of the unique index that identifies each row of data.
Version	Type: text (max 32 characters). Key The version of the software file defined by the vendor.
SoftwareFileNameID	Type: integer. Key The name of the file that was tracked, minus the path. This is a foreign key into the SoftwareFileName table.
LongName	Type: text (max 4000 characters). Nullable The full path and file that was tracked.
CompanyName	Type: text (max 50 characters). Key The company name of the software.
Description	Type: text (max 1024 characters). Key The file description of the software.
ProductName	Type: text (max 50 characters). Key The product name of the software file.
ProductVersion	Type: text (max 32 characters). Key The version of the product of the software file defined by the vendor.

SoftwareUsagePerWeek Table

Software usage information is stored in weekly batches. Information received by the server is stored in the SoftwareUsagePerWeek table. Each row in the table represents usage information received from a specified user, on a specified managed device, regarding usage of specified software, during the week where the Monday is the specified date.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 784: Database columns for SoftwareUsagePerWeek table

Database Column	Details
SoftwareUsagePerWeekID	Type: integer. Key. Generated ID Auto-generated identity number
ComputerID	Type: integer. Key The id of the computer this information applies to. This id is a foreign key to the Computer table. It forms part of the unique-clustered-index that identifies each row of data.
UserID	Type: integer. Key The id of the user context in which the application was detected. This id is a foreign key to the User table. It forms part of the unique-clustered-index that identifies each row of data.
SoftwareID	Type: integer. Key The id of the software that was used. This is a foreign key to the SoftwareVersion table. It forms part of the unique-clustered-index that identifies each row of data.
SoftwareFileUsageID	Type: integer. Key. Nullable The id of the software file usage that was used. This is a foreign key to the SoftwareFileUsage table. It forms part of the unique-clustered-index that identifies each row of data.
StartOfWeek	Type: datetime. Key The first day for the week. This date identifies the week that usage data applies to.
Duration	Type: integer. Nullable The total duration, in seconds, that the application was run. It represents the total spanning across many sessions.

Database Column	Details
ActiveTime	<i>Type:</i> integer. Nullable The total active time, in seconds, that the application was in the foreground. It represents the total spanning across many sessions.
Sessions	<i>Type:</i> integer. Nullable The number of sessions the in which the application was used within the week.
Days	<i>Type:</i> integer. Nullable The number of distinct days the application was used within the week.

WakeOnLAN Tables

The complete set of database tables documented here includes:

- WakeOnLANDistributionJob table (see [WakeOnLANDistributionJob Table](#))
- WakeOnLANStatus table (see [WakeOnLANStatus Table](#))
- WakeOnLANTask table (see [WakeOnLANTask Table](#))

WakeOnLANDistributionJob Table

Wake on LAN distribution jobs control the distribution of a Wake on LAN task to the nearest distribution server for the targeted managed devices. The status of these distribution jobs is stored in the WakeOnLANDistributionJob table. Each row in the table represents a Wake on LAN job, which is any Wake on LAN task (or a subset of a Wake on LAN task), that has been distributed to a distribution server. Be aware: There can be multiple distribution jobs for a given Wake on LAN task.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 785: Database columns for WakeOnLANDistributionJob table

Database Column	Details
DistJobUID	Type: binary (max 16 bytes). Key A unique identifier for this distribution job.
TaskUID	Type: binary (max 16 bytes). Key A unique identifier for the task that created this distribution job. This is a foreign key linked to the TaskUID in the WakeOnLANTask table.
ServerUID	Type: binary (max 16 bytes). Key A unique identifier for the distribution server that this distribution job targets. This foreign key links to the ServerUID in the DistributionServer table.
State	Type: text (max 16 characters) The state of this distribution job. This can be one of the following values: + Pending + Failed + Success

WakeOnLANStatus Table

All managed devices targeted by a Wake on LAN task have a status associated with them. The status of the managed devices is stored in the WakeOnLANStatus table. Each row in the table represents a managed device to be woken by a Wake on LAN task from a distribution job.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 786: Database columns for WakeOnLANStatus table

Database Column	Details
DistJobUID	<p><i>Type:</i> binary (max 16 bytes). Key</p> <p>A unique identifier for a distribution job. This foreign key links to the DistJobUID in the WakeOnLANDistributionJob table. It forms part of the unique index that identifies each row of data.</p>
ComputerID	<p><i>Type:</i> integer. Key</p> <p>The id for the managed device. It forms part of the unique index that identifies each row of data.</p>
State	<p><i>Type:</i> text (max 16 characters)</p> <p>The state of this managed device. This can be one of the following values:</p> <ul style="list-style-type: none"> • Pending • Failed • Woken • Awake

WakeOnLANTask Table

Wake on LAN tasks control any targeted managed devices. The details of these tasks are stored in the WakeOnLANTask table. Each row in the table represents a Wake on LAN task.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 787: Database columns for WakeOnLANTask table

Database Column	Details
TaskUID	Type: binary (max 16 bytes). Key A unique identifier for the task that created a Wake on LAN job.
FriendlyName	Type: text (max 400 characters) The descriptive name assigned to the Wake on LAN task.
StartTime	Type: datetime. Nullable The time at which the managed devices will be woken.

WorkFlow Tables

The complete set of database tables documented here includes:

- Action table (see [Action Table](#))
- ActionApplies table (see [ActionApplies Table](#))
- ActionState table (see [ActionState Table](#))
- Job table (see [Job Table](#))
- Task table (see [Task Table](#))
- TaskSchedule table (see [TaskSchedule Table](#))
- TaskType table (see [TaskType Table](#))

Action Table

An Action arising from a Task, to be applied (possibly repeatedly) by an actor (often a distribution server) to a set of target devices.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 788: Database columns for Action table

Database Column	Details
ActionUID	Type: binary (max 16 bytes). Key The unique identifier for the Action.
TaskID	Type: integer. Key The Task which gave rise to this Action.
ServerUID	Type: binary (max 16 bytes). Key. Nullable True if this Action has been delegated to a distribution server.
JobUID	Type: binary (max 16 bytes). Key. Nullable The Job which instructed the DS to perform the Action, if the Job still exists.
ActionStateID	Type: integer .One of the action states defined in the ActionState table.
PackageVersionID	Type: integer. Nullable If Task is of type Distribution, a PackageVersion applies.
FailureReason	Type: text. Nullable If not empty, text describing the reason the Action failed.
LastUpdate	Type: datetime The last time that the ActionState was updated. This value is the UTC date time of the event.
DSVersion	Type: text (max 32 characters). Nullable The version of the DS used to execute the Action.

ActionApplies Table

An action applies/applied to this computer, which can be identified by its computer id, device id, DNS, IP or MAC address. One of the five related cross-references must be non-null. If more than one is non-null, precedence is applied top to bottom in the order documented below.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 789: Database columns for ActionApplies table

Database Column	Details
ActionAppliesID	Type: integer. Key. Generated ID Auto-generated identity number
ActionUID	Type: binary (max 16 bytes). Key The Action which applies.
ComputerID	Type: integer. Key. Nullable The computer id of the device to which the Action applies. Index into the Computer table.
DeviceID	Type: integer. Key. Nullable Index into the NetworkDevice table for this device.
MACAddress	Type: text (max 18 characters). Key. Nullable The network hardware address of the device.
DNSName	Type: text (max 128 characters). Key. Nullable The DNS name of the device.
IPAddress	Type: text (max 64 characters). Key. Nullable The IP Address of the device.
ActionStateID	Type: integer One of the action states defined in the ActionState table.
FailureReason	Type: text. Nullable If not empty, text describing the reason the action failed.
LastUpdate	Type: datetime The last time that the state of this action was updated. This value is the UTC date-time of the event.

ActionState Table

All possible states for an action are reflected in a record here.

Table 790: Database columns for ActionState table

Database Column	Details
ActionStateID	<i>Type:</i> integer. Key. Generated ID The id for the action state.
ActionStateName	<i>Type:</i> text (max 32 characters). Key The name for the action state. Possible id-name pairs are: <ul style="list-style-type: none">• 1 = Created• 2 = DistributionInProgress• 3 = DistributionFailed• 4 = Distributed• 5 = SchedulePending• 6 = ScheduledFailed• 7 = Scheduled• 8 = Applied• 9 = ApplyFailed• 10 = CancelPending• 11 = CancelFailed• 12 = Cancelled• 13 = NotSupported

Job Table

This table stores the information about the jobs.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 791: Database columns for Job table

Database Column	Details
JobUID	Type: binary (max 16 bytes). Key The unique id for the job.
TaskID	Type: integer. Key The id for the task.
ServerUID	Type: binary (max 16 bytes). Key The unique id for the server.

Task Table

This table stores the information about the tasks.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 792: Database columns for Task table

Database Column	Details
TaskID	Type: integer. Key. Generated ID The id of the task.
TaskUID	Type: binary (max 16 bytes). Key. Nullable The id of the task.
TaskTypeID	Type: integer The id for the task type.
TaskName	Type: text (max 128 characters). Key The name for the task.
PackagePathID	Type: integer. Key. Nullable For a distribution task, which package.
TaskScheduleID	Type: integer The id for the task schedule.
MinimumVersion	Type: text (max 16 characters). Nullable The minimum version required to execute the task.

TaskSchedule Table

This table stores the required information about the task schedule, such as the start and finish times number of retries, delays and other related information.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database `TenantID` has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 793: Database columns for TaskSchedule table

Database Column	Details
TaskScheduleID	<i>Type:</i> integer. Key. Generated ID The id for the task schedule.
StartTime	<i>Type:</i> datetime. Nullable The time that the scheduled task must start.
EndTime	<i>Type:</i> datetime. Nullable The time that the scheduled task must end.
RetryCount	<i>Type:</i> integer. Nullable Number of times for task retries.
MinRetryDelay	<i>Type:</i> integer. Nullable Number of seconds before a retry occurs in case of a failure.
RepeatDelay	<i>Type:</i> integer. Nullable Number of seconds before the task is repeated.
NumParallelTasks	<i>Type:</i> integer. Nullable Number of tasks that can be run in parallel.
SleepBetweenTasks	<i>Type:</i> integer. Nullable Amount of time before the next task can start.

TaskType Table

This table stores the information about different types of tasks and their associated IDs.

Table 794: Database columns for TaskType table

Database Column	Details
TaskTypeID	<i>Type:</i> integer. Key. Generated ID The id for the task.
TaskTypeName	<i>Type:</i> text (max 32 characters). Key The name of the task.

4

License Portal Database Schema

This chapter describes additions made to the database schema for FlexNet Manager Suite to accommodate a separate licensing portal. With the entire product now presented in a web interface, this separation is entirely historical. The tables described in this chapter continue to appear in the database for all implementations.

Information Structure

The following information is provided about database tables. Items appear only when relevant to the database column, and are suppressed where they do not apply. Two of these items (shown bold) are columns in the following pages, and the remainder are displayed within the **Details**.

Item	Comment
Database Column	The name of the column in the SQL table.
<i>Type</i>	The data type of the contents of the database column.
Size	For types that have a maximum capacity, the upper limit is provided in parentheses.
Key	The word "Key" appears when a column is a unique key field within the table. It is possible for several database columns to be part of the key, so that this indicator may appear for several columns in a table.
Generated ID	This indicates that a numeric ID is assigned by the database.
Nullable	If this indicator is present, the database column permits nulls.
Computed	This indicator appears for columns that are automatically computed by the database.
Default	If a column has a default value declared in the schema, this is specified at the end of the first set of details for the column.
Details	Describes the data stored in the database column, including many of the indicators described above.

Compliance.ECM.Logic Tables

The complete set of database tables documented here includes:

- ComplianceActionHistory table (see [ComplianceActionHistory Table](#))
- ComplianceActionHistoryResource table (see [ComplianceActionHistoryResource Table](#))
- EcmSettings table (see [EcmSettings Table](#))
- SoftwareLicenseUsageHistory table (see [SoftwareLicenseUsageHistory Table](#))
- TrackGroup table (see [TrackGroup Table](#))
- TrackSoftwareLicenseUsage table (see [TrackSoftwareLicenseUsage Table](#))
- TrackSoftwareTitle table (see [TrackSoftwareTitle Table](#))
- TrackSoftwareTitleUsage table (see [TrackSoftwareTitleUsage Table](#))

ComplianceActionHistory Table

ComplianceActionHistory records actions performed in the Compliance portal on a contract or software license, including usage activation/deactivation.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database TenantID has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 795: Database columns for ComplianceActionHistory table

Database Column	Details
ComplianceActionHistoryID	Type: integer. Key. Generated ID Unique identifier for the record.
ComplianceActionHistoryResourceID	Type: integer. Key Identifies the type of action performed. Foreign key to the ComplianceActionHistoryResource table.
History	Type: text Detailed information about the action performed.
HistoryParameters	Type: text Details of parameters changed and their changed values.
AssociatedObjectID	Type: integer The ID of the contract or license associated with the action.
AssociatedObjectName	Type: text (max 512 characters) The name of the contract or license associated with the action.
Comment	Type: text (max 1024 characters) Comments recorded about the change by the operator.
CreationUser	Type: text (max 512 characters) The username of the operator who made the change.
CreationDate	Type: datetime The date of the change.

ComplianceActionHistoryResource Table

ComplianceActionHistoryResource table stores string resources required by the ComplianceActionHistory table.

Table 796: Database columns for ComplianceActionHistoryResource table

Database Column	Details
ComplianceActionHistoryResourceID	<p><i>Type:</i> integer. Key. Generated ID</p> <p>Unique identifier for each record. Possible values and the corresponding default strings that may be written into a history list are:</p> <ul style="list-style-type: none"> • 1 = Payment made • 2 = Payment edited • 3 = Payment cancelled • 4 = Activated application usage tracking for contract • 5 = Deactivated application usage tracking for contract • 6 = Activated application usage tracking for software license • 7 = Deactivated application usage tracking for software license • 8 = Modified application usage tracking for software license • 9 = Modified application usage tracking for contract • 10 = Not defined • 11 = Obligated to pay: (amount) • 12 = Actual amount was set to: (amount) • 13 = Actual amount currency rate was set to: (rate) • 14 = Estimated amount was set to: (amount) • 15 = Estimated amount currency rate was set to: (rate) • 16 = Budgeted amount was set to: (amount) • 17 = Budgeted amount currency rate was set to: (amount) • 18 = Payment status was set to: (status) • 19 = Payment amount: (amount); Payment date: (date) • 20 = Payment date was set to: (date) • 21 = Software license: (license name) • 22 = Software title: (application name) • 23 = Contract: (contract name) • 24 = Tracked: (yes/no); Track group: (group); Track start date: (date); Track end date: (date) • 25 = Applications tracked: (number).

Database Column	Details
ResourceName	<i>Type:</i> text (max 256 characters). Key The name of the resource that determines the text to display on the user interface.
DefaultValue	<i>Type:</i> text (max 512 characters) The default value to display if there is no resource string available to define the history action.

EcmSettings Table

EcmSettings stores operator-specific settings for the Compliance portal.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 797: Database columns for EcmSettings table

Database Column	Details
EcmSettingID	Type: integer. Key. Generated ID A unique identifier for the record.
ComplianceOperatorID	Type: integer. Key An operator of the Compliance portal. Foreign key to the ComplianceOperator table.
SettingKey	Type: text (max 512 characters). Key A resource describing the operator setting.
SettingType	Type: text (max 512 characters) The data type of the operator setting.
SettingValueString	Type: text Serialized value of the operator setting.
LastUpdated	Type: datetime Date and time when this setting was last updated.

SoftwareLicenseUsageHistory Table

SoftwareLicenseUsageHistory records snapshots of software license utilization.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 798: Database columns for SoftwareLicenseUsageHistory table

Database Column	Details
SoftwareLicenseUsageHistoryID	Type: integer. Key. Generated ID A unique identifier for each record in this table.
SnapshotDate	Type: datetime Date that the snapshot was recorded and the projected usage was calculated.
SoftwareLicenseID	Type: integer. Key SoftwareLicenseID that identifies the software license. This field is a foreign key to the SoftwareLicense table.
NumberPurchased	Type: integer Total number of licenses purchased, as of the Snapshot Date.
NumberInstalled	Type: integer Total number of installations for the license, as of the Snapshot Date.
NumberUsedActual	Type: integer. Nullable Total consumption of the license, as of the Snapshot Date. If application usage is not being tracked, this field is blank.
NumberUsedProjected	Type: integer. Nullable The projected usage calculated for this license, based on patterns of usage over time.

TrackGroup Table

The TrackGroup table contains a list of the different tracking groups that tracked computer belong to.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 799: Database columns for TrackGroup table

Database Column	Details
TrackGroupID	<p>Type: integer. Key. Generated ID</p> <p>A unique identifier for each TrackGroup. Possible values and the corresponding default strings are:</p> <ul style="list-style-type: none">• 1 = Sample• 2 = Enterprise.
ResourceName	<p>Type: text (max 50 characters). Nullable</p> <p>The name of the resource that determines the text to display on the user interface.</p>
GroupName	<p>Type: text (max 64 characters). Key</p> <p>The default name of the TrackGroup. This is the value displayed if there is no resource string available to define the TrackGroup.</p>

TrackSoftwareLicenseUsage Table

TrackSoftwareLicenseUsage keeps track of usage for each license.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 800: Database columns for TrackSoftwareLicenseUsage table

Database Column	Details
TrackSoftwareLicense UsageID	Type: integer. Key. Generated ID Unique identifier for each record.
SoftwareLicenseID	Type: integer. Key Identifies a license. This field is a foreign key to the SoftwareLicense table.
TrackGroupID	Type: integer. Key. Nullable Identifies the track group associated with the license. This field is a foreign key to the TrackGroup table.
SampleSize	Type: integer. Nullable Number of computers in sample group.
UsedPercentage	Type: decimal. Nullable Percentage of computers within the tracking group that reported use of applications associated with this license.
LastUpdated	Type: datetime Date and time when software license usage was updated.

TrackSoftwareTitle Table

TrackSoftwareTitle stores details related to tracking software usage for a software title.



Note: To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 801: Database columns for TrackSoftwareTitle table

Database Column	Details
TrackSoftwareTitleID	Type: integer. Key. Generated ID Unique identifier for each record. This field is a foreign key to the SoftwareTitle table.
SoftwareTitleID	Type: integer. Key. Nullable Identifies the application for which usage is being tracked. This field is a foreign key to the SoftwareTitle table.
SoftwareLicenseID	Type: integer. Key. Nullable Identifies the license associated with the application. This field is a foreign key to the SoftwareLicense table.
TrackGroupID	Type: integer. Key Identifies if usage tracking has been activated for the Sample or Enterprise tracking group. This field is a foreign key to the TrackGroup table.
LastTrackStartDate	Type: datetime. Nullable Date that tracking was last turned on.
LastTrackEndDate	Type: datetime. Nullable Date that tracking was last turned off. This field may be null if the operator cleared the end date when activating application usage.
TrackEndDueDate	Type: datetime. Nullable Date that the current tracking period ends. Should be null when IsTracked is False.
IsTracked	Type: boolean. Key Indicates whether usage tracking is enabled for this application entry.

TrackSoftwareTitleUsage Table

TrackSoftwareTitleUsage keeps track of whether licensed software is being used on a computer.


 **Note:** To cater for multi-tenant mode, this table may contain data for multiple tenants. Access requires that the database *TenantID* has been set in the SQL Server connection context information. That setting filters an underlying table to produce this view of data for the single, selected tenant.

Table 802: Database columns for TrackSoftwareTitleUsage table

Database Column	Details
TrackSoftwareTitleUsageID	<i>Type:</i> integer. Key. Generated ID Unique identifier for each record.
ComplianceComputerID	<i>Type:</i> integer. Key Identifies the computer on which usage tracking details were recorded. This field is a foreign key to the ComplianceComputer table.
SoftwareTitleID	<i>Type:</i> integer. Key Identifier for the application that was installed on the computer. This field is a foreign key to the SoftwareTitle table.
SoftwareLicenseID	<i>Type:</i> integer. Key. Nullable Identifier for the license associated with the installed application on the computer. This field is a foreign key to the SoftwareLicense table.
TrackGroupID	<i>Type:</i> integer. Key. Nullable Identifies the track group to which the computer has been assigned.
IsUsed	<i>Type:</i> boolean. Nullable Indicates whether the application is used on the computer.
LastUsed	<i>Type:</i> datetime. Nullable Date and time when software was last used on computer.

5

Inventory Spreadsheet Templates

In contrast with other chapters in this document, this chapter takes a different approach: rather than documenting the schema of the central database for FlexNet Manager Suite, it describes the formats acceptable for spreadsheet (.xlsx) or comma-separated value (.csv) files that can be used to import various kinds of inventory information into the central database. For each data element, it shows which database table, and which column in that table, is the final destination for the imported data. (For details about importing inventory as spreadsheets or CSV files, see the chapter *Importing Inventory Spreadsheets and CSV Files* in the companion volume, *FlexNet Manager Suite System Reference*.)

Such spreadsheet (including CSV) files can be imported through two different paths:

- Using the web interface for FlexNet Manager Suite, the data may be uploaded directly to the central application server(s) as a one-time upload
- Optionally with a repeatable schedule, the data may also be uploaded through an inventory beacon.


The same templates are used for inventory imports through either of these channels.

Information Structure for Spreadsheet Inventory Imports


The following information is provided about the structure of spreadsheet (.xlsx) and comma-separated value (.csv) template files that can be prepared as a data source for importing inventory. The items listed below appear only when relevant to the spreadsheet column, and are suppressed where they do not apply. Four of these items (shown bold) are columns in the following pages, and the remainder are displayed within the **Details** column.


Below this key is a mapping between:

- The file name of the downloaded template
- The prompt in the web interface of FlexNet Manager Suite for upload of the completed spreadsheet
- The topic below that covers this data (topic names are driven by the underlying database schema).

 **Remember:** The template files are fixed format. While adding data to each file, you may not change:


- The file name
- The names of columns
- The number of columns
- The order of columns.

Item	Comment
Column	The name of the column in the spreadsheet template (and uploaded data file).
	 Important: Some column names are long, and must be wrapped over more than one line in this document. In all cases, the wrapped text should be continuous on a single line without white space in the template column names.
Example values	Some sample data, or in some cases the list of supported values. When such a list is present, ensure that each row has a value that is an exact match for one of the available values (except that the validation is case insensitive).
Details	Describes the data required in the spreadsheet column, including many of the indicators described below.
<i>Type</i>	The data type of the contents of the spreadsheet column.
max	For types that have a maximum capacity, the upper limit is provided in parentheses.

Item	Comment
Key	The word "Key" appears when a column is a unique key field for data matching between the row of the spreadsheet and the data in the central database table (the destination for the data). Keep in mind that a single spreadsheet may include data destined for multiple database tables; and even within a single database table, it is possible for several database columns to be part of the key. For these reasons, this indicator may appear in several rows in the documentation list.
Nullable	If this indicator is present, the spreadsheet column may be left blank (and the target database entity allows nulls). Be careful about spaces in a cell of your spreadsheet: white space is a valid value, and is not equivalent to a null.
Destination	Where the imported data is eventually saved in the central database for FlexNet Manager Suite. This is given with a dot separating the database table and the column name within the table, in the format <i>tableName.columnName</i> . For further details on these database tables and columns, see the other chapters in this volume.
	 Tip: A single value in the imported spreadsheet may update data in more than one database column. Where that happens, this Destination listing shows the multiple destinations for the individual row.

Mapping templates to topics

The following table relates the template names (and the related prompts in the web interface) to the topics in this section that describe the individual columns within the templates. Templates are listed alphabetically. The naming of the following topics is driven by the related table names in the underlying database schema, so this list helps map the real world presentation to the database.

 **Tip:** Templates are provided in matching pairs of XLSX and CSV files. As these are structurally identical, only the base file name (without an extension) is listed here.

Template file name	Web prompt	See topic
Cluster	Cluster evidence	<i>ConsolidatedCluster Template</i>
ClusterGroup	Cluster group data	<i>ConsolidatedClusterGroup Template</i>
ClusterHostAffinityRule	Cluster host affinity rule data	<i>ConsolidatedClusterHostAffinityRule Template</i>
Computer	Computers and VMs	<i>ConsolidatedComputer Template</i>
FileEvidence	File evidence	<i>ConsolidatedFileEvidence Template</i>
InstallerEvidence	Installation evidence	<i>ConsolidatedInstallerEvidence Template</i>
OracleDatabaseUser	Oracle database user	<i>ConsolidatedOracleDatabaseUser Template</i>

Template file name	Web prompt	See topic
RemoteAccessFile	Access shown by file evidence	<i>ConsolidatedRemoteAccessFile Template</i>
RemoteAccessInstaller	Access shown by installer evidence	<i>ConsolidatedRemoteAccessInstaller Template</i>
VMPool	Virtual machine pool data	<i>ConsolidatedVMPool Template</i>
WMIEvidence	WMI evidence	<i>ConsolidatedWMIEvidence Template</i>

Compliance.InventoryReader.Logic Tables

The complete set of database tables documented here includes:

- ConsolidatedAccessEvidence table (see [ConsolidatedAccessEvidence Template](#))
- ConsolidatedCluster table (see [ConsolidatedCluster Template](#))
- ConsolidatedClusterGroup table (see [ConsolidatedClusterGroup Template](#))
- ConsolidatedClusterHostAffinityRule table (see [ConsolidatedClusterHostAffinityRule Template](#))
- ConsolidatedComputer table (see [ConsolidatedComputer Template](#))
- ConsolidatedFileEvidence table (see [ConsolidatedFileEvidence Template](#))
- ConsolidatedInstallerEvidence table (see [ConsolidatedInstallerEvidence Template](#))
- ConsolidatedOracleDatabaseUser table (see [ConsolidatedOracleDatabaseUser Template](#))
- ConsolidatedRemoteAccessFile table (see [ConsolidatedRemoteAccessFile Template](#))
- ConsolidatedRemoteAccessInstaller table (see [ConsolidatedRemoteAccessInstaller Template](#))
- ConsolidatedVMPool table (see [ConsolidatedVMPool Template](#))
- ConsolidatedWMIEvidence table (see [ConsolidatedWMIEvidence Template](#))

ConsolidatedAccessEvidence Template

ConsolidatedAccessEvidence provides a simpler interface to specify client access happening on application installed on server computers. It combines the server computer, and its access evidence details into a single row.

Table 803: Columns included with ConsolidatedAccessEvidence templates

Column	Details
ComputerID	<p><i>Type:</i> big integer. Key</p> <p>The identifier used in the source connection for the computer. It must match the ComputerID from the Computer spreadsheet or the row will be ignored.</p> <p>Destination:</p> <p><code>ImportedClientAccessedAccessEvidence.ImportedClientAccessedAccessEvidenceID</code></p> <p><code>ImportedClientAccessedAccessEvidence.ExternalServerComputerID</code></p> <p><code>ImportedClientAccessedAccessOccurrence.ImportedClientAccessedAccessEvidenceID</code></p>
ProductName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The product name of the software as reported by the access evidence.</p> <p>Destination:</p> <p><code>ImportedClientAccessEvidence.ExternalAccessEvidenceID</code></p> <p><code>ImportedClientAccessEvidence.ProductName</code></p> <p><code>ImportedClientAccessedAccessEvidence.ImportedClientAccessedAccessEvidenceID</code></p> <p><code>ImportedClientAccessedAccessEvidence.ExternalAccessEvidenceID</code></p> <p><code>ImportedClientAccessedAccessOccurrence.ImportedClientAccessedAccessEvidenceID</code></p>

Column	Details
Version	<p><i>Type:</i> text (max 72 characters). Key. Nullable</p> <p>The version of the software as reported by the access evidence.</p> <p>Destination:</p> <p><code>ImportedClientAccessEvidence.ExternalAccessEvidenceID</code></p> <p><code>ImportedClientAccessEvidence.Version</code></p> <p><code>ImportedClientAccessedAccessEvidence.ImportedClientAccessedAccessEvidenceID</code></p> <p><code>ImportedClientAccessedAccessEvidence.ExternalAccessEvidenceID</code></p> <p><code>ImportedClientAccessedAccessOccurrence.ImportedClientAccessedAccessEvidenceID</code></p>
Edition	<p><i>Type:</i> text (max 50 characters). Key. Nullable</p> <p>The edition of the software as reported by the access evidence.</p> <p>Destination:</p> <p><code>ImportedClientAccessEvidence.ExternalAccessEvidenceID</code></p> <p><code>ImportedClientAccessEvidence.Edition</code></p> <p><code>ImportedClientAccessedAccessEvidence.ImportedClientAccessedAccessEvidenceID</code></p> <p><code>ImportedClientAccessedAccessEvidence.ExternalAccessEvidenceID</code></p> <p><code>ImportedClientAccessedAccessOccurrence.ImportedClientAccessedAccessEvidenceID</code></p>
AccessingDeviceIPAddress	<p><i>Type:</i> text (max 256 characters). Key. Nullable</p> <p>IP Address of the accessing device.</p> <p>Destination:</p> <p><code>ImportedAccessingDevice.ExternalAccessingDeviceID</code></p> <p><code>ImportedAccessingDevice.IPAddress</code></p> <p><code>ImportedClientAccessedAccessEvidence.ImportedClientAccessedAccessEvidenceID</code></p> <p><code>ImportedClientAccessedAccessEvidence.ExternalAccessingDeviceID</code></p> <p><code>ImportedClientAccessedAccessOccurrence.ImportedClientAccessedAccessEvidenceID</code></p>

Column	Details
AccessingDevice ComputerName	<p>Type: text (max 256 characters). Key. Nullable</p> <p>IP Address of the device accessing the product.</p> <p>Destination:</p> <p>ImportedAccessingDevice.ExternalAccessingDeviceID</p> <p>ImportedAccessingDevice.ComputerName</p> <p>ImportedClientAccessedAccessEvidence.ImportedClientAccessedAccessEvidenceID</p> <p>ImportedClientAccessedAccessEvidence.ExternalAccessingDeviceID</p> <p>ImportedClientAccessedAccessOccurrence.ImportedClientAccessedAccessEvidenceID</p>
AccessingDeviceSerialNo	<p>Type: text (max 100 characters). Nullable</p> <p>Serial number of the device accessing the product.</p> <p>Destination:</p> <p>ImportedAccessingDevice.SerialNo</p>
AccessingDeviceDomain	<p>Type: text (max 100 characters). Key. Nullable</p> <p>Domain name of the device accessing the product.</p> <p>Destination:</p> <p>ImportedAccessingDevice.ExternalAccessingDeviceID</p> <p>ImportedAccessingDevice.Domain</p> <p>ImportedClientAccessedAccessEvidence.ImportedClientAccessedAccessEvidenceID</p> <p>ImportedClientAccessedAccessEvidence.ExternalAccessingDeviceID</p> <p>ImportedClientAccessedAccessOccurrence.ImportedClientAccessedAccessEvidenceID</p>

Column	Details
AccessingUser	<p><i>Type:</i> text (max 128 characters). Key. Nullable</p> <p>The DOMAIN/SAMAccountName of the user accessing the product.</p> <p><i>Destination:</i></p> <p>ImportedAccessingUser.ExternalAccessingUserID</p> <p>ImportedAccessingUser.UserName (Element 2 after splitting on '\')</p> <p>ImportedAccessingUser.DomainName (Element 1 after splitting on '\')</p> <p>ImportedClientAccessedAccessEvidence.ImportedClientAccessedAccessEvidenceID</p> <p>ImportedClientAccessedAccessEvidence.ExternalAccessingUserID</p> <p>ImportedClientAccessedAccessOccurrence.ImportedClientAccessedAccessEvidenceID</p>
AccessDate	<p><i>Type:</i> datetime. Key. Nullable</p> <p>The date that the product was accessed. The date must be specified in the following format: 'yyyyMMdd'.</p> <p><i>Possible values:</i></p> <ul style="list-style-type: none"> • yyyy/MM/dd • yyyy/MM/dd HH:mm:Ss • yyyy/MM/dd HH:mm • yyyy-MM-dd • yyyy-MM-dd HH:mm:Ss • yyyy-MM-dd HH:mm • yyyyMMdd • yyyyMMdd HH:mm:Ss • yyyyMMdd HH:mm <p><i>Destination:</i></p> <p>ImportedClientAccessedAccessOccurrence.AccessDate</p> <p>ImportedClientAccessedAccessOccurrence.LicenseDate</p>
AccessCount	<p><i>Type:</i> integer. Nullable</p> <p>Number of times the product was accessed on the given access date.</p> <p><i>Destination:</i></p> <p>ImportedClientAccessedAccessOccurrence.AccessCount</p>

Column	Details
InventoryDate	<p><i>Type:</i> datetime. Nullable</p> <p>The date (and optionally time) the access evidence record was inventoried.</p> <p>Possible values:</p> <ul style="list-style-type: none"> • yyyy/MM/dd • yyyy/MM/dd HH:mm:Ss • yyyy/MM/dd HH:mm • yyyy-MM-dd • yyyy-MM-dd HH:mm:Ss • yyyy-MM-dd HH:mm • yyyyMMdd • yyyyMMdd HH:mm:Ss • yyyyMMdd HH:mm <p><i>Destination:</i></p> <p>ImportedClientAccessedAccessOccurrence.InventoryDate</p>
ClientAccessSource	<p><i>Type:</i> text (max 100 characters). Nullable</p> <p>The source type of the access evidence.</p> <p><i>Destination:</i></p> <p>ImportedClientAccessedAccessEvidence.ClientAccessSource</p>

ConsolidatedCluster Template

The Cluster spreadsheet provides a simple interface for defining server clustering. It is useful when combined with the ClusterGroup and ClusterHostAffinityRule spreadsheets.

Table 804: Columns included with ConsolidatedCluster templates

Column	Details
ClusterID	<p><i>Type:</i> big integer. Key</p> <p>The unique identifier for this imported cluster. This may be a string or an integer.</p> <p>Destination:</p> <p><code>ImportedCluster.ExternalID</code></p>
ClusterName	<p><i>Type:</i> text (max 128 characters)</p> <p>The name of the cluster in the external cluster management system.</p> <p>Destination:</p> <p><code>ImportedCluster.ExternalName</code></p> <p><code>ImportedCluster.Name</code></p>
Namespace	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>Where the cluster is contained: + The fully-qualified domain name (for HyperV clusters) - example: 'france.thc.myenterprise.com' + The datacenter name (for VMWare clusters) - example: 'MelProdDataCenter'</p> <p>Destination:</p> <p><code>ImportedCluster.Namespace</code></p>
ClusterType	<p><i>Type:</i> text (max 128 characters)</p> <p>The kind of cluster. The value must be an exact case-insensitive match to one of the permitted values.</p> <p>Possible values:</p> <ul style="list-style-type: none"> • vMotion Cluster • Hyper-V Cluster • Host Affinity Group • VM Affinity Group • Oracle VM <p>Destination:</p> <p><code>ImportedCluster.ClusterTypeID</code></p>

Column	Details
InventoryDate	<p><i>Type:</i> datetime. Nullable</p> <p>The date (with optional time) that the cluster last had inventory reported. The date must be entered in one of the supported formats.</p> <p>Possible values:</p> <ul style="list-style-type: none"> • yyyy/MM/dd • yyyy/MM/dd HH:mm:Ss • yyyy/MM/dd HH:mm • yyyy-MM-dd • yyyy-MM-dd HH:mm:Ss • yyyy-MM-dd HH:mm • yyyyMMdd • yyyyMMdd HH:mm:Ss • yyyyMMdd HH:mm <p>Destination:</p> <p><code>ImportedCluster.InventoryDate</code></p>
InventoryAgent	<p><i>Type:</i> text (max 64 characters). Nullable</p> <p>The name of the person or tool that performed the last inventory. For imported spreadsheets, you may wish to include the name of the person preparing the data, in case there is subsequent follow-up required.</p> <p>Destination:</p> <p><code>ImportedCluster.InventoryAgent</code></p>
DRS	<p><i>Type:</i> boolean. Nullable</p> <p>Whether Distributed Resource Scheduler (DRS) is enabled on the cluster.</p> <p>Possible values:</p> <p>true, false, 0 or 1</p> <p>Destination:</p> <p><code>ImportedCluster.DRS</code></p>
DPM	<p><i>Type:</i> boolean. Nullable</p> <p>Whether Distributed Power Management (DPM) is enabled on the cluster.</p> <p>Possible values:</p> <p>true, false, 0 or 1</p> <p>Destination:</p> <p><code>ImportedCluster.DPM</code></p>

ConsolidatedClusterGroup Template

The ClusterGroup spreadsheet uses data from the Cluster spreadsheet and defines groups of servers as well as computers that are members of these groups.

Table 805: Columns included with ConsolidatedClusterGroup templates

Column	Details
ClusterID	<p><i>Type:</i> big integer. Key</p> <p>The unique identifier for the imported cluster. This may be a string or an integer and must match a value for the ClusterID in the cluster spreadsheet.</p> <p>Destination:</p> <p>ImportedClusterGroup.ClusterExternalID</p>
ClusterGroupID	<p><i>Type:</i> big integer. Key</p> <p>The unique identifier for this cluster group. This may be a string or an integer.</p> <p>Destination:</p> <p>ImportedClusterGroup.ExternalID</p> <p>ImportedClusterGroupMember.ClusterGroupExternalID</p>
ClusterGroupName	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>The name of the cluster group. Depending on the value of the ClusterGroupType this will be a group of hosts or virtual machines.</p> <p>Destination:</p> <p>ImportedClusterGroup.Name</p>
ClusterGroupType	<p><i>Type:</i> text (max 128 characters)</p> <p>The kind of cluster included in the group. The value must be an exact case-insensitive match to one of the permitted values.</p> <p>Possible values:</p> <ul style="list-style-type: none"> • vMotion Cluster • Hyper-V Cluster • Host Affinity Group • VM Affinity Group • Oracle VM <p>Destination:</p> <p>ImportedClusterGroup.ClusterTypeID</p>

Column	Details
ComputerID	<p><i>Type:</i> big integer. Key</p> <p>The identifier used in the 'Computer' spreadsheet for a computer which is a member of the group. To identify all the members of the group, repeat as many lines as required in your spreadsheet where the other values in the row are identical, and only the 'ComputerID' value changes. Values in this column must match a ComputerID in the computer spreadsheet or the row will be skipped.</p> <p><i>Destination:</i></p> <p><code>ImportedClusterGroupMember.ComputerExternalID</code></p>

ConsolidatedClusterHostAffinityRule Template

The ClusterHostAffinity spreadsheet defines the groups of virtual machines which may run on groups of host servers.

Table 806: Columns included with ConsolidatedClusterHostAffinityRule templates

Column	Details
ClusterID	<p><i>Type:</i> big integer. Key</p> <p>The unique identifier for the imported cluster, to which this affinity rule applies. This may be a string or an integer and must match a ClusterID from the cluster spreadsheet.</p> <p>Destination:</p> <p>ImportedClusterHostAffinityRule.ClusterExternalID</p>
Name	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>The name of the cluster host affinity rule.</p> <p>Destination:</p> <p>ImportedClusterHostAffinityRule.Name</p>
ClusterHostGroupName	<p><i>Type:</i> big integer. Key</p> <p>The name of the group of hosts that the ClusterVMGroupName virtual machines may run on.</p> <p>Destination:</p> <p>ImportedClusterHostAffinityRule.ClusterHostGroupExternalID</p>
ClusterVMGroupName	<p><i>Type:</i> big integer. Key</p> <p>The name of the virtual machine group that may run on the ClusterHostGroupName hosts.</p> <p>Destination:</p> <p>ImportedClusterHostAffinityRule.ClusterVMGroupExternalID</p>
ClusterHostAffinityRuleType	<p><i>Type:</i> text (max 128 characters)</p> <p>The type of affinity rule. The value must be an exact case-insensitive match to one of the permitted values.</p> <p>Possible values:</p> <ul style="list-style-type: none"> • must run on • must not run on <p>Destination:</p> <p>ImportedClusterHostAffinityRule.ClusterHostAffinityRuleTypeID</p>

ConsolidatedComputer Template

'ConsolidatedComputer' consolidates data for the Computer, VirtualMachine, Domain, User and Cluster objects, providing a simpler way to populate this information. Any spreadsheet row that includes a 'HostComputerID' is making that row a virtual machine, and the import process expects that virtualization data will be provided.

Table 807: Columns included with ConsolidatedComputer templates

Column	Details
ComputerID	<p><i>Type:</i> big integer. Key</p> <p>The unique identifier for a computer (either physical or virtual). This identifier can either be an integer or a string. Keep this consistent across multiple imports: it is used to track the computer over time.</p> <p>Destination:</p> <p><code>ImportedComputer.ExternalID</code></p> <p><code>ImportedVirtualMachine.VMComputerID</code></p> <p><code>ImportedClusterNode.ComputerExternalID</code></p>
ComputerName	<p><i>Type:</i> text (max 256 characters)</p> <p>The name of the computer. In Windows, this is the NetBIOS name of the local computer, as returned by <code>GetComputerName()</code>. For UNIX, it is the host name of the machine, as returned by <code>gethostname(2)</code>.</p> <p>Destination:</p> <p><code>ImportedComputer.ComputerName</code></p>
DomainFlatName	<p><i>Type:</i> text (max 100 characters). Key. Nullable</p> <p>The flatname of the domain of the computer. Example: 'mycompany'.</p> <p>Destination:</p> <p><code>ImportedDomain.FlatName</code></p>
DomainQualifiedName	<p><i>Type:</i> text (max 100 characters). Key. Nullable</p> <p>The fully qualified domain name for the computer. Example: 'prod.mycompany.eu'.</p> <p>Destination:</p> <p><code>ImportedComputer.Domain</code></p> <p><code>ImportedDomain.QualifiedName</code></p>

Column	Details
BIOSUUID	<p><i>Type:</i> unique identifier. Nullable</p> <p>The BIOS UUID of the computer (physical or virtual), as provided by the operating system.</p> <p>Possible values:</p> <p>93B5BE3B-88B0-450E-9F75-F6294210DFA0</p> <p>Destination:</p> <p>ImportedComputer.UUID</p>
OperatingSystem	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>The operating system of the computer. For virtual machines, it is the configured operating system of the guest. Note that this operating system identification is not used for licensing.</p> <p>Destination:</p> <p>ImportedComputer.OperatingSystem</p> <p>ImportedVirtualMachine.GuestFullName</p>
ServicePack	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>The service pack installed for the operating system.</p> <p>Destination:</p> <p>ImportedComputer.ServicePack</p>
EmailAddress	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>The email address associated with the device. Typically used for mobile devices.</p> <p>Destination:</p> <p>ImportedComputer.EmailAddress</p>
PhoneNumber	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>The phone number of the device. Used for mobile devices.</p> <p>Destination:</p> <p>ImportedComputer.PhoneNumber</p>

Column	Details
Manufacturer	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>The manufacturer of the computer hardware. Some examples include:</p> <ul style="list-style-type: none"> • On Windows, the SMBios manufacturer (the WMI Manufacturer property of the 'Win32_ComputerSystem' class). • On Linux, 'Manufacturer' in the 'System Information' section resulting from the 'dmidecode' command. Sample command: 'dmidecode -s system-manufacturer' • On Solaris x86, as for Linux, with failovers first to 'sysinfo SI_HW_PROVIDER' and then to 'ModelNo'. • On Solaris SPARC, the 'sysinfo SI_HW_PROVIDER'. Typically this value is 'Sun_Microsystems' or, more recently, 'Oracle Corporation'. Failover to the 'ModelNo'. • On HP-UX, the string literal 'HP'. • On AIX, the 'modelname' system attribute preceding the comma character. For example, if the 'modelname' system attribute is 'IBM,8202-E4B', then use 'IBM'. This value is typically 'IBM'. <p>Destination:</p> <p>ImportedComputer.Manufacturer</p> <p>ImportedVirtualMachine.Manufacturer</p>

Column	Details
ModelNo	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>The model of the computer hardware or the virtual machine. This value is defined for the context of the current execution environment, rather than the physical server that may be hosting a virtual machine or partition.</p> <p>Examples:</p> <ul style="list-style-type: none"> • On Windows, the SMBios product name. The WMI Model property of the Win32_ComputerSystem class. • On Linux, the SMBios product name read using the command 'dmidecode -s system-product-name'. Specifically, the 'System Information' section and the 'Product Name' in that section is used. • On Solaris x86, as for Linux, with failover to the 'sysinfo SI_PLATFORM', stripping 'SUNW', and replacing hyphen characters with space characters. • On Solaris SPARC, the 'openprom' "banner-name" value read from '/dev/openprom'. Failover to the 'sysinfo SI_PLATFORM', stripping 'SUNW', and replacing hyphen characters with space characters. • On HP-UX, the 'confstr _CS_MACHINE_MODEL'. • On AIX, the 'modelname' system attribute following the comma character. For example, if the 'modelname' system attribute is 'IBM,8202-E4B', then use '8202-E4B'. <p>Destination:</p> <p>ImportedComputer.ModelNo</p> <p>ImportedVirtualMachine.ModelNo</p>

Column	Details
SerialNo	<p><i>Type:</i> text (max 100 characters). Nullable</p> <p>The hardware serial number of the computer. The goal of this value is to be tied to the physical hardware, partition or virtual machine and to be as unique as possible across all computers in the organization. This is due to its use in tracking computers, particularly after an operating system rebuild. This value is also used to socialize computer inventory from different inventory sources, and is used to map virtual machine guest operating system inventory to the VM host on which the virtual machine is running. Example sources:</p> <ul style="list-style-type: none"> • On Windows, the SMBios serial number. The WMI 'SerialNumber' property of the 'Win32_BIOS' class. Can fail over to the 'SerialNumber' property of the 'Win32_SystemEnclosure' class which is typically the same value. • On Linux, the SMBios serial number read using the command 'dmidecode -s system-serial-number'. Specifically, the 'System Information' section and the 'Serial Number' in that section is used. • On Solaris 10 8/07 or later, for a non-global zone, the UUID value from the /etc/zones/index file. For a global zone, the same as Solaris 10 releases earlier than 8/07. • For Solaris 10 releases earlier than 8/07, the hexadecimal version of 'SI_HW_SERIAL' with an appended hyphen character followed by the Zone's name. For example, '838bfc7b-global' or '838bfc7b-myzone'. • For Solaris 8 and 9, The hexadecimal version of 'SI_HW_SERIAL'. • For Mac OS X, the serial number of the machine as printed on the packaging and found in "About this Mac" from the desktop. • For HP-UX, the 'confstr _CS_PARTITION_IDENT' partition identifier if it is an nPar or vPar, or '_CS_MACHINE_IDENT' if not; with a failover to the machine serial number, and a final failover to the 'uname' machine identification number. • For AIX, the 'id_to_partition' system attribute, starting from the third character (strips a '0X' from the start). For example, if the 'id_to_partition' system attribute is '0X0473409002F7B201' then use '0473409002F7B201'. <p>Destination:</p> <p>ImportedComputer.SerialNo</p>

Column	Details
ChassisType	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>The type of case of the computer. The value must be a (case insensitive) exact match for one of the values shown. Note that some license types use this information to optimize the licensing position, particularly with desktop and laptop computers.</p> <p>Destination:</p> <p><code>ImportedComputer.ChassisType</code></p>
TotalMemory	<p><i>Type:</i> big integer. Nullable</p> <p>The total RAM in the computer, in bytes.</p> <p>Destination:</p> <p><code>ImportedComputer.TotalMemory</code></p>
NumberOfDisplayAdapters	<p><i>Type:</i> integer. Nullable</p> <p>The number of graphics cards in the computer.</p> <p>Destination:</p> <p><code>ImportedComputer.NumberOfDisplayAdapters</code></p>
VirtualMachineUUID	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>The unique identifier of the virtual machine provided by the virtualization infrastructure. (This may have the same value as the 'BIOSUUID', or have byte order reversed, or be altogether different.)</p> <p>Destination:</p> <p><code>ImportedVirtualMachine.UUID</code></p>
IMEI	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>IMEI (International Mobile Equipment Identity) is a 15- or 17-digit code that uniquely identifies mobile phone sets. Leave blank (null) for other device types.</p> <p>Destination:</p> <p><code>ImportedComputer.IMEI</code></p>
NumberOfProcessors	<p><i>Type:</i> integer. Nullable</p> <p>The total number of physical processors (CPU) in the computer. Note that a number of server-based licenses depend on complete details of the processor types, counts and speeds to calculate a correct license position.</p> <p>Destination:</p> <p><code>ImportedComputer.NumberOfProcessors</code></p> <p><code>ImportedVirtualMachine.NumberOfProcessors</code></p>

Column	Details
ProcessorType	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>The descriptive string of the processor(s) in the computer. This may be a comma-separated list in the case where there is more than one physical processor in the system. Note that a number of server-based licenses depend on complete details of the processor types, counts and speeds to calculate a correct license position.</p> <p>Destination:</p> <p><code>ImportedComputer.ProcessorType</code></p> <p><code>ImportedVirtualMachine.ProcessorType</code></p>
MaxClockSpeed	<p><i>Type:</i> integer. Nullable</p> <p>The maximum clock speed of the fastest processor in the computer in kHz. Note that a number of server-based licenses depend on complete details of the processor types, counts and speeds to calculate a correct license position.</p> <p>Destination:</p> <p><code>ImportedComputer.MaxClockSpeed</code></p>
NumberOfCores	<p><i>Type:</i> integer. Nullable</p> <p>The total number of cores in the computer. If there is more than one physical processor in the computer, then this would be the sum of the core counts for all the processors. For example, in a computer with two quad-core processors, this value would be 8. Note that a number of server-based licenses depend on complete details of the processor types, counts and speeds to calculate a correct license position.</p> <p>Destination:</p> <p><code>ImportedComputer.NumberOfCores</code></p>
NumberOfSockets	<p><i>Type:</i> integer. Nullable</p> <p>The number of physical sockets into which a processor may be placed in the computer. It is rare that an inventory source can know this value. If unset, it is typically approximated by the number of processors.</p> <p>Destination:</p> <p><code>ImportedComputer.NumberOfSockets</code></p>

Column	Details
NumberOfLogicalProcessors	<p><i>Type:</i> integer. Nullable</p> <p>The number of logical processors in the computer. This is the number of 'execution contexts' the operating system has access to. It will commonly be equivalent to the number processors in a single core, non-multi-threaded processor architecture, to the number of cores in a multi-core single threaded processor architecture, and to the number of threads in a multi-threaded processor architecture. For example, in a two processor, quad-core and hyper-threaded computer, this value would be 16. Note that a number of server-based licenses depend on complete details of the processor types, counts and speeds to calculate a correct license position.</p> <p>Destination:</p> <p><code>ImportedComputer.NumberOfLogicalProcessors</code></p>
PartialNumberOfProcessors	<p><i>Type:</i> decimal. Nullable</p> <p>Used in processor-based licensing, this is the non-integer number of cores allocated to this partition or virtual machine. When this property is null, the 'NumberOfCores' is used. Note that a number of server-based licenses depend on complete details of the processor types, counts and speeds to calculate a correct license position.</p> <p>Possible values:</p> <p>120.45</p> <p>Destination:</p> <p><code>ImportedComputer.PartialNumberOfProcessors</code></p>
NumberOfHardDrives	<p><i>Type:</i> integer. Nullable</p> <p>The number of physical hard drives in the computer. While the intent is physical drives, often this can end up being the number of disk partitions.</p> <p>Destination:</p> <p><code>ImportedComputer.NumberOfHardDrives</code></p> <p><code>ImportedVirtualMachine.NumberOfHardDrives</code></p>
TotalDiskSpace	<p><i>Type:</i> big integer. Nullable</p> <p>The total size of all hard drives in the computer in bytes. Note that this can be a very large number on modern systems. The maximum value for a bigint is 9,223,372,036,854,775,807, which can represent about 9.2 exabyte. While in practice it is unlikely that this size of storage capacity is reached for a single system, some systems can end up with large values through virtualized drives. Therefore, it is worth considering capping values when calculating total disk space, particularly when converting values from kilobytes or megabytes to bytes.</p> <p>Destination:</p> <p><code>ImportedComputer.TotalDiskSpace</code></p>

Column	Details
NumberOfNetworkCards	<p><i>Type:</i> integer. Nullable</p> <p>The number of network cards in the computer.</p> <p><i>Destination:</i></p> <p><code>ImportedComputer.NumberOfNetworkCards</code></p> <p><code>ImportedVirtualMachine.NumberOfNetworkCards</code></p>
IPAddress	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>The IP address of the computer in IPv4 or IPv6 format. This may be a comma-separated list if there is more than one active network adapter in the system. Do not include inactive network adapters and network adapters with invalid IP addresses. Examples:</p> <ul style="list-style-type: none"> • '69.89.31.226' • '2002:4559:1FE2::4559:1FE2' <p><i>Destination:</i></p> <p><code>ImportedComputer.IPAddress</code></p>
MACAddress	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>The MAC address of the computer. This may be a comma-separated list if there is more than one active network adapter in the system. Do not include inactive network adapters and network adapters with invalid MAC addresses.</p> <p><i>Destination:</i></p> <p><code>ImportedComputer.MACAddress</code></p>
LastLoggedOnUser	<p><i>Type:</i> text (max 128 characters). Key. Nullable</p> <p>The DOMAIN/SAMAccountName of the user last logged onto the computer.</p> <p><i>Destination:</i></p> <p><code>ImportedComputer.LastLoggedOnUser</code></p> <p><code>ImportedUser.ExternalID</code></p> <p><code>ImportedUser.UserName</code> (Element 2 after splitting on '\')</p> <p><code>ImportedUser.Domain</code> (Element 1 after splitting on '\')</p> <p><code>ImportedUser.SAMAccountName</code> (Element 2 after splitting on '\')</p>

Column	Details
LastLogonDate	<p><i>Type:</i> datetime. Nullable</p> <p>The date and time when the user last logged on to the computer. The date must be entered in one of the supported formats.</p> <p>Possible values:</p> <ul style="list-style-type: none"> • yyyy/MM/dd • yyyy/MM/dd HH:mm:Ss • yyyy/MM/dd HH:mm • yyyy-MM-dd • yyyy-MM-dd HH:mm:Ss • yyyy-MM-dd HH:mm • yyyyMMdd • yyyyMMdd HH:mm:Ss • yyyyMMdd HH:mm <p>Destination:</p>
CalculatedUser	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>The domain/SAMAccountName of the calculated user. Some inventory systems calculate the user who owns a computer. For example, it might be the user who, over the last ten logins, logged in most often.</p> <p>Destination:</p> <p>ImportedComputer.CalculatedUser</p>
HostComputerID	<p><i>Type:</i> text (max 256 characters). Key. Nullable</p> <p>The ComputerID of the server this virtual machine is hosted on. This may be a string or an integer and must match the ComputerID for another computer in this spreadsheet.</p> <p>Destination:</p> <p>ImportedVirtualMachine.HostComputerID</p>

Column	Details
VirtualMachineType	<p><i>Type:</i> text (max 100 characters). Nullable</p> <p>The type of the virtual machine. If present, the value must be a (case insensitive) exact match to one of the values shown.</p> <p>Possible values:</p> <ul style="list-style-type: none"> • VMware • HyperV • LPAR • WPAR • nPar • vPar • SRP • Zone • Unknown • Oracle VM <p>Destination:</p> <p>ImportedVirtualMachine.VirtualMachineType</p>
VMEnabledState	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>The operational state of the virtual machine. If present, the value must be a (case insensitive) exact match to one of the values shown.</p> <p>Possible values:</p> <ul style="list-style-type: none"> • Started • Stopped • Suspended • Unknown <p>Destination:</p> <p>ImportedVirtualMachine.VMEnabledStateID</p>
AffinityEnabled	<p><i>Type:</i> boolean</p> <p>Set this to true (or 1) if this VM has affinity for its current host (so that it is unable to move to different host computers).</p> <p>Possible values:</p> <p>true, false, 0 or 1</p> <p>Destination:</p> <p>ImportedVirtualMachine.AffinityEnabled</p>

Column	Details
CPUAffinity	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>Contains a comma-separated list of processor numbers (Host Logical Processors) or ranges for which this virtual machine has affinity. Example: 1,3-5,8</p> <p>Destination: ImportedVirtualMachine.CPUAffinity</p>
CoreAffinity	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>Contains a comma-separated list of core numbers (or ranges) for which this virtual machine has affinity. Cores are numbered sequentially up the sequence of processors. Example: 1,5-8,10</p> <p>Destination: ImportedVirtualMachine.CoreAffinity</p>
ComplianceComputerType	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>If you know that the computer is a virtual machine or VM host, record that data here. If you are unsure, leave this cell empty (NULL): this allows the system to infer the computer type (for example, a computer with VMs linked to it is inferred to be a VM host). If data comes from multiple inventory sources, leaving this value as null also allows the value to be inserted from another source. So, unless there is a very good reason, do not just specify 'Computer', but allow the inference rules to help.</p> <p>Possible values:</p> <ul style="list-style-type: none"> • Computer • VM Host • Virtual Machine • Remote Device • Mobile Device • VDI Template <p>Destination: ImportedComputer.ComplianceComputerTypeID</p>

Column	Details
HostIdentifyingNumber	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>A physical server may have an identifier that is unique only across that hardware model, and may be less unique than the true hardware serial number, for example. This value is typically set for physical machines only, which include virtualization hosts, partitioned server hosts, and standalone machines. For a partitioned server, this value can be reported by each of the partitions on that server, such that a record of the physical computer can be created using one of the instances of this value. This value is used for matching computers.</p> <p>Destination:</p>
HostType	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>The type of the physical host computer. This value is similar to the model number, but it is always for the physical server that an execution context may be running on. Therefore, this will generally be a known value for standalone machines and partitions, but it will not be known for virtual machines. This value is used for matching computers. Examples:</p> <ul style="list-style-type: none"> • 'i86pc' • 'Sun-Fire-T1000' • 'rx7620' • '785' (for a 9000/785/C3700) • '8202' (for an IBM,8202-E4B). <p>Destination:</p>
VMLocation	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>Location of the virtual machine on the file system.</p> <p>Destination:</p> <p>ImportedVirtualMachine.VMLocation</p>
PoolName	<p><i>Type:</i> text (max 100 characters). Nullable</p> <p>The name of the pool that the virtual machine belongs to.</p> <p>Destination:</p> <p>ImportedVirtualMachine.PoolName</p>

Column	Details
PoolType	<p><i>Type:</i> text (max 100 characters). Nullable</p> <p>The type of the pool that the virtual machine belongs to.</p> <p>Possible values:</p> <ul style="list-style-type: none"> • Folder • Datacenter • ComputeResource • HostSystem • ResourcePool • VirtualMachine • PhysicalSharedPool • VirtualSharedPool • LPAR • RSET • ClusterComputeResource <p>Destination:</p> <p>ImportedVirtualMachine.PoolType</p>
CPUUsage	<p><i>Type:</i> integer. Nullable</p> <p>The maximum CPU usage of the virtual machine (MHz).</p> <p>Destination:</p> <p>ImportedVirtualMachine.CPUUsage</p>
MemoryUsage	<p><i>Type:</i> big integer. Nullable</p> <p>The maximum memory usage of the virtual machine (bytes).</p> <p>Destination:</p> <p>ImportedVirtualMachine.MemoryUsage</p>

Column	Details
InventoryDate	<p><i>Type:</i> datetime. Nullable</p> <p>The date (and optionally time) the computer last had inventory reported. This field is generally used for differential updates (that is, if the date/time has not changed since the previous import, the data record is not imported/updated). The date must be entered in one of the supported formats.</p> <p>Possible values:</p> <ul style="list-style-type: none"> • yyyy/MM/dd • yyyy/MM/dd HH:mm:Ss • yyyy/MM/dd HH:mm • yyyy-MM-dd • yyyy-MM-dd HH:mm:Ss • yyyy-MM-dd HH:mm • yyyyMMdd • yyyyMMdd HH:mm:Ss • yyyyMMdd HH:mm <p>Destination:</p> <p>ImportedComputer.InventoryDate</p>
ClusterID	<p><i>Type:</i> big integer. Key. Nullable</p> <p>The unique identifier for the cluster containing this computer. This must match the ClusterID used in the Cluster spreadsheet. If both the ClusterID and the ClusterNodeType do not match the data provided in the Cluster spreadsheet then the computer will not be associated with a cluster.</p> <p>Destination:</p> <p>ImportedClusterNode.ClusterExternalID</p>

Column	Details
ClusterNodeType	<p><i>Type:</i> text (max 128 characters). Nullable</p> <p>The Cluster node type of the computer. Must be a (case insensitive) exact match for one of the values shown. If both the ClusterID and the ClusterNodeType do not match the data provided in the Cluster spreadsheet then the computer will not be associated with a cluster.</p> <p>Possible values:</p> <ul style="list-style-type: none"> • Active • Passive • Hot • Warm • Cold <p>Destination:</p> <p>ImportedClusterNode.ClusterNodeTypeID</p>
HostID	<p><i>Type:</i> text (max 100 characters). Nullable</p> <p>The HostID hardware property for the server hosting this machine partition (when inventorying a machine partition such as Solaris Zone, AIX IPar, HP-UX nPar/vPar).</p> <p>Destination:</p> <p>ImportedComputer.HostID</p>
FirmwareSerialNumber	<p><i>Type:</i> text (max 100 characters). Nullable</p> <p>The Serial number in the system firmware such as BIOS, EEPROM etc.</p> <p>Destination:</p> <p>ImportedComputer.FirmwareSerialNumber</p>
MachineID	<p><i>Type:</i> text (max 100 characters). Nullable</p> <p>For AIX, it is the System ID. For HP-UX, it is the Machine/Software ID. It is unset for other platforms.</p> <p>Destination:</p> <p>ImportedComputer.MachineID</p>

ConsolidatedFileEvidence Template

ConsolidatedFileEvidence provides a simpler interface to specify files and their usage on computers. It combines the computer, file evidence and usage details into a single row.

Table 808: Columns included with ConsolidatedFileEvidence templates

Column	Details
ComputerID	<p><i>Type:</i> big integer. Key</p> <p>The identifier used in the source connection for the computer. It must match the ComputerID from the Computer spreadsheet or the row will be ignored.</p> <p>Destination:</p> <p>ImportedInstalledFileEvidence.ExternalID</p> <p>ImportedInstalledFileEvidenceUsage.ExternalID</p>
FileName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The name of the file used as evidence of software installation. For unix operating systems include the full path in the file name, including the opening '/'. For Windows operating systems the file path is specified in the FilePath column and this column must only contain the file name.</p> <p>Destination:</p> <p>ImportedFileEvidence.ExternalFileID</p> <p>ImportedFileEvidence.FileName</p> <p>ImportedInstalledFileEvidence.ExternalFileID</p> <p>ImportedInstalledFileEvidenceUsage.ExternalFileID</p>
FileVersion	<p><i>Type:</i> text (max 100 characters). Key. Nullable</p> <p>The version number of the file used as evidence of software installation.</p> <p>Destination:</p> <p>ImportedFileEvidence.ExternalFileID</p> <p>ImportedFileEvidence.FileVersion</p> <p>ImportedInstalledFileEvidence.ExternalFileID</p> <p>ImportedInstalledFileEvidenceUsage.ExternalFileID</p>
ProductVersion	<p><i>Type:</i> text (max 200 characters). Nullable</p> <p>The product version number in the file header.</p> <p>Destination:</p> <p>ImportedFileEvidence.ProductVersion</p>

Column	Details
ProductName	<p><i>Type:</i> text (max 200 characters). Nullable</p> <p>The product name in the file header.</p> <p>Destination:</p> <p>ImportedFileEvidence.ProductName</p>
FilePath	<p><i>Type:</i> text (max 400 characters). Nullable</p> <p>The path of the file used as evidence of software installation.</p> <p>Destination:</p> <p>ImportedFileEvidence.FilePath</p>
Company	<p><i>Type:</i> text (max 100 characters). Key. Nullable</p> <p>The company in the file header.</p> <p>Destination:</p> <p>ImportedFileEvidence.ExternalFileID</p> <p>ImportedFileEvidence.Company</p> <p>ImportedInstalledFileEvidence.ExternalFileID</p> <p>ImportedInstalledFileEvidenceUsage.ExternalFileID</p>
Description	<p><i>Type:</i> text (max 200 characters). Key. Nullable</p> <p>The description in the file header.</p> <p>Destination:</p> <p>ImportedFileEvidence.ExternalFileID</p> <p>ImportedFileEvidence.Description</p> <p>ImportedInstalledFileEvidence.ExternalFileID</p> <p>ImportedInstalledFileEvidenceUsage.ExternalFileID</p>
FileSize	<p><i>Type:</i> integer. Key. Nullable</p> <p>The size of the file in bytes.</p> <p>Destination:</p> <p>ImportedFileEvidence.ExternalFileID</p> <p>ImportedFileEvidence.FileSize</p> <p>ImportedInstalledFileEvidence.ExternalFileID</p> <p>ImportedInstalledFileEvidenceUsage.ExternalFileID</p>
Language	<p><i>Type:</i> text (max 200 characters). Nullable</p> <p>The language in the file header.</p> <p>Destination:</p> <p>ImportedFileEvidence.Language</p>

Column	Details
AccessMode	<p><i>Type:</i> text (max 128 characters). Key. Nullable</p> <p>The access mode of the file evidence. Leave this blank unless this row is a virtualized application. In that case choose one of the values below that matches your application or desktop virtualization infrastructure.</p> <p>Possible values:</p> <ul style="list-style-type: none"> • Local • App-V • XenApp • XenDesktop • VMware View • Office 365 <p>Destination:</p> <p>ImportedFileEvidence.ExternalFileID</p> <p>ImportedFileEvidence.AccessModeID</p> <p>ImportedInstalledFileEvidence.ExternalFileID</p> <p>ImportedInstalledFileEvidenceUsage.ExternalFileID</p>
NumberOfSessions	<p><i>Type:</i> big integer. Nullable</p> <p>The number of sessions that the file evidence was in use by the user specified in the UserID column during the usage tracking period. If multiple users used the same application on the computer, create one row for each user with usage.</p> <p>Destination:</p> <p>ImportedInstalledFileEvidenceUsage.NumberOfSessions</p>
StartDate	<p><i>Type:</i> text (max 10 characters). Nullable</p> <p>The start date of the usage. The date must be specified in the following format: 'yyyyMMdd'.</p> <p>Destination:</p> <p>ImportedInstalledFileEvidenceUsage.StartDate</p>
LastUsedDate	<p><i>Type:</i> text (max 10 characters). Nullable</p> <p>The last used date of the usage. The date must be specified in the following format: 'yyyyMMdd'.</p> <p>Destination:</p> <p>ImportedInstalledFileEvidenceUsage.LastUsedDate</p>

Column	Details
UserID	<p>Type: big integer. Key. Nullable</p> <p>The DOMAIN/SAMAccountName for the user that the file evidence was used by. If this software was used by multiple users, create one row for each user of the software on the computer.</p> <p>Destination:</p> <p>ImportedInstalledFileEvidenceUsage.ExternalUserID</p> <p>ImportedUser.ExternalID</p> <p>ImportedUser.UserName (Element 2 after splitting on '\\')</p> <p>ImportedUser.Domain (Element 1 after splitting on '\\')</p> <p>ImportedUser.SAMAccountName (Element 2 after splitting on '\\')</p>

ConsolidatedInstallerEvidence Template

ConsolidatedInstallerEvidence provides a simpler interface to specify installed applications and their usage on computers. It combines the computer, installer evidence and usage details into a single row.

Table 809: Columns included with ConsolidatedInstallerEvidence templates

Column	Details
ComputerID	<p><i>Type:</i> big integer. Key</p> <p>The identifier used in the source connection for the computer. It must match the ComputerID from the Computer spreadsheet or the row will be ignored.</p> <p>Destination:</p> <p>ImportedInstalledInstallerEvidence.ExternalComputerID</p> <p>ImportedInstalledInstallerEvidenceUsage.ExternalID</p> <p>ImportedInstance.ExternalComputerID</p>
DatabaseName	<p><i>Type:</i> big integer. Key. Nullable</p> <p>If this installer evidence is an Oracle database, then this field specifies the name of the database.</p> <p>Destination:</p> <p>ImportedInstalledInstallerEvidence.ExternalInstanceID</p> <p>ImportedInstalledInstallerEvidenceUsage.ExternalInstanceID</p> <p>ImportedInstance.InstanceID</p> <p>ImportedInstance.ParentInstanceID</p>
InstanceName	<p><i>Type:</i> big integer. Key. Nullable</p> <p>If this installer evidence is an Oracle database, then this field specifies the name of the database instance. If there are multiple instances, create a row for each instance in this spreadsheet.</p> <p>Destination:</p> <p>ImportedInstalledInstallerEvidence.ExternalInstanceID</p> <p>ImportedInstalledInstallerEvidenceUsage.ExternalInstanceID</p> <p>ImportedInstance.InstanceID</p> <p>ImportedInstance.InstanceName</p>

Column	Details
DisplayName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The display name of the software as reported by the installer evidence.</p> <p>Destination:</p> <p><code>ImportedInstallerEvidence.ExternalInstallerID</code></p> <p><code>ImportedInstallerEvidence.DisplayName</code></p> <p><code>ImportedInstalledInstallerEvidence.ExternalInstallerEvidenceID</code></p> <p><code>ImportedInstalledInstallerEvidenceUsage.ExternalInstallerID</code></p>
Version	<p><i>Type:</i> text (max 72 characters). Key. Nullable</p> <p>The version of the software as reported by the installer evidence.</p> <p>Destination:</p> <p><code>ImportedInstallerEvidence.ExternalInstallerID</code></p> <p><code>ImportedInstallerEvidence.Version</code></p> <p><code>ImportedInstalledInstallerEvidence.ExternalInstallerEvidenceID</code></p> <p><code>ImportedInstalledInstallerEvidenceUsage.ExternalInstallerID</code></p>
Publisher	<p><i>Type:</i> text (max 200 characters). Key. Nullable</p> <p>The publisher of the software as reported by the installer evidence.</p> <p>Destination:</p> <p><code>ImportedInstallerEvidence.ExternalInstallerID</code></p> <p><code>ImportedInstallerEvidence.Publisher</code></p> <p><code>ImportedInstalledInstallerEvidence.ExternalInstallerEvidenceID</code></p> <p><code>ImportedInstalledInstallerEvidenceUsage.ExternalInstallerID</code></p>
Evidence	<p><i>Type:</i> text (max 32 characters). Key. Nullable</p> <p>Identifier for the type of installer evidence.</p> <p>Destination:</p> <p><code>ImportedInstallerEvidence.ExternalInstallerID</code></p> <p><code>ImportedInstallerEvidence.Evidence</code></p> <p><code>ImportedInstalledInstallerEvidence.ExternalInstallerEvidenceID</code></p> <p><code>ImportedInstalledInstallerEvidenceUsage.ExternalInstallerID</code></p>

Column	Details
ProductCode	<p><i>Type:</i> text (max 55 characters). Nullable</p> <p>The product code of the evidence. This is usually the MSI product code.</p> <p>Destination:</p> <p><code>ImportedInstallerEvidence.ProductCode</code></p>
AccessMode	<p><i>Type:</i> text (max 128 characters). Key. Nullable</p> <p>The access mode of the installer evidence. Leave this blank unless this row is a virtualized application. In that case choose one of the values below that matches your application or desktop virtualization infrastructure.</p> <p>Possible values:</p> <ul style="list-style-type: none"> • Local • App-V • XenApp • XenDesktop • VMware View • Office 365 <p>Destination:</p> <p><code>ImportedInstallerEvidence.ExternalInstallerID</code></p> <p><code>ImportedInstallerEvidence.AccessModeID</code></p> <p><code>ImportedInstalledInstallerEvidence.ExternalInstallerEvidenceID</code></p> <p><code>ImportedInstalledInstallerEvidenceUsage.ExternalInstallerID</code></p>
InstallDate	<p><i>Type:</i> text (max 10 characters). Nullable</p> <p>The install date of the installer evidence. The date must be specified in the following format: 'yyyyMMdd'.</p> <p>Destination:</p> <p><code>ImportedInstalledInstallerEvidence.InstallDate</code></p>
DiscoveryDate	<p><i>Type:</i> text (max 10 characters). Nullable</p> <p>The date that the installer evidence was first seen. The date must be specified in the following format: 'yyyyMMdd'.</p> <p>Destination:</p> <p><code>ImportedInstalledInstallerEvidence.DiscoveryDate</code></p>

Column	Details
NumberOfSessions	<p><i>Type:</i> big integer. Nullable</p> <p>The number of sessions that the installer evidence was in use by the user specified in the UserID column during the usage tracking period. If multiple users used the same application on the computer, create one row for each user with usage.</p> <p>Destination:</p> <p><code>ImportedInstalledInstallerEvidenceUsage.NumberOfSessions</code></p>
StartDate	<p><i>Type:</i> text (max 10 characters). Nullable</p> <p>The start date of the usage. The date must be specified in the following format: 'yyyyMMdd'.</p> <p>Destination:</p> <p><code>ImportedInstalledInstallerEvidenceUsage.StartDate</code></p>
LastUsedDate	<p><i>Type:</i> text (max 10 characters). Nullable</p> <p>The last used date of the usage. The date must be specified in the following format: 'yyyyMMdd'.</p> <p>Destination:</p> <p><code>ImportedInstalledInstallerEvidenceUsage.LastUsedDate</code></p>
UserID	<p><i>Type:</i> big integer. Key. Nullable</p> <p>The DOMAIN/SAMAccountName for the user that the installer evidence was used by. If this software was used by multiple users, create one row for each user of the software on the computer.</p> <p>Destination:</p> <p><code>ImportedInstalledInstallerEvidenceUsage.ExternalUserID</code></p> <p><code>ImportedUser.ExternalID</code></p> <p><code>ImportedUser.UserName (Element 2 after splitting on '\\')</code></p> <p><code>ImportedUser.Domain (Element 1 after splitting on '\\')</code></p> <p><code>ImportedUser.SAMAccountName (Element 2 after splitting on '\\')</code></p>

ConsolidatedOracleDatabaseUser Template

ConsolidatedOracleDatabaseUser provides a list of the users for each Oracle database instance.

Table 810: Columns included with ConsolidatedOracleDatabaseUser templates

Column	Details
UserID	<p><i>Type:</i> big integer. Key</p> <p>The identifier used in the source connection for the instance end-user. This may be an integer or a string.</p> <p>Destination:</p> <p>ImportedInstanceUser.ExternalID</p> <p>ImportedLicenseUser.ExternalID</p>
ComputerID	<p><i>Type:</i> big integer. Key</p> <p>The identifier used in the source connection for the computer. It must match the ComputerID from the Computer spreadsheet or the row will be ignored.</p> <p>Destination:</p> <p>ImportedInstanceUser.ExternalID</p> <p>ImportedInstanceUser.ComputerID</p> <p>ImportedLicenseUser.ExternalID</p>
DatabaseName	<p><i>Type:</i> big integer. Key</p> <p>This field specifies the name of the database. It must match a row in the InstallerEvidence spreadsheet for the same ComputerID or this row will be skipped.</p> <p>Destination:</p> <p>ImportedInstanceUser.ExternalID</p> <p>ImportedInstanceUser.InstanceID</p> <p>ImportedLicenseUser.ExternalID</p>
InstanceName	<p><i>Type:</i> big integer. Key</p> <p>This field specifies the name of the database instance. If there are multiple instances, create a row for each instance in this spreadsheet. It must match a row in the InstallerEvidence spreadsheet for the same ComputerID and DatabaseName or this row will be skipped.</p> <p>Destination:</p> <p>ImportedInstanceUser.ExternalID</p> <p>ImportedInstanceUser.InstanceID</p> <p>ImportedLicenseUser.ExternalID</p>

Column	Details
Name	<p>Type: text (max 256 characters)</p> <p>The name of the user.</p> <p>Destination:</p> <p><code>ImportedLicenseUser.UserName</code></p>
AccountStatus	<p>Type: text (max 256 characters). Nullable</p> <p>The current status of the end-user account.</p> <p>Destination:</p> <p><code>ImportedInstanceUser.AccountStatus</code></p>
CreationDate	<p>Type: datetime. Nullable</p> <p>The date and time when the end-user was created. The date must be entered in one of the supported formats.</p> <p>Possible values:</p> <ul style="list-style-type: none"> • <code>yyyy/MM/dd</code> • <code>yyyy/MM/dd HH:mm:Ss</code> • <code>yyyy/MM/dd HH:mm</code> • <code>yyyy-MM-dd</code> • <code>yyyy-MM-dd HH:mm:Ss</code> • <code>yyyy-MM-dd HH:mm</code> • <code>yyyyMMdd</code> • <code>yyyyMMdd HH:mm:Ss</code> • <code>yyyyMMdd HH:mm</code> <p>Destination:</p> <p><code>ImportedInstanceUser.CreationDate</code></p>

Column	Details
LastLogonDate	<p><i>Type:</i> datetime. Nullable</p> <p>The date and time when the end-user last logged on to the computer. The date must be entered in one of the supported formats.</p> <p>Possible values:</p> <ul style="list-style-type: none"> • yyyy/MM/dd • yyyy/MM/dd HH:mm:Ss • yyyy/MM/dd HH:mm • yyyy-MM-dd • yyyy-MM-dd HH:mm:Ss • yyyy-MM-dd HH:mm • yyyyMMdd • yyyyMMdd HH:mm:Ss • yyyyMMdd HH:mm <p>Destination:</p> <p>ImportedInstanceUser.LastLogonDate</p>
DefaultTablespace	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>The default tablespace for an Oracle end-user.</p> <p>Destination:</p> <p>ImportedInstanceUser.DefaultTablespace</p>
TempTablespace	<p><i>Type:</i> text (max 256 characters). Nullable</p> <p>The temporary tablespace for an Oracle end-user.</p> <p>Destination:</p> <p>ImportedInstanceUser.TempTablespace</p>
DisplayName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The display name of the software as reported by the installer evidence. It must match a row in the InstallerEvidence spreadsheet for the same ComputerID, Version, Publisher, DatabaseName and InstanceName or this row will be skipped.</p> <p>Destination:</p> <p>ImportedInstanceUser.ApplicationID</p>

Column	Details
Version	<p><i>Type:</i> text (max 72 characters). Key</p> <p>The version of the software as reported by the installer evidence. It must match a row in the InstallerEvidence spreadsheet for the same ComputerID, DisplayName, Publisher, DatabaseName and InstanceName or this row will be skipped.</p> <p>Destination: ImportedInstanceUser.ApplicationID</p>
Publisher	<p><i>Type:</i> text (max 200 characters). Key</p> <p>The publisher of the software as reported by the installer evidence. It must match a row in the InstallerEvidence spreadsheet for the same ComputerID, DisplayName, Version, DatabaseName and InstanceName or this row will be skipped.</p> <p>Destination: ImportedInstanceUser.ApplicationID</p>
Evidence	<p><i>Type:</i> text (max 32 characters). Key. Nullable</p> <p>Identifier for the type of installer evidence.</p> <p>Destination: ImportedInstanceUser.ApplicationID</p>
AccessMode	<p><i>Type:</i> text (max 128 characters). Key. Nullable</p> <p>The access mode of the installer evidence. Leave this blank unless this row is a virtualized application. In that case choose one of the values below that matches your application or desktop virtualization infrastructure.</p> <p>Possible values:</p> <ul style="list-style-type: none"> • Local • App-V • XenApp • XenDesktop • VMware View • Office 365 <p>Destination: ImportedInstanceUser.ApplicationID</p>

ConsolidatedRemoteAccessFile Template

The RemoteAccessFile spreadsheet is used for capturing application virtualization information. Systems such as Microsoft AppV and Citrix XenApp allow a user to access applications that are not installed on a local computer. This object allows you to provide applications that a user may access by specifying the file evidence.

When populating the RemoteAccessFile template, please note that an application can be identified by file evidence. If the evidence does not match the ARL then no application will be created. The evidence not recognised will appear under the 'Unrecognised Evidence' screen within Flexnet Manager Suite. From there, you may create applications for any unrecognised evidence as required, and lastly ensure any new application relates to a license. This results in the evidence now being recognised for the new application and may cause license consumption after the next reconciliation. This application virtualization access using files is a special case in application matching. It does not require a mandatory file link to the application and can user a 'not for recognition' file to link to an application. This is because application and desktop virtualization systems rarely provide enough file information for more complex application recognition rules to function.

If entering file evidence, you must provide the following key identifier fields. + 1 = FileName

The following identifier fields are typically required for matching evidence in the ARL, however are not mandatory. + 1 = Company + 2 = FileVersion + 3 = Description + 4 = FileSize

File evidence does not have to be specified in the FileEvidence spreadsheet as well as here.

Table 811: Columns included with ConsolidatedRemoteAccessFile templates

Column	Details
ServerID	<p><i>Type:</i> big integer. Key</p> <p>This is the ComputerID of the server that publishes this virtual application. The ComputerID must match a computer from the Computer spreadsheet, and that computer must have an installation of the application this file is part of. If the server does not have an installation of an appropriate application then the user will not be shown as having access to that application. This is a mandatory field.</p> <p>Destination:</p> <p>ImportedRemoteUserToApplicationAccess.ExternalServerID</p>
FileName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The name of the file used as evidence of software installation. For unix operating systems include the full path in the file name, including the opening '/'. For Windows operating systems the file path is specified in the FilePath column and this column must only contain the file name.</p> <p>Destination:</p> <p>ImportedRemoteUserToApplicationAccess.ExternalFileID</p> <p>ImportedFileEvidence.ExternalFileID</p> <p>ImportedFileEvidence.FileName</p>

Column	Details
FileVersion	<p><i>Type:</i> text (max 100 characters). Key. Nullable</p> <p>The version number of the file used as evidence of software installation.</p> <p>Destination:</p> <p>ImportedRemoteUserToApplicationAccess.ExternalFileID</p> <p>ImportedFileEvidence.ExternalFileID</p> <p>ImportedFileEvidence.FileVersion</p>
ProductVersion	<p><i>Type:</i> text (max 200 characters). Nullable</p> <p>The product version number in the file header.</p> <p>Destination:</p> <p>ImportedFileEvidence.ProductVersion</p>
ProductName	<p><i>Type:</i> text (max 200 characters). Nullable</p> <p>The product name in the file header.</p> <p>Destination:</p> <p>ImportedFileEvidence.ProductName</p>
FilePath	<p><i>Type:</i> text (max 400 characters). Nullable</p> <p>The path of the file used as evidence of software installation.</p> <p>Destination:</p> <p>ImportedFileEvidence.FilePath</p>
Company	<p><i>Type:</i> text (max 100 characters). Key. Nullable</p> <p>The company in the file header.</p> <p>Destination:</p> <p>ImportedRemoteUserToApplicationAccess.ExternalFileID</p> <p>ImportedFileEvidence.ExternalFileID</p> <p>ImportedFileEvidence.Company</p>
Description	<p><i>Type:</i> text (max 200 characters). Key. Nullable</p> <p>The description in the file header.</p> <p>Destination:</p> <p>ImportedRemoteUserToApplicationAccess.ExternalFileID</p> <p>ImportedFileEvidence.ExternalFileID</p> <p>ImportedFileEvidence.Description</p>

Column	Details
FileSize	<p><i>Type:</i> integer. Key. Nullable</p> <p>The size of the file in bytes.</p> <p><i>Destination:</i></p> <p><code>ImportedRemoteUserToApplicationAccess.ExternalFileID</code></p> <p><code>ImportedFileEvidence.ExternalFileID</code></p> <p><code>ImportedFileEvidence.FileSize</code></p>
Language	<p><i>Type:</i> text (max 200 characters). Nullable</p> <p>The language in the file header.</p> <p><i>Destination:</i></p> <p><code>ImportedFileEvidence.Language</code></p>
UserID	<p><i>Type:</i> big integer. Key</p> <p>The UserID must be populated with the fully qualified name e.g. Mydomain\JohnSmith. If not then a User is not created.</p> <p>If fully qualified then this field populates the following user related fields. + 1 = The user name of the end-user from the text following the ". + 2 = The login name (SAM account name) of the end-user from the text following the ". + 3 = The domain name of the end-user from the text before the ".</p> <p><i>Destination:</i></p> <p><code>ImportedRemoteUserToApplicationAccess.ExternalUserID</code></p> <p><code>ImportedUser.ExternalID</code></p> <p><code>ImportedUser.UserName (Element 2 after splitting on '\')</code></p> <p><code>ImportedUser.Domain (Element 1 after splitting on '\')</code></p> <p><code>ImportedUser.SAMAccountName (Element 2 after splitting on '\')</code></p>

Column	Details
AccessMode	<p>Type: text (max 128 characters). Key. Nullable</p> <p>The AccessMode states how an application has been accessed.</p> <p>Possible values:</p> <ul style="list-style-type: none">• Local• App-V• XenApp• XenDesktop• VMware View• Office 365 <p>Destination:</p> <p><code>ImportedRemoteUserToApplicationAccess.ExternalFileID</code></p> <p><code>ImportedRemoteUserToApplicationAccess.AccessModeID</code></p> <p><code>ImportedFileEvidence.ExternalFileID</code></p> <p><code>ImportedFileEvidence.AccessModeID</code></p>

ConsolidatedRemoteAccessInstaller Template

The RemoteAccessInstaller spreadsheet is used for capturing application virtualization information. Systems such as Microsoft AppV and Citrix XenApp allow a user to access applications that are not installed on a local computer. This object allows you to provide applications that a user may access by specifying the installer evidence.

When populating the RemoteAccessInstaller, please note that an application can be identified by installer evidence. If the evidence does not match the ARL then no application will be created. The evidence not recognised will appear under the 'Unrecognised Evidence' screen within Flexnet Manager Suite. From there, you may create applications for any unrecognised evidence as required, and lastly ensure any new application relates to a license. This results in the evidence now being recognised for the new application and may cause license consumption after the next reconciliation.

If entering installer evidence, you must provide the following key identifier fields. + 1 = DisplayName

The following identifier fields are typically required for matching evidence in the ARL, however are not mandatory. + 1 = Version + 2 = Publisher + 3 = Evidence

Installer evidence does not have to be specified in the InstallerEvidence spreadsheet as well as here.

Table 812: Columns included with ConsolidatedRemoteAccessInstaller templates

Column	Details
DisplayName	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The display name of the software as reported by the installer evidence and is part of the unique identifier for installer evidence.</p> <p>Destination:</p> <p>ImportedRemoteUserToApplicationAccess.ExternalInstallerEvidenceID</p> <p>ImportedInstallerEvidence.ExternalInstallerID</p> <p>ImportedInstallerEvidence.DisplayName</p>
Version	<p><i>Type:</i> text (max 72 characters). Key</p> <p>The version of the software as reported by the installer evidence and is part of the unique identifier for installer evidence.</p> <p>Destination:</p> <p>ImportedRemoteUserToApplicationAccess.ExternalInstallerEvidenceID</p> <p>ImportedInstallerEvidence.ExternalInstallerID</p> <p>ImportedInstallerEvidence.Version</p>

Column	Details
Publisher	<p><i>Type:</i> text (max 200 characters). Key</p> <p>Publishers of software applications (for example, "Microsoft") as reported by the installer evidence and publisher is part of the unique identifier for installer evidence.</p> <p><i>Destination:</i></p> <p><code>ImportedRemoteUserToApplicationAccess.ExternalInstallerEvidenceID</code></p> <p><code>ImportedInstallerEvidence.ExternalInstallerID</code></p> <p><code>ImportedInstallerEvidence.Publisher</code></p>
Evidence	<p><i>Type:</i> text (max 32 characters). Key</p> <p>The evidence type of the software as reported by the installer evidence and is part of the unique identifier for installer evidence.</p> <p><i>Destination:</i></p> <p><code>ImportedRemoteUserToApplicationAccess.ExternalInstallerEvidenceID</code></p> <p><code>ImportedInstallerEvidence.ExternalInstallerID</code></p> <p><code>ImportedInstallerEvidence.Evidence</code></p>
ProductCode	<p><i>Type:</i> text (max 55 characters). Nullable</p> <p>The product code of the evidence. This is usually the MSI product code and is not part of the unique identifier.</p> <p><i>Destination:</i></p> <p><code>ImportedInstallerEvidence.ProductCode</code></p>
UserID	<p><i>Type:</i> big integer. Key</p> <p>The UserID must be populated with the fully qualified name e.g. Mydomain\JohnSmith. If not then a User is not created.</p> <p>If fully qualified then this field populates the following user related fields. + 1 = The user name of the end-user from the text following the "...". + 2 = The login name (SAM account name) of the end-user from the text following the "...". + 3 = The domain name of the end-user from the text before the "...".</p> <p><i>Destination:</i></p> <p><code>ImportedRemoteUserToApplicationAccess.ExternalUserID</code></p> <p><code>ImportedUser.ExternalID</code></p> <p><code>ImportedUser.UserName (Element 2 after splitting on '\')</code></p> <p><code>ImportedUser.Domain (Element 1 after splitting on '\')</code></p> <p><code>ImportedUser.SAMAccountName (Element 2 after splitting on '\')</code></p>

Column	Details
AccessMode	<p>Type: text (max 128 characters). Key. Nullable</p> <p>The AccessMode states how an application has been accessed.</p> <p>Possible values:</p> <ul style="list-style-type: none"> • Local • App-V • XenApp • XenDesktop • VMware View • Office 365 <p>Destination:</p> <p>ImportedRemoteUserToApplicationAccess.ExternalInstallerEvidenceID</p> <p>ImportedRemoteUserToApplicationAccess.AccessModeID</p> <p>ImportedInstallerEvidence.ExternalInstallerID</p> <p>ImportedInstallerEvidence.AccessModeID</p>

ConsolidatedVMPool Template

The VMPool spreadsheet provides a simple method to associate virtual machines with groups (pools) on their host.

Table 813: Columns included with ConsolidatedVMPool templates

Column	Details
PoolName	<i>Type:</i> text (max 100 characters). Key The name of the pool. Destination: ImportedVMPool.PoolName
ParentName	<i>Type:</i> text (max 100 characters). Nullable The name of the parent pool. Destination: ImportedVMPool.ParentName
PoolFriendlyName	<i>Type:</i> text (max 256 characters) The friendly name of the pool. Destination: ImportedVMPool.PoolFriendlyName
HostComputerID	<i>Type:</i> big integer. Key The identifier used in the source connection for the computer which is hosting the pool. The HostComputerID should match the ComputerID in the Computer spreadsheet. Otherwise the record will be ignored. Destination: ImportedVMPool.HostComputerID

Column	Details
ObjectType	<p>Type: text (max 256 characters). Key. Nullable</p> <p>The type of pool.</p> <p>Possible values:</p> <ul style="list-style-type: none"> • Folder • Datacenter • ComputeResource • HostSystem • ResourcePool • VirtualMachine • PhysicalSharedPool • VirtualSharedPool • LPAR • RSET • ClusterComputeResource <p>Destination:</p> <p>ImportedVMPool.ObjectType</p>
ComplianceConnectionID	<p>Type: integer. Key. Nullable</p> <p>The identifier for a data source connection in the ComplianceConnection table.</p> <p>Destination:</p> <p>ImportedVMPool.ComplianceConnectionID</p>
ParentObjectType	<p>Type: text (max 256 characters). Nullable</p> <p>The type of pool of the parent.</p> <p>Destination:</p> <p>ImportedVMPool.ParentObjectType</p>
NumberOfProcessors	<p>Type: decimal. Nullable</p> <p>The number of processors in this pool.</p> <p>Possible values:</p> <p>120.45</p> <p>Destination:</p> <p>ImportedVMPool.NumberOfProcessors</p>

Column	Details
NumberOfCores	<i>Type:</i> decimal. Nullable The number of cores in this pool. <i>Possible values:</i> 120.45 <i>Destination:</i> ImportedVMPool1.NumberOfCores

ConsolidatedWMIEvidence Template

ConsolidatedWMIEvidence provides a simpler interface to specify Windows Management Instrumentation (WMI) properties on computers. Other Web-Based Enterprise Management (WBEM) properties are supported from Unix computers as well. The most important data to provide in this spreadsheet is operating system installs. The 'Win32_OperatingSystem' class and the 'Name' property contains this data.

Table 814: Columns included with ConsolidatedWMIEvidence templates

Column	Details
ComputerID	<p><i>Type:</i> big integer. Key</p> <p>The identifier used in the source connection for the computer. It must match the ComputerID from the Computer spreadsheet or the row will be ignored.</p> <p><i>Destination:</i></p> <p><code>ImportedInstalledWMIEvidence.ExternalComputerID</code></p>
ClassName	<p><i>Type:</i> text (max 50 characters). Key</p> <p>The WMI class name of the evidence. An example is 'Win32_OperatingSystem'.</p> <p><i>Destination:</i></p> <p><code>ImportedWMIEvidence.ExternalEvidenceID</code></p> <p><code>ImportedWMIEvidence.ClassName</code></p> <p><code>ImportedInstalledWMIEvidence.ExternalEvidenceID</code></p>
PropertyName	<p><i>Type:</i> text (max 50 characters). Key</p> <p>The WMI property name of the WMI evidence. An example is 'Name'.</p> <p><i>Destination:</i></p> <p><code>ImportedWMIEvidence.ExternalEvidenceID</code></p> <p><code>ImportedWMIEvidence.PropertyName</code></p> <p><code>ImportedInstalledWMIEvidence.ExternalEvidenceID</code></p>
PropertyValue	<p><i>Type:</i> text (max 256 characters). Key</p> <p>The value of the property of the WMI evidence. An example is 'Microsoft Windows 7 Enterprise'</p> <p><i>Destination:</i></p> <p><code>ImportedWMIEvidence.ExternalEvidenceID</code></p> <p><code>ImportedWMIEvidence.PropertyValue</code></p> <p><code>ImportedInstalledWMIEvidence.ExternalEvidenceID</code></p>

Column	Details
InstanceName	<p>Type: text (max 256 characters). Key. Nullable</p> <p>The name of the WMI class instance. This is important when there a multiple instances of a WMI class on a computer. An example is the 'Win32_VideoController' class that may have many instances with the same properties. In this case you need to specify the name of the instance here, 'Intel(R) HD Graphics Family' or 'NVIDIA Quadro K2100M' for example.</p> <p>Destination:</p> <p>ImportedWMIEvidence.ExternalEvidenceID</p> <p>ImportedInstalledWMIEvidence.ExternalEvidenceID</p> <p>ImportedInstalledWMIEvidence.InstanceName</p>

A

AccessedSoftwareOccurrence table 383
 AccessedSoftware table 381
 AccessEvidenceEx table 378
 AccessEvidenceMatchCount table 379
 AccessEvidence table 377
 AccessingDeviceSnapshot table 385
 AccessingDevice table 384
 AccessingUserSnapshot table 387
 AccessingUser table 386
 AccessMode table 380
 AcquisitionMode table 43
 ActionApplies table 1067
 ActionClass table 781,1040
 ActionState table 1068
 Action table 1066
 ActiveDirectoryComputer table 67
 ActiveDirectoryDomain table 68
 ActiveDirectoryGroup table 69
 ActiveDirectoryMember table 70
 ActiveDirectoryUser table 71
 ActivitySource table 136
 Activity table 135
 ActivityTraceLog table 137
 ActivityType table 138
 ADComputer table 912
 ADExternalMember table 913
 AdministrationAccount table 72
 ADSDOU table 914
 ADUser table 915
 AlertCategory table 140
 Alert table 139
 AlertTarget table 141
 AlertType table 142
 AllocationDetails table 917
 AMTEventLog table 1046
 APIServiceAccount table 19
 AppVPackageMapping table 73
 Architecture table 1018
 ASN1Object table 352
 AssetComplianceColumn table 50
 AssetComplianceStatus table 52
 AssetContractPaymentSchedule table 143
 AssetContract table 53
 AssetPropertyValue table 54
 AssetPurchaseOrder table 55
 AssetStatus table 56
 Asset table 44
 AssetTypeProperty table 59

AssetType table 57
 AssetWarrantyType table 60
 Attribute table 144
 AvailablePackage table 74
 AvailablePackageType table 75

B

BaselineImport table 76
 BatchProcessExecutionDataName table 7
 BatchProcessExecutionData table 6
 BatchProcessExecution table 4
 BatchProcessorProcessType table 17
 BatchProcessor table 16
 BatchProcessSchedule table 8
 BatchProcessStatus table 9
 BatchProcessTypeLimit table 14
 BatchProcessType table 10
 BeaconActivityStatus table 79
 BeaconAdministrationAccount table 80
 BeaconAgentEvent table 81
 BeaconDiscoveryStatus table 82
 BeaconDiscoveryTaskSummaryStatus table 83
 BeaconDownloadedPolicy table 84
 BeaconExecutionStatusType table 85
 BeaconFilter table 86
 BeaconIssueStatus table 87
 BeaconIssueStatusType table 88
 BeaconPolicyPropertyValue table 90
 BeaconPolicy table 89
 BeaconPropertyValue table 91
 BeaconRuleActionPropertyValue table 94
 BeaconRuleAction table 93
 BeaconRuleBeaconTargetMapping table 95
 BeaconRule table 92
 BeaconSiteSubnetMapping table 96
 Beacon table 77
 BeaconTargetAgentEvent table 98
 BeaconTargetDiscoveredDeviceMapping table 99
 BeaconTargetPropertyValue table 100
 BeaconTargetSiteMapping table 101
 BeaconTargetSiteSubnetMapping table 102
 BeaconTarget table 97
 BeaconUpgradeMode table 103
 BeaconUpgradeStatus table 104
 BeaconWebServerStatus table 105
 BusinessImportLogDetail table 145
 BusinessImportLogObject table 146
 BusinessImportLogSummary table 148
 BusinessImportResult table 149

C

ClientAccessDetail table 926
 ClientAccessedAccessEvidence table 389
 ClientAccessedAccessOccurrence table 390
 ClientAccessingDevice table 928
 ClientAccessingUser table 929
 ClientAccessOccurrence table 927
 ClientAccessSourceType table 388
 ClusterComputer table 393
 ClusterHostAffinityRule table 394
 ClusterHostAffinityRuleType table 395
 ClusterNodeType table 396
 Cluster table 391
 ClusterType table 397
 ComplianceActionHistoryResource table 1077
 ComplianceActionHistory table 1076
 ComplianceComputerConnection table 156
 ComplianceComputerContract table 157
 ComplianceComputerInventorySourceType table 158
 ComplianceComputerMatchResult table 902
 ComplianceComputerPropertyValue table 159
 ComplianceComputerRole table 160
 ComplianceComputerSnapshot table 398
 ComplianceComputerStatus table 161
 ComplianceComputer table 150
 ComplianceComputerTag table 399
 ComplianceComputerTypeProperty table 163
 ComplianceComputerType table 162
 ComplianceComputerUsage table 164
 ComplianceConnectionParameter table 23
 ComplianceConnection table 20
 ComplianceCultureType table 24
 ComplianceDomain table 664
 ComplianceEventAction table 166
 ComplianceEventHistory table 167
 ComplianceEventState table 168
 ComplianceEvent table 165
 ComplianceEventType table 169
 ComplianceHistoryColumn table 173
 ComplianceHistory table 170
 ComplianceHistoryType table 174
 ComplianceImage table 177
 ComplianceLicenseUser table 178
 ComplianceOperator table 25
 ComplianceOperatorTenant table 27
 CompliancePredefinedSearch table 179
 ComplianceResourceString table 28
 ComplianceResponsibility table 181
 ComplianceSavedSearch table 182
 ComplianceSchedule table 184
 ComplianceSearchFolder table 185
 ComplianceSearchTypeColumn table 191
 ComplianceSearchTypeRelation table 194
 ComplianceSearchType table 187
 ComplianceSetting table 29
 ComplianceTask table 195
 ComplianceTenantSetting table 30
 ComplianceUserConnection table 676
 ComplianceUserInventorySourceType table 677
 ComplianceUserPropertyValue table 196
 ComplianceUserSnapshot table 400
 ComplianceUserStatus table 678
 ComplianceUser table 672
 ComplianceUserTag table 401
 ComplianceUserTypeProperty table 197
 ComputerChassisType table 198
 ComputerScriptResult table 1044
 Computer table 932
 ComputerUsage table 1057
 ConfigurationFile table 31
 ConfigurationFileType table 32
 ConnectionType table 33
 ConsolidatedAccessEvidence table 1091
 ConsolidatedClusterGroup table 1098
 ConsolidatedClusterHostAffinityRule table 1100
 ConsolidatedCluster table 1096
 ConsolidatedComputer table 1101
 ConsolidatedFileEvidence table 1117
 ConsolidatedInstallerEvidence table 1121
 ConsolidatedLicenseUser table 202
 ConsolidatedOracleDatabaseUser table 1125
 ConsolidatedRemoteAccessFile table 1129
 ConsolidatedRemoteAccessInstaller table 1133
 ConsolidatedVMPool table 1136
 ConsolidatedWMIEvidence table 1139
 ConsolidationType table 203
 ContractNote table 211
 ContractNotificationResponsibility table 213
 ContractNotification table 212
 ContractProperty table 214
 ContractPropertyValue table 215
 ContractScopingData table 216
 ContractSecurityUser table 217
 ContractState table 218
 ContractStatus table 219
 Contract table 204
 ContractType table 220
 ContractUseRightIBM table 225
 ContractUseRight table 222

ContractVendor table 226
 Country table 777,1036
 CurrencyRateSnapshot table 228
 CurrencyRate table 227
 Currency table 34
 CustomPropertyDisplayXML table 229

D

DatabaseConfiguration table 775,1013
 DatabaseMutex table 402
 DepreciationMethod table 61
 DeviceRole table 353
 DiscoveredDeviceCalculatedMember table 357
 DiscoveredDeviceDiscoveredBy table 106
 DiscoveredDeviceDiscoveryStatus table 107
 DiscoveredDeviceInventoryStatus table 108
 DiscoveredDeviceParent table 358
 DiscoveredDeviceSNMPInfo table 359
 DiscoveredDevice table 354
 DiscoveredDeviceTaskDetailedError table 109
 DiscoveredDeviceTaskStatusHistory table 112
 DiscoveredDeviceTaskStatus table 110
 DiscoveredDeviceTaskType table 114
 DiscoveredDeviceVDIBrokerInfo table 361
 DiscoveredDeviceVDIInfo table 362
 DiscoveredDeviceVirtualizationInfo table 363
 DisplayXML table 230
 DistributedPackage table 944
 DistributionGroupMember table 947
 DistributionGroup table 946
 DistributionServerStatus table 950
 DistributionServer table 948
 DistributionServerType table 951
 DocumentHistory table 234
 DocumentNote table 236
 Document table 231
 DocumentType table 237
 DomainConfiguration table 938
 Domain table 936

E

EcmSettings table 1080
 EmploymentStatus table 679
 EndOfLifeReason table 62
 EndOfSupportLifeName table 404
 EndOfSupportLife table 403
 EntitlementRecommendationState table 407
 EntitlementRecommendation table 405
 EntitlementTransactionOtherCandidate table 411
 EntitlementTransactionState table 412
 EntitlementTransaction table 408

EntitlementTransactionType table 413
 ErrorCategory table 115
 EventLogCategory table 239
 EventLogDetail table 240
 EventLogLevel table 241
 EventLogStatus table 242
 EventLogSummary table 243
 EventParameter table 244
 EventParameterType table 245
 EventSeverity table 246
 Event table 238
 EventTarget table 247
 EventTypeStatus table 249
 EventType table 248
 EvidenceExistenceRule table 414
 EvidenceStatus table 415
 ExpiredImportedComputer table 797

F

FileEvidenceCompany table 418
 FileEvidenceEx table 419
 FileEvidenceFile table 420
 FileEvidenceLanguage table 421
 FileEvidenceMatchCount table 422
 FileEvidencePath table 423
 FileNameMap table 1019
 FlexeraLicense table 790,1054
 FNMEAAgent table 116
 FNMEAFeature table 416
 FNMEALicensedFeature table 417

G

GroupExPathCultureType table 667
 GroupEx table 665
 GroupSnapshot table 424
 Group table 939
 GroupType table 668

H

HardwareClass table 962
 HardwareObject table 963
 HardwareProperty table 964
 HardwareValue table 965

I

ILMTPVUCounts table 250
 ImportedAccessingDevice table 807
 ImportedAccessingUser table 808
 ImportedActiveDirectoryComputer table 809
 ImportedActiveDirectoryDomain table 810
 ImportedActiveDirectoryExternalMember table 811
 ImportedActiveDirectoryGroup table 812
 ImportedActiveDirectoryMember table 813

- ImportedActiveDirectoryUser table 814
- ImportedActiveSyncDevice table 815
- ImportedARSLicense table 805
- ImportedAttributeMapping table 817
- ImportedClientAccessedAccessEvidence table 820
- ImportedClientAccessedAccessOccurrence table 821
- ImportedClientAccessEvidenceMapping table 819
- ImportedClientAccessEvidence table 818
- ImportedClusterGroupMember table 824
- ImportedClusterGroup table 823
- ImportedClusterHostAffinityRule table 825
- ImportedClusterNode table 826
- ImportedCluster table 822
- ImportedComputerCustomProperty table 836
- ImportedComputerMatchResult table 903
- ImportedComputerScriptResult table 837
- ImportedComputer table 827
- ImportedCustomPropertyName table 838
- ImportedDomain table 839
- ImportedEvidenceAttribute table 840
- ImportedFileEvidenceMapping table 848
- ImportedFileEvidence table 846
- ImportedFNMEAFeature table 841
- ImportedFNMEAProduct table 843
- ImportedFNMEAUsageStatus table 845
- ImportedGuidMapping table 849
- ImportedILMTPVUCounts table 850
- ImportedILMTPVUCreatedLicenses table 852
- ImportedILMTVMMMapping table 853
- ImportedInstalledFileEvidence table 854
- ImportedInstalledFileEvidenceUsage table 855
- ImportedInstalledInstallerEvidenceAttribute table 857
- ImportedInstalledInstallerEvidence table 856
- ImportedInstalledInstallerEvidenceUsage table 858
- ImportedInstalledWMIEvidence table 859
- ImportedInstallerEvidenceMapping table 861
- ImportedInstallerEvidenceRepackageMapping table 862
- ImportedInstallerEvidence table 860
- ImportedInstance table 863
- ImportedInstanceUser table 864
- ImportedMissingComputer table 865
- ImportedMissingLicenseUser table 866
- ImportedMissingUser table 867
- ImportedProductCodeEvidenceMapping table 868
- ImportedRelatedInstalledInstallerEvidence table 869
- ImportedRemoteApplicationAccess table 871
- ImportedRemoteApplicationInstallerData table 872
- ImportedRemoteApplicationServer table 873
- ImportedRemoteApplication table 870
- ImportedRemoteServerFileEvidenceMapping table 874
- ImportedRemoteUsage table 875
- ImportedRemoteUserToApplicationAccess table 876
- ImportedSiteSubnet table 878
- ImportedSite table 877
- ImportedSoftwareBundleInstallerEvidence table 904
- ImportedSoftwareLicenseAllocation table 880
- ImportedSoftwareLicense table 879
- ImportedStringMappingLatin1CS table 882
- ImportedStringMapping table 881
- ImportedUser table 883
- ImportedVDIEndPointAccess table 886
- ImportedVDI table 885
- ImportedVDITemplate table 887
- ImportedVDIUser table 888
- ImportedVirtualMachineMatchResult table 907
- ImportedVirtualMachine table 893
- ImportedVMHostDatastore table 889
- ImportedVMHostManagedBySoftware table 890
- ImportedVMHostProperty table 891
- ImportedVMPool table 892
- ImportedWMIEvidenceRuleMapping table 897
- ImportedWMIEvidence table 896
- ImporterRun table 425
- ImporterStepValidationIssue table 426
- ImporterStepValidationIssueType table 428
- ImporterValueMapping table 898
- ImportResolverErrorResult table 251
- ImportResolverType table 252
- IncomingBaseline table 117
- InstallationHistory table 957
- InstallationPostponement table 919
- Installation table 955
- InstalledApplications table 899
- InstalledFileEvidence table 429
- InstalledInstallerAttribute table 430
- InstalledInstallerEvidence table 431
- InstalledInstanceReplacement table 432
- InstalledSoftwareAttribute table 253
- InstalledSoftwareData table 433
- InstalledSoftwareRemoval table 435
- InstalledSoftwareReplacement table 436
- InstalledSoftwareUsageData table 437
- InstalledWMIEvidence table 439
- InstallerEvidenceEx table 441
- InstallerEvidenceMatchCount table 442
- InstallerEvidence table 440
- InstallerEvidenceType table 443

InstanceAttribute table 257
 InstanceEnvironment table 258
 InstancePropertyValue table 259
 InstanceRole table 260
 Instance table 254
 InstanceTypeProperty table 262
 InstanceType table 261
 InstanceUser table 263
 IntervalType table 264
 InventoryReport table 966

J

Job table 1069

K

KnownOracleListener table 364
 KnownOracleService table 365

L

Language table 778,1037
 LeaseEndReason table 63
 LicenseAllocation table 1005
 LicenseBreachReason table 447
 LicenseDefinitionTitle table 448
 LicenseDefinitionType table 449
 LicenseDefinitionUsageRight table 450
 LicenseMeasurement table 451
 LicenseModel table 1006
 LicensePurchase table 1007
 LicenseSimulationBreachStatus table 453
 LicenseSimulationChangeType table 454
 LicenseSimulationHWDDetails table 455
 LicenseSimulationLicenseDetails table 458
 LicenseSimulationResults table 459
 LicenseSimulationRowType table 461
 LicenseSimulationScenario table 464
 LicenseSimulationSWDDetails table 462
 LicenseSimulation table 452
 LicenseStatus table 465
 LicenseUserConnection table 266
 LicenseUserExcluded table 267
 LicenseUser table 265
 LicenseUserType table 268
 Locale table 779,1038
 LogFile table 269

M

MasterConfigurationFile table 36
 MediaContainsPackagePath table 1021
 MediaContainsPackageVersion table 1022
 Media table 1020
 MediaType table 1023
 MemberEx table 669

Member table 940
 MobileDevice table 273
 MSEAARLSoftwareTitleEdition table 270
 MSSelectLevel table 271
 MSSelectPool table 272

N

NetworkLocation table 1015
 NewFileEvidence table 466
 NotificationItem table 274
 NotificationTemplate table 275
 NotificationType table 276

O

OperatingSystem table 933
 OperatorManageState table 277
 OperatorTaskTypeSetting table 278
 OperatorTenantSetting table 37
 OracleInstance table 279
 OracleLegacyLicenseType table 468
 Organization table 941

P

PackageAllocation table 921
 PackageApplies table 922
 PackageFamily table 1024
 PackagePath table 1025
 PackagePathType table 1026
 PackageProvides table 1027
 PackageRequires table 1028
 PackageState table 1029
 PackageVersionArchitecture table 1031
 PackageVersionEnvironment table 1032
 PackageVersionInState table 1033
 PackageVersionLocale table 1034
 PackageVersion table 1030
 PartitionType table 782,1041
 PaymentScheduleCategory table 283
 PaymentScheduleDetailPaymentStatus table 287
 PaymentScheduleDetail table 284
 PaymentSchedule table 280
 PaymentScheduleTerm table 288
 PaymentScheduleType table 289
 PeriodType table 470
 PODetailProcess table 469
 PolicyApplies table 924
 Policy table 923
 ProcessAction table 471
 ProcessState table 476
 ProductContainsSoftware table 1008
 Project table 290
 PurchaseOrderDetailProperty table 299

PurchaseOrderDetailPropertyValue table 300
 PurchaseOrderDetailStatus table 301
 PurchaseOrderDetail table 294
 PurchaseOrderDetailType table 302
 PurchaseOrderProperty table 303
 PurchaseOrderPropertyValue table 304
 PurchaseOrderStatus table 305
 PurchaseOrder table 291
 PurchaseOrderType table 306
 PurchaseProgram table 307

Q

QuerySnapshot table 311

R

Reason table 959
 ReconcileAccessedSoftwareData table 477
 ReconcileInstalledSoftwareData table 479
 ReconcileInstalledSoftwareUsageData table 481
 ReconcileInterestingBundleAccessComputer table 482
 ReconcileInterestingBundleInstallComputer table 483
 ReconcileInterestingLicenses table 484
 ReconcileInterestingTitles table 485
 ReconcileSoftwareAccessDeviceLicensePointsConsumedData table 486
 ReconcileSoftwareAccessUserLicensePointsConsumedData table 487
 ReconcileSoftwareLicenseComputerProblem table 488
 ReconcileSoftwareLicenseCoresConsumedData table 489
 ReconcileSoftwareLicenseGroupPointsConsumedData table 490
 ReconcileSoftwareLicenseILMTPointsConsumedData table 492
 ReconcileSoftwareLicensePointsConsumedData table 493
 ReconcileSoftwareLicensePointsConsumedReason table 494
 ReconcileSoftwareLicenseProcessorData table 495
 ReconcileSoftwareLicenseReconcileExemptionReason table 118
 ReconcileSoftwareLicenseSecondUseMappingData table 497
 ReconcileSoftwareUserLicensePointsConsumedData table 498
 ReconcileVirtualMachineLayer table 499
 RegistryEvidenceHive table 502
 RegistryEvidenceKey table 503
 RegistryEvidence table 501
 RegistryEvidenceValue table 504
 RelatedInstalledApplications table 900

RelatedInstalledInstallerEvidenceSourceMap table 506
 RelatedInstalledInstallerEvidence table 505
 RelatedInstalledSoftwareData table 507
 RelationType table 312
 ResourceStringCultureType table 38
 Resource table 783,1042
 ResponsibilityType table 313
 RestrictedAccessType table 314
 RightDefinition table 39
 Right table 953
 RoleRight table 670
 RuleDiscoveryActionSummary table 119
 RuleInventoryActionSummary table 120
 RulesEngineRuleDefinition table 315
 RulesEngineRuleType table 316

S

SAPActivityCheckMultipleLogons table 685
 SAPActivityCheckSummary table 686
 SAPActivityCheckWorkTime table 687
 SAPCompositeRole table 688
 SAPConnectivityDirectionType table 689
 SAPConnectivityType table 690
 SAPConsolidatedUserDuplicate table 692
 SAPConsolidatedUser table 691
 SAPConsumption table 693
 SAPContentEngineRule table 695
 SAPContentEngine table 694
 SAPDuplicateUserRecommendation table 696
 SAPEngineConsumptionSummary table 699
 SAPEngineMetricName table 702
 SAPEngineMetric table 701
 SAPEngineName table 703
 SAPEnginePeriodType table 704
 SAPEngineSystemConsumption table 705
 SAPEngine table 698
 SAPImportedInventoryFileDigest table 706
 SAPLicenseRatio table 707
 SAPLicenseRecommendation table 708
 SAPLicenseTypeHierarchy table 711
 SAPLicenseTypeName table 712
 SAPLicenseType table 710
 SAPModule table 713
 SAPMultipleLogon table 714
 SAPObject table 715
 SAPObjectType table 716
 SAPRecommendationAdjustmentReason table 721
 SAPRecommendationProcessedStatus table 722
 SAPRecommendationSetStatus table 725
 SAPRecommendationSetSummary table 726

SAPRecommendationSet table 723
 SAPRFCCConnectionSummary table 719
 SAPRFCCConnection table 717
 SAPRoleConsumption table 729
 SAPRole table 728
 SAPRoleTransactionCode table 730
 SAPRuleAlgorithm table 733
 SAPRuleCategory table 734
 SAPRuleMapping table 735
 SAPRuleSetMapping table 738
 SAPRuleSet table 736
 SAPRule table 731
 SAPRuleType table 739
 SAPSecurityUser table 740
 SAPSoftwareLicense table 508
 SAPSoftwareLicenseType table 509
 SAPSpecialVersion table 510
 SAPSystemActivityCheckSummary table 745
 SAPSystemEngineMetric table 746
 SAPSystemEnvironment table 747
 SAPSystemGroup table 748
 SAPSystemLandscapeEngineMapping table 753
 SAPSystemLandscapeEngine table 751
 SAPSystemLandscapeLicenseTypeHierarchy table 756
 SAPSystemLandscapeLicenseTypeImport table 757
 SAPSystemLandscapeLicenseType table 754
 SAPSystemLandscapeStatus table 758
 SAPSystemLandscape table 749
 SAPSystemModule table 759
 SAPSystemObject table 760
 SAPSystemPriceListName table 762
 SAPSystemPriceList table 761
 SAPSystemRFCCConnectionSummary table 763
 SAPSystemRoleType table 764
 SAPSystem table 741
 SAPSystemType table 765
 SAPTransactionProfileObject table 767
 SAPTransactionProfile table 766
 SAPUserRole table 772
 SAPUser table 769
 SAPUserType table 773
 SecurityType table 317
 SerialNumberBlackList table 318
 ServiceComponent table 967
 ServicePackName table 512
 ServicePack table 511
 ServiceProviderApplicationOracle table 969
 ServiceProviderApplicationUsagePerMonth table 970
 ServiceProviderApplicationUsageType table 971
 ServiceProviderApplicationUserOracle table 972
 ServiceProviderComponentProperty table 974
 ServiceProviderComponent table 973
 ServiceProviderComponentValue table 975
 ServiceProviderName table 976
 ServiceProviderProperty table 977
 ServiceProvider table 968
 ServiceProviderType table 978
 ServiceProviderValue table 979
 ServiceUserOracle table 981
 ServiceUser table 980
 SessionUIDBeacon table 319
 SettingName table 40
 ShippingMethod table 320
 SiteSubnet table 367
 Site table 366
 SoftwareAccessDeviceLicensePointsConsumedData table 513
 SoftwareAccessMode table 514
 SoftwareAccessUserLicensePointsConsumedData table 515
 SoftwareDetails table 982
 SoftwareFileName table 985
 SoftwareFilePath table 986
 SoftwareFileProperty table 987
 SoftwareFile table 983
 SoftwareFileUsage table 1058
 SoftwareIsoTagEntity table 988
 SoftwareIsoTagFile table 989
 SoftwareIsoTagSoftwareVersion table 992
 SoftwareIsoTagUnique table 993
 SoftwareLicenseAllocationStatus table 530
 SoftwareLicenseAllocation table 528
 SoftwareLicenseAllocationUserType table 531
 SoftwareLicenseBreachReasonData table 532
 SoftwareLicenseChangeEventReason table 534
 SoftwareLicenseChangeEventSource table 535
 SoftwareLicenseChangeEvent table 533
 SoftwareLicenseComplianceStatus table 536
 SoftwareLicenseComputerProblemData table 537
 SoftwareLicenseComputerProblemType table 538
 SoftwareLicenseConnection table 539
 SoftwareLicenseContractPaymentSchedule table 321
 SoftwareLicenseContract table 540
 SoftwareLicenseCoresConsumedData table 541
 SoftwareLicenseCreation table 542
 SoftwareLicenseDefinition table 543
 SoftwareLicenseDuration table 545
 SoftwareLicenseExemptionReason table 546

- SoftwareLicenseExemptionRole table 547
 - SoftwareLicenseGroupAllocationReportingType table 548
 - SoftwareLicenseGroupAssignmentHistory table 549
 - SoftwareLicenseGroupAssignmentHistoryType table 551
 - SoftwareLicenseGroupBreachStatus table 552
 - SoftwareLicenseGroupPointsConsumedData table 553
 - SoftwareLicenseILMTPointsConsumedData table 555
 - SoftwareLicenseKey table 556
 - SoftwareLicenseKeyType table 557
 - SoftwareLicenseMetric table 558
 - SoftwareLicensePartitioningDefault table 564
 - SoftwareLicensePointsConsumedData table 567
 - SoftwareLicensePointsConsumedReasonData table 568
 - SoftwareLicensePointsConsumedReasonType table 569
 - SoftwareLicensePointsDefault table 570
 - SoftwareLicensePointsRuleSet table 575
 - SoftwareLicensePointsRule table 572
 - SoftwareLicensePoints table 565
 - SoftwareLicenseProcessorPointsData table 576
 - SoftwareLicenseProduct table 578
 - SoftwareLicensePropertyValue table 581
 - SoftwareLicenseProposalStatus table 582
 - SoftwareLicensePurchaseType table 583
 - SoftwareLicenseReconcileExemptionReasonData table 121
 - SoftwareLicenseReservationNecessityCheckResult table 585
 - SoftwareLicenseReservationStatus table 586
 - SoftwareLicenseReservation table 584
 - SoftwareLicenseReservationType table 587
 - SoftwareLicenseScopeTag table 588
 - SoftwareLicenseScopeTagType table 589
 - SoftwareLicenseScoping table 590
 - SoftwareLicenseSecondUseMappingData table 591
 - SoftwareLicenseSnapshot table 592
 - SoftwareLicense table 516
 - SoftwareLicenseTierType table 594
 - SoftwareLicenseTypeChangeProposal table 600
 - SoftwareLicenseTypePriority table 602
 - SoftwareLicenseTypeProperty table 603
 - SoftwareLicenseType table 595
 - SoftwareLicenseUsageHistory table 1081
 - SoftwareLicenseUseRightIBM table 606
 - SoftwareLicenseUseRightName table 607
 - SoftwareLicenseUseRightProposal table 611
 - SoftwareLicenseUseRight table 604
 - SoftwareLifeCycle table 613
 - SoftwareOccurrenceSoftwareIsoTagFile table 996
 - SoftwareOccurrence table 994
 - SoftwareProduct table 1009
 - SoftwareProperty table 997
 - SoftwarePublisher table 1010
 - SoftwareRecognition table 614
 - SoftwareReseller table 1011
 - SoftwareSKULookup table 616
 - SoftwareSku table 617
 - SoftwareTitleAccessEvidence table 621
 - SoftwareTitleAction table 622
 - SoftwareTitleClassification table 623
 - SoftwareTitleEdition table 624
 - SoftwareTitleEx table 625
 - SoftwareTitleFileEvidence table 627
 - SoftwareTitleHierarchyEx table 630
 - SoftwareTitleHierarchy table 628
 - SoftwareTitleInstallerEvidence table 631
 - SoftwareTitleLicenseProposalAction table 635
 - SoftwareTitleLicenseProposal table 633
 - SoftwareTitleLicenseReason table 636
 - SoftwareTitleLicense table 632
 - SoftwareTitleOracle table 637
 - SoftwareTitleProduct table 638
 - SoftwareTitleProperty table 639
 - SoftwareTitlePropertyValue table 640
 - SoftwareTitlePublisher table 641
 - SoftwareTitleRegistryEvidence table 642
 - SoftwareTitleSuiteEx table 644
 - SoftwareTitleSuite table 643
 - SoftwareTitle table 618
 - SoftwareTitleType table 645
 - SoftwareTitleVersionServicePack table 647
 - SoftwareTitleVersion table 646
 - SoftwareTitleWMIEvidence table 648
 - SoftwareUsagePerWeek table 1059
 - SoftwareUserLicensePointsConsumedData table 649
 - SoftwareUserLicensePointsConsumedSuggestedHistory table 651
 - SoftwareUserLicensePointsConsumedSuggested table 650
 - SoftwareUserLicensePointsHistory table 652
 - SoftwareValue table 998
 - SoftwareVersion table 999
 - StatusCodeCategory table 122
 - Subnet table 1016
 - SystemShutdown table 322
- T**
- Tag table 653

TargetOperatingSystemType table 654
 TargetType table 785,1049
 TaskExecutionStatusStep table 324
 TaskExecutionStatus table 323
 TaskSchedule table 1071
 TaskStepEventType table 326
 TaskStep table 325
 Task table 1070
 TaskType table 1072
 Tenant table 791,1055
 TermAndCondition table 327
 TermAndConditionTask table 329
 TermAndConditionType table 330
 TimezoneType table 41
 TrackGroup table 1082
 TrackSoftwareLicenseUsage table 1083
 TrackSoftwareTitle table 1084
 TrackSoftwareTitleUsage table 1085
 TransitiveMember table 942

U

UALSoftwareDetail table 930
 UIAlignmentType table 123
 UIFieldType table 124
 UIInsertType table 125
 UIItem table 126
 UIItemTargetSubType table 128
 UserNameBlacklist table 331
 UserSuffix table 680
 User table 934
 UserTitle table 681

V

VDIEndPointAccess table 656
 VDIGroup table 657
 VDISite table 658
 VDI table 655
 VDITemplate table 659
 VDIUser table 660
 VendorContact table 342
 VendorProperty table 345
 VendorPropertyValue table 346
 Vendor table 340
 VirtualDesktopAccess table 1000
 VirtualDesktopApplicationUsage table 1001
 VirtualDesktopGroupAccessScan table 1003
 VirtualDesktopGroupAccess table 1002
 VirtualizationProductName table 368
 VirtualMachineMatchResult table 908
 VirtualMachine table 347
 VMEnabledState table 332

VMHostManagedBySoftware table 333
 VMPool table 334
 VMPoolType table 336
 VMSourceType table 337
 VMState table 338
 VMType table 339

W

WakeOnLANDistributionJob table 1062
 WakeOnLANStatus table 1063
 WakeOnLANTask table 1064
 WMIEvidenceMatchCount table 662
 WMIEvidence table 661

X

XMLInsertType table 350